

Understand<sup>scitools™</sup>  
*User Guide and  
Reference Manual*

**Version 5.0  
February 2018**



Scientific Toolworks, Inc.  
53 N Main  
St. George, UT 84770

Copyright © 2018 Scientific Toolworks, Inc. All rights reserved.

The information in this document is subject to change without notice. Scientific Toolworks, Inc. makes no warranty of any kind regarding this material and assumes no responsibility for any errors that may appear in this document.

RESTRICTED RIGHTS: Use, duplication, or disclosure by the Government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFAR 252.227-7013 (48 CFR). Contractor/Manufacturer is Scientific Toolworks, Inc., 53 N. Main, St. George, UT 84770.

NOTICE: Notwithstanding any other lease or license agreement that may pertain to or accompany the delivery of this restricted computer software, the rights of the Government regarding use, reproduction, and disclosure are as set forth in subparagraph (c)(1) and (2) of Commercial Computer Software-Restricted Rights clause at FAR 52.227-19.

Part Number: USTAND5.0-GEN-UG-901 (2/18)

# Contents

<b>Chapter 1</b>	<b>Introduction</b>	
	What is Understand? . . . . .	13
	Languages Supported . . . . .	14
	For Those Who Don't Like to Read Manuals . . . . .	15
<b>Chapter 2</b>	<b>Parts and Terminology</b>	
	Using Understand Windows . . . . .	17
	Understand Terminology . . . . .	18
	Parts . . . . .	19
	Starting Understand . . . . .	20
	Other Ways to Run Understand . . . . .	21
	Context Menus Are Everywhere . . . . .	22
	Quickly Find Things in Your Source . . . . .	24
	Entity Filter . . . . .	24
	Entity Locator . . . . .	25
	Instant Search . . . . .	25
	Find in Files . . . . .	26
	Favorites . . . . .	26
	Information Browser . . . . .	27
	Source Editor . . . . .	28
	Architecture Browser . . . . .	29
	Graphical Views . . . . .	30
	ASCII and HTML Reports . . . . .	31
	APIs for Custom Reporting . . . . .	31
<b>Chapter 3</b>	<b>Configuring Your Project</b>	
	About Understand Projects . . . . .	33
	The Understand Project Database . . . . .	33
	Creating a New Project . . . . .	34
	New Project Wizard . . . . .	34
	Project Configuration Dialog . . . . .	39
	Languages Category . . . . .	41
	Files Category . . . . .	43
	Adding Directories . . . . .	44
	Adding Files . . . . .	45
	Removing Directories and Files . . . . .	45
	Setting Overrides . . . . .	46
	Scanning Watched Directories . . . . .	47
	Setting File Portability . . . . .	48
	File Types . . . . .	49
	File Options . . . . .	50
	Scheduled Activities . . . . .	51
	Metrics . . . . .	53

Metrics > Selected Category . . . . .	54
Reports . . . . .	55
Reports > Output Category . . . . .	55
Reports > Options Category . . . . .	56
Reports > Selected Category . . . . .	57
Visual Studio . . . . .	58
CMake . . . . .	60
Annotations . . . . .	61
Ada Options . . . . .	63
Ada > Macros Category . . . . .	65
Assembly Options . . . . .	67
Visual Basic Options . . . . .	68
COBOL Options . . . . .	69
COBOL > Copybooks Category . . . . .	70
C++ (Fuzzy) Options . . . . .	71
C++ > Includes Category . . . . .	73
C++ > Includes > Auto Category . . . . .	74
C++ > Includes > Ignore Category . . . . .	74
C++ > Includes > Replacement Text . . . . .	75
C++ > Macros Category . . . . .	75
C++ > Macros > Undefines Category . . . . .	77
C++ (Strict) Options . . . . .	78
C++ (Strict) > Includes Category . . . . .	80
C++ (Strict) > Includes > Frameworks Category . . . . .	81
C++ (Strict) > Includes > Prefix Headers Category . . . . .	82
C++ (Strict) > Macros Category . . . . .	82
C# Options . . . . .	83
Fortran Options . . . . .	84
Fortran>Includes Category . . . . .	86
Other Fortran Categories . . . . .	86
Java Options . . . . .	87
Java > Class Paths Category . . . . .	88
Eclipse Plugin . . . . .	88
JOVIAL Options . . . . .	89
Jovial > !Copy Category . . . . .	90
Pascal Options . . . . .	91
Pascal > Macros Category . . . . .	92
Pascal > Standard Library Paths Category . . . . .	92
Pascal > Search Paths Category . . . . .	92
PL/M Options . . . . .	93
PL/M>Includes Category . . . . .	93
Python Options . . . . .	94
Python > Imports Category . . . . .	95
VHDL Options . . . . .	95
Web Options . . . . .	96
Setting General Preferences . . . . .	98
General Category . . . . .	99

User Interface Category . . . . .	101
User Interface > Lists Category . . . . .	102
User Interface > Alerts Category . . . . .	103
User Interface > Windows Category . . . . .	104
User Interface > Application Styles Category. . . . .	106
Key Bindings Category. . . . .	107
Analyze Category. . . . .	108
Portability Category . . . . .	109
Dependency Category . . . . .	110
Editor Category . . . . .	111
Editor > Advanced Category . . . . .	113
Editor > Macros Category . . . . .	116
Editor > Styles Category . . . . .	117
Editor > Navigation Category . . . . .	118
Editor > External Editor Category. . . . .	119
Graphs Category . . . . .	120
Analyzing the Code. . . . .	123
Improving the Analysis. . . . .	124
Using the Missing Header Files Tool . . . . .	125
Using the Undefined Macros Tool . . . . .	127

## Chapter 4

### Exploring Your Codebase

PLEASE RIGHT-CLICK . . . . .	129
Various Windows Explained... . . . .	130
Entity Filter . . . . .	131
Using the Filter Field . . . . .	132
Customizing the Display. . . . .	132
Root Filters. . . . .	133
Information Browser . . . . .	133
Drilling Down a Relationship . . . . .	134
Displaying More or Less Information . . . . .	135
Searching the Information Browser . . . . .	135
Syncing the Information Browser . . . . .	136
Visiting Source Code . . . . .	136
Visiting References . . . . .	137
Viewing Metrics . . . . .	137
Saving and Printing Information Browser Text. . . . .	138
Entity History . . . . .	138
Project Browser . . . . .	139
Exploring a Hierarchy . . . . .	141
Dependency Browser . . . . .	142
Favorites . . . . .	144
Creating a Favorite Entity. . . . .	144
Creating a Favorite View . . . . .	145
Using a Favorites Group . . . . .	145
Creating a Plain Text Favorite . . . . .	147

## Chapter 5

### Searching Your Source

Searching: An Overview . . . . .	149
----------------------------------	-----

Instant Search . . . . .	150
Find in Files . . . . .	152
Find Results . . . . .	154
Replace in Files . . . . .	155
Entity Locator . . . . .	157
Resizing Columns . . . . .	157
Long versus Short Names . . . . .	157
Column Headers . . . . .	158
Choosing Columns . . . . .	158
Filtering the List . . . . .	159
Finding Windows . . . . .	162
Source Visiting History . . . . .	163
View Menu Commands . . . . .	163
Displaying Toolbars . . . . .	164
Searching in a File . . . . .	165
Find Next and Previous . . . . .	165
Find & Replace . . . . .	165
Contextual Information Sidebar . . . . .	166

## Chapter 6

### Editing Your Source

Source Editor . . . . .	168
Scope List . . . . .	169
Status Icons . . . . .	169
Status Line . . . . .	169
Selecting and Copying Text . . . . .	170
Browse Mode . . . . .	170
Context Menu . . . . .	171
Hover Text . . . . .	172
Saving Source Code . . . . .	172
Refactoring Tools . . . . .	173
Renaming Entities . . . . .	174
Inlining Functions . . . . .	175
Extracting Functions . . . . .	176
Inline Temp . . . . .	177
Extract Temp . . . . .	178
Other Editing Features . . . . .	179
Previewer . . . . .	179
Bracket Matching . . . . .	180
Folding and Hiding . . . . .	180
Splitting the Editor Window . . . . .	181
Commenting and Uncommenting . . . . .	181
Changing Case . . . . .	181
Indentation . . . . .	182
Line Wrapping . . . . .	182
Insert and Overtyping Modes . . . . .	182
Sorting Lines Alphabetically . . . . .	182
Keyboard Commands . . . . .	182
Recording, Playing, and Saving Macros . . . . .	182
Creating and Opening Files . . . . .	183

Bookmarking . . . . .	183
Managing Source Editor Tabs . . . . .	185
Changing the Source Code Font Size . . . . .	185
Annotations . . . . .	186
Adding an Annotation . . . . .	186
Editing an Annotation . . . . .	188
Deleting an Annotation . . . . .	188
Managing Annotation Files and Display . . . . .	188
Searching Annotations . . . . .	189
Filtering Annotations . . . . .	190
Managing Orphaned Annotations . . . . .	191
Printing Source Views . . . . .	192

## Chapter 7

### Architecting Your Codebase

About Architectures . . . . .	194
Using the Architecture Browser . . . . .	195
Exploring Architectures . . . . .	195
Viewing Architecture Dependency Graphs . . . . .	198
Graph Customizer Toolbar . . . . .	199
Graph Architecture View . . . . .	201
Viewing Architecture Metrics . . . . .	202
Managing Architectures . . . . .	203
Creating an Architecture . . . . .	204
Using the Architecture Wizard . . . . .	205
Editing an Architecture . . . . .	206
Using XML to Manage Architectures . . . . .	208
Exporting Architectures to XML . . . . .	208
Importing XML Architectures . . . . .	208

## Chapter 8

### Using Reports

Configuring Reports . . . . .	210
Customizing Report Colors . . . . .	212
Generating Reports . . . . .	212
Viewing Reports . . . . .	213
An Overview of Report Categories . . . . .	214
Augment with the PERL or C API . . . . .	215
Cross-Reference Reports . . . . .	216
Data Dictionary Report . . . . .	216
Program Unit Cross-Reference Report . . . . .	217
File Contents Report . . . . .	217
Object Cross-Reference Report . . . . .	218
Type Cross-Reference Report . . . . .	218
Class and Interface Cross-Reference . . . . .	218
Macro Cross-Reference . . . . .	219
Include File Cross-Reference . . . . .	219
Exception Cross-Reference Report . . . . .	220
Structure Reports . . . . .	221
Declaration Tree . . . . .	221

Extend Tree . . . . .	222
Invocation Tree Report. . . . .	222
Simple Invocation Tree Report. . . . .	222
With Tree Report . . . . .	223
Simple With Tree Report . . . . .	223
Generic Instantiation Report . . . . .	223
Renames Report . . . . .	223
Import Report . . . . .	223
Quality Reports . . . . .	224
Program Unit Complexity Report . . . . .	224
Fortran Extension Usage Report . . . . .	225
Implicitly Declared Objects Report . . . . .	225
Uninitialized Items . . . . .	226
Unused Objects and Functions . . . . .	226
Unused Objects Report . . . . .	226
Unused Types Report . . . . .	227
Unused Program Units Report . . . . .	227
Uses Not Needed Report . . . . .	227
Withs Not Needed Report . . . . .	227
Metrics Reports. . . . .	228
Project Metrics Report . . . . .	228
Class Metrics Report . . . . .	229
Class OO Metrics Report . . . . .	229
Program Unit Metrics Report . . . . .	230
File Metrics Report . . . . .	230
File Average Metrics Report. . . . .	231
Importing Report Plugins . . . . .	231

## Chapter 9

### Using Metrics

About Metrics . . . . .	233
Metrics Summary . . . . .	234
Metrics Browser . . . . .	235
Exporting Metrics to HTML . . . . .	236
Exporting Metrics to a CSV File . . . . .	237
Configuring Metric Charts . . . . .	239
Using the Metrics Treemap. . . . .	242
Exporting Dependency Metrics. . . . .	244
Exporting Dependencies to a CSV File . . . . .	246
Exporting Dependencies to a CSV Matrix File . . . . .	247
Exporting Dependencies to Cytoscape . . . . .	247

## Chapter 10

### Using Graphical Views

Project Overview Graphics . . . . .	249
Graphical View Browsers . . . . .	251
Hierarchy Views . . . . .	252
Structure Views . . . . .	253
General Commands for Using Graphical Browsers . . . . .	253
Filtering Out Entities. . . . .	255



Reuse Checkbox . . . . .	256
Sync Checkbox . . . . .	256
Graph Options . . . . .	256
Types of Views . . . . .	257
Hierarchy View Types . . . . .	257
Hierarchy View Examples . . . . .	258
Structure View Types . . . . .	261
Structure View Examples . . . . .	261
Graphical Notation . . . . .	266
Controlling Graphical View Layout . . . . .	266
Called by Menu . . . . .	267
Comments Menu . . . . .	267
Constants Menu . . . . .	267
Default Members Menu . . . . .	267
Dependent Of Menu . . . . .	267
Dependent Menu . . . . .	267
Depth . . . . .	267
Duplicate Subtrees Menu . . . . .	267
Expand Recursive Notes . . . . .	268
Expand Repeated Notes . . . . .	268
Extended By Menu . . . . .	268
Extends Menu . . . . .	268
External Functions Menu . . . . .	268
Filename Menu . . . . .	268
Function Pointer Menu . . . . .	268
Globals Menu . . . . .	268
Implements Menu . . . . .	268
Implemented By Menu . . . . .	268
Imports Menu . . . . .	269
Included By Menu . . . . .	269
Includes Menu . . . . .	269
Inherits Menu . . . . .	269
Inherited By Menu . . . . .	269
Intrinsic Functions Menu . . . . .	269
Invocations Menu . . . . .	269
Layout Menu . . . . .	270
Level Menu . . . . .	271
Locals Menu . . . . .	271
Members Menu . . . . .	271
Name Menu . . . . .	271
Objects Menu . . . . .	271
Operators Menu . . . . .	271
Parameters Menu . . . . .	272
Private Members Menu . . . . .	272
Protected Members Menu . . . . .	272
Public Members Menu . . . . .	272
Renames Menu . . . . .	272
Routines Menu . . . . .	272
Scale Menu . . . . .	272
Sort Menu . . . . .	273

Spacing Menu .....	273
Sql Menu .....	273
Static Menu .....	273
Text Menu .....	273
Types Menu .....	273
Typetext Menu .....	274
Unknown Menu .....	274
Unresolved Menu .....	274
Usedby Menu .....	274
Uses Menu .....	274
Variables Menu .....	274
Withs Menu .....	274
With Bys Menu .....	274
Controlling Cluster Graph Layout .....	275
Cluster Control Flow Graphs .....	277
Saving Graphical Views .....	278
Saving Views to Files .....	279
Saving Views as Visio Files .....	279
Saving Views as DOT Files .....	280
Importing Graphical View Plugins .....	280
Printing Graphical Views .....	281
Graphical View Printing .....	281

## Chapter 11

### Using CodeCheck for Standards Verification

About CodeCheck .....	284
Running a CodeCheck .....	285
Files Tab .....	285
Checks Tab .....	286
Exporting and Importing Configurations .....	288
Viewing CodeCheck Results .....	288
Using the Result Log .....	288
Using the Results by File Tab .....	289
Using the Results by Check Tab .....	290
Using the Result Locator .....	291
Using the Result Treemap .....	292
Printing and Exporting Results .....	293
Ignoring Checks and Violations .....	293
Using CodeCheck Configurations .....	295
Writing CodeCheck Scripts .....	296
Installing Custom Scripts .....	297

## Chapter 12

### Comparing Source Code

Comparing Files and Folders .....	299
Comparing Entities .....	302
Comparing Text .....	303
Exploring Differences .....	304
Code Comparison .....	304
Patch File .....	307

---

	Difference List .....	307
<b>Chapter 13</b>	<b>Running Tools and External Commands</b>	
	Configuring Tools .....	309
	Variables .....	311
	Adding Tools to the Context Menus .....	316
	Adding Tools to the Tools Menu .....	317
	Adding Tools to the Toolbar .....	318
	Importing and Exporting Tool Commands .....	319
	Running External Commands .....	320
	Using the Eclipse Plugin .....	321
<b>Chapter 14</b>	<b>Command Line Processing</b>	
	Using the und Command Line .....	323
	Getting Help on Und. ....	325
	Creating a New Project .....	325
	Adding Files to a Project .....	325
	Removing Items from a Project .....	326
	Getting Information about a Project .....	326
	Modifying Project Settings .....	327
	Importing into a Project .....	327
	Exporting from a Project. ....	327
	Analyzing a Project .....	328
	Generating Reports .....	328
	Generating Metrics .....	329
	Using CodeCheck .....	329
	Running Perl Scripts .....	329
	Creating a List of Files .....	330
	Using the understand Command Line .....	331
	Using Buildspy to Build Understand Projects .....	332
<b>Chapter 15</b>	<b>Quick Reference</b>	
	File Menu .....	334
	Edit Menu .....	335
	Search Menu .....	335
	View Menu .....	336
	Project Menu .....	336
	Reports Menu .....	337
	Metrics Menu .....	337
	Graphs Menu .....	338
	CodeCheck Menu .....	338
	Annotations Menu .....	338
	Tools Menu .....	339
	Window Menu .....	339
	Help Menu .....	340

## Chapter 1

# Introduction

This chapter introduces the *Understand* software.

This manual assumes a moderate understanding of the programming language in which your project is written.

This chapter contains the following sections:


Section	Page
What is Understand?	13
Languages Supported	14
For Those Who Don't Like to Read Manuals	15

## What is Understand?

*Understand* is a static analysis tool focused on source code comprehension, metrics, and standards testing. It is designed to help maintain and understand large amounts of legacy or newly created source code. It provides a cross-platform, multi-language, maintenance-oriented IDE (interactive development environment).

The source code analyzed may include C, C++, C#, Objective C/Objective C++, Ada, Assembly, Visual Basic, COBOL, Fortran, Java, JOVIAL, Pascal/Delphi, PL/M, Python, VHDL, and Web (PHP, HTML, CSS, JavaScript, and XML).

It offers code navigation using a detailed cross-referencing, a syntax-colorizing “smart” editor, and a variety of graphical reverse engineering views.



*Understand* creates a repository of the relations and structures contained within the software project. The repository is then used to learn about the source code.

*Understand* has analysis features that help you quickly answer questions such as:

- What is this entity?
- Where is it changed?
- Where is it referenced?
- Who depends on it?
- What does it depend on?

*Understand* has architecture features that help you create hierarchical aggregations of source code units. You can name these units and manipulate them in various ways to create interesting hierarchies for analysis.

---

## Languages Supported

The following list provides a brief overview of the language versions and/or compilers that *Understand* supports:

- **Ada:** *Understand* supports Ada83, Ada95, Ada05, and Ada12 code, separately, or in combination.
- **Assembly:** *Understand* supports assembly code for Freescale Coldfire 68K, JIPSE MIL-STD-1750A, and IBM 390.
- **Visual Basic:** *Understand* supports Visual Basic 2002 through 2015.
- **C/C++:** *Understand* analyzes K&R or ANSI C source code and most constructs of the C++ language. *Understand* works with any C compiler, and has been tested with most of the popular ones.
- **Objective C/Objective C++:** *Understand* provides a strict analyzer option that supports these languages.
- **C#:** *Understand* supports C#.
- **COBOL:** *Understand* supports the Ansi85, Micro Focus, AcuCobol, and IBM compilers.
- **Fortran:** *Understand* supports FORTRAN 77, Fortran 90, Fortran 95, Fortran 2003, and Fortran 2008 in both free and fixed format. Extensions supported include Harris Fortran and DEC Fortran. We often expand *Understand* to support common compiler extensions. If you find that the compiler extensions you are using are not currently supported, contact us at [support@scitools.com](mailto:support@scitools.com).
- **Java:** *Understand* supports most of JDK 1.3, 1.4, 5, 6, 7, and 8. Specifically, the generics introduced in JDK 5 are not currently supported. Source code containing generics may be analyzed but generics information will be ignored.
- **JOVIAL:** JOVIAL73 and JOVIAL3 are supported.
- **Pascal:** *Understand* supports all versions of Borland's Delphi language and Borland's Turbo Pascal language. It also supports ISO 7185: 1990 (also known as Unextended Pascal) with DEC Pascal extensions. You can also enable support for Ingres embedded SQL statements.
- **PL/M:** The standard version for PL/M 80/86 is supported.
- **Python:** *Understand* supports both Python 2.x and 3.x.
- **VHDL:** Versions VHDL-87, VHDL-93, and VHDL-2001 are supported.
- **Web:** HTML, PHP, CSS, JavaScript, and XML files are supported.

For information about support for a specific language syntax, search the Build Log on the Scientific Toolworks website ([www.scitools.com/support/buildLogs.php](http://www.scitools.com/support/buildLogs.php)).

## For Those Who Don't Like to Read Manuals

If you are like many engineers at Scientific Toolworks, you like to just dig in and get going with software. We encourage that, or at least we are pragmatic enough to know you will do it anyway! So feel free to use this manual as a safety net, or to find the less obvious features. However, before you depart the manual, skim the next chapter for tips on effectively utilizing what *Understand* has to offer.

Here are some places other than this manual to look for advice:

- Use the links in the Getting Started display (**Help > Getting Started** from the menus)
- Choose **Help > Help Content** from the menus.
- Use **Help > Example Projects** to play with sample code.
- Choose **Help > Frequently Asked Questions** to see the FAQ list on our website.
- For information about various features, see [www.scitools.com/support](http://www.scitools.com/support).

For more advanced users, try these information sources:

- Choose **Help > About Understand** to see which build you are currently running.
- See [www.scitools.com/support/buildLogs.php](http://www.scitools.com/support/buildLogs.php) to search through the build logs. Use the link on that page to “Sign up to receive via Email” new build notes and build announcements.
- Choose **Help > Key Bindings** for keystroke help.
- See [scitools.com/support/metrics\\_list/](http://scitools.com/support/metrics_list/) for details about specific metrics.
- Choose **Help > Perl API Documentation** and **Help > Python API Documentation** for help on scripting. Java API documentation is provided in the doc/manuals/java subdirectory of the *Understand* installation.

This chapter helps you put *Understand* to good use quickly and easily by describing the basic windows in *Understand*.


This chapter contains the following sections:





Section	Page
Using Understand Windows	17
Understand Terminology	18
Starting Understand	20
Context Menus Are Everywhere	22
Quickly Find Things in Your Source	24
Information Browser	27
Source Editor	28
Architecture Browser	29
Graphical Views	30
ASCII and HTML Reports	31
APIs for Custom Reporting	31



## Using Understand Windows

*Understand* has a main window and many smaller areas that open within the *Understand* application window. You can arrange these areas in your workspace to meet your needs.



- **Title Bar:** You can drag the title bar of an area around the main window. If you move to the edge of the main window, a docking area expands. If you drop the area there, it “docks” to the edge of the main window.
- **Pushpins and Drawers:** Click the  icon to move an area to a tab along the same edge of the main window to which this area was docked. This is a “drawer” that opens automatically if you point your mouse at the tab title. The drawer closes if you move your mouse away from the area without clicking on it or if you click the title tab of the currently open drawer.  
Click the  icon to “pin” a drawer open. Pinned drawers have a title bar and title bar icons like the ones shown above.
- **Dock/Undock:** Click the  icon to change the area to an undocked window. Click the icon again in an undocked window to return to a docked area.
- **Close:** Click the “X” icon to close the area or undocked window.
- **Drop-down:** Click the  icon to see the context menu for this area. Right-clicking an item within an area usually displays a context menu specific to that item.
- **Sliding Frame:** You can drag the frames between window areas to change their sizes.
- **Previous and Next:** Each area type has different icons below the title bar. For the Information Browser area shown, you can browse through the history of entities viewed. For other areas, you will see other icons.

## Understand Terminology

Before continuing with the rest of this manual, please take a moment to familiarize yourself with *Understand's* terminology. Doing so will make reading the manual more helpful and put you on the same sheet of music as the technical support team should you need to email or call.

**Architecture:** An architecture is a hierarchical aggregation of source code units (entities). An architecture can be user created or automatically generated. Architectures need not be complete (that is, an architecture's flattened expansion need not reference every source entity in the database), nor unique (that is, an architecture's flattened expansion need not maintain the set property).

**Database:** The database is where the results of the source code analysis, as well as project settings, are stored. By default, this is a project's ".udb" file.

**Entity:** An *Understand* "entity" is anything it has information about. In practice this means anything declared or used in your source code and the files that contain the project. Subroutines, variables, and source files are all examples of entities.


**Project:** The set of source code you have analyzed and the settings and parameters chosen. A "project file" contains the list of source files and the project settings.

**Relationship:** A particular way that entities relate to one another. The names of relationships come from the syntax and semantics of a programming language. For instance, subroutine entities can have "Call" relationships and "CalledBy" relationships.

**Script:** Generally a Perl script. These can be run from within *Understand's* GUI, or externally via the "upperl" command. The *Understand* Perl API provides easy and direct access to all information stored in an Understand database.

## Parts

The following figure shows some commonly used main parts of the *Understand* graphical user interface (GUI):




## Starting Understand

When you install *Understand* on Windows, a command to launch the software is added to your Windows **Start** menu in the SciTools folder.

When you start *Understand*, you see the **Getting Started** tab in the Understand window. To begin creating a new project, click **New Project...** and see *Creating a New Project* on page 34 for details.

If you've used a project recently, it is listed in the Getting Started tab, and you can click to open it. If the existing project you want to open isn't listed, click **Open Project...** and browse for it.



You can also choose **File > Open > Project** and **File > Recent Projects** from the menus to open projects.

If you are learning about *Understand*, use the links in the **Getting Started** box. You can click **Open Sample Project** and choose an example project that uses a source code language used in your own projects.

If you are a more experienced *Understand* user, use the links in the **News & Announcements** box to keep your knowledge current.

If you have closed the Getting Started tab and want to reopen it, choose **Help > Getting Started** from the menus. If you don't want to see the Getting Started tab every time you run *Understand*, uncheck the **Show on Startup** box.

When you are finished using a project, you can open another project or choose **File > Close <project\_name>.udb**. You will be asked if you are sure you want to close the project. If you have made any changes to files, you will be prompted to save or discard the changes for each file individually.

If you want to make sure you have installed the latest version of *Understand*, you can choose **Help > Check for Updates** from the menus. (You'll see the **Get New Version** button in the Getting Started tab if a new version is available.)

---

## Other Ways to Run Understand

For information on running *Understand* from the command line, see Chapter 14, Command Line Processing.

If multiple users will run *Understand* from the same Windows machine, each user may have a separate initialization file. These files store user preferences. *Understand* looks for the initialization file location in the following locations, depending on the operating system (on Windows, this location is referenced by the WINDIR environment variable):

- **Windows 2000/XP:** C:\Documents and Settings\USERID\Application Data\SciTools\Understand.ini
- **Windows Vista/7/8:** C:\Users\USERID\AppData\Roaming\SciTools\Understand.ini
- **Linux/Unix:** ~/.config/SciTools/Understand.conf
- **Mac OS X:** ~/Library/Preferences/com.scitools.Understand.plist


## Context Menus Are Everywhere

Right-clicking gets you a long way in *Understand*; almost everywhere you point, you can learn more and do more by bringing up menus with your right mouse button.


For example, if you right-click on an entity in the Source Editor, you see the list of commands shown here.

Hold down the Ctrl key while right-clicking to create new windows rather than re-using existing ones.

Remember to right-click, anytime, anywhere, on any entity to get more information about that entity.



Right-clicking on an entity in the filter area and the Information Browser provides the following lists of options:



## Quickly Find Things in Your Source


*Understand* provides several ways to quickly locate items of interest in your source code. These features include the Filter Area, the Entity Locator, and the Find in Files dialog.

### Entity Filter

The filter area of the *Understand* window helps you quickly find things in your code by separating that database into lists of Files, Classes, Functions, Objects, Types, Macros, Subprograms, Packages, Modules, Blocks, Methods, Interfaces, SQL Tables, and more. The types of filters available depend on the languages you have configured your *Understand* project to understand.

After clicking in the filter area, you can type a letter to move to the first entity beginning with that letter in the current list.

By default, the *Information Browser* shows all known information about the selected entity. It is a key to navigating in *Understand*.




For details, see *Entity Filter* on page 131 and *Information Browser* on page 133.



## Entity Locator

The filter provides a quick way to find major items that were declared and used in your project. However, some items such as local parameters, variables, undefined (never declared or defined), and unresolved variables (declared but not defined) are not listed in the filters. To search or browse the entire database for your project, use the *Entity Locator*.

To open the *Entity Locator*, choose **View > Entity Locator**.



By default, this area lists all the entities in the project. You can search for entities matching a particular text or regex string using the fields above each column.

For details, see *Entity Locator* on page 157.


As in any other window, the context menu is also active.

You can select multiple rows and columns and copy their contents to the clipboard. When you paste, the contents will be pasted as tab-separated text.

## Instant Search

Instant Search lets you search your entire project instantly, even if it contains millions of lines of source code. As you type, you can see terms that match the string you have typed so far.

A number of powerful search options are supported with Instant Search. See *Instant Search* on page 150.




## Find in Files

Similar to the Unix command *grep*, you may search files for the occurrence of a string. Select **Find in Files** either from the **Search** menu or from a context menu.

When you click **Find**, a list of all occurrences matching the specified string or regular expression is displayed in the *Find Results* window. Double click on any result to display the *Source View* where the string occurs.

The options let you set behaviors such as case-sensitivity and wildcard pattern matching.


See *Find in Files* on page 152 for more information.



## Favorites

You can place entities and code locations that you often use on your Favorites list. To add a favorite, right-click on it and select **Add to Favorites** along with the name of the list to contain this item.

To see the Favorites list, choose **View > Favorites** and the name of the list to open.



See *Favorites* on page 144 for more information.


## Information Browser

Just about everything *Understand* knows about code is shown in the Information Browser (IB). The IB is used for all types of entities.

The Information Browser shows different things depending on the type of entity selected.

It shows different kinds of information about entities such as source files, classes, members, functions, types, methods, packages, interfaces, and more. Information that is hierarchical in nature (such as a call relationship) can be expanded multiple levels.

Below are Information Browser windows for a file and a C function:




For details, see *Information Browser* on page 133.

## Source Editor

*Understand* has a source editor that not only lets you edit your source code, it colorizes the source code and tells you about the code you are editing.

Source can be visited by double-clicking almost anywhere else in the tool. You can move forward or backward through such “visits” by using the **Next** and **Previous** icons in the toolbar.




As with any other place in *Understand*, a context menu is available throughout the editor. To learn about something just right-click on it to see what information is available.

For details, see *Source Editor* on page 168.

## Architecture Browser

The Architecture Browser allows you to manage *architectures*. It shows a list of all the defined architectures in the database and provides a way to navigate individual architectures.

For example, this window shows the auto-architectures provided with *Understand*: Calendar, Directory Structure, Languages. The architectures are expanded somewhat here to show the top-level nodes for an example application.



You can use the auto-architectures, create your own architectures, import and export architectures (as XML files), generate graphs and metrics for any level in an architecture hierarchy, and combine architectures through filtering.


For details, see *About Architectures* on page 194.

## Graphical Views

*Understand* analyzes your software code and creates a database containing information about the entities and the relations between entities. The database can then be browsed using various “graphical view” windows. The graphical views are divided into these kinds:

- **Hierarchy** views show relations between entities. Each view follows a relation (for instance “Calls”) from the starting entity (that you inquired about) through its children and successors.
- **Structure** views quickly show the structure of any entity that adds to the structure of your software (for instance a package, function, procedure, or task).

Examples of each type are shown in the following figure:



For details, see *Using Graphical Views* on page 248.

## ASCII and HTML Reports

Views in *Understand* provide information about individual entities. The reports bundle information about all entities in ASCII or HTML format.

### Understand

### Table of Contents

[\(Index\)](#)

---

[Data Dictionary](#)

[File Contents](#)

[Program Unit Cross Reference](#)

[Object Cross Reference](#)

### Program Unit Cross Reference

Non-Alpha	<a href="#">A</a>	<a href="#">B</a>	<a href="#">C</a>	<a href="#">D</a>	<a href="#">E</a>	<a href="#">F</a>	<a href="#">G</a>	<a href="#">H</a>	<a href="#">I</a>	<a href="#">J</a>	<a href="#">K</a>	<a href="#">L</a>	<a href="#">M</a>	<a href="#">N</a>	<a href="#">O</a>	<a href="#">P</a>
-----------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------

```

alternate      (Function)
  Declared as: char *
    Declare    [egrep.c, 137]
    Call       [egrep.c, 259]
    Define     [egrep.c, 707]
                                     egrep.c
                                     main
                                     egrep.c

atoi          (Unknown Function)
  Call         [timer.c, 61]
                                     main
  Call         [timer.c, 62]
                                     main
  Call         [timer.c, 63]
                                     main

```

The HTML and ASCII reports also show information not available interactively, such as project metrics and quality reports. These reports are suitable for printing or browsing with a web browser.

See *Using Reports* on page 209 for more information.

## APIs for Custom Reporting

*Understand* data is also available directly from scripts and programs that you (or we) write. A C API (usable from C, C++ or other languages that can call C libraries), a Python interface, a Java interface, and a Perl interface are provided with *Understand*.

Using the API, you have exactly the same access that we have when we write the existing GUI and report generators.

This manual doesn't cover the APIs. Choose **Help > PERL API Documentation** or **Help > Python API Documentation** for more information. Java API documentation is provided in the doc/manuals/java subdirectory of the *Understand* installation. Tutorials for the APIs are available online at [scitools.com/api-tutorials/](http://scitools.com/api-tutorials/).

The **Reports > Project Interactive Reports** and **Graphs > Project Graphs** commands display a list of user-created plugins, which can be created using the Perl API. For information about creating plugins, please contact [support@scitools.com](mailto:support@scitools.com). The SciTools Support website at [www.scitools.com/support](http://www.scitools.com/support) contains related information in the "API/Plugins" category.

This chapter shows how to create new *Understand* project files that you will use to analyze your source code.

This chapter contains the following sections:

Section	Page
About Understand Projects	33
Creating a New Project	34
Project Configuration Dialog	39
Languages Category	41
Files Category	43
File Types	49
File Options	50
Scheduled Activities	51
Metrics	53
Reports	55
Visual Studio	58
Annotations	61
Ada Options	63
Assembly Options	67
Visual Basic Options	68
COBOL Options	69
C++ (Fuzzy) Options	71
C++ (Strict) Options	78
C# Options	83
Fortran Options	84
Java Options	87
JOVIAL Options	89
Pascal Options	91
PL/M Options	93
Python Options	94
VHDL Options	95
Web Options	96
Setting General Preferences	98
Analyzing the Code	123



## About Understand Projects

*Understand* is like a compiler, except it creates information, not executable code.

In order for *Understand* to analyze your source code, it needs much of the information your compiler needs. It needs to know:

- What source files to analyze
- The type of source code
- The standard library paths and include directories
- Where to find Java .jar files that provide classes for which you do not have source code
- Compiler/environment specific macros that need to be defined for the pre-processor
- Application-specific macro definitions
- What implementation parameters (such as integer precision) and column truncation settings to use
- Any namespaces

If you developed the program or have been working with it for some time, this information is probably obvious to you. However, if you inherited this source code from another programmer, team, or company, you will probably have to examine the project building files (for example, a makefile) in order to come up with the information needed for accurate analysis of the code.

The easiest way to analyze your code is to use *Understand*'s GUI to build and analyze a project. This chapter will walk you through that process.

---

### **The *Understand* Project Database**

The *Understand* project database is stored in a proprietary binary format. The file format uses a network/object format that is optimized for storing *Understand* information.

*Understand* databases have a file extension of \*.udb.

The project database permits multiple simultaneous read accesses, but it does not support multi-user write access. You will see a message if the project database is locked.

Occasionally, a new feature to *Understand* requires a change to the database format. Such changes are noted in the Change Log. When you install a build that modifies the database format, existing projects are automatically re-analyzed when you open them.

## Creating a New Project

To begin analyzing code, you create a project and specify what source files to analyze. *Understand* analyzes your code and creates a database you can browse. This database can be refreshed incrementally in the GUI or updated using command-line tools.

This section shows how to create a new project. The project will be stored in a *Project Database*, which has a file extension of *.udb*.

To create a new project, follow these steps:


- 1 Click the **New Project** link in the Getting Started tab that you see when you start *Understand*. Or, choose **File > New > Project** from the menus.
  - By default, this opens the New Project Wizard, which is described on page 34.
  - Alternately, you may have disabled the option to run this wizard, in which case, you see the “Create new project as...” dialog. Browse to the folder where you wish to create the project database. Type the name of the project in the **File name** field. A \*.udb file extension will be added automatically. Click **Save**. You will see the Understand Project Configuration dialog, which is described in page 39.
  - Another way to create a project is to add Buildspy to your gcc/g++ build process. This automatically generates an *Understand* project when you compile your project. See *Using Buildspy to Build Understand Projects* on page 332.

---


### New Project Wizard

Unless you have disabled the New Project Wizard, this is the tool you use to create projects. To open it, click the **New Project** link in the Getting Started tab that you see when you start *Understand*. Or, choose **File > New > Project** from the menus.

- 1 In the Create a Project File page of the wizard, type a **Name** for the project and browse for a directory to contain the *Understand* project files. It is often handy to have the project file in the top-level directory of the source code, but this is not required. If the directory does not exist, you are asked if you want it created.




- 2 Click **Next** to see the Languages page of the wizard. The defaults for this and other configuration categories are the most recent settings you saved for another project.




- 3 Put checkmarks next to languages used in the source code for this project. See *Languages Category* on page 41 for more information about specific languages and the strict C/C++ option. Then click **Next**.
- 4 If one of your language choices was C/C++, C#, or Fortran, choose the way you want to add source files to this project. Then click **Next**.
  - For all languages, source files can be **added manually**. In addition, you can manually specify the include paths and macro definitions used by the project. Directories can be “watched” so that you can keep the source code and your *Understand* project synchronized.
  - For C/C++, C#, and Fortran, you can choose to **import a Visual Studio project**. By default, the *Understand* project will continue to be synchronized with the Visual Studio project, but you can check the box at the bottom of this dialog if you do not want the *Understand* project to be synchronized.
  - For C/C++, you can choose to **import a CMake project**. These are usually stored in `compile_commands.json` files generated by the Unix makefile and other generators. By default, the *Understand* project will continue to be synchronized

with the CMake project, but you can check the box at the bottom of this dialog if you do not want the *Understand* project to be synchronized.




- 5 If you selected the **Import Visual Studio project files** option, you see the Visual Studio File(s) page. Otherwise, skip to the next step.




To synchronize your Understand project with Visual Studio projects, click **Add**. In the Add a new Visual Studio file dialog, click ... and browse for your Visual Studio project file. In the Add a new Visual Studio file dialog, select the project configuration you want used when *Understand* analyzes your project. Then click **OK**. See *Visual Studio* on page 58 for more information.

You can add multiple Visual Studio projects or use the **Edit** button to change the Configuration setting. Then click **Next**.

- 6 If you selected the **Import CMake compile command database files** option, you see the CMake File(s) page. Otherwise, skip to the next step.




- 7 Click **Add** and select a `compile_commands.json` file. The text in the left panel of the CMake File(s) page explains how to enable generation of the compile commands database file with CMake. You can add multiple files as needed. Then click **Next**.
- 8 In the Source Files page of the wizard, you add source files to a project by clicking **Add a Directory** or **Add a File**.



The **Portability** button lets you choose whether file paths will be stored using absolute paths, relative paths, or user-defined root path variables. See page 48.

To add a file, just browse for the file and add it.


When you add a directory, you can browse for a directory, modify the list of languages used in the source files, add additional filters for file extensions not expected by *Understand*, filter out any files you want to exclude (for example, temp\*.\*), and choose whether all the subdirectories of this directory should be added. You can also choose whether the directory will be watched for changes. See *Adding Directories* on page 44 for details.



If you already chose a Visual Studio project, those files are automatically listed in the Source Files page of the New Project Wizard.

If you want to delete a file or a directory (and its subdirectories), select that item and click the “X” icon. Click **Next** when you have finished selecting files and directories.

- 9 Choose whether to **Analyze project now** or further configure the project. Choosing **Configure more settings** takes you to the Project Configuration dialog, which is described starting on page 39. In either case, you can go to the Project Configuration dialog anytime you like.






## Project Configuration Dialog

The Understand Project Configuration dialog opens when you create a new project or when you choose the **Project > Configure Project** menu item.

The categories on the left in the Project Configuration dialog allow you to specify various project settings to be used during analysis. The Project Configuration dialog contains the following categories:


- **Languages:** Set the types of languages to be analyzed. For details, see *page 41*.
- **Files:** Set the locations of source files to be analyzed. For details, see *page 43*.
- **File Types:** Set how to handle source file types and what file extensions are used. For details, see *page 49*.
- **File Options:** Set the file encoding and editing mode for source files. For details, see *page 50*.
- **Scheduled Activities:** Schedule events to take place at regular intervals. For details, see *page 51*.
- **Metrics:** Select the metrics you want computed for this project. For details, see *page 53*.
- **Reports:** Select reports you want generated. For details, see *page 55*.
- **Visual Studio:** Select a Visual Studio project to synchronize this *Understand* project with. For details, see *page 58*.
- **CMake:** Select a CMake compile commands database file to synchronize this *Understand* project with. For details, see *page 60*.
- **Annotations:** Set how to store and display annotations. For details, see *page 61*.
- **Language-Specific Options:** Set options for the languages you selected in the Languages category. For details, see:
  - Ada Options, *page 63*
  - Assembly Options, *page 67*
  - Visual Basic Options, *page 68*
  - COBOL Options, *page 69*
  - C++ Fuzzy Options, *page 71*
  - C++ Strict Options, *page 78*
  - C# Options, *page 83*
  - Fortran Options, *page 84*
  - Java Options, *page 87*
  - JOVIAL Options, *page 89*
  - Pascal Options, *page 91*



- PL/M Options, *page 93*
- Python Options, *page 94*
- Web Options, *page 96*

For advice about ways to adjust the project configuration to improve the accuracy of project analysis, see the [SciTools website](#).

After you change the project configuration, click the **OK** button and the configuration will be saved. Whenever you modify the files in the project configuration, including at the time of project creation, a dialog alerting you to the change in configuration appears.



Click **OK** and *Understand* begins analyzing (also called parsing) the code (page 123).


If you want to close the Project Configuration dialog without saving any changes, click **Cancel**, and then click **Yes** in the box that asks if you really want to cancel changes.

If you want to make a copy of the current configuration, for example to create two variants of one configuration, choose **File > Save project.udb As**. This makes a copy of the \*.udb file and modifies uses of the database name within the configuration as needed.




## Languages Category

In the **Languages** category of the Project Configuration dialog, you can check boxes for the languages used in your project. A project can contain source code in one or more languages.



For more information about language support for a particular language, hover your mouse cursor over the language name.



When you select a language, categories for that language are added to the list on the left in the Project Configuration dialog. The languages you choose here not only affect how the source files are analyzed. They also affect the filter types available, the metrics available, and the report types available.

If you select multiple languages, references between those languages are analyzed. For example, if C code calls a Java function, that reference will be found.

If you have C or C++ code, you can decide to use either the default C/C++ analyzer (the “fuzzy” analyzer) or the newer “strict analyzer”. To use the strict analyzer, check the **Strict** option next to C/C++. Internally, checking this box causes a completely separate analyzer to be used to analyze your C/C++ code.

The “strict C/C++ analyzer” provides the following features:


- Support for Objective C and Objective C++ (used for Mac OS and iOS) is provided with the strict analyzer, but not with the fuzzy analyzer.
- Provides better support for Templates.
- Provides better support for Overloaded functions.

The default C/C++ analyzer aims to use fuzzy logic to handle incomplete, non-compiling code gracefully and as accurately as possible. The new analyzer is more strict than the old analyzer and requires a more accurate project definition—for example, by specifying all include paths and macro definitions and including only those files in the project that are used in the software build. For details, see the [Creating Accurate C/C++ Projects](#) web page.

If you are using the strict analyzer, see *C++ (Strict) Options* on page 78 for how to configure your project.

## Files Category

In the **Files** category of the Project Configuration dialog, you can add source code directories and/or individual files to the project. You can also delete specific files from the analysis and modify language-specific options for individual directories and files.



You can add source files here, or you can tie the project to those specified in an MS Visual Studio project file (MS Windows versions of *Understand* only). See *Visual Studio* on page 58.

The top area shows the directories and files you have added in a tree that you can expand. It also shows how many files are currently in the project.








The bottom area shows any overrides you have set for the selected directory or file.

Click **Portability** to set portability options for file paths. See page 48.

Click **Rescan** if you have added files to a directory that are not shown in this dialog.

Right-click for options to remove a directory, expand or collapse the directory tree, rescan the directory for changes, and configure the override settings.

Icons at the top of the dialog perform the following actions:


-  Open the Add a Directory dialog.
-  Open the Add a File dialog.
-  Choose Add a File or import a list of files
-  Delete the selected directory or file from the project analysis.
-  Copy the override settings for the selected directory or file.
-  Paste the override settings to the selected directory or file.
-  Configure override settings for the selected directory or file.

Note that your changes are not saved until you click **OK**.

---



## Adding Directories

To add source directories to the project, click . You see the Add a Directory dialog:



- 1 In the **Directory** field, type the full directory path. Or, you can click the ... button and use the Browse for Folder dialog to locate a directory containing source files and click **OK**.
- 2 In the **Configured Filters** field, click the ... button if you want to add or delete languages from the list shown. In the Select Filters from Configured File Types dialog, put a checkmark next to any languages you want to be recognized as part of the project. Notice that additional languages are listed beyond those shown in the Languages category. These include Basic, MSDos Batch, Perl, Tcl, Text, and Verilog.

If this directory contains source files with extensions that are not listed, click **Configure**. Also, see *File Types* on page 49. For example, you might add \*.a64 as an assembly file type.


- 3 In the **Additional Filters** field, type a pattern-matching string that matches only the files you want to keep in the analysis. For example, `std*.*` includes only files that begin with “std”. You can separate filters with a comma.
- 4 In the **Exclude** field, type a pattern-matching string that matches files you want to exclude from the analysis. For example, `temp*.*` excludes all files that begin with “temp”. You can separate filters with a comma.
- 5 To select and add multiple subdirectories to a project configuration, check the **Include subdirectories** box (on by default). This causes all source files matching the filter in all subdirectories of the specified path to be added to the project.
- 6 If you want this directory to be watched for any new files or deleted files, check the **Watch this directory** box. Whenever a source file is added to or deleted from this directory, the change is reflected in this project. Watched directories are indicated by the  icon in the files list. Directories excluded from being watched are indicated by the  icon. By default, the subdirectories of a watched directory are also watched. See page 46 for watch setting overrides.
- 7 After you have set the fields, click the **OK** button to add the source files in that directory to the project. You can click **Cancel** if the add file process is taking too long.



**Tip:** You may add files from multiple directory trees.

If you are using Microsoft Windows, you may drag and drop a directory, a file, or a selection of files, from another window into the Project Configuration dialog to add it to the project. If you drag a folder, the Add a Project Directory dialog opens automatically. If you drag an individual file, that file will be added to the project whether it matches the file filter or not.


All directory paths are absolute.

## Adding Files

To add individual source files to the project, click . You see a file selection dialog, which allows you to select one or more source files to add to the project. Browse for and select a file or files. Then click **Open**. The file(s) are added to the project.

If you click the  down arrow next to the  icon, you can choose to import a text file that contains a list of source files to import. For example, you might generate such a file from a compiler application or code management system. The file should contain one absolute file path per line. See *Adding Files to a Project* on page 325 for an example of such a file.

## Removing Directories and Files


To remove a directory or file from the project, select the items you want to remove and click . The directory or file itself is not deleted from the file system.


You can right-click on a removed file or directory and choose **Add file to project** or **Add directory to project** to re-add it to the project.

## Setting Overrides

Normally, each file in the project is processed according to the rules you specify in the Project Configuration window for the language of the file. For example, for C++ you can set include directories and macro definitions. However, you can override the default settings on a directory-by-directory or file-by-file basis if you like.

**Directory:** To override settings for a directory, follow these steps:


- 1 Select a directory.
- 2 Click  or right-click and select **Configure override settings**.




- 3 In the **Watched Properties** category, you can choose how files in this directory should be watched for new files to add to the project or deleted files to remove from the project. For **Watch Settings**, you can choose to watch a directory, not watch a directory, or inherit watch settings from the parent directory. In addition to specifying whether to watch a directory, you can set filters and exclude filters for an individual directory that control what types of new and deleted files will be found.
- 4 In the various **Override** categories, you can make directory-specific language-related settings. The list of categories depends upon the languages enabled in your project.




The **File Type** category lets you override the language of this file indicated by the file extension. The **File Encoding** category lets you override the encoding setting described in *File Options* on page 50.

**File:** To override settings for a file, follow these steps:

- 1 Select a file.
- 2 Click  or right-click and select **Configure override settings**.



- 3 In the various **Override** categories, select a category and make changes. The categories available are different depending on the language of the source file. See page 63 through page 93 for details. The **Watched Properties** category is available for file overrides if you are using Relative or Named Root portability.
- 4 Click **OK** to save your overrides.

Special icons in the directory tree indicate which directories are being watched , have overrides , or both .

The various **Override** categories have an **Ignore Parent Overrides** checkbox. Checking this box makes only the override settings you apply at this level (directory or file) apply; settings from higher levels are not inherited.

## Scanning Watched Directories

If you set directories to be watched, you can scan those directories for new files to be added or deleted files to be removed by choosing **Project > Rescan Project Directories**.


If files are found that you don't want to include in the project, uncheck the boxes next to those files to exclude them from the project configuration.

Directories that you include in the project are automatically scanned for new files when you use **Analyze All Files** to analyze the project.

You can schedule automatic scans of watched directories. See *Scheduled Activities* on page 51 for details.

**Setting File  
Portability**

You can control the portability of *Understand* projects by clicking the **Portability** button at the top of the **Files** page of the Project Configuration dialog. You will see the following dialog.



A more portable project can allow you to share the project with other users and to use the project unchanged after moving the source code files.

The choices are as follows:


- **Absolute:** This option is the default. It stores full file paths for all directories. If the source files change location, the paths will be incorrect.
- **Relative:** This option stores the relative path to directories from the location of the *Understand* project database. If you store the project database in the source file tree and move it along with the source files, the project can still be used.
- **Named Root:** This option allows you to specify "Named Roots" that are similar to environment variables to point to a root directory. Different users may then use different definitions for a named root. Click the **Edit Named Roots** button and see page 109 for details.

Check the **Use File Portability Mode to convert paths** box if you want all the file paths currently stored in the project to be updated when you click **OK**.



## File Types


In the **File Types** category of the Project Configuration dialog, you can control how file extensions are interpreted by *Understand*.



The list shows all the file extensions already understood. Files with the types understood for the languages you checked in the Languages category are analyzed as part of the project. Other file types are not analyzed.

To modify an existing type, select the type and click **Edit**.

To add a file extension to the list, click **New**. Type a file extension and select the language to use for the file extension. Then click **OK**.




The file extension you type should begin with the period. It can contain simple \* and ? wildcards.

Certain file types may be interpreted differently depending on the languages you selected. For example, in a Visual Fortran project, .h files are interpreted as Fortran files, rather than as C headers files.

## File Options


In the **File Options** category of the Project Configuration dialog, you can control how files are opened and saved by *Understand*.



- **File Encoding:** Select the type of encoding to use when saving source files. Many encoding formats are supported. You should change this only if your other applications have problems opening or displaying files saved by *Understand*. See *Editor Category* on page 111 for more information. The default file encoding is “System”, which means the default encoding for your computer. If you change the setting here, new projects you create use the last setting you saved. You can override the file encoding setting on a file-by-file or directory-by-directory basis (see *Setting Overrides* on page 46).
- **Open all project files as read only files:** Check this option if you do not want files to be edited and saved within *Understand*.
- **Maximum size for files to be analyzed:** Limits the size of files analyzed by *Understand*. You can use this option to exclude very large files. The default is 10 MB. An error message is provided if you attempt to edit a file that is too large to open.

## Scheduled Activities

In the **Scheduled Activities** category of the Project Configuration dialog, you can cause certain events to be performed on a regular basis. You can also open this dialog quickly by choosing **Tools > Scheduler > Scheduled Activities — <project\_name>**.



To schedule events for the project you currently have open, follow these steps:


- 1 Check the **Process At** box.
- 2 Select either a processing time, a processing interval, or to not process events. For a processing time, check the boxes for one or more days of the week. For a processing interval, specify a number of minutes up to 1440 (24 hours).
- 3 Check the boxes for the events you want performed. The events occur in the sequence shown. For example, watched directories are scanned before the project is analyzed, and the project is analyzed before metrics are processed.

**Note:** *Understand* must be running at the processing time or the events will not occur.

The following activities are available for scheduling:

- **Rescan watched directories:** Check this box to automatically check for files that have been added to or deleted from project directories. See *Adding Directories* on page 44 for how to specify which directories to watch. If you have watched directories, you should always run this task before the “Analyze all files” task. To run this action without scheduling it, choose **Project > Rescan Project Directories**.
- **Analyze all files:** Check this box to automatically analyze all project files as described in *Analyzing the Code* on page 123. Run this task before generating any metrics so that the statistics will reflect the current state of the project. To run this action without scheduling it, choose **Project > Analyze All Files**.
- **Analyze changed files:** Check this box to automatically analyze any project files that have changed as described in *Analyzing the Code* on page 123. Run this task before generating metrics so that statistics will reflect the current state of the project. To run this action without scheduling it, choose **Project > Analyze Changed Files**.
- **Metric processing:** Check this box to automatically calculate project metrics. The metrics selected in *Metrics > Selected Category* on page 54 are processed. Run this task if you plan to schedule either of the following metrics export tasks.
- **Metric CSV export:** Check this box to automatically export metrics as a comma-separated value file. If this box is checked, you can select the directory path and output filename for the export. By default, any existing file with the same name is renamed to provide a backup. You can check the **Overwrite** box if you simply want to replace the old export file. To further configure the export, see *Metrics* on page 53. To run this action without scheduling it, choose **Metrics > Export Metrics** and see *Exporting Metrics to a CSV File* on page 237.
- **Metric export HTML:** Check this box to automatically export metrics as web pages. If this box is checked, you can select the directory path for the export. By default, any existing file with the same name is renamed to provide a backup. You can check the **Overwrite** box if you simply want to replace the old export file. To run this action without scheduling it, choose **Metrics > Project Reports** and see *Exporting Metrics to HTML* on page 236.

When scheduled activities are about to run, you see a dialog that gives you a chance to cancel the action. You can avoid this message by checking the **Suppress Scheduler MessageBox** in the configuration.




If you schedule activities, you see a message that asks if you are sure you want to prevent the scheduled activities from running when you exit *Understand*.

To see a list of all projects for which you have scheduled activities, choose **Tools > Scheduler > Scheduled Activities — All Projects**. To change these times, you must open the project and then use the Project Configuration dialog for that project.

## Metrics

In the **Metrics** category of the Project Configuration dialog, you can control how metrics are generated when a CSV file is exported. These options set the defaults for both manual updates (page 237) and scheduled automatic updates (page 51).

The Metrics category has two sub-categories: **Options** and **Selected**.




You see this window when you choose the **Project > Configure Project** menu item and then the **Metrics** category. If you attempt to generate metrics before configuring metrics, this window opens automatically.

The **Options** subcategory has the following fields:

- **Output file:** Specify the location and name of the file you want to use for metrics output. *Understand* sends its metrics output to a \*.csv (comma-separated values) file. This file can be opened with Microsoft Excel and other spreadsheets.
- **Show File Entities Name as:** Specify whether files should be displayed with **Short** names (just the filename), **Full** names (including the absolute path), or **Relative** names (relative directory path).
- **Show Declared in File:** Check this box if you want the file in which each entity is declared to be included in the output. You can specify whether you want these files displayed with **Short** names, **Full** names, or **Relative** names.
- **Show Function Parameter Types:** Check this box if you want the type of each function parameter listed.
- **Write Column Titles:** Check this box if you want column headings in the CSV file.

## Metrics > Selected Category

The **Selected** subcategory has lists like the following:




- 1 In the **Available Metrics** list (left), select metrics you want to include in the output you generate. You can hold down Shift to select a continuous group or Ctrl to select discontinuous items.
- 2 Click **Add** to copy the selected metrics to the right column.
- 3 You can reorder the metrics in the right column using the **Move Up** and **Move Down** buttons.

The metrics available depend on the languages used in your project. See [scitools.com/support/metrics\\_list/](http://scitools.com/support/metrics_list/) for descriptions.

## Reports

In the **Reports** category of the Project Configuration dialog, you can control how reports are generated. The Reports category has the following sub-categories: **Output**, **Options** and **Selected**.



This window opens if you choose the **Project > Configure Project** menu item and then the **Reports** category. You can also reach this window by clicking **Configure** in the Project Reports window.

You can control the colors and font styles in HTML reports as described in *Customizing Report Colors* on page 212.

### Reports > Output Category

The **Output** subcategory has two main areas:

- **Generate HTML:** This option causes the report generation to create a large group of HTML files that are interlinked.
  - You may generate **Single** or multiple HTML files for each report type. It is recommended that you split up the files for large projects. Choose **Alphabetic** to generate multiple HTML files per report that are split up alphabetically by the first letter of the entity name. Choose **Every n Entities** to generate multiple HTML files per report that are split up every "n" number of entities. By default, a single HTML file is generated for each letter of the alphabet.


- The “home” page for reports is index.html. You can select an alternate **Title Page**.
- The default **Save in directory** is the `<proj_file>_html` folder below the folder where your \*.udb file is stored, but you can select an alternate location.
- You can choose to clear the contents of the previously generated reports and anything else in the selected directory at the beginning of the report generation.
- **Generate Text:** This option causes the report generation to create simple text files containing the report data.
  - You may generate one text file of the specified location and name (by choosing **Single Text File**). Alternately, you may generate multiple text files (by choosing **Separate Files**) and specify a directory to contain all the files. The file extensions of each text file will denote the separate reports. Depending on which option you select, you can also select either a file or directory location for the output.

You can choose to generate either or both of the HTML and text report formats.

---

### Reports > Options Category

You can use the **Report > Options** category to control the contents and headers of reports.




The **Options** category has the following fields:

- **Display full filenames:** If you check this box, the invocation tree and metrics reports show full entity names. The default is to use short names.
- **Write generation time on report:** If you check this box, the generation date and time are included at the top of text report files. This is on by default.
- **Display parameters:** If you check this box, reports that list the names of functions and similar entities also include any list of parameters declared for that function.
- **Index by method name:** If you check this box, entities are sorted in the data dictionary, index, and reports by their short names, rather than full names (for example including the class path).
- **Left aligned text:** If you check this box, the text “Report generated by Understand” will be printed in the upper-left corner of each page of the text report.
- **Right aligned text:** If you check this box, the text you provide will be printed in the upper-right corner of each page of the text report. This text can be up to 45 characters.



## Reports > Selected Category


The **Selected** subcategory lets you check the boxes for the reports you want to generate. The list of reports differs depending on which languages are used in your project. See Chapter 8 for descriptions of these report formats.



## Visual Studio

In the **Visual Studio** category of the Project Configuration dialog, you can tell *Understand* to use the source, macro, and include path settings from a Microsoft Studio project file.


You see this window when you choose the **Project > Configure Project** menu item and select the **Visual Studio** category.



Follow these steps:

- 1 Click **Add**.
- 2 In the **Add a new Visual Studio file** dialog, click the "..." button next to **Visual Studio File**. Then browse to select a Visual Studio project file and click **Open**. MS Visual Studio project files with extensions of .csproj (C# project), .dsp, .dsw (workspace file), .sln, .vcp (Windows CE project), .vcproj (Visual C project), .vcxproj (VS2010 project), .vfproj (Visual Fortran project), and .vcw (workbench file) are supported.
- 3 Select the **Configuration** you want *Understand* to use when analyzing your project. You can select a project configuration or a solution configuration.
- 4 You can type an **Exclude Filter** to specify file extensions to exclude when importing a Visual Studio project.

- 5 You can expand the **Unfiltered Contents** list to see the includes, defines, and files for the configuration currently selected.



- 6 Click **OK** to add this to your project.

**Note:** If you sync with a Visual Studio workspace file, the default target is used because there is no mechanism for specifying targets for each .dsp project within a .dsw file.


Once set, the source files, macros and include paths from the Visual Studio project are used by *Understand*. This is in addition to any project settings you configure in the other categories.

**Note:** Settings in other categories for include path and macros take priority over the Visual Studio project settings. This permits you to use the bulk of the Visual Studio settings while selectively overriding as your needs require.

## CMake

In the **CMake** category of the Project Configuration dialog, you can tell *Understand* to use the source, macro, and include path settings from a compile commands database file generated by CMake or other generators that work with Unix makefiles. These files are usually called `compile_commands.json`.

You see this window when you choose the **Project > Configure Project** menu item and select the **CMake** category.



To cause your CMake project to generate the compile commands database, set the `CMAKE_EXPORT_COMPILE_COMMANDS` variable in your CMake variable cache. You can do this by running the following command:


```
cmake -DCMAKE_EXPORT_COMPILE_COMMANDS=ON ...
```

Then, in *Understand*, follow these steps:

- 1 Click **Add**.
- 2 In the **Open Compile Command Database** dialog, browse for and select your `compile_commands.json` file. Click **Open**.
- 3 You can optionally type an **Exclude Filter** to specify file extensions to exclude when importing a CMake project.

## Annotations

The **Annotations** category of the Project Configuration dialog lets you control how annotations are stored and displayed. See page 186 for details on using annotations.



- **Author:** Type your name or the username you want to be associated with the annotations you create.
- **Add Files:** Click this button to browse for an existing annotation file (\*.ann). For example, you might want to add files created by other developers of this project so that you can see everyone's annotations. (If other developers are also annotating code using Understand, choose **Annotations > Refresh Annotations** from the menus when you want to get the latest annotations they have added.)
- **Create File:** Click this button to create a new annotation file. The default directory is the project directory.
- **Remove File:** Select a file and click this button to remove it from the list of files that are used to display annotations. Removing a file from this list does not delete the file from the file system.
- **Default file:** Select the file that should contain annotations you create.
- **FG:** Click on the colored block to change the text color for annotations in this file.
- **BG:** Click on the colored block to change the background color for annotations in this file.

- **Show inline:** When this box is checked, annotations are shown following the place where the associated entity is defined in the code. You can also turn this display feature on and off by choosing **Annotations > Display Inline** from the menus.
- **Show in hover text:** When this box is checked, annotations are shown if you point to a place where the associated entity is used in the code for 2 seconds. You can also turn this display feature on and off by choosing **Annotations > Display hover text** from the menus.
- **Show indicator:** When this box is checked, the entity has a squiggly line under it wherever it is used in the code. You can also turn this display feature on and off by choosing **Annotations > Display indicator** from the menus.
- **Reload annotations every 60 seconds:** Check this box if other users may be updating the same annotations file. Reloading the annotations file allows you to see the most recent annotations for your project. An annotations file is reloaded only if it has been changed since the last time it was loaded. This option can also be enabled and disabled with the **Annotations > Automatic Reload** menu command.

Annotations are stored in \*.ann files, which use the SQLite database format. In addition to viewing annotations in *Understand*, you can use other applications that support SQLite to modify and search annotation files.

Multiple projects can reference the same \*.ann files. Sharing annotation files across projects allows the same annotation to appear in multiple projects that share one or more source code files.

## Ada Options

In the **Ada > Options** category of the Project Configuration dialog, you can tell *Understand* how to analyze Ada source code. You see this window when you choose the **Project > Configure Project** menu item and select the **Ada** category.

**Compiler**

Version:

Preprocessor:

Standard:

**Multiple Language Linkage**

The case of externally linkable entities is

☒ all lowercase ☐ all uppercase

**Metrics**

☐ Count and/or operators in strict complexity

☒ Count exception handlers in complexity

☒ Count for-loops in complexity

**Optimize**

☐ Create and cross reference record object components

☐ Create relations between formal and actual parameters

☐ Less memory usage versus speed

☒ Save comments associated with entities

**Options**

Display entity names as:

☒ Prompt on parse errors

Main subprograms: (main1, main2..)

Library Directories:

The fields in this category are as follows:

- **Version:** Choose the version of Ada used in your project. *Understand* supports Ada83, Ada95, Ada05, and Ada12.
- **Preprocessor:** Choose which type of preprocessor statements are used in your Ada code. The choices are None, C, Gnatprep, and Verdix. Note that if your source code directories contain a Gnat \*.gpr project file, that file will be analyzed whether or not you select the Gnatprep preprocessor.

- **Standard:** You may choose a directory that contains a standard library used by this project. Default standards are provided in <install\_directory>/conf/understand/ada.

Sometimes it is helpful to analyze code in context of its compilation environment rather than the environment defined as “Standard” in the Ada Language Reference Manual. This is most often needed when your compiler vendor offers bindings to other languages or low level attributes of a chip or system. To do so, place all the source files containing the Ada specifications for the new standard in one directory. Then point to this directory in the **Standard** field.

- **Case of externally linkable entities:** Choose which case should be used for “exporting” entities in this language that can be linked to (for example, called as functions) by other languages. For example, if an entity is declared in this language as “MYITEM” and you choose “all lowercase” here, other languages would be expected to call that entity as “myitem”.
- **Count and/or operators in strict complexity:** Place a check in this box if you also want “and” and “or” operators considered when calculating the strict complexity metric shown in the Program Unit Complexity report. Strict complexity is like cyclomatic complexity, except that each short-circuit operator (“and then” and “or else”) adds 1 to the complexity.
- **Count exception handlers in complexity:** If this box is checked (it is on by default), exception handlers are considered when calculating the complexity metrics shown in the Information Browser and the Program Unit Complexity report.
- **Count for-loops in complexity:** Remove the check from this box if you do not want FOR-loops considered when calculating the complexity metrics shown in the Information Browser and the Program Unit Complexity report. Complexity measures the number of independent paths through a program unit.
- **Create and cross-reference record object components:** If this box is checked (off by default), separate entities are created for components of all parameters and objects of a record type. By default, all references to object components are treated as references to the record type component.
- **Create relations between formal and actual parameters:** Place a check in this box if you want the analysis to create relations between formal and actual parameters. The actual parameters linked to formal parameters include items used in expressions passed as actual parameters. This option is off by default to speed up analysis.
- **Less memory usage versus speed:** Place a check in this box if you want to use *Understand* in a very low memory consumption mode. In order to conserve memory, *Understand* frees memory used to process a program unit if that program unit is not needed. Using this option may slow down operation significantly. It is off by default.
- **Save comments associated with entities:** Choose whether source code comments that occur before and after an entity should be associated with that entity.
- **Display entity names as:** Choose whether entity names should be displayed in *Understand* with the same case as the source code (original), all uppercase, all lowercase, only the first letter capitalized, or mixed case.



- **Prompts on parse errors:** By default, you are prompted for how to handle errors that occur when analyzing files. When prompted, you may choose to ignore that error or all future errors. Turn this option off to disable this prompting feature. If you turned it off during analysis, but later want to turn error prompting back on, check it here.
- **Main subprograms:** Provide a comma-separated list of the names of the main subprograms in the project.
- **Library Directories:** Type a directory path or click **Edit** to browse for the location of a directory that contains Ada libraries. Library files are analyzed as part of a project, but are not included in reports. All subdirectories of the directory you select will also be used to find libraries.

### Ada > Macros Category


Ada code may contain conditional compiler instructions in pragma statements. For example:

```
PRAGMA IF DEVICE == D129
```


The supported pragmas are IF, IFDEF, ELSIF, ELSE, and ENDIF. These pragmas are similar to preprocessor directives such as #ifdef in C code.

For *Understand* to successfully analyze your software it needs to know what macro definitions should be set. For more about ways to configure macro definitions, see *Using the Undefined Macros Tool* on page 127 and the [SciTools website](#).

In the **Ada > Macros** category of the Project Configuration dialog, you can specify what macros to define for use with pragmas. You see this window when you choose the **Project > Configure Project** menu item and select the **Ada** category and the **Macros** subcategory.



The Macros category lists macros and their optional definitions. Each macro may be edited or deleted. To define a macro, click **New**.



Type the name of the macro in the first field and the definition (if any) in the second field. Then click **OK**.

A macro must have a name, but the definition is optional. Macros that have no definition value are commonly used in conjunction with PRAGMA IFDEF statements to test whether a macro is defined.

To change the definition of an existing macro without changing the name, select the macro and click **Edit**.

You can import or export a list of macros and their optional definitions by clicking **Import** or **Export** and selecting the file. The file must contain one macro definition per line. A # sign in the first column of a line in the file indicates a comment. Separate the macro name and its definition with an equal sign (=). For example, `DEBUG=true`.


You can set macros on the und command line with the `-define name[=value]` option.

## Assembly Options

In the **Assembly > Options** category of the Project Configuration dialog, you can tell *Understand* how to analyze assembly source code. You see this window when you choose the **Project > Configure Project** menu item and select the **Assembly** category. Currently the only setting is the assembler. The assemblers supported are:


- Freescale Coldfire 68K
- JIPSE MIL-STD-1750A
- IBM 390

For Coldfire 68K, the **Assembly > Includes** category in the Project Configuration dialog (which you open with **Project > Configure Project**) allows you to specify include directories for assembly code. You can specify multiple directories to search for include files used in the project.



Typically only include files that are not directly related to your project, and that you do not want to analyze fully are defined here. For project-level includes that you want to be analyzed, add those include files as source files in the **Files** category.

To add a directory, click the **New** button and then the ... button, browse to the directory, and click **OK**.



During analysis, the include directories will be searched in the order that they appear in the dialog. You can click **Move Up** or **Move Down** to change the order in which directories will be searched.

For the **System Include Path**, browse to select the directory that contains system include files (include filenames surrounded by < >).

Include files found in regular include directories are added to the project. Include file found in system include directories are not added.

Include paths are not recursively searched; that is, any subdirectories will not be searched for include files unless that subdirectory is explicitly specified in the list of include directories.

You may use environment variables in include file paths. Use the \$var format on Unix and the %var% format on Windows. You can also use named root in include file paths (see page 109).

You can import a list of include directories from a text file by clicking **Import** and selecting the file. The file must contain one directory path per line. (In all such imported text files, a # sign in the first column of a line in the file indicates a comment. Full or relative paths may be used. Any relative paths are relative to the project file.)

---

## Visual Basic Options

In the **Visual Basic > Options** category of the Project Configuration dialog, you can tell *Understand* how to analyze Visual Basic source code. You see this window when you choose **Project > Configure Project** and select the **Visual Basic** category.



The fields in the **Visual Basic > Options** category are as follows:

- **Analyze found reference files:** If this box is unchecked, entities in reference libraries are not counted for the purpose of computing metrics. The default is on.
- **Root Namespace:** Specify the root namespace for this project.


In the **Visual Basic > Imported Namespace** category of the Project Configuration dialog, you can click **New** to name a namespace to be imported or **Import** to select a text list file that contains a list of namespaces to import.

In the **Visual Basic > Preprocessor Symbols** category of the Project Configuration dialog, you can click **New** to specify the name and definition of preprocessor symbols that should be treated as defined when analyzing the project. Use **Import** to select a text list file that contains a list of symbols to import.

In the **Visual Basic > References** category of the Project Configuration dialog, you can click **New** to name a reference to be imported or **Import** to select a text list file that contains a list of references to import.

## COBOL Options

In the **COBOL > Options** category of the Project Configuration dialog, you can tell *Understand* how to analyze COBOL source code. You see this window when you choose the **Project > Configure Project** menu item and select the **COBOL > Options** category.




The fields in the **COBOL > Options** category are as follows:

- **Compiler:** Select the compiler that you use. The options are Ansi85, MicroFocus, AcuCobol, IBM, HP OpenVMS, and Unisys.
- **Format:** Choose whether the source code is in fixed or free format.

### COBOL > Copybooks Category

The **COBOL > Copybooks** category in the Project Configuration dialog (which you open with **Project > Configure Project**) allows you to specify directories that contain files included with the COPY statement. Typically, such files have a \*.cpy file extension. You can specify multiple directories to search for such files used in the project.

Specify directories here if they contain files that are not directly related to your project, and that you do not want to analyze fully. For copybooks that you want to be analyzed, add those files as source files in the **Files** category.



To add a directory, click the **New** button and then the ... button, browse to the directory, and click **OK**.

During analysis, the copybook directories are searched in the order that they appear in the dialog. You can click **Move Up** or **Move Down** to change the order in which directories will be searched.

If you check the **Search for copybook files among project files** box, your project directories will be searched along with any directories you specify here. When searching for a copybook, the search looks in the directories specified in this dialog first. It then searches among the project files if this box is checked.


Copybook paths are not recursively searched; that is, any subdirectories will not be searched for copybook files unless that subdirectory is explicitly specified in the list of copybook directories.

You may use environment variables in copybook file paths. Use the \$var format on Unix and the %var% format on Windows. You can also use named root in copybook file paths (see page 109).

You can import or export a list of copybook directories from a text file by clicking **Import** or **Export** and selecting the file. The file must contain one directory path per line. (In all such imported text files, a # sign in the first column of a line in the file indicates a comment. Full or relative paths may be used. Relative paths are relative to the project file.)

## C++ (Fuzzy) Options

In the **C++ > Options** category of the Project Configuration dialog, you can tell *Understand* how to analyze C and C++ source code. If you selected the **Fuzzy** option for C/C++ in the Languages category, you see the following window when you choose the **Project > Configure Project** menu item and select the **C++** category.



**Compiler**

Compiler: Microsoft Visual C++

Compiler include paths: %include%

☐ Allow nested comments

**Multiple Language Linkage**

Prepend the names of externally linkable entities with:

Append the names of externally linkable entities with:

**Optimize**

- ☐ Create implicit special member functions
- ☒ Create references in inactive code
- ☒ Create references to local objects
- ☐ Create references to macros during macro expansion
- ☒ Create references to parameters
- ☒ Create references in inline assembly
- ☒ Save comments associated with entities
- ☐ Save duplicate references
- ☐ Save macro expansion text
- ☒ Use include cache

(If you selected the **Strict** option in the Languages category, see *C++ (Strict) Options* on page 78 for how to configure your project.)

The fields in the **C++ > Options** category are as follows:

- **Compiler:** Select the compiler/platform that you use. Many different compilers are supported. Your choice affects how *Understand* analyzes the project. Note that not all features of a particular compiler will necessarily be handled.
- **Compiler Include Paths:** Type the path the compiler uses to find include files. For example, %include%.
- **Allow nested comments:** By default, this is off. If turned on it permits C style (*/\* \*/*) comments to be nested. This isn't permitted by the ANSI standard, but some compilers do permit it.

- **Prepend the names of externally linkable entities with:** You may optionally type a string that you want used as a prefix to reference all linkable entities in other source code languages.
- **Append the names of externally linkable entities with:** You may optionally type a string that you want used as a suffix to reference all linkable entities in other source code languages.
- **Create implicit special member functions:** Check this box if you want a default constructor and destructor to be created in the database and given implicit declaration references, if they are not declared in the source code for class and struct entities. This option provides entities for the analyzer to reference when they are called. The default is off.
- **Create references in inactive code:** If you wish to exclude cross-reference information for code that is IFDEFed out by the current macro settings, turn this option off. By default, this option is on and cross-reference information for inactive code is included.
- **Create references to local objects:** By default, all local object declarations are included in the database. If you wish to exclude variables declared within functions from the database, turn this option off. Local objects included for analysis can then be either included or excluded from the HTML output generated. Specify whether to include local objects in the HTML output on the main window of *Understand*.
- **Create references to macros during macro expansion:** Checking this box causes references to be stored during macro expansion. In some cases, this is useful. Be aware that enabling this option can add many references and make the database large and slower. The default is off.
- **Create references to parameters:** If you wish to exclude cross-reference information for parameters, turn this option off. By default, this option is on and all cross-reference information for parameters is included.
- **Create references in inline assembly:** Check this box if you want cross-references to be created to assembly code for any `#asm` preprocessor macros in your code.
- **Save comments associated with entities:** Choose whether source code comments that occur before and after an entity should be associated with that entity.
- **Save duplicate references:** By default, duplicate cross-references are condensed to a single cross-reference. To keep duplicates, check this box.
- **Save macro expansion text:** If you put a check in this box, you can right-click on a macro and choose **Expanded Macro Text** from the context menu to see how the macro expands.
- **Use include cache:** By default, include files are cached during the analysis phase as they are often referenced in multiple source files. This speeds up analysis, but also uses more memory. If you have problems with excessive memory use during analysis, turn this option off. Note that there are also situations where turning the include cache on or off can affect analysis results, particularly where include actions are dependent on where they are included.




## C++ > Includes Category

The **C++ > Include** category in the Project Configuration dialog (which you open with **Project > Configure Project**) allows you to specify include directories. You can specify multiple directories to search for include files used in the project.

The configuration of your include file directories is important to improving the accuracy of project analysis. For more about ways to configure these directories, see *Using the Missing Header Files Tool* on page 125.

Include paths are not recursively searched; that is, any subdirectories will not be searched for include files unless that subdirectory is explicitly specified in the list of include directories.

To add a directory, click the **New** button and then the ... button, browse to the directory, and click **OK**.



During analysis, the include directories will be searched in the order that they appear in the dialog. You can click **Move Up** or **Move Down** to change the order in which directories will be searched.

Typically only include files that are not directly related to your project (such as system-level includes) and that you do not want to analyze fully are defined here. For project-level includes that you want to be analyzed, add those include files as source files in the **Files** category.

You may use environment variables in include file paths. Use the \$var format on Unix and the %var% format on Windows. You can also use named roots in include file paths (see page 109).

You can import or export a list of include directories from a text file by clicking **Import** or **Export** and selecting the file. The file must contain one directory path per line. (In all such imported text files, a # sign in the first column of a line in the file indicates a comment. Full or relative paths may be used. Any relative paths are relative to the project file.)

The **C++ > Include** category provides the following options to control include handling:

- **Add found include files to source list:** Enabling this option causes include files found during project analysis to be added to the project automatically. This allows you to see more detailed information about such include files. The default is off.
- **Add found system include files to source list:** If you choose to add include files that are found to the source list, you can also choose whether system include files should be added. The default is off.
- **Prompt for missing include files:** If any include files cannot be found during analysis, you will normally see the **Include Paths** button in the Analysis Log after

you analyze the project. If you want to be prompted for how to handle missing files during the analysis, you must choose **Tools > Options** and enable the **Allow prompting for missing include files on a per project basis** checkbox in the **Analyze** category (page 108). Then, you will see this field in the Project Configuration dialog. If you then check the **Prompt for missing include files** box, you may choose to add a directory to the include path, ignore the missing file, or stop warning about missing files during the analysis.

- **Search for include files among project files:** This option directs the analyzer to look among project files as a last resort for missing include files. The default is on.
- **Treat system includes as user includes:** This option tells the analyzer to look for system includes (surrounded by < >) using the same strategies as normal includes (surrounded by quotes). If this item is off, the analyzer looks for system includes only in directories defined by the compiler configuration. The default is on.
- **Ignore directories in include names:** Check this option if you want to ignore any directory specifications in #include statements and instead use the include file wherever it is found in the project. The default is off.
- **Use case-insensitive lookup for includes:** This option tells the analyzer whether to ignore the case of filenames in #include statements. The default is off. (Not available on Windows; Windows lookups are always case-insensitive.)

---

#### **C++ > Includes > Auto Category**

In the **C++ > Includes > Auto** category you can specify include files that should be included before each file in a project.

To add a file, click **New** and browse for the file(s). Then click **Open**.

You can import or export a list of auto include files from a text file by clicking **Import** or **Export** and selecting the text file that contains one file path per line.


Use the **Move Up** and **Move Down** buttons to change the order in which these files are included.

---

#### **C++ > Includes > Ignore Category**

In the **C++ > Includes > Ignore** category you can specify individual include files that you wish to ignore during analysis.

To add a file to be ignored, click **New** and type the filename of the include file. Then click **OK**. The filename can use wildcards, such as `moduleZ_*.h`, to match multiple files.



Any missing files you choose to ignore when prompted during analysis will be added to this list.


You can import or export a list of files to ignore from a text file by clicking **Import** or **Export** and selecting the text file that contains one filename per line.

## C++ > Includes > Replacement Text

In the **C++ > Includes > Replacement Text** category you can specify text that should be replaced in include file text.

For example, you might use this feature to replace VAX/VMS include paths like [sys\$somewhere] with valid Unix or Windows paths without modifying the source code.

To add an item, type the string found in the actual include files in the **Include String** field. Type the text you want to replace it with in the **Replace With** field. Then click **OK**.



You can import or export a list of include strings and their replacements from a text file by clicking **Import** or **Export** and selecting the file. The file must contain one include string per line. The file should separate the include string and its replacement with an equal sign (=).

Use the **Move Up** and **Move Down** buttons to change the order in which these replacements are made.

## C++ > Macros Category

C source code is often sprinkled with pre-processor directives providing instructions and options to the C compiler. Directives such as the following affect what the software does and how it should be analyzed:


```
#define INSTRUMENT_CODE
#ifdef INSTRUMENT_CODE
... statements ...
#endif
```

Macros are often defined with directives (**#define**) in include files (.h files) or are passed in via the compiler (typically with the **-D** option).

For *Understand* to successfully analyze your software it needs to know what macro definitions should be set. For more about ways to configure macro definitions, see *Using the Undefined Macros Tool* on page 127 and the [SciTools website](#).

The **C++ > Macros** category in the Project Configuration dialog (which you open with **Project > Configure Project**) allows you to define preprocessor macros that are used when compiling the code.

To add a macro definition, click the **New** button and type the name of the macro and optionally a definition. Then click **OK**.



Note that a macro must have a name, but that the definition is optional. Macros that are defined but have no definition value are commonly used in conjunction with *#ifdef* pre-processor statements to see if macros are defined.

**Note:** A number of preprocessor macros are automatically supported. In additions to the common macros, *Understand* supports the following macro formats for embedded assembly code if you are using the “fuzzy” analyzer. (The strict C/C++ analyzer does not support these macro formats.)

```
#asm(<embedded assembly code>);  
#asm "<embedded assembly code>";  
#asm  
<embedded assembly code>  
#endasm
```


You can import or export a list of macros and their optional definitions from a text file by clicking **Import** or **Export** and selecting the file. The file must contain one macro definition per line. A *#* sign in the first column of a line in the file indicates a comment. The file should separate the macro name and its definition with an equal sign (=). For example, *DEBUG=true*.

The priority for macro definitions is as follows, from lowest to highest priority:

- 1 Built-in language macros (*\_\_FILE\_\_*, etc.)
- 2 Compiler configuration file
- 3 Macro definitions in a synchronized Visual Studio project
- 4 Undefines of compiler defines (via the **Configure Undefines** button)
- 5 Project defines (Macros category)
- 6 Define on und command line using *-define*
- 7 Define in source file (*#define* / *#undef* in source)

.....  
**C++ > Macros >  
Undefines Category**

You can list undefined macros in the **C++ > Macros > Undefines** category in the Project Configuration dialog. Click **New** and type the name of a macro that you do not want to be defined. Then click **OK**.




You can import or export a list of undefined macros from a text file by clicking **Import** or **Export** and selecting the file. The file must contain one macro name per line. A # sign in the first column of a line in the file indicates a comment.

## C++ (Strict) Options

See *Languages Category* on page 41 for information about the differences between the default C/C++ analyzer and the strict analyzer.

**Note:** If you did not select the **Strict** option in the Languages category next to the C/C++ box, see *C++ (Fuzzy) Options* on page 71 for how to configure your project.

In the **C++ (Strict) > Options** category of the Project Configuration dialog, you can control how C/C++ source code is analyzed. You see this window when you choose the **Project > Configure Project** menu item and select the **C++ (Strict)** category.



**Target**

Arch: x86\_64

Vendor: pc

OS: win32

Env: unknown

Version: 1300

☒ Delayed Template Parsing

**Language Standard**

C: c89

C++: c++98

**Optimize**

☒ Create references in inactive code

☒ Save comments associated with entities

☐ Save macro expansion text

Warnings: ☒ None ☐ Default ☐ All

Kill worker processes after 2 minutes

**Objective-C**

Memory Management: ☒ MRR ☐ ARC ☐ GC

The first three fields in the Target section of this dialog match target triplets used by the GNU Compiler Collection (GCC). The defaults match the platform on which you are running *Understand*. These fields are used to control which extensions (such as preprocessor defines, header search paths and language syntax) are analyzed. If your choices here do not match the code used, errors are likely to occur during the analysis.

If your code is built for multiple targets, use these options to switch between target environments for the code analysis.

The fields in the **C++ (Strict) > Options** category are as follows:

- **Arch:** Select the architecture of the chip for which your project is written. Examples of the many supported options include ARM, PowerPC64, and x86\_64.
- **Vendor:** Select the source of the chip architecture. Examples include Unknown, Apple, PC, and SCEI (Sony PlayStation). Use the “Unknown” option to select the most generic C/C++ code analysis.
- **OS:** Select the operating system that this program will be used under. Examples include iOS, Linux, and Win32.
- **Env:** Select the build environment you use to build this project. Examples include GNU, EABI, and Mach-O. For most projects, the default of “unknown” is fine.
- **Version:** Specify the appropriate version number. If your OS is IOS or MacOSX, specify the operating system version number. If your OS is Win32, specify the Microsoft C (MSC) version of your compiler. For example, specify 1300 for Visual C++ .NET and 1700 for Visual C++ 2012.
- **Delayed Template Parsing:** If your OS is Win32, you can choose whether to delay parsing of template files. This option is required for compatibility with MSVC. However, be aware that unreferenced template code will not be analyzed at all if you enable delayed template parsing.
- **C Language Standard:** Select the C standard to which you want your C code to conform.
- **C++ Language Standard:** Select the C++ standard to which you want your C++ code to conform.
- **Create references in inactive code:** If you wish to exclude cross-reference information for code that is IFDEFed out by the current macro settings, turn this option off. By default, this option is on and cross-reference information for inactive code is included.
- **Save comments associated with entities:** Choose whether source code comments that occur before and after an entity should be associated with that entity.
- **Save macro expansion text:** If you put a check in this box, you can right-click on a macro and choose **Expanded Macro Text** from the context menu to see how the macro expands.
- **Warnings:** Choose how many of the warnings provided by the strict analyzer you want reported. These warnings indicate potential problems in the source code. Choosing to see some or all warnings is likely to slow down the project analysis somewhat.
- **Kill worker processes after \_\_ minutes:** The strict analyzer launches a separate worker process for each source file it analyzes. If any file takes too long to be analyzed, *Understand* kills the process and no analysis data is generated for that file. *Understand* prints an error message to the analysis log about any files that are not analyzed and continues analyzing the next file. You can reduce the analysis load

by, for example, using forward declarations and removing includes. Alternately, you can use this option to increase the analysis time before the process gets killed. By default, worker processes analyze files for up to 2 minutes.

- **Memory Management:** If you use Objective-C, select the memory management mode used. The options are MMR (manual retain-release), ARC (automatic reference counting), and GC (garbage collection).

---


### **C++ (Strict) > Includes Category**

The **C++ (Strict) > Includes** category in the Project Configuration dialog (which you open with **Project > Configure Project**) allows you to specify include directories. You can specify multiple directories to search for include files used in the project.

The configuration of your include file directories is important to improving the accuracy of project analysis. For more about ways to configure these directories, see *Using the Missing Header Files Tool* on page 125 and the [SciTools Support website](#).

Include paths are not recursively searched; that is, any subdirectories will not be searched for include files unless that subdirectory is explicitly specified in the list of include directories.

To add a directory, click the **New** button and then the ... button, browse to the directory, and click **OK**.



During analysis, the include directories will be searched in the order that they appear in the dialog. You can click **Move Up** or **Move Down** to change the order in which directories will be searched.

Typically only include files that are not directly related to your project (such as system-level includes) and that you do not want to analyze fully are defined here. For project-level includes that you want to be analyzed, add those include files as source files in the **Files** category.

You may use environment variables in include file paths. Use the \$var format on Unix and the %var% format on Windows. You can also use named roots in include file paths (see page 109).

You can import or export a list of include directories from a text file by clicking **Import** or **Export** and selecting the file. The file must contain one directory path per line. (In all such imported text files, a # sign in the first column of a line in the file indicates a comment. Full or relative paths may be used. Any relative paths are relative to the project file.)

The **C++ (Strict) > Include** category provides the following options to control how includes are handled:



- **Sysroot/SDK:** This field allows you to specify the root of the default header search path. For example, if you set Sysroot to `/dir`, the analyzer searches `/dir/usr/include` instead of `/usr/include`. This is useful if you use cross compilers or builds against a different SDK from the host machine. This option corresponds to the `--sysroot` command line option in compilers such as gcc, icc, and clang. This option is available for all supported platforms.
- **Add found include files to source list:** Enabling this option causes include files found during project analysis to be added to the project automatically. This allows you to see more detailed information about such include files. The default is off.
- **Add found system include files to source list:** If you choose to add include files that are found to the source list, you can also choose whether system include files should be added. The default is off.
- **Prompt for missing include files:** If any include files cannot be found during analysis, you will normally see the **Include Paths** button in the Analysis Log after you analyze the project. If you want to be prompted for how to handle missing files during the analysis, you must choose **Tools > Options** and enable the **Allow prompting for missing include files on a per project basis** checkbox in the **Analyze** category (page 108). Then, you will see this field in the Project Configuration dialog. If you then check the **Prompt for missing include files** box, you may choose to add a directory to the include path, ignore the missing file, or stop warning about missing files during the analysis.
- **Search for include files among project files:** This option directs the analyzer to look among project files as a last resort for missing include files. The default is on.
- **Ignore directories in include names:** Check this option if you want to ignore any directory specifications in `#include` statements and instead use the include file wherever it is found in the project. The default is off.
- **Compare files by content instead of path:** Check this option if you want include files to be compared by their contents rather than by their file path. The default is off.
- **Analyze unincluded headers in isolation:** Check this option to omit analysis of header files that are not included by C/C++ files in the project.

There are a number of additional options for include file handling that are available only if you are using the default analyzer rather than the strict analyzer.

#### C++ (Strict) > Includes > Frameworks Category

In the **C++ (Strict) > Includes > Frameworks** category lets you specify Mac OS and iOS framework paths that the project uses.

To search a directory and its subdirectories for a framework, click **Search**.

To add a location, click **New** and browse for the folder. Then click **Select Folder** and then **OK**. You can import or export a list of framework folders from a text file by clicking **Import** or **Export** and selecting the text file that contains one path per line.

Use the **Move Up** and **Move Down** buttons to change the order in which these folders are processed.

.....

**C++ (Strict) >  
Includes > Prefix  
Headers Category**

A prefix header is a C/C++ header file that is included at the beginning of every source file by the compiler. This is done without the use of a `#include` directive. It is common for Mac OS X programs to use prefix header files.

In the **C++ (Strict) > Includes > Prefix Headers** category, you can specify files that are used as prefix header files.

To add a file, click **New** and browse for the file. Then click **Open**. You can import or export a list of files from a text file by clicking **Import** or **Export** and selecting a text file that contains one file path per line.

Use the **Move Up** and **Move Down** buttons to change the order in which these files are processed.

.....


**C++ (Strict) > Macros  
Category**

For information about the **C++ (Strict) > Macros** category, see *C++ > Macros Category* on page 75.

For information about the **C++ (Strict) > Macros > Undefines** category, see *C++ > Macros > Undefines Category* on page 77.

## C# Options


In the **C# > Options** category of the Project Configuration dialog, you can control how C# source code is analyzed. You see this window when you choose the **Project > Configure Project** menu item and select the **C#** category.



The fields in the **C++ (Strict) > Options** category are as follows:

- **Count standard files in MaxInheritance metric:** Determines whether extending standard classes (those provided with the compiler) are counted when determining the maximum inheritance level. By default, such classes are not counted.
- **Save comments associated with entries:** Choose whether source code comments that occur before and after an entity should be associated with that entity. The default is on.
- **Analyze found reference files:** If this box is unchecked, methods in reference libraries are not counted for the purpose of computing metrics. The default is on.

In the **C# > References** category, click **New**. Click ... and browse for a \*.dll file. Type the alias for that file used in the code and click **OK**.



You can import or export a list of reference files and their aliases from a text file by clicking **Import** or **Export** and selecting a file that contains one reference and its alias per line. The file should separate the reference file and its alias with an equal sign (=).

By default, reference files are analyzed as part of the project. If you do not want them to be analyzed, uncheck the **Analyze found reference files** box in this category. If this box is unchecked, methods in reference libraries are not counted for the purpose of computing metrics.

In the **C# > Preprocessor Symbols** category, you can click **New** to add symbol names that should be treated as defined when analyzing preprocessor directives such as #if.

## Fortran Options

In the **Fortran > Options** category of the Project Configuration dialog, you can specify how to analyze Fortran source code. You see this window when you choose the **Project > Configure Project** menu item and select the **Fortran** category.

**Compiler**

Version: Fortran2003

Format Options

Format: Auto

Truncate column: 72 Column: 72

Free format file filters:

☐ Allow C-style comments

☐ Allow ;\* comments

☐ Allow colons in names

☐ Allow function declaration without parentheses

☐ Allow parameter declaration without parentheses

☐ Allow quote in octal constants

☐ Case sensitive identifiers

☒ Use preprocessor

Intrinsic File: C:\Program Files\SciTools\confunderstand\fortran\intrinsic03.txt ... Reset

**Multiple Language Linkage**

The case of externally linkable entities is

☒ all lowercase ☐ all uppercase ☐ preserved

Prepend the names of externally linkable entities with:

Append the names of externally linkable entities with:

**Options**

☒ Prompt on parse errors

Display entity names as: Original

The fields in the **Fortran > Options** category are as follows:

- **Version:** Select the variant of Fortran used by the source code in this project. If you change the version after creating a project, the project will be reanalyzed when you click OK. The choices are Fortran77, Fortran90, Fortran95, Fortran2003, and Fortran2008. If you have a mix of code, choose the newest language variant. That is, if you have F77 and F95 code, choose F95.
- **Format:** Some older Fortran variants and all new variants permit *free form* statements, which may cross lines). Fixed form statements are terminated by a line end or column number. The default is “Auto,” which automatically detects the

parsing format (fixed or free) on a file-by-file basis. This allows you to mix free and fixed format. Auto format also determines the correct truncation point for fixed format files. Choose “Fixed” or “Free” only if all your source files have the same format. Blocks of freeform code can be used within a fixed format file if you bracket the blocks with `!dec$freeform` and `!dec$nofreeform`.

- **Truncate column:** If you choose fixed form, you may choose what column terminates statements. Common columns 72 and 132 are available or you may specify a column or no truncation.
- **Allow C-style comments:** Check this option if your Fortran code contains comments of the form `/* ... */`.
- **Allow `;` comments:** Allow the use of end-of-line comments that begin with `;`.
- **Allow colons in names:** Check this box to allow colons (`:`) to be used in identifiers in F77 code. Enabling this option could cause problems in F77 code that does not use this extension, so the default is off.
- **Allow function declaration without parentheses:** Check this box if you want to allow functions to be declared without the use of parentheses. By default, parentheses are required.
- **Allow parameter declaration without parentheses:** Check this box if you want to allow parameters to be declared without the use of parentheses. By default, parentheses are required.
- **Allow quote in octal constants:** Check this box if a double quote mark ( `"` ) should be treated as the start of a DEC-style octal constant. For example, `"100000`. If this box is not checked (the default), a double quote mark begins a string literal.
- **Case sensitive identifiers:** Check this box if you want identifier names to be treated case-sensitively. By default, case is ignored.
- **Use preprocessor:** Use this option to disable or enable preprocessor support.
- **Intrinsics file:** Type or browse for a file that contains intrinsic functions you want to be analyzed. Default intrinsics files are provided in the `<install_directory>/conf/understand/fortran` directory: `intrinsics77.txt`, `intrinsics90.txt`, and `intrinsics95.txt`.
- **Case of externally linkable entities:** Choose which case should be used for “exporting” entities in this language that can be linked to (for example, called as functions) by other languages. For example, if an entity is declared in this language as `“MYITEM”` and you choose “all lowercase” here, other languages would be expected to call that entity as `“myitem”`.
- **Prepend the names of externally linkable entities with:** You may optionally type a string that you want used as a prefix to reference all linkable entities in other source code languages.
- **Append the names of externally linkable entities with:** You may optionally type a string that you want used as a suffix to reference all linkable entities in other source code languages.

- **Prompt on parse errors:** By default, a prompt asks how to handle any parsing errors. When prompted during analysis, you may choose to ignore that error or all future errors. Turn this option off to disable this prompting feature. If you turned it off during analysis, but later want to turn error prompting back on, check it here.
- **Display entity names as:** Choose whether entity names should be displayed in *Understand* with the same case as the source code (original), all uppercase, all lowercase, only the first letter capitalized, or mixed case.

---

### **Fortran>Includes Category**

The **Fortran > Includes** category in the Project Configuration dialog (which you open with **Project > Configure Project**) allows you to specify include directories. You can specify multiple directories to search for include files used in the project.

The configuration of your include file directories is important to improving the accuracy of project analysis. For more about ways to configure these directories, see *Using the Missing Header Files Tool* on page 125 and the [SciTools Support website](#).

Include paths are not recursively searched; that is, any subdirectories will not be searched for include files unless that subdirectory is explicitly specified in the list of include directories.

To add a directory, click the **New** button and then the ... button, browse to the directory, and click **OK**.

During analysis, the include directories will be searched in the order that they appear in the dialog. You can click **Move Up** or **Move Down** to change the order in which directories will be searched.

Typically only include files that are not directly related to your project (such as system-level includes) and that you do not want to analyze fully are defined here. For project-level includes you want analyzed, add those include files as source files in the **Files** category.

You can import or export a list of include directories from a text file by clicking **Import** or **Export** and selecting the file. The file must contain one directory path per line. (In all such imported text files, a # sign in the first column of a line in the file indicates a comment. Full or relative paths may be used. Any relative paths are relative to the project file.)

For more information, see *C++ > Includes Category* on page 73.

---

### **Other Fortran Categories**

For information about the **Fortran > Includes > Replacement Text** category, see *C++ > Includes > Replacement Text* on page 75.

For information about the **Fortran > Macros** category, see *C++ > Macros Category* on page 75. The following predefined macros are supported: `__LINE__`, `__FILE__`, `__DATE__`, and `__TIME__`.

## Java Options

In the **Java > Options** category of the Project Configuration dialog, you can specify how to analyze Java source code. You see this window when you choose the **Project > Configure Project** menu item and select the **Java** category.

**Compiler**

Version Java8

**Metrics**

☒ Count Javadoc comments in line count metrics

☐ Count standard files in MaxInheritance metric

**Multiple Language Linkage**

Prepend the names of JNI/KNI external entities with Java\_

☒ Include package name

**Optimize**

☒ Save comments associated with entities

- **Version:** Select the version of Java used by the source code in this project. If you change the version after creating a project, the project will be reanalyzed when you click OK. The choices are Java 1.3, 1.4, 5, 6, 7, and 8.
- **Count Javadoc comments in line count metrics:** If this box is checked, Javadoc comments are included when computing the CountLine, CountLineComment, and RatioCommentToCode metrics. The default is on.
- **Count standard files in MaxInheritance metric:** Determines whether extending standard classes (those provided with Java) are counted when determining the maximum inheritance level. By default, such classes are not counted.
- **Prepend the names of JNI/KNI external entities with:** You can specify a prefix used by Java to call functions in other languages. A Java call to a function “func” would match the C function *prepend\_pkg\_class\_func*, where *prepend* is the string you specify here, *pkg* is the Java package name, and *class* is the Java class. This follows the Java Native Interface (JNI) and the Kaffe Native Interface (KNI).
- **Include package name:** By default, the package name is included in the prefix used to call functions in other languages. Uncheck this box to remove the package name from the names of external functions.
- **Save comments associated with entities:** Choose whether source code comments that occur before and after an entity should be associated with that entity.


## Java > Class Paths Category

The **Java > Class Paths** category allows you to identify Java .jar and .class files that provide classes for which you do not have source code.

Both .jar files and .class files are supported. Jar files contain compressed .java (source) files. Class files contain compiled sources. By default, the src.jar (or src.zip) file provided by the Java Developers Kit is located. You can add other .jar files as needed.

To add a directory with .class and .java files, follow these steps:

- 1 Click **New Path**.
- 2 Locate and select the directory containing .class files. You can provide a relative path to a directory by typing the path directly in the Class Path field rather than browsing for a directory. Then click **OK**.



To add a .jar file to the list, follow these steps:


- 1 Click **New Jar**.
- 2 Locate and select the .jar or .zip file(s). You can select multiple .jar files while holding down the Ctrl key. You can provide a relative path to a file by typing the path directly in the Jar File field rather than browsing for a file. Then click **Open**.

If a class is found in both a .java and .class file in the class path, the class in the .java file is used.

You can import or export a list of class paths and/or jar files from a text file by clicking **Import** or **Export** and selecting the file. The file must contain one directory or file path per line. (In all such imported text files, a # sign in the first column of a line in the file indicates a comment. Full or relative paths may be used. Any relative paths are relative to the project file.)

## Eclipse Plugin

If you use the Eclipse IDE for code development, you can access a number of *Understand* features within the Eclipse IDE by installing the Understand plugin for Eclipse. These features include the Entity Filter, Information Browser, Metrics, Treemaps, Butterfly graphs and Control Flow graphs. See <http://scitools.com/eclipse/> for details on installing this plugin.





## JOVIAL Options

In the **Jovial > Options** category of the Project Configuration dialog, you can specify how to analyze JOVIAL source code. You see this window when you choose the **Project > Configure Project** menu item and select the **Jovial** category.

**Compiler**

Version: Jovial73

Truncate column: None Column: 72

Automatic compool file: [Browse]

**Implementation**

Bits In Byte: 8

Bits In Pointer: 16

Bits In Word: 16

Fixed Precision: 15

Float Exp Bits: 8

Float Precision: 23

Int Precision: 15

**Multiple Language Linkage**

The case of externally linkable entities is...

☒ all lowercase ☐ all uppercase ☐ preserved

**Options**

Display entity names as: Original

The **Jovial > Options** category contains the following fields:

- **Version:** Select the JOVIAL version you use. JOVIAL73 and JOVIAL3 are supported.
- **Truncate column:** By default, statements are not truncated by column location. You may choose to truncate statements at column 72 or at some other user-defined column.
- **Automatic compool file:** Click ... and browse to the compool file you want to use. The file extension can be \*.txt, \*.cpl, or \*.jov. The selected file is automatically imported into all other files in the project.
- **Implementation fields:** The fields in this section allow you to specify the sizes and precision of various datatypes. These sizes vary with different implementations of JOVIAL. The sizes are used to determine data overlay. You can specify the number

of bits in a byte, number of bits in a pointer, number of bits in a word, precision for fixed datatypes, number of bits in a floating exponent, precision for floating datatypes, and the precision for an integer.

- **Case of externally linkable entities:** Choose which case should be used for “exporting” entities in this language that can be linked to (for example, called as functions) by other languages. For example, if an entity is declared in this language as “MYITEM” and you choose “all lowercase” here, other languages would be expected to call that entity as “myitem”.
- **Display entity names as:** Choose whether entity names should be displayed in *Understand* with the same case as the source code (original), all uppercase, all lowercase, only the first letter capitalized, or mixed case.


---

### **Jovial > !Copy Category**

The **Jovial > !Copy** category in the Project Configuration dialog (which you open with **Project > Configure Project**) lets you select directories to be searched for files named in !COPY directives.

To add a directory to the list, follow these steps:

- 1 Click the **New**.



- 2 Click the ... button and browse to the directory you want to add.
- 3 Click **OK**.

When a !COPY directive is analyzed, the directories are searched in the order listed. To change the search order, select a directory and click **Move Up** or **Move Down**.

You can import or export a list of directories to be searched for files named in !COPY directives from a text file by clicking **Import** or **Export** and selecting the file. The file must contain one directory path per line. (In all such imported text files, a # sign in the first column of a line in the file indicates a comment. Full or relative paths may be used. Any relative paths are relative to the project file.)

## Pascal Options

In the **Pascal > Options** category of the Project Configuration dialog, you can specify how to analyze Pascal source code. You see this window when you choose the **Project > Configure Project** menu item and select the **Pascal** category.

**Compiler**

Version: Delphi

☒ Allow embedded SQL

Predeclared entities file: `ols\conf\ Understand\pascal\predeclareddelphi.txt`

dfm converter exe:

**Multiple Language Linkage**

The case of externally linkable entities is: Preserve

Prepend the names of externally linkable entities with:

**Options**

Display entity names as: Original

Namespaces:

The **Pascal > Options** category contains the following fields:

- **Version:** Select the version of Pascal used by the source code in this project. The choices are Delphi, Compaq/DEC/HP, Pascal86, and Turbo. Select Compaq for legacy DEC Pascal projects. *Understand* supports all versions of Embarcadero's Delphi language and Embarcadero's Turbo Pascal language. It also supports ISO 7185:1990 (also known as Unextended Pascal) with HP Pascal extensions.
- **Allow embedded SQL:** Check this box to enable parsing of embedded SQL statements in your source code. Ingres embedded SQL statements are supported.
- **Predeclared entities file:** Click ... to select a text file (\*.txt) that contains predeclared routines, types, constants, and parameters used in your source code. Two versions of this file are provided in <install\_directory>/conf/understand/pascal: predeclared.txt and predeclareddelphi.txt. The default is set according to your choice in the Version field.
- **dfm converter exe:** Browse for and select the executable to be used to convert binary Delphi Form (DFM) files in the project to text files. The text files will then be analyzed as part of the project. A number of third-party converters are available; *Understand* does not provide a converter.
- **Case of externally linkable entities:** Choose which case should be used for “exporting” entities in this language that can be linked to (for example, called as functions) by other languages. For example, if an entity is declared in this language

as “MYITEM” and you choose “Lowercase” here, other languages would be expected to call that entity as “myitem”.

- **Prepend the names of externally linkable entities with:** You may optionally type a string that you want used as a prefix to reference all linkable entities in other source code languages.
- **Display entity names as:** Choose whether entity names should be displayed in *Understand* with the same case as the source code (original), all uppercase, all lowercase, only the first letter capitalized, or mixed case.
- **Namespaces:** List the names of the namespaces used by the project. The names must be separated by spaces, blanks, or semicolons.

---

#### **Pascal > Macros Category**

The **Pascal > Macros** category allows you to add support for preprocessor macros in source code. For example, the `$IF`, `$IFDEF`, and `$ELSE` directives are supported.

The CPU386 and MSWINDOWS macros are predefined for some types of Pascal/Delphi sources to avoid generating syntax errors with the standard library.

For more information about the **Pascal > Macros** category, see *C++ > Macros Category* on page 75.

---

#### **Pascal > Standard Library Paths Category**

The **Pascal > Standard Library Paths** category allows you to specify directories that should be searched for standard libraries.

Standard library paths are used to find units that are not found in the project files. Only files that contain the required units are processed. For example, the following statement causes the standard libraries to be searched for a unit names `System`:

```
Uses System;
```

The standard libraries are not used when computing project metrics.

To add a directory, follow these steps:

- 1 Click the **New** button.
- 2 Click the ... button and browse to a directory. Then click **OK**.
- 3 You can click **Move Up** or **Move Down** to change the precedence order in which the standard libraries are checked.

You can import or export a list of directories that should be searched for standard libraries from a text file by clicking **Import** or **Export** and selecting the file. The file must contain one directory path per line.

---

#### **Pascal > Search Paths Category**

The **Pascal > Search Paths** category allows you to specify directories to search for include files. To add a directory, follow these steps:


- 1 Click the **New** button. Then click the ... button and browse to a directory. Click **OK**.
- 2 You can click **Move Up** or **Move Down** to change the precedence order in which the standard libraries are checked.

You can type a list of directory paths separated by semicolons.

You can import or export a list of directories to search from a text file by clicking **Import** or **Export** and selecting the file. The file must contain one directory path per line.

## PL/M Options

In the **PL/M > Options** category of the Project Configuration dialog, you can specify how to analyze PL/M source code. You see this window when you choose the **Project > Configure Project** menu item and select the **PL/M** category.



The **PL/M > Options** category contains the following fields:

- **Compiler Version:** Choose the version of PL/M your compiler uses. The choices are PL/M-80 and PL/M-86.
- **Display entity names as:** Choose whether entity names should be displayed in *Understand* with the same case as the source code (original), all uppercase, all lowercase, only the first letter capitalized, or mixed case.

### PL/M>Includes Category

The **PL/M > Includes** category in the Project Configuration dialog (which you open with **Project > Configure Project**) allows you to specify include directories. You can specify multiple directories to search for include files used in the project.

The configuration of your include file directories is important to improving the accuracy of project analysis. For more about ways to configure these directories, see *Using the Missing Header Files Tool* on page 125 and the [SciTools Support website](#).

Include paths are not recursively searched; that is, any subdirectories will not be searched for include files unless that subdirectory is explicitly specified in the list of include directories. To add a directory, click the **New** button and then the ... button, browse to the directory, and click **OK**.

During analysis, the include directories will be searched in the order that they appear in the dialog. You can click **Move Up** or **Move Down** to change the order in which directories will be searched.

Typically include files not directly related to your project (such as system-level includes) and that you do not want to analyze fully are defined here. For project-level includes you want analyzed, add those include files as source files in the **Files** category.

You can import or export a list of include directories from a text file by clicking **Import** or **Export** and selecting the file. The file must contain one directory path per line. (In all such imported text files, a # sign in the first column of a line in the file indicates a comment. Full or relative paths may be used. Any relative paths are relative to the project file.) For more information, see *C++ > Includes Category* on page 73.

For information about the **PL/M > Includes > Replacement Text** category, see *C++ > Includes > Replacement Text* on page 75.

## Python Options

In the **Python > Options** category of the Project Configuration dialog, you can specify how to analyze Python source code. You see this window when you choose the **Project > Configure Project** menu item and select the **Python > Options** category.

**Version**

☒ Python executable  ...

Version: Python3

☐ Python2

☐ Python3

**Standard Library**

☒ Use built-in standard library files

**Dynamic Resolve**

☐ Assume nearest matches

☐ Assume single choices

**Errors**

☐ Ignore import errors in try blocks

The **Version** section lets you specify the version of Python to use. You can select one of the following:

- **Python executable.** Click ... and browse for the location of the file you use to run Python programs. The version of this executable will be detected and displayed. In addition, the Python interpreter's `sys.path` variable is examined to find the directories to be searched for modules. The **Default** button fill in a Python executable path if one is found in the `PATH` environment variable definition.
- **Python 2.** Select this option to analyze the project using the Python 2 standard.
- **Python 3.** Select this option to analyze the project using the Python 3 standard.

**Use Built-in Standard Library Files:** By default, *Understand* uses the files in the `./conf/understand/python/python2` or `./conf/understand/python/python3` subdirectory of the *Understand* installation to resolve Python standard library entities. These files contain stubs for such entities. You can disable this part of the search here.

If a module is found in both the built-in libraries (*Understand's* copy) and the installed Python libraries, the version in the installed libraries takes precedence.

**Assume nearest matches:** Enables resolving attribute references to match attributes defined in the same file or imported files. This option is now off by default.

**Assume single choices:** Enables resolving attribute references to match any single attribute with the same name in the project. This option is now off by default.

**Ignore import errors in try blocks:** Suppresses warning messages due to import statements that occur in try-except blocks.

---

### Python > Imports Category

The **Python > Imports** category in the Project Configuration dialog (which you open with **Project > Configure Project**) allows you to specify import directories. You can specify multiple directories to search for import files used in the project.

Import paths are not recursively searched; that is, any subdirectories will not be searched for import files unless that subdirectory is explicitly specified in the list of import directories.

To add a directory, click the **New** button and then the ... button, browse to the directory, and click **OK**.

During analysis, the import directories will be searched in the order that they appear in the dialog. You can click **Move Up** or **Move Down** to change the order in which directories will be searched.

Typically only import files that are not directly related to your project and that you do not want to analyze fully are defined here. For project-level imports you want analyzed, add those files as source files in the **Files** category.

You can import or export a list of directories from a text file by clicking **Import** or **Export** and selecting the file. The file must contain one directory path per line. (In all such imported text files, a # sign in the first column of a line in the file indicates a comment. Full or relative paths may be used. Any relative paths are relative to the project file.)

For more information, see *C++ > Includes Category* on page 73.

---

## VHDL Options

There is currently no Project Configuration category for VHDL.

If you are new to *Understand*, you should be aware that the following terms have different meanings in *Understand* than they do in VHDL:

- **Entity.** Any source construct such as a file, function, or variable. This also includes, but is not limited to, VHDL entities.
- **Architecture.** An arbitrary collection of Understand entities organized in a hierarchy. This collection may contain, but is not limited to, VHDL architectures.

## Web Options

In the **Web** category of the Project Configuration dialog, you can specify what types of tags to allow in PHP files that are part of the project. You see this window when you choose the **Project > Configure Project** menu item and select the **Web** category.

Web languages included in the analysis include CSS, HTML, JavaScript, PHP, and XML. For some file types, such as XML, only line count metrics are generated.

The **Web** category contains the following fields:

- **Analyze jQuery:** Check this box if you want the analysis to interpret a `$(...)` call as a jQuery call. A **JQuery Selector** entity is created for the string literal parameter passed to `"$"`. For example, `$(".foo")` would create a JQuery Selector entity named `".foo"`. Also, a **JQuery Selector Uses** category is added to the Information Browser for files and functions that use the jQuery selectors. By default, this option is off.
- **Analyze Node.js:** Check this box if you want the analysis to recognize the `node.js` "require" function. A **Requires** category is added to the Information Browser for files that contain calls to "require" and a **Required by** category is added to the Information Browser for files that are named in a "require" call. Requires and Required By graph views are also available.

The **Search Path** field allows you to specify a semicolon-separated list of directories to be searched in the order given for files named in "require" calls.

The **Predefined** field allows you to specify the name of a file containing a list of predefined node.js modules. This field defaults to the path to `scitools\conf\understand\javascript\nodejs_predefined.txt`.

- **Search Strings for Entity Names:** Check this box if you want strings within JavaScript code to be searched for references to entities.




- **Module Search Path:** You may specify a search path for JavaScript modules.
- **PHP Version:** Select the version of PHP used by your project. The options are 5.3, 5.4, 5.5, and 5.6.
- **Allow Short Tags:** Check this box if your PHP code ever uses the short form of PHP tags.
- **Allow ASP Style Tags:** Check this box if your PHP: Hypertext Preprocessor (PHP) code ever uses Active Server Pages (ASP) style tags.
- **Save comments associated with entities:** Choose whether source code comments that occur before and after an entity should be associated with that entity.

## Setting General Preferences

*Understand* allows you to control a number of aspects of its operation using the Understand Options dialog. To open this dialog, choose **Tools > Options**. This dialog provides options to set in the categories shown to the right:

The subsections that follow describe each of the categories:

- *General Category* on page 99
- *User Interface Category* on page 101
- *User Interface > Lists Category* on page 102
- *User Interface > Alerts Category* on page 103
- *User Interface > Windows Category* on page 104
- *User Interface > Application Styles Category* on page 106
- *Key Bindings Category* on page 107
- *Analyze Category* on page 108
- *Portability Category* on page 109
- *Dependency Category* on page 110
- *Editor Category* on page 111
- *Editor > Advanced Category* on page 113
- *Editor > Macros Category* on page 116
- *Editor > Styles Category* on page 117
- *Editor > Navigation Category* on page 118
- *Editor > External Editor Category* on page 119
- *Graphs Category* on page 120



**General Category**

The following options can be controlled from the **General** category of the **Tools > Options** dialog:

- **Application font:** To change the font used in dialogs and lists in *Understand*, click **Change Font** and select the font, font style, and font size you want to use and click **OK**.
- **Show the Splash-Screen on startup:** If checked (on by default), the logo is shown while *Understand* is starting.
- **Show the Getting Started dialog on startup:** If checked (on by default), the Getting Started tab (see page 20) is shown in the document area when you start *Understand*.
- **Save all modified editor windows when application loses focus:** If checked (off by default), then whenever you move to another application, any editor windows in which you have made changes have their contents saved automatically.

- **Open last project on startup:** If checked (off by default), the most recently opened project is automatically opened when you start *Understand* with no other project specified. This is a useful option if you typically work with only one project.
- **Use default working directory:** If checked (off by default), you can select an alternate default directory. This will be the starting place when you are browsing for other directories and the directory to which relative directory specifications relate. The default is the directory where your project is saved.
- **Enable permissions checking for NTFS filesystems:** If you check this box, file permissions are checked on NTFS filesystems when you use the editor to modify files. This option is off by default, since this checking can significantly degrade performance in some cases.
- **Auto-detect network proxy settings:** If the Getting Started tab does not show the Scientific Toolworks News & Announcements feed, you can check this option to have your system's proxy settings checked so that the feed can be loaded. However, scanning for proxy settings takes some time and slows down the *Understand* startup process. This option is disabled by default. After you enable this option, you will need to restart *Understand* in order for it to take effect.
- **Allow interactivity during intensive processing:** If checked (on by default), you can interact with *Understand* while it is performing background processing. Your interactive events are processed at the interval you specify in milliseconds.
- **Allow events processing every n milliseconds:** Specify how often interactive events are processed. By default, such events are processed every 100 milliseconds (0.1 seconds). You can improve background processing performance by reducing this value.
- **Settings Folder:** Specify where files used internally by *Understand* but not associated with a specific project are stored. You can browse to change this location. You will need to restart *Understand* to have changes to this directory location take effect.
- **Backup File:** Specify a location for the backup *Understand* initialization file. By default, this file is the `Understand_bak.ini` file in the Settings Folder. You can click **Save Settings** to save all the current option settings to this file. If you want to load different settings, change the Backup File location to point to a different or edited file and click **Load Settings**.
- **Restore Defaults:** This button restores the default settings for all Option categories.

## User Interface Category

The following options can be set from the **User Interface** category of the **Tools > Options** dialog:

☒ Animate Windows/Drawers

Speed -  +

Document Area

☒ Show tabs

☐ Use "Most Recently Used" order for next tab activation when documents close

Dock Window Layouts

☐ Tight Layout Dock windows auto-hide to give maximum space for working in the Document Area

☒ Classic Layout Docks are laid out as in Understand 1.4

☐ Multi-monitor Layout Docks are laid out on a separate screen

Title Formats

Window Titles:  Tab Titles:

Selector Files:

Command Window Font

Font:  Size:

Project Configuration Options


☒ Use the New Project Wizard when creating new projects

- **Animate Windows/Drawers:** If checked (on by default), opening and closing windows and tabbed areas (drawers) is animated. You can choose a faster or slower speed than the default.
- **Show tabs:** If checked (the default), tabs are shown at the top of the document area for each of the windows open in that area. This includes the source editor windows, graphical views, and other windows.
- **Use "Most Recently Used" order for next tab activation when documents close:** If this box is checked, the most recently used window becomes the current window when you close another. If this box is unchecked (the default), the tab to the left becomes the current window.
- **Dock Window Layouts:** Choose which window layout you would like to use as the default. The **Tight Layout** is useful if you will be opening several source files and want plenty of screen space for that. The **Classic Layout** is similar to earlier versions. The **Multi-monitor Layout** allows you to take advantage of multiple screens if you have them.

- **Title Formats:** Choose whether you want filenames in the title areas of windows, tabs, and selector files to be short names, long (full path) name, or relative to the project database.
- **Command Window Font:** Controls the font used in the “Run a Command” dialog to display output from the commands you issue.
- **Use the New Project Wizard when creating new projects:** The check in this box causes the New Project Wizard (page 34) to be used when you choose **File > New > Project**. If you uncheck this box, you can specify a project database location and filename and then use the full Project Configuration dialog.

### User Interface > Lists Category

The following options can be set from the **User Interface > Lists** category of the **Tools > Options** dialog:



- **Recent files list:** The default is to show five items in a list of recently used files. You can change that default here. You can remove items from the list that you do not want displayed. Note that you can choose **File > Recent Files > Clear Menu** to clear the history of recent files.
- **Recent projects list:** The default is to show five items in a list of recently used projects. You can change that default here. You can remove items from the list that you do not want displayed. Note that you can choose **File > Recent Projects > Clear Menu** to clear the history of recent projects.

## User Interface > Alerts Category

The following options can be set from the **User Interface > Alerts** category of the **Tools > Options** dialog:

The screenshot shows the 'User Interface > Alerts' category in the 'Tools > Options' dialog. It contains five sections:

- Save On Parse:** Three radio buttons. 'Always Prompt' is selected.
- Save On Command:** Three radio buttons. 'Always Prompt' is selected.
- Project Close:** A checkbox 'Prompt before closing the current project' is checked.
- CodeCheck:** A checkbox 'Prompt when Violation count exceeds 300,000' is checked.
- Entity Filter Window:** A checkbox 'Sound beep when entity filter entry does not match' is unchecked.

These options can be used to re-enable warnings that you have disabled in a warning dialog box.

- **Save on parse:** Choose what you want done with changed but unsaved source files when the database is to be analyzed. The default is to always prompt you to choose whether to save files. Alternately, you can choose to automatically save changed files or to not save changed files.
- **Save on command:** Choose what you want done with changed but unsaved source files when a command is to be run. The default is to always prompt you to choose whether to save files. Alternately, you can choose to automatically save changed files or to not save changed files.
- **Prompt before closing the current project:** If checked (the default), you are asked whether you want to close the current project and all associated windows when you attempt to open a different project.
- **Prompt when Violation count exceeds 300,000:** If checked (the default), you are asked if you want to continue the CodeCheck when 300,000 violations have been detected.
- **Sound beep when entity filter entry does not match:** By default, the computer beeps if you type a filter in the Entity Filter that does not match any of the entities of the selected type. You can uncheck this option to turn off these beeps.

**User Interface >  
Windows Category**

The following options can be set from the **User Interface > Windows** category of the **Tools > Options** dialog:

The screenshot shows the 'User Interface > Windows' category in the 'Tools > Options' dialog. It contains several sections with various settings:

- Editor Windows**: 'Open as:' with radio buttons for 'Captured' (selected) and 'Released'.
- Find in Files Search Window**: 'Display' with a spinner set to '5' and the text 'items in the Find in Files 'Find' list.'; 'Directory & Find List:' with radio buttons for 'Global' (selected) and 'Project'.
- Find in Files Result Window**: A 'Restore Default Position' button; checkboxes for 'Expand/Collapse code snippet when result double clicked.' (checked), 'Visit result in editor when result double clicked.' (unchecked), 'Use Contiguous Selection' (unchecked), and 'Show Code Snippet ToolTip' (checked).
- Graph Windows**: 'Open as:' with radio buttons for 'Captured' (selected) and 'Released'; a checkbox for 'Re-Open existing graphs when project is opened' (unchecked).
- Information Browser Windows**: A checkbox for 'Show Code Snippet ToolTip in References' (checked).
- Released Windows**: 'Save Released Window Positions' and 'Clear Saved Positions' buttons.

You can choose various options for different types of windows.


- **Editor Windows:** Choose whether to open source code files as captured windows contained within the document area of the *Understand* window (MDI windows) or as released windows you can move anywhere on your desktop (SDI windows). The default is captured.
- **Find in Files Search Window:**
  - **Display:** Choose how many items to list in the drop-down list of recent searches. The default is 5.
  - **Directory & Find List:** Choose whether lists of recently used search strings should show all searches or only those searches used with the current project.



- **Find in Files Result Window:**
  - Click **Restore Default Position** if you want to re-dock the results for the Find in Files dialog to the bottom of the *Understand* window.
  - **Expand/Collapse code snippet when result double-clicked:** By default, code found in the Find in Files results is expanded to show surrounding lines of code when you double-click. Uncheck this box if you don't want this behavior to occur.
  - **Visit result in editor when result double-clicked:** If you check this box, the code is shown in the Source Editor when you double-click on a result.
  - **Use alternating row colors:** By default, the results for Find in Files and CodeCheck have a slightly darker background for every second row. You can turn off this shading by unchecking this box.
  - **Use Contiguous Selection:** Enable this option if you want the Find in Files results to allow you to select multiple rows while holding down the Ctrl or Shift key. This is useful if you want to copy multiple result rows to the clipboard for pasting into some other document. This option is off by default.
  - **Show Code Snippet ToolTip:** Choose whether you want several lines of code to be shown in the hover text when you point to a line number shown in the Find in Files results. This option is on by default.
- **Graph Windows:** Choose whether to open graphical views as captured windows contained within the document area of the *Understand* window (MDI windows) or as released windows you can move anywhere on your desktop (SDI windows). The default is captured.
  - **Re-open existing graphs when project is opened:** Choose whether you want graphs that were opened in your previous session to be reopened the next time you open this *Understand* project.
- **Information Browser Windows:**
  - **Show Code Snippet ToolTip in References:** Choose whether you want several lines of code to be shown in the hover text when you point to a line number shown in the References list in the Information Browser. If the Information Browser does not show line numbers, click the drop-down arrow next to "References" and choose **Reference > Full**.
- **Released Windows:** Click the **Save Released Window Positions** button if you have released windows from the document area and you want *Understand* to remember the window positions. If you have used this button to save locations, you can use the **Clear Saved Positions** button to forget the locations.

**User Interface >  
Application Styles  
Category**

The following options can be set from the **User Interface > Application Styles** category of the **Tools > Options** dialog:




You can choose various options for different types of windows.

- **Use Editor Colors:** Click this button to apply the source editor colors from the Editor > Styles category (page 117) to item views, such as the Information Browser.
- **Item View colors:** These colors are used in item views, such as the Information Browser. Click a color square next to an item in the list. Use the Select Color dialog to choose a new color for that item.
- **Tree Row Indentation:** You can change the amount of indentation in hierarchical tree displays.
- **Use alternating row colors in tables and lists:** If checked (off by default), lists and tables, such as the results of a CodeCheck, have shading for alternate rows.
- **Use alternating row colors in rich text trees:** By default, formatted results have a slightly darker background for every second row. You can turn off this shading by unchecking this box.
- **Dim highlight color on selected items when the view is inactive.** The Windows default is to dim the highlighting for the selected object when a windows loses focus. If this makes it difficult for you to read the selected object, you can change the behavior by unchecking this box or by changing the background and foreground colors for such items.

## Key Bindings Category

The functions of keys in *Understand* can be customized. The **Key Bindings** category of the **Tools > Options** dialog lets you choose how keys will work in *Understand*:




- **Keyboard Scheme:** This field allows you to choose groups of keyboard settings that are similar to other applications. The default settings are those native to *Understand*. Other choices are Visual Studio .NET key bindings and the Emacs editor key bindings. If you choose a scheme and click **OK**, that scheme will be used. If you make a change to one of the provided schemes, that becomes a “Custom” scheme. You can click **Save As** to name and save your key binding scheme.
- **Search By Name:** Type part of a command name and click the Find icon. All commands that contain that string will be shown.
- **Search By Key Binding:** Click on the field and press the key sequence you want to search for. Then click the Find icon. For example, press F3 to find all the key bindings that contain the F3 key.
- **Component:** Different portions of *Understand* have different key behaviors. The “Component” column in the table indicates where a particular command is available. You can see the key bindings for a particular component by selecting a sub-category under the main Key Bindings category in the left side of the dialog. (The Application component applies to dialogs and items not otherwise listed.)

To see a full list of all the current key bindings, choose **Help > Key Bindings**.

To change the key sequence for an action, follow these steps:

- 1 Use the Component categories or the Search fields to find a command whose key binding you want to change.
- 2 Put your cursor in the **Primary Sequence** or **Alternate** column for the command you want to modify.
- 3 Press the key combination you want to use to perform that action.
- 4 You can't use normal editing keys like Backspace or Delete to edit the keys shown in these fields. To delete the key combination you have entered, click the **X** in the red circle.


- 5 When you move focus away from a key binding you changed, you may see a warning message if the key combination you chose is already used. For example:



- 6 Click **Yes** to make the change or **No** to cancel the change. Use the **Restore Defaults** or **Cancel** button if you make changes you don't want to save. Or, you can choose one of the provided **Keyboard Schemes** to go back to a default set of key bindings.


## Analyze Category

The **Analyze** category of the **Tools > Options** dialog allows you to specify options for how the project is analyzed.



- **Show log during analysis:** By default, the Analysis Log is shown while the analysis is being performed. If you uncheck this box, the Analysis Log area is not shown when an analysis is running.
- **Sound beep on analysis completion:** By default, a beep notifies you when the analysis is complete.
- **Show standard library files:** For languages whose standard libraries are analyzed by *Understand* (such as Ada), if you check this box the standard library files are shown in the Analysis Log. By default, this box is not checked, and the Analysis Log is shorter.
- **Rescan project before analyzing changed files:** If you check this box, *Understand* scans for files that have been added to project directories and to any Visual Studio projects referenced by this *Understand* project before analyzing the files currently in the project. This has the same effect as using the **Project > Rescan Project Directories** menu command before analyzing the project. By default, this option is off.

**Portability Category** The Portability category of the **Tools > Options** dialog lets you specify names to use as substitutes for file paths. Named roots are similar to environment variables.



After you have defined a named root, you can use that name in other *Understand* dialogs, such as the Project Configuration, and in “und” command lines (see page 323). This is useful, for example, if you want to share projects with people who reference project files over a network using different paths.

To add a named root, click the **Add Named Root** button. This adds a new row where you can type a name and a path (or click the folder icon to browse for the location).

You can uncheck one or more named roots if you want to temporarily deactivate certain names.

If you change a named root, the project will most likely need to be re-analyzed.

You can define operating system environment variables that will be used as named roots in *Understand*. At the operating system level, define environment variable that have a prefix of “UND\_NAMED\_ROOT\_”. The prefix is not used when you reference a named root within *Understand*. For example, suppose you define a system environment variable as follows:

```
UND_NAMED_ROOT_SOURCEDIR=c:\my\project\dir
```


The named root that you would then use within *Understand* is “SOURCEDIR”.

If you are using the “und” command-line tool, named roots definitions on the “und” command line have the highest precedence. The next precedence is named roots defined as environment variables at the operating system level, and finally by named roots defined in the *Understand* project configuration.

To use a named root, see *Setting File Portability* on page 48.

**Dependency Category**

The Dependency category of the **Tools > Options** dialog lets you set options related to the Dependency Browser (page 142), dependency graphs (page 198), and dependency exports.



- **Use Include/Import References:** By default, “includes” and “imports” are treated as dependencies. However, you may want to omit such relationships from dependency lists if they are required for building but are not logically dependent.
- **Allow PreExpansion:** By default, nodes in the Dependency Browser are expanded. You can uncheck this box to have them closed by default.
- **Exclude Standard Entities:** By default, entities in the standard libraries are excluded from dependency reports, dependency graphs, and the dependency browser. Uncheck this option to include such standard entities.
- **Cytoscape Application Location:** You can browse for the location where you installed Cytoscape ([www.cytoscape.org](http://www.cytoscape.org)), a free open-source program for analysis and visualization. Specifying this location allows *Understand* to open Cytoscape for viewing the dependency XML files exported as described in *Exporting Dependencies to Cytoscape* on page 247.

**Editor Category**

The following options can be set in the **Editor** category of the **Tools > Options** dialog:

The screenshot shows the 'Editor' category settings in the 'Tools > Options' dialog. The settings are organized into several sections:


- Default Style:**
  - Font: Courier New (pull-down menu)
  - Size: 10 (spin box)
  - ☒ Antialias
- File Mode:**
  - Encoding: System (pull-down menu)
  - Line Endings: CRLF (Windows) (pull-down menu)
  - On Save:
    - ☐ Convert existing line endings
    - ☐ Convert tabs to spaces
    - ☒ Add newline at end of file if absent
    - ☐ Remove trailing whitespace
- Indent:**
  - ☒ Show Indent Guide
  - ☐ Insert Spaces Instead of Tabs
  - Indent Width: 10 (spin box)
  - Tab Width: 2 (spin box)
- Page Guide:**
  - ☐ Show Page Guide
  - Column: 80 (spin box)
- Whitespace:**
  - ☒ Invisible
  - ☐ Always Visible
  - ☐ Visible After Indent
  - ☐ Show End-of-Line
- Caret Line:**
  - ☒ Highlight Caret Line
- Externally Modified Files:**
  - ☒ Prompt
  - ☐ Reload
  - ☐ Reload & Analyze
- Margins:**
  - ☒ Line Number
  - ☒ Bookmark
  - ☒ Fold

- **Default style:** Use the **Font** pull-down list to select a font for Source Editor windows. The fonts shown are the fixed-width fonts available on your system. Select a **Size** for the Source Editor text. If you check the **Antialias** box, the font is smoothed. The fields in this area set the default size. You can change it on a per-file basis by choosing one of the **View > Zoom** menu options.
- **File Mode:** Select the type of **Encoding** to use when saving source files and the **Line Endings** character you want used. Many encoding formats are supported. The "System" encoding uses the same encoding format defined for your operating system. You should change these settings only if your other applications have problems opening or displaying files created by *Understand*. By default, these settings apply only to new files you create, including text and CSV files. The previous format is preserved for existing files. However, if you check the **Convert existing line endings** box, files you save are converted to the format chosen here.

- **Windows** line-endings are terminated with a combination of a carriage return (`\r`) and a newline (`\n`), also called CR/LF. When opening a file, a CR, CR, LF sequence is interpreted as a single line ending.
- **Unix** line-endings are terminated with a newline (`\n`), also referred to as a linefeed (LF).
- **Classic Macintosh** line-endings are terminated with a single carriage return (CR).

If you check the **Convert tabs to spaces** box, tabs are changed to the number of spaces specified in the **Width** field when you save the file. Also, if you check the **Add newline at end of file if absent** box, a new line character is added to a file that doesn't have one when you save the file (checked by default). If you check the **Remove trailing whitespace** box, any spaces or tabs at the end of lines is deleted automatically when a file is saved.

- **Caret Line:** Check the **Highlight Caret Line** box if you want the full line on which your cursor is located to be highlighted.
- **Externally Modified Files:** If an open file is changed in some other program, *Understand* detects this. Choose **Prompt** if you want to be notified and asked to load that changed version. **Reload** and **Reload & Analyze** do these actions without prompting.
- **Indent:** Check the **Show Indent Guide** box if you want a dotted line to show to column to which lines should be indented.




By default, the **Insert Spaces Instead of Tabs** box is off; turning it on adds spaces to a source file when you press `<Tab>`.

For **Indent Width**, specify the number of columns in an indentation level. For **Tab Width**, specify the number of columns for each tab stop. For example, if you set the Tab Width to 4, each `<Tab>` moves 4 columns to the right. If you set Indent Width to 6 and Tab Width to 4, each automatic indentation level is made up of one `<Tab>` and 2 spaces. You can set a tab width for a specific file to override the project-wide tab width (see page 182). Also, see *Editor > Advanced Category* on page 113 for advanced indentation options.

- **Show Page Guide:** Check the **Page Guide** box to display a line similar to the Indent Guide at a defined line width (that is, at the right edge of the code). Set the **Column** to the character width you want to see indicated.
- **Whitespace:** Select whether you want to see indicators about whitespace characters. A dot indicates a space, and an arrow indicates a tab. You can choose Invisible (the default), Always Visible, or Visible after Indent. Check the **Show End-of-Line** box to see the characters that force a line break.



- **Margins:** Check **Line Number** (on by default) to turn on line numbering in the source view. Check **Bookmark** (on by default) if you want bookmarks (red arrows) shown in the margin next to line numbers. Check **Fold** (on by default) to turn on the ability to “fold” source code entity blocks out of the way.




## Editor > Advanced Category

You can further customize the code editor's behavior in the Options dialog. To open this dialog, choose **Tools > Options**. Expand the **Editor** category, and select the **Advanced** category.

The following options control how source code looks when you print it from an editor window:


- **Font Size:** Choose the size of the source code you want to use for printing. To zoom in and out in an individual source code window, see page 185.
- **Color Mode:** Choose a color mode for printing. The choices are as follows. Note that colors other than black and white are printed only if you are using a color printer and the printer driver is set to print in color.
  - “Normal” matches the current display appearance.
  - “Invert Light” prints black as white and white as black. This is useful if you set the background to a dark color and the text to light colors for your display.
  - “Black on White” prints black code on a white background regardless of the current display appearance.
  - “Color on White” prints colored code on a white background regardless of the current display appearance.
- **Wrap Mode:** Choose the wrap mode you want to use for printing. The default is to wrap words to the next line, but you can choose to truncate lines or wrap at the character level, which breaks words across lines. The line breaks displayed are for printing only; no actual line breaks are added to your source file. See *Line Wrapping* on page 182 to change the wrap mode for screen display.
- **Print absolute file name:** Check this box if you would like the full file path printed at the top of a source file printout, rather than just the filename.
- **Date:** Choose whether to show the date a file was last modified or the current date when printing. The default is the current date.



- **Date Format:** Choose whether to print the date in long or short format. Your system's preferred long and short date format are used.
- **Form feed prints new page:** If this box is checked, a form feed character in the source code file causes a page break. If you uncheck this box, form feed characters are printed as "FF" and no page break occurs.


The **Copy-and-paste** area lets you control how text is formatted when you copy and paste code into a word processor.

- **Include line numbers in rich text** pastes line numbers (in bold). HTML is used to format the pasted text. This option is off by default.
- **Use preformatted white space** pastes code using HTML `<pre>` tags to preserve whitespace. If you disable this option, whitespace is preserved using `&nbsp;` (non-breaking space) and `<br>` tags. Some applications may not respect the `<pre>` tag, in which case you can disable this option to force the formatting to match.



The screenshot shows a configuration panel with two sections. The 'Copy-and-paste' section has two checkboxes: 'Include line numbers in rich text' (unchecked) and 'Use preformatted white space' (checked). The 'Auto-complete' section has three checkboxes: 'Enable Auto-complete' (unchecked), 'Automatically suggest matches' (unchecked), and 'Ignore case' (checked).

The **Auto-complete** options provide for auto-completion of keyword and entities you type in the editor. As you type, words are shown below your text. You can arrow down through the list and press Enter to choose a suggestion.



- **Enable Auto-complete:** This box is unchecked by default. If you want to enable auto-completion, check this box.
- **Automatically suggest matches:** If this box is checked, suggestions automatically appear below your typing. If you uncheck this box, you can still see and choose from a list of auto-completion options by pressing Esc while typing.
- **Ignore case:** If this box is checked, suggestions include upper and lowercase versions of the text you are typing.

The **Auto-indent** options allow you to control how tab characters are automatically added to code. If you check the **Enable auto-indent** box, automatic indentation happens as you type in the Source Editor. This smart indenting is currently implemented for C/C++, C#, Java, JavaScript, and Perl code.

- **Indent after newline:** If this box is checked, when you start a new line, tabs are added so that you begin typing directly below the first character in the previous line. If you uncheck this box, the cursor is always in the first column when you start new lines.
- **Tab auto-indents:** If this field is set to **Never** (the default), the <Tab> key always inserts tab or space characters. If it is set to **Always**, the <Tab> key always adjusts indentation to the “correct” level. If it is set to **Leading Whitespace**, the <Tab> key causes the appropriate amount to indenting in leading whitespace and inserts tabs or spaces everywhere else.
- **Trigger characters:** If you type one of the specified characters, the indentation level for the current line is modified to the correct level based on parsing of the code. For example, a “{” increases the indentation level, and a “}” decreases the indentation level. You can press Ctrl+Z to undo an automatic indentation that just occurred. The default trigger characters are # : { }
- **Indent braces:** If you check this box, the automatic indenting formats code with braces as in the following example:

```
if (true)
{
    // block of code here
}
```

**Auto-indent**

☒ Enable auto-indent

☒ Indent after newline

Tab auto-indents: Never

Trigger characters: #{ }

☒ Indent Braces

**Vertical Caret Policy**

☒ Even ☒ Jumps ☐ Strict ☐ Slop

Slop Value 0

**Unused Entities**

☐ Highlight Unused Entities

Color:

**Annotation Wrap**

☒ Wrap Annotations

Column: 60

The **Vertical Caret Policy** fields let you control how the Source Editor scrolls as the text cursor or current location highlight moves up and down. You can use these fields to optimize the amount of context you see when the Source Editor jumps to a new location. Most users will not need to modify these settings. If you are curious, you can see the descriptions of interactions between these fields at [www.scintilla.org/ScintillaDoc.html#SCI\\_SETYCARETPOLICY](http://www.scintilla.org/ScintillaDoc.html#SCI_SETYCARETPOLICY).

- **Even:** Checking this box causes the source code to scroll the same way both up and down.
- **Jumps:** Checking this box causes code to scroll multiple lines as needed to show some context for the current line of code.
- **Strict:** Checking this box specifies that you don't want the text cursor to go into the zone defined by the Slop Value. If Slop is unchecked, code scrolls to keep the current line in the middle of the window.
- **Slop:** Checking this box lets you define the number of lines at the top and bottom of the Source Editor which you do not want the text cursor to enter.
- **Slop Value:** This field lets you set a number of lines at the top and bottom of the Source Editor that the text cursor should avoid.

The **Unused Entities** fields let you use a colored background to highlight entities that are never used. By default, this feature is off. If you turn this feature on, the default background is gray for code that defines an unused entity. For example, if a function is never called, all code in that function has a gray background if you enable this feature.

The **Annotation Wrap** fields let you cause annotation text to be wrapped at the specified column. This feature is off by default.

---

#### **Editor > Macros Category**

You can record, save, and replay Source Editor macros as described page 182. After you have saved Source Editor macros, you can rename and delete macros using the Options dialog. Follow these steps:


- 1 Choose **Tools > Options**, expand the **Editor** category, and select the **Macros** category.
- 2 In the top box, choose the macro you want to configure.
- 3 Click **Edit** if you want to rename the macro or assign a different key sequence to trigger it. Note that you cannot edit the actions performed by the macro. To modify the actions, record a new macro.
- 4 Click **Remove** if you want to delete the macro.

## Editor > Styles Category

You can customize the colors used in the Source Code Editor in the Options dialog. To open this dialog, choose **Tools > Options**. Expand the **Editor** category, and select the **Styles** category.

To choose a color scheme with a set of defined colors, choose a scheme from the **Predefined** list. The default scheme is “understand”.

To change a color, click a color square next to an item in the list. Use the Select Color dialog to choose a new color for that item.



You can change the text foreground (FG) and background (BG) colors for any item. You can also make the text bold (B), italic (I), or underlined (U) for any item. To highlight the whole line for an item, check the EOL box.

You can use the **Import** and **Export** buttons to save your Editor style settings to an Understand Theme (\*.lua) file. This allows you to share styles between computers.

By default, the following color codes are used for the source code:

- **Dark blue text:** Used for language keywords
- **Red text:** Used for characters and character strings
- **Italic blue text:** Used for comments
- **Green text:** Used for preprocessor statements
- **Black text:** Used for all other source text and for line numbers
- **White background:** Used for most source text
- **Pink background:** Used for inactive lines of code
- **Gray background:** Used for line numbers
- **Yellow background:** Used to highlight text in Find Results for Find in Files

Additional items are available for customization depending on your source code language. For example, with C++, you can customize class, enumerator, and namespace names. With Pascal, you can customize the colors of module, routine, and type names. With Fortran, you can customize the colors of block, module, subprogram, and type names. With Ada, you can customize the colors of package names, subprogram names, and type names.

To create additional categories, click **New**. In the User Style dialog, type a name for the style, select the language to which this style applies, and type keywords to be highlighted in this style. Separate the keywords with spaces, line breaks, or tabs. Then click **Save**. You can then set the formatting for your new style.

---

### Editor > Navigation Category

You can control the behavior of Browse Mode (see page 170) in the Source Editor. To see this dialog, choose **Tools > Options**. Expand the **Editor** category, and select the **Navigation** category.

- **Activate when Control is pressed:** If this is checked (on by default), Source Editor windows use Browse Mode if you hold down the Ctrl key when pointing at an entity.
- **Edit Source:** If this box is checked (on by default), clicking an entity while in Browse Mode causes focus to jump to the declaration of that entity. You can choose a key (none, Alt, or Shift) that must be pressed along with the click to have this action occur. By default, you must press the Alt key when clicking to jump to the declaration of an entity.
- **Update Information Browser:** If this box is checked (on by default), clicking an entity while in Browse Mode causes the Information Browser to show information about an entity when you click on it. You can choose a key that must be pressed along with the click to have this action occur. The default is that no key is required along with the click.
- **Enable Editor Tooltips:** Check this box if you want to see brief information when the mouse cursor hovers over an entity name in source code. The information may include the full name, the type for a variable, and parameters and return values for a function. These tooltips are on by default.
- **Number Format:** Choose whether to display numeric values as decimal, binary, or hexadecimal values in hover text for source code. For example, variables initialized with a numeric literal and enumerated values would show such hover text.


## Editor > External Editor Category

You can use an editor other than the one provided with *Understand* for viewing and editing your source code. The editor you select is used whenever you open source code. This provides convenient source navigation while using a familiar editor. For example, you can use Microsoft Visual C++ or Emacs as your editor.

You should choose an editor that accepts command line parameters that specify the file to open, and a line and column number to go to.

To change the editor, follow these steps:

- 1 Choose **Tools > Options**. Expand the **Editor** category, and select the **External Editor** category.
- 2 In the Select an External Editor dialog, check the **Use External Editor** box if you do not want to use *Understand* for editing.



- 3 In the **Editor** field, click the folder icon and select the executable file for the editor you want to use.
- 4 In the **Parameters** field, type the command line parameters you want to use when opening the editor. Use the `$File`, `$Line`, and `$Col` variables to allow *Understand* to open source files to the correct location.

For example, for the GVIM editor on Unix, the **Editor** is "gvim", and the **Parameters** should be as follows (for GVIM 6.0 or later):

```
--servername UND --remote +$line $file
```

For the TextPad editor on Windows, the **Editor** is most likely `c:\Program Files\textpad4\textpad.exe`, and the **Parameters** should be as follows:

```
$file($line,$col)
```

The *Understand* context menus (also called right-click menus) can be made usable in external editors. Steps are provided in the SciTools support website. For EMACS, vi, and Visual Studio, see [scitools.com/support/understand-context-menu-in-ema](http://scitools.com/support/understand-context-menu-in-ema). For SlickEdit, see [scitools.com/support/using-understand-with-an-exter-2](http://scitools.com/support/using-understand-with-an-exter-2).

## Graphs Category

The Graphs category of the **Tools > Options** dialog lets you control options related to how graphs are displayed. These options apply only to certain types of graphs, such as the Cluster Call and Cluster Call Butterfly graphs.



- **Highlight edges on hover:** If this option is enabled, relationships (connecting lines) within a dependency graph are highlighted when your mouse cursor hovers over the relationship. This makes it easier to distinguish between overlapping relationships. Text describing the relationship is always shown when your mouse cursor hovers over a relationship; this option does not affect display of the relationship description. See page 198.
- **Colored cluster backgrounds:** By default, the background of a cluster is colored. Uncheck this box to hide such colors.
- **Animate Transitions:** By default, when you expand or compress a node in a cluster graph, the transition to reorganize the graph and display children of the expanded node is animated. Uncheck this box if you want to omit the animated transition.
- **On node/cluster double-click:** Controls what happens when you double-click on a node in a graph. By default, clusters are expanded or contracted. You can change this setting to show/hide relationships in one direction or the other. More options let you both expand/contract clusters and show/hide relationships at the same time.
- **Maximum References Shown in Edge Context Menu:** If you right-click on an line between nodes in a cluster graph, a list of the relationships represented by this edge is provided. By default, up to 25 relationships per node are shown. You can make this limit higher or lower. The maximum allowed value is 99.



The **Graphs** category also lets you customize the display colors, shapes, and arrows for cluster graphs. By default, the settings you make in this area apply only to Architecture Dependency graphs (page 198). If you check the **Use custom style on cluster call graphs** box, your style settings also apply to cluster call graphs (page 275).

**Cluster Graph Styles**

In cases where multiple styles apply to a particular node the first matching style is used. For edges, the arrow head and arrow tail are always determined by the first matching style. If the first matching style is custom, then the colors will be a composite of all matching custom styles.

☒ Use custom style on cluster call graphs

**Nodes**

Style	Fill	Line	Shape
Expandable Files			box3d
Expandable Classes			tab
Expandable Architecture			box3d
Default Architecture			box
Default Entity			note

**Edges**

Style	Line	Arrow Head	ArrowTail
Bidirectional		diamond	diamond
Default		normal	none

Buttons: New, Move Up, Move Down (for both Nodes and Edges)


To change the color of a type of node or edge (arrow between entities), click the box in the **Fill** column or the **Line** column. To change the shape of the box for an entity or architecture node, use the drop-down list to select a different **Shape**. To change the ends of an arrow, select a different **Arrow Head** or **Arrow Tail**.

If multiple node styles apply, the first matching style in the list is used. You can use the **Move Up** and **Move Down** buttons to change the order of the styles.

You can create custom styles for nodes as follows:

- 1 Click the **New** button for Nodes.
- 2 Type a unique name for the new style.
- 3 Choose whether this style should apply to only collapsed clusters, only non-clusters, or any cluster.
- 4 Choose whether this style should apply to only architecture nodes, only entity nodes, or all nodes.
- 5 If this is an entity node style, you can choose a way to filter entities that should have this style. Several sample filters are provided, and you can modify the suggested filters to create your own. For example, the “local object” filter applies the style to


locally-defined objects only. The “type ~unnamed” filter applies the style to entities whose type is not unnamed.



If multiple edge styles apply and the first matching edge style is "Default" or "Bidirectional", then only the first style is shown. However, if the first matching style is a custom style, then multiple edges are drawn for each matching custom style. The arrow head and arrow tail for the first matching custom style are used for all arrows.

You can create custom styles for edges as follows:

- 1 Click the **New** button for Edges.
- 2 Type a unique name for the new style.
- 3 Choose whether this style should apply to only forward references, bi-directional references, or all references.
- 4 You can choose a way to filter the edges that should have this style. Several sample filters are provided, and you can modify the suggested filters to create your own. For example, the “inherit, inheritby” filter applies the style only to inheritance relationships. The “call ~inactive, callby ~” filter applies the style only to call and callby relationships that are active.




## Analyzing the Code

Once you configure a project, *Understand* can analyze the project. During analysis, the source files are examined and data is stored in the *Understand* database. After the analysis, the *Understand* database contains lots of data to browse.


When you save or modify the project configuration, a prompt to analyze the project appears automatically. You can also analyze the project in the following ways:

**Project > Analyze Changed Files:** This menu command analyzes all files that have been changed and all files that depend on those changed since the last analysis. This is also referred to as “incremental analysis.” To analyze changed files, you can also use the toolbar icon shown here. (Ctrl+R)




**Project > Analyze All Files:** This menu command forces a full analysis of all project files, whether they have changed since the last analysis or not. (Ctrl+Alt+R)

If some files have been modified but not saved, you are asked whether you want to save all the modified files. You can click **Show Details** to see a list of the files that will be saved.



Analyzing a large project can take some time. If you click **Cancel** while the project is being analyzed you will see a message that says this action will leave the project in an incomplete state. You will need to analyze the project in order to explore it. You can choose to **Abort** the analysis and revert to the previous analysis, **Stop** the analysis and keep the incomplete data, or **Continue** the analysis process.

For either command, the *Analysis Log* shows the results as the analysis is being performed.



When the analysis is complete, the source code for any errors or warnings may be examined by double-clicking on the message in the *Analysis Log* window. If there are missing includes, the Analysis Log contains a link to “Search for missing includes”. You can double-click this link to open the Missing Header Files dialog (see page 125).

To save the Analysis Log to a text file, right-click the white background of the Analysis Log and choose **Save As**. Specify the location and name of the file you want to save. Or, you can use **Copy All** to paste the Analysis Log into another application.

If you have analyzed the project during this session, you can choose **View > Analysis Log** command to reopen the log. See *Analyze Category* on page 108 for options that affect the project analysis.

You can schedule automatic project analysis. See page 51 for details.

**Tip:** A configured project may be analyzed in batch mode using the command line program “und”. Refer to *Using the und Command Line* on page 323 for details on using “und”.

---

### Improving the Analysis

If your project analysis results in warnings about missing files, choose **Project > Improve Project Accuracy > Missing Includes** and see page 125 for how to use the Missing Header Files tool.


If your project analysis results in warnings about undefined macros, choose **Project > Improve Project Accuracy > Undefined Macros** and see page 127 for how to use the Undefined Macros tool.

For other types of warnings, revisit the categories of the *Project Configuration Dialog* on page 39 to make sure your project is configured correctly. Multiple similar errors can often be fixed quickly. For advice about tuning configuration settings to improve your project analysis, choose **Project > Improve Project Accuracy > More Information**.

## Using the Missing Header Files Tool


Configuring your include file directories is important to improving the accuracy of project analysis. If your project analysis results in warnings about missing files, use the Missing Header Files tool as follows:

- 1 Choose **Project > Improve Project Accuracy > Missing Includes** or double-click the link to “Search for missing includes” in the Analysis Log.
- 2 Expand the item for a missing header file and select the source file path to see references to a header file. You will see the code that includes this missing file.



- 3 Click the ... button in the upper-right corner of the dialog and browse to find a directory that may contain one or more missing header files. All subdirectories of the directory you select will be searched. The search is case-insensitive on Windows.

- 4 Click **Select Folder** and then click the **Search** button in the Missing Header Files dialog. If any of the missing files are found, the number of files found and their names are listed in the Missing Header Files dialog.




- 5 If any of the header files you want to use in the analysis are found, click the + icon next to a directory you want to add or the **Add All** button below the list.
- 6 The list of missing headers files is updated to show which header files remain missing with a red X icon and which files have been found with a green checkmark icon. You can continue searching and adding additional directories as needed.
- 7 Click **Save** to apply your changes to the project configuration.
- 8 Click **Yes** at the prompt that asks if you want to analyze the project now.

## Using the Undefined Macros Tool

Configuring your macro definitions is important to improving the accuracy of project analysis. If your project analysis results in warnings about undefined macros, use the Undefined Macros tool as follows:

- 1 Choose **Project > Improve Project Accuracy > Undefined Macros**.



- 2 Select a macro from the list. You can use the headings and fields at the top to sort and filter the list and the **Show Inactive References** box to show or hide such macros. See *Filtering the List* on page 159 for more about using these filter fields.
- 3 Type a definition for the macro in the Global Macro Definition area.
- 4 You can click the **Detail View** button to see the code where the selected macro is used. In this view, you can define a macro value for a specific file or folder instead of project-wide.
- 5 You can select other macros and type definitions for them before saving your changes.
- 6 Click **Save** to apply your changes to the project configuration.
- 7 Click **OK** in the Project Configuration dialog to save the project configuration.
- 8 Click **Yes** at the prompt that asks if you want to analyze the project now.

## Chapter 4

# Exploring Your Codebase

This chapter covers the basic windows in *Understand* and their options in detail. It also covers operations within the Filter Area and the Information Browser.

Details on the use and operation of the Entity Locator and Find in Files for searching for and locating entities are provided in the chapter *Searching Your Source* on page 148.

Details on the use and operation of the **Source Editor** is contained in the chapter *Editing Your Source* on page 167.

This chapter contains the following sections:

Section	Page
PLEASE RIGHT-CLICK	129
Various Windows Explained...	130
Entity Filter	131
Information Browser	133
Project Browser	139
Exploring a Hierarchy	141
Dependency Browser	142
Favorites	144




## PLEASE RIGHT-CLICK

Sorry for shouting (by using all caps above). In order to make the *Understand* interface as quick, tight and elegant as possible, we have hidden a lot of power beneath your mouse buttons.

The general rule is that anywhere you look you can right-click to do or learn something.

A second general rule is that right-click reuses windows where it can and **Ctrl + right-click brings up new windows**.

So please right-click. There will be no more reminders.



Check out all the stuff you can learn or do right-clicking!

Right-click almost anywhere to bring up a menu.

Ctrl + right-click brings up the same menu but actions happen in a new window.

## Various Windows Explained...

*Understand*'s GUI has a number of tools for locating and examining entities. This chapter provides a brief list of all these tools and describes the Entity Filter, Information Browser, and Favorites in detail.


The tools available for finding and exploring entities are:

- **Entity Filter:** Provides an alphabetic list of entities of the selected type. See page 131.
- **Information Browser:** Provides an explorer for entity characteristics and connections. See page 133.
- **Project Browser:** Lets you browse a hierarchical file list. See page 139.
- **Exploring View:** Lets you browse a relationship hierarchy. See page 141.
- **Dependency Browser:** Lets you browse dependency relationships. See page 142.
- **Favorites:** Lets you provide quick links to frequently-used entities. See page 144.
- **Entity Locator:** Lets you filter all entities in a project in complex ways. See page 157.
- **Find in Files:** Searches multiple files. See page 152.
- **Source Editor:** Shows source code. See page 167.
- **Contextual Information Sidebar:** Show context information about the current source editor file. See page 166.
- **Scope list:** Lists the functions or similar constructs in a file. See page 169.
- **Architectures:** Defines named regions and views of the project. See Chapter 7.
- **Graphical Views:** Shows connections and structures of entities. See Chapter 10.
- **Reports:** Generate reports about entities. See Chapter 8.
- **Metrics:** Generate statistics about entities. See page 228.

## Entity Filter


The *Entity Filter* provides a quick list of the selected entity type. You can filter this list to match a text string.


The options in the **Show** list depend upon the languages you have enabled for your project and the types of entities and relationships found in your project. If your project uses multiple languages, the language is listed along with the type.



**Note:** For especially large projects, the All Entities option may be disabled to prevent memory errors.

For each of the entity types, you can quickly find any entity that has been declared (or used) in the source code.




By default, the entities are sorted in ascending (A to Z) order. You can reverse the order by clicking the drop-down icon  and choosing **Sort Descending**.

You can only have one Entity Filter open. If you close the Entity Filters window, reopen it by choosing **View > Entity Filter**.


---

**Using the Filter Field**

In the **Filter** field, you can type a string to match a set of entities. Entity names match if the string is contained anywhere in the name. So, for example, you can type “y” to list only entities that contain a Y or y anywhere in the name.

By default, filtering is case-insensitive. You can make it case sensitive by clicking the drop-down icon  and choosing **Filter Case Sensitivity > Case Sensitive**.


If you want to quickly jump to the point in the list where entities begin with a particular letter, just click in the list of entities and type a letter.

You can select other ways for the **Filter** field to work. Click the drop-down icon  and choose **Filter Pattern Syntax**. The options are:

- **Fixed String:** This is the default behavior.
- **Wildcard:** With this option selected, you can use \* (any characters) and ? (any single character) wildcards for pattern matching. See page 159 for examples.
- **Regular Expression:** With this option selected, you can use Unix-style regular expressions. See page 159 for an overview.

To see only unknown or unresolved entities, click the drop-down icon and choose **Filter Unresolved Entities > Hide Resolved Entities**. To see only resolved entities, click the drop-down icon and choose **Filter Unresolved Entities > Hide Unresolved Entities**.

When you are finished using a filter and want to see all the entities for the selected type, click the drop-down icon and choose **Clear Filter**.

If you change the type of entity in the **Show** field, any filter you have typed is cleared if the **Clear Filter Text on Filter Type Changes** option is selected in the menu available from the drop-down icon .

You can select from filters you have used by right-clicking the Filter area and choosing from the **Most Recent Filters** list. Filters are shown in this list if you have selected any entity found using a filter.

---

**Customizing the Display**

You can modify how the Entity Filter lists entities as follows:

By default, the full entity name is shown in the Entity Filters list and entities are alphabetized by their full name. This name may include a class prefix or other language-specific prefix type. To list entities by their “short”, unprefixed names, click the drop-down icon and choose **Entity Name as > Short Name**.

By default, only the name of the file is shown in a Files list in the Entity Filter. This name does not include the file location. To list files including their locations, click the drop-down icon and choose **File Name as > Relative Name** or **File Name as > Long Name**.

By default, only the name of a function or method is shown. To also show the parameters of such entities, click the drop-down icon and choose **Show Parameters as > Full Parameters** or **Show Parameters as > Short Parameters**.

## Root Filters


Notice that there are the filter type names that contain “Root”, as in **Root Calls**, **Root Callbys**, and **Root IncludeBys**. These “Root” types show only the top of a given tree. The tops (or bottoms) of relationship trees are often helpful points to begin exploring code that is new to you.

- **Root Calls:** Lists only entities that call others, but are not called themselves. These are either high-level code (mains), code called by hardware (interrupt handlers), or dead (unused) code.
- **Root CallBys:** Lists only entities that are called by others, but that do not call anybody else. These are low-level routines.
- **Root IncludeBys:** Lists only files included by others, but not included themselves. These are “lower” level include files.
- **Root Classes:** Lists only classes not derived from other classes. These are candidates for lower level classes, or library classes.
- **Root Decls:** Lists only the highest level declaring routines. (Ada)
- **Root Withs:** Lists only program units (packages, tasks, subprograms) that With other program units, but are not withed by anybody else. (Ada)

## Information Browser

When you click on an item in the *Entity Filter* or in a number of other windows, the *Information Browser* updates to show everything that *Understand* knows about that entity. The *Information Browser* shows this data as a tree whose branches can be expanded individually or all at once.


If the Information Browser isn’t open, you can open it by either clicking on an item in the Entity Filter or Project Browser. You can also right-click on an item anywhere and choose **View Information**. Or, choose **View > Information Browser** from the menus.



Everything *Understand* knows about an entity can be learned using the *Information Browser*. The information is shown in a tree. The tree can be expanded selectively or in bulk. Each terminating item (leaf) of a tree provides some information about that entity.

All information in an *Information Browser* window can be saved to a text file, or copied and pasted via standard Windows or X11 copying functions.

As you drill down you can change which entity you are learning about. Each time you change the entity, it is remembered in the Information Browser history for quick backtracking.



### Drilling Down a Relationship


Drilling down the tree works as expected (mostly). To expand a tree, click on the + sign. To close the tree click on the - sign.

Right-clicking brings up a menu that includes expand/collapse options.


**Expand All** provides a shortcut to expand all levels of the selected branch.

To open or close the entire tree, right-click on the top item and choose **Expand All** or **Collapse All**.

See *Saving and Printing Information Browser Text* on page 138 for details on the other options in this context menu.



## Displaying More or Less Information


If you click the  icon next to a bold heading such as **Calls**, **Called By** or **References** in the Information Browser (or right-click on the heading), you'll see options that let you modify how that entity is listed. These options include:

- **Fullname:** If checked, the fully-qualified name of the entity is shown.
- **Parameter:** Lists the parameters.
- **Reference:** Choose "Full" to include the file and line location of the reference.
- **Return Type:** Lists the return type.
- **Sort:** Controls the sort order of the list.
- **Type:** If checked, the datatype is shown.
- **Filename:** Controls whether the reference format is short, long, or relative to the project database.
- **View by:** For lists of references, you can choose whether to display a flat list of references or to group references by the files that contain them or by one of the defined architectures.
- **Group by:** For C++ classes, you can choose whether to sort class members by the type of access available (public or private) or the kind of member (function or object).

## Searching the Information Browser

If you click the binocular icon at the top of the Information Browser (or click in the Information Browser and press Ctrl+F), a Find bar appears at the bottom of the Information Browser.

Type text in the box and click a forward or backward arrow to find an occurrence of the string in the Information Browser text. All text is searched, including node names and items that are currently hidden by collapsed nodes. If you type a string that does not appear anywhere in the Information Browser text, the field turns red.




To make the search **Case Sensitive** or to match only **Whole Words**, use the drop-down arrow to select those commands.

## Syncing the Information Browser

You can have multiple Information Browser windows open if you uncheck the **Sync** box. Selecting an entity or choosing **View Information** updates the Information Browser that has its **Sync** box checked.


If **Sync** is checked but you want to open a separate Information Browser, hold down the Ctrl key while choosing **View Information** from the right-click menu.

The **File Sync** box synchronizes the Information Browser with the file in the active Source Editor.



## Visiting Source Code

In general, if you double-click on an entity in an informational window (*Information Browser* or *Entity Filter*) the declaration of that entity will be loaded into the *Document Area*.




Another way to visit source from any entity you see in *Understand*, is the context menu. Where appropriate, an entity's context menu contains an **Edit Source** (Ctrl+Shift+S) menu item. In some cases, there are separate menu items for **Edit Definition** and **Edit Declaration** (Ctrl+Shift+D) or separate menus for other language-specific locations. If you have a \*.c or \*.h file selected, the **Edit Companion File** command opens the other file if one exists for that filename.




## Visiting References

The portion of the *Information Browser* labeled “References” lists everywhere the entity is referred to in the analyzed source code:



Left-click on any reference to visit that location in the source code.

Right-click on the “References” title for the node or click the down-arrow next to the node to choose how to organize the references. Your choices are the default flat list, and all of your architectures.




## Viewing Metrics

The last node on the Information Browser tree is **Metrics**. This branch shows the metrics available for the current entity.

By default, when you switch to another entity in the Information Browser, the Metrics node is closed automatically. This is because it can take a long time to update the metrics for each entity in a large project.

If your project is small enough that updating metrics as you switch between entities does not take a long time, you can right-click on the **Metrics** node and choose **Allow Pre-expansion**. The Metrics node will then stay open when you change entities. You see the following warning about the time required for metric updates.



See *Metrics Reports* on page 228 for details on metrics.


### Saving and Printing Information Browser Text

All text shown in the *Information Browser* can be copied to the clipboard for pasting into another application as unformatted text. Only the currently expanded branches are pasted. When saving or pasting in text format, the branches of the tree are represented by indents in the text.

The context menu offers choices to **Copy** (only the selected line) and **Copy All**. For entities with a class path and files, the **Copy** command copies the short name and the **Copy Full Name** command copies the full class path or file path.

### Entity History

As you explore your code, you can go many places quickly. Often you want to backtrack to explore a new path. To help you do this, the *Information Browser* contains a full history of what it has displayed. The *Information Browser* history can be found in the upper-left corner:




Use the right and left arrows to move back and forward in the history list. The down-arrows show the whole list.

You can choose **Clear History** from the drop-down history list to clear the browsing history.

## Project Browser

To open the Project Browser, choose **View > Project Browser** from the menus.



By default, the Project Browser is in the same area as the Entity Filter (and the Architecture Browser). Use the tabs on the left to switch between browser tools in this area.

The Project Browser shows the project files in their directory hierarchy. You can expand and collapse the tree as needed.


Press Ctrl+F to display a search line at the bottom of the Project Browser.

The **File Sync** box synchronizes the Project Browser with the file in the active Source Editor.

The context menus when you click on a file in this view offer the same commands as other views such as the Information Browser or Entity Filer.

The context menu when you click the background of this view offers a number of options. The options with icons are also available in the toolbar for the Project Browser.

Add a file to the project  
Remove selected file from project  
Expand all nodes of project tree  
Collapse all nodes of project tree  
Open file in Source Editor  
Open file with default OS tool  
Copy filename to clipboard  
Search for text in Project Browser  
Search in reverse direction  
Copy selected file to clipboard  
Change sort order of files



For a file, the context menu includes additional commands, including commands to open graphical views, rename the file, analyze this file only, find uses of the filename in project files, and add the file to the Favorites list.

The **Add Existing File** command lets you browse for and add source code files to the project.

To use the **Remove** command, select one or more files and folders and choose this command. The Confirm Project Modification dialog lists files that will be deleted from the project if you click **Yes**.

The **Open Externally** command opens an operating system dependent tool for the directory or file. For example, on Windows it opens a directory using the Windows Explorer. For a file it opens the default tool for the file extension.

The **Incremental Find** command opens a Find bar at the bottom of the Information Browser. Type text in the box and click an arrow to find an occurrence of the string in the Project Browser text. All text is searched, including files in folders that are currently closed. If you type a string that does not appear anywhere in the Project Browser, the field turns red. See page 135 for details on search options.

The **Sort By** command lets you organize the list alphabetically by filename or by file extension.

## Exploring a Hierarchy

The Exploring view lets you browse up and down a relationship hierarchy within your project.



The context menu in the Information Browser, Entity Filter, and Project Browser offers commands to Explore certain types of entities. The command will be similar to **Explore > Explore Called By/Calls** or **Explore > Explore Includes**.


If you click on an item in one column, you see its relationships in the columns on either side. As you choose items to the left or right, columns resize to show more of the hierarchy. Calls and Includes go from left to right. Callbys and Includebys go from right to left.

If you double-click an item, a Source Editor window shows the entity's definition.

The **References** area shows the line number of the currently highlighted relationship. Double-click to visit that code.

If you check the **Generate Syncs** box, then the Information Browser automatically displays information about any entity you select in the Exploring window. Holding the Shift key down temporarily activates this behavior.


If you check the **Jump to First Reference** box, then the Source Editor automatically displays the initial reference to any entity you select in the Exploring window. Holding the Ctrl key down temporarily activates this behavior.

Click the drop-down icon  if you want to enable any of the following display options:

- **Show Long Name:** Shows the long name of each call.
- **Show Parameters:** Shows the parameter list for each call.


## Dependency Browser

The Dependency Browser lets you examine which items are dependent on others. You can use the Dependency Browser with architecture nodes, files, classes, packages, and interfaces.



To open the Dependency Browser, right-click on an architecture node, filename, class name, or package name anywhere in *Understand*, for example in the Entity Filter, Information Browser, or a graphical view. Choose **View Dependencies** from the context menu. Or, click the **View Dependencies** button in a dependency graph. You can also open the Dependency Browser by choosing **View > Dependency Browser**.

The left panel shows the item you selected and the items it contains. The right panel shows items that either depend on the item selected in the left panel or are dependent on that item, depending on your choice in the **Dependency Kind** field. For example, an item depends on another if it includes, calls, sets, uses, casts, or refers to that item.




You can expand hierarchies in the left and right panels. For example, when you view dependencies for an architecture node, you can expand it to see lower-level architecture nodes, then files, then the entities in the files. Letters next to items identify whether they are architecture nodes ("a"), files ("f"), classes ("c") or entities in files ("e"). You can also right-click on either panel and choose **Expand All** or **Collapse All**.




You can use the **Group By** field to select an architecture to control how the items in the right panel are organized.


In the **Files, Classes, Entities** drop-down list, you can select whether to show each of these types of items in the right panel. If multiple items are checked, files are listed below the lowest-level architecture node that applies, classes are listed below files, and entities are listed below classes.





In the **All Dependencies** drop-down list, you can select types of dependencies to show. By default, all types are shown.

If you have the **Sync** box checked in the Dependency Browser and click on a relationship (connecting line or “edge”) in a dependency graph, the graph’s **Show** and **Group By** settings are copied to the Dependency Browser and the **Dependency Kind** is changed to Depends On.



Click the  **Graph** icon to create a graphical view of the dependencies currently shown in the Dependency Browser. While the Dependency Browser shows one level of dependency, graphical views can show multiple levels. See page 198 for details.


Click the  **Export** icon to export a comma-separated values (CSV) report of dependencies for the top item in the left panel of the Dependency Browser. You can also use the mouse to select items in the right panel of the Dependency Browser. Then right-click on a letter icon and choose **Copy** to place the currently selected text on your clipboard for pasting into other applications. See page 244 for other ways to export information about dependencies.

Click the  **Favorites** icon to add the current dependency to your Favorites list. See page 144.

If the **Reuse** box is unchecked, a new Dependency Browser is opened when **View Dependencies** is selected. The Reuse box is checked by default.

If the **Sync** box is checked, the Dependency Browser displays information about any architecture node, file, class, or package you select in the Project Browser, Entity Filter, Architecture Browser, or similar window.

If you have a dependency graph open and the **Sync** box is checked, the Dependency Browser syncs to show any relationship you select in the dependency graph, and the two nodes connected by the relationship are highlighted in the Dependency Browser. In addition, **Show** and **Group By** settings from the dependency graph are synced with the Dependency Browser and the **Dependency Kind** is changed to Depends On.

Click the drop-down icon  if you want to change any of the following display options:

- **Architecture Name.** The default is to show the relative name, but you can select short name or long name instead.
- **Entity Name.** The default is the short name. You can select the long name instead.
- **File Name.** The default is the short name. You can select the relative name or long name instead.



- **Use Include/Import References.** By default, “includes” and “imports” are treated as dependencies. You may want to omit such relationships if they are required for building but are not logically dependent. This option can also be controlled in the Dependency category of the **Tools > Options** dialog (page 110).
- **Allow Pre-Expansion.** If you enable this option, nodes in the Dependency Browser are automatically shown as expanded. This option is on by default, and can also be controlled in the Dependency category of the **Tools > Options** dialog.

## Favorites


You can mark all kinds of things in Understand as “Favorites” so that you can quickly access them as you would web pages in a browser’s Favorites group. Your favorites can include entities, code locations, graphs, Information Browser displays, and dependencies. You can also store multiple plain text strings in your favorites, so that you can quickly copy one of your saved strings to the clipboard.

Favorites are saved as part of a project. If you want to mark code locations on a cross-project basis, see *Annotations* on page 186.

### Creating a Favorite Entity

To mark an entity as a favorite, follow these steps:

- 1 Select an entity name and right-click in source code, the Entity Filters area, the Information Browser, a graphical view, or anywhere else entities occur.




- 2 Choose **Add to Favorites > Add To New Favorites** (or an existing favorites group). This adds a link to the entity itself, even if the line number changes later. If you’ve already created a favorites group, you can select it from the submenu instead of using **Add To New Favorites**.
- 3 Alternately, if you right-click on a source file, you can choose **Add Location to Favorites** to add the line number in the file to a favorites group.

See *Creating a Plain Text Favorite* on page 147 for information about the **Add Selection to Favorites** command, which stores text for pasting from the clipboard.




- 4 If you choose to create a new favorites group, you see the New Favorite dialog. Type a name for the new group and click **OK**.



- 5 When you create a favorite, the Favorites group opens.


### Creating a Favorite View

Besides entities and code locations, favorites can include graphical views, Information Browser views, and Dependency Browser views.



To add a favorite for any of these items, click the  **Favorites** icon in the toolbar for the view. By default, the view is added to the last favorites group you used. If you want to place it in a different group, choose a group from the drop-down menu.

### Using a Favorites Group


To open a Favorites group, choose **View > Favorites** and choose a group name from the menus. You see the favorites saved to that group.



In the Favorites view, you can use the drop-down list to switch to a different Favorites list.

Click on a link in the favorites group to jump to that location. You can open all the favorites in the current list by clicking the  **Open Favorites** icon and close all the favorites in the list by clicking the  **Close Favorites** icon.

You can add all the currently open files and graphical views to a Favorites list by clicking the small dimple icon in the upper-right corner of the document area and selecting the **Add Open Editors/Graphs to Favorites** command.




As with just about every place in Understand, you can right-click on a favorite to see a context menu that includes commands such as View Information, Graphical Views, and Find In.


An icon to the left of each favorite (and the text after the name of the favorite) identifies each favorite's type. For example, in the previous figure the first five favorites link to various types of entities or line numbers in the code.


Favorites with a  file icon link to a file.

Favorites with an  information icon link to an Information Browser view.

Favorites with a  dependency icon link to a Dependency Browser view.

Favorites with a  graph icon link to a graphical view.

Favorites with a  clipboard icon store text that you can paste into source code. See *Creating a Plain Text Favorite* on page 147 to store text as a favorite. When you click on a text favorite, the text is placed in your clipboard and you can paste it into Source Editor windows or other applications.

If you click the  **Configure** wrench icon at the top of a Favorites group, additional toolbar icons are displayed. These let you manage favorites you have already created as follows:



The arrow icons move the selected favorite up or down in the group.



Click this icon to create a header that you can use to organize your Favorites.



Click this icon to create a text favorite. See *Creating a Plain Text Favorite* on page 147 for details.



Delete the selected favorite from the group. You can also delete a favorite by going to its location, right-clicking, and choosing the **Remove from Favorites** command.



Rename the current favorites group.




Delete the current group of favorites.

## Creating a Plain Text Favorite

You can store multiple plain text strings in your favorites, so that you can quickly copy a saved string to your clipboard and paste it as needed into your code. For example, you might use a standard comment at the beginning of files or elsewhere in your code.



To save text as a favorite, follow these steps:


- 1 Select text in a Source Editor and right-click.



- 2 Choose **Add Selection to Favorites** and select a favorites group from the submenu.

- 3 When you create a favorite, the Favorites group opens.

You can also create a text favorite by clicking the  icon in the Favorites area (which you can see if you select the  **Configure** icon at the top of the Favorites area). You see the New Text Favorite dialog.



In the first field, type a short name to be shown in the Favorites list.

In the second field, type the full text of the favorite.

To use a text favorite, double-click on the name of the favorite in your Favorites list. This copies the longer text from the second field to your clipboard, so that you can paste it into a Source Editor.

If you check the **All Text Favorites copy to Understand Editor also** box, then when you click on a Text Favorite, the text you typed in the second field is automatically pasted into your current Source Editor window at the text cursor position.

## Chapter 5

# Searching Your Source

This chapter covers how to use *Understand*'s Find in Files and Entity Locator features to locate thing in your source code.

This chapter contains the following sections:

Section	Page
Searching: An Overview	149
Instant Search	150
Find in Files	152
Entity Locator	157
Finding Windows	162
Searching in a File	165

---

## Searching: An Overview

Finding things in large bodies of source code can be difficult, tedious, and error prone.

*Understand* offers a number of ways to search for strings in your source code or to locate particular lines. The commands for these options are located in the **Search** menu. These commands are described in the locations listed in the following table:

Search Command	See	Comments
Entity Locator	page 157	project-wide, entity-based
Find in Files	page 152	project-wide, text-based
Replace in Files	page 155	project-wide text-based
Instant Search	page 150	project-wide text-based
Find Next and Previous	page 165	single file
Find & Replace	page 165	single file
History	page 163	project-wide
Bracket Matching	page 180	single file
Favorites	page 144	project-wide
Contextual Information Sidebar	page 166	single file
Bookmarks	page 183	project-wide

Each of these searching methods has advantages and disadvantages. Together they provide powerful ways to easily find what you need to find to better understand and modify your code.

See page 130 for a more complete list of the code exploration tools in *Understand*.

## Instant Search

Instant Search lets you search your entire project instantly, even if it contains millions of lines of source code. As you type, you can see terms that match the string you have typed so far.

The search box for Instant Search is in the upper-right corner of the *Understand* window.


If you don't see this field, choose **View > Toolbars > Search** from the menus.

To begin searching, click in the Search field and type a string you want to find. You can also press Ctrl+Alt+S or choose **Search > Instant Search** from the menus to move your cursor to the Search field.



The easiest way to use Instant Search is to type a string that you want to match in your code. Press Enter after typing a search string to see a list of files that match your search in the Search Results area.

Right-click in this area to **Expand** or **Collapse** the results tree. Choose **Find** to use the **Previous** and **Next** icons to move through the results one-by-one. You can double-click on a file to open the file and see the line of code in the Search Results area.



A number of more powerful search options are supported with Instant Search. The syntax used by this field is based on the syntax used by Apache Lucene, an open-source text search engine library. See [lucene.apache.org/core/3\\_6\\_2/queryparsersyntax.html](http://lucene.apache.org/core/3_6_2/queryparsersyntax.html) for syntax details.

The following list explains some of the syntax options available:

- Searching is case insensitive. A search for test also matches “Test” and “TEST”.
- Unless you use wildcards, searching matches whole words. A search for test does not match occurrences of “testfile”.
- The wildcards available are \* (any number of letters and digits), ? (any single letter or digit). You cannot use a wildcard as the first character in a search string.

- When indexing the code (which happens in the background), Instant Search breaks code into searchable strings by splitting the code at white space and punctuation (and syntax conventions for C/C++, Java, and Ada). So, the searchable strings in the following line of code are “foreach”, 1, and 10:

```
foreach (i=1, i<10, i++)
```

- You cannot use Instant Search to find strings that cross punctuation boundaries or to search for punctuation itself. For example, you cannot search for “i=1”. You can search for strings that contain spaces (such as text in comments) by surrounding them with quotes.
- You can narrow the search to look within strings, identifiers, and comments. By default, it searches for all three types of matches. For example, the following search finds “test” only in quoted strings:

```
string:test
```

The following search finds “test” only in identifiers such as variable and function names:

```
identifier:test
```

The following search finds “test” only in comments:

```
comment:test
```

- You can use Boolean searches. The default is that multiple search terms are ORed. So, a search of “for delta” is the same as a search of “for OR delta”. Both match files that contain either “for” or “delta”. Remember that the search string is used to match terms in the entire file, not just in a single statement.
- If you want to AND the terms, use a search like “for AND delta”. This matches files that contain both “for” and “delta”.
- You can use the + operator to require that a search term exists in all documents found. For example, the following search finds documents that all contain “delta” and may contain “for”:

```
+delta for
```

- You can use the NOT (or -) operator to remove any documents that contain a particular search term from the results. For example, the following searches find documents that contain “delta” or “delta0” but not “delta2”:

```
delta delta0 NOT delta2
```

```
delta delta0 -delta2
```

- You can use parentheses to define the order of Boolean operators in searches. For example:


```
(delta0 OR delta1) AND change
```

- You can perform a “fuzzy” search by placing a tilde (~) at the end of a search term. For example boo~ matches foo, too, and book.

## Find in Files

You may search all project files or another selection of files for the occurrence of a text string or regular expression. Matches are shown in the *Find Results* window and can be visited in the source code by double-clicking on any line in the results. You can switch between the Find in Files and Replace in Files (see page 155) dialogs by checking the **Replace** box.

To open the Find in Files tool, choose **Search > Find in Files** from the menu bar, choose **Find in...** from any context menu, or press F5.




The Find in Files area allows you to search multiple files for the occurrence of a string. In previous versions, this feature was called Hyper Grep for its similarity to the Unix command *grep*. Specify a search as follows:

- **Find:** Type the string for which you want to search. The other fields control how this search is performed. The drop-down list lets you select from recent Find strings.
- **File Types:** You can select file extensions for various languages to narrow the search. Or, type your own file extension pattern. Leave this field blank to search all files. You cannot use this field if you have the **Find In** field set to “Open Files”. Check the **Exclude the File Types** box to exclude the selected file types from the search and search all other files in the project.



- **Case Sensitive:** Check this box for case-sensitive searching. The default is to ignore case.
- **Match Whole Words:** Check this box to match whole words only in regular expressions (“test” matches “test” but not “testing”). For fixed string and wildcard searches, word boundaries are ignored.
- **Search Type:** Choose whether to use Fixed String, Wildcard, or Regular Expression matching. See page 160 for details.
- **Find In:** Choose whether to search project files (either all files or just the open files), files in architecture nodes you select, files in directories you select, or files you select.



For **Architecture**, **Directory List**, and **File List** searches, click + to add a location. Click the pencil icon to modify the selected location. Click the red X icon to delete the selected location. You can uncheck a location to temporarily disable searching it.

If you select **Architecture**, click + to browse for an architecture node.

If you select **Directory List**, click + to browse for directories. You can click the minus icon to exclude the selected directory from the search. Sort the list with up and down arrows.

If you select **File List**, you can click + to browse for files.

If you select **Open Files**, all files that are currently open are searched. The **File Types** specification can be used to limit which open files are searched.


When you right-click on an entity in source code or elsewhere, the **Find In** command lets you choose one of these options for the selected text string. The Find and Find In fields are filled in for you automatically.

- **Semantic Options:** If you choose to Find In “Project Files” or “Architecture”, you can check the **Only Show Results In** box to be able to control which matches are reported. Then you can check any combination of the **Comments**, **Strings**, **Statements**, and **Inactive Code** boxes to include those types of lines in the results. You must check at least one of these boxes if you check the **Only Show Results In** box.
- **Replace:** Switch to the Replace in Files (see page 155) dialog by checking this box.

Click **Find** after specifying the search criteria. A list of all matching instances will be displayed in the *Find Results* window. If the search is taking a long time and you want to change the criteria, you can click **Stop**.

## Find Results

The Find Results window lists the matches found. Each line where the string occurs is listed in the Results list.



You can view the source code for a match by double-clicking on a result. This opens the Source Editor and highlights the match. See *User Interface > Windows Category* on page 104 for ways to customize the Find Results display.

Multiple searches are shown in the results list. Right-click on the background of the window and choose **Expand All** to expand all search nodes in the window. Or, choose **Collapse All** to compress the list to just the top-level search listing.

The toolbar (and context menu) for the results provides the following controls:

- Go to Find in Files dialog.
- Search within the currently selected set of results (using the same search bar described in *Searching the Information Browser* on page 135).
- Delete the current set of results.
- Delete all the results.
- Open the selected match in the Source Editor.
- Move to the previous or next match.
- Check the **Criteria** box to show the settings used to perform the search.

The drop-down icon in the upper-right corner of the Find Results area provides the following commands:

- By default, only the names of files are shown. To show full file paths, select "Long Names" from the **Display Files As** drop-down.
- Use the **Organize Results By** drop-down to change the organization of the most recent results. The choices are a flat list (the default), a file-based list, and hierarchies using the architectures.
- Choose **Show Criteria** to have the line that shows the number of results also list the search options that were used for each search.

- Choose **Expand All by Default** to automatically expand all lines when new results are added.
- Choose **Clear Results Before Search** to automatically clear the results of the previous search whenever you run a new search.

From the context menu, you can choose **Copy** or **Copy All** to copy the contents of the window as text for pasting elsewhere.

You can reopen the Find Results window by choosing **Search > Show Find in Files Results**. All the results from the current session are shown unless you have used the toolbar in the Find Results window to delete some results.

## Replace in Files

You can use the Replace in Files tool by choosing **Search > Replace in Files** from the menu bar or by checking the **Replace** box in the Find in Files tool.


The fields in this tool are the same as those in the Find in Files tool with the following exceptions:

- There is a **Replace** field where you type the text you want to replace the matched string.
- In the **Search Type** field, you can select “Regular Expression - Non Greedy” in addition to the options available for Find in Files.


To switch between the Replace in Files and Find in Files tools, check or uncheck the **Replace** box just above the Stop button.

*Understand* checks for any unsaved source files. If there are unsaved files, you must click **Yes** to save all unsaved changes before making or previewing the changes.


If you click **Replace All**, you are asked if you want to replace all results automatically. The changes will be saved automatically, so you should be sure you want to make all the changes.



If you click **Preview Replace**, you see the Preview Replace Changes window. You can use this window to accept or reject replacements on a change-by-change basis, file-by-file basis, or all at once.




The top area shows the pre-change code on the left and the post-change code on the right. Replacements are in pink and the currently selected replacement is highlighted in blue. The left side has the **Hide Common Lines** option set so that most lines that will not be affected by the replacement are hidden.

The middle area shows the replacements in patch file format. Such patch files can be used with the Unix patch tool and other similar programs. You can hide this area by clicking the small  fold icon above the area.


The lower area lists the files where replacements will be made and the number of replacements accepted and unresolved.

The navigation icons let you move to the next and previous file and the next and previous replacement.

The accept and reject icons let you accept or reject replacements on a change-by-change basis, file-by-file basis, or all at once.



Replacements that you have accepted are marked in the source display with green circles. Replacements that you have rejected are marked with red circles. Unresolved replacements are marked with question marks. You can click on a green circle to change it to red, and vice versa.



When you have finished resolving differences by either accepting them or rejecting them, click **Commit**. You are asked whether you are sure you want to make the replacement. The message shows how many replacements will be made.


If you are sure you want to make all the changes, click **Accept All** and then click **Commit Changes** in the All Changes Resolved message window.

If you decide not to make changes, you can click **Cancel** at any time. If you have accepted any replacements, you see a message that asks if you are sure you want to cancel without making replacements.

## Entity Locator

Not all entities fall into one of the tab categories shown in the *Entity Filter*. You can find and learn more about any entity by using the *Entity Locator*, which provides a filterable list of entities in the database. You can filter by name, by entity type, by where the entity is declared, within what container the entity is declared, or when the entity was last modified. You can also use architecture hierarchies to sort entities.

To open the *Entity Locator*, choose **Search > Find Entity** or **View > Entity Locator** from the main menu bar.



As in other windows in *Understand*, when you right-click on an entity anywhere in the *Entity Locator*, a menu of commands available for the item appears.


If you check the **Sync** box, selecting entities in other *Understand* windows causes the Entity Locator to select that entity unless filters prevent the entity from being displayed.

### Resizing Columns

Column widths can be sized to adjust how much of each column is visible. You can drag the column header divider between two columns to resize the column to the left. Or, double-click on the column header divider while the double-headed arrow is displayed and the field to the left of the divider will be expanded or shrunk to the maximum size needed to view all items in that column.


You can right-click on a column header and choose **Freeze Column** to move that column to the left and prevent it from being repositioned. By default, the File column is frozen and is the left column.

### Long versus Short Names

In the *Entity*, *Declared In* and *File* columns, you can right-click the column header or click the drop-down icon  to specify the display format for entity names and filenames. For entities, you can choose the short or full name (which includes the name of the compilation unit). For filenames, you can choose the short, full, or relative path.

## Column Headers


Column headers are tools in the *Entity Locator*. Left-click them to sort according to that column. Right-click a column or click the drop-down icon to see a menu that lets you control how entities are listed, sorted, and filtered.



The entity list may be sorted by any column. Left-click on the column header to toggle between sorting in ascending order and descending order. The default sorting order is in ascending order of entity names.

## Choosing Columns

Click the + icon in the upper-right of the Entity Locator to see the Locator Column Chooser.



The **Entity** column must always be displayed. You can enable or disable the other columns.

## Filtering the List

The field below each column heading lets you filter the entities shown by the *Entity Locator*. The filter can be entered manually or automatically based on what was right-clicked on.


For example, you may filter by the *Kind* column selecting a kind from the drop-down list. You can also right-click on any item listed in the *Kind* column and select **Filter By Selection** from the menu. This filters the list of entities to contain only entities of the kind you selected. The title bar shows how many entities match the filter.

Or, you can simply type a filter in any of the fields. To search for field values that do not contain a particular string, type ! (exclamation mark) and then the filter.

To clear a filter, just delete the text from the field in the column heading or right-click a column header and choose **Clear Filter** or **Clear All Filters**.

You can use the **Previous** and **Next** buttons to move through the history of filters you have used.

The following example shows **Filter By Selection** for an entity *Kind*:



To filter the Date Modified column, the left drop-down lets you select a comparison operator ( <, <=, =, >=, > ), and the right drop-down lets you select a date from a calendar. You can modify the time by typing. You must select a comparison operator in addition to a date in order to filter the entities.

Similarly, the metrics columns allow you to filter with a comparison operator. For example, you can filter the entities to show only those with a Cyclomatic complexity greater than some value or a Comment-to-Code ratio less than some value.

Right-click a column or click the drop-down icon to see the context menu for that column. You can choose for the filter case sensitivity to be **Case Sensitive** or **Case Insensitive** (the default). You can also set the **Filter Pattern Syntax** to use fixed strings (the default), wildcards, or regular expressions.

- **Fixed string:** The string you type matches if that exact string is found anywhere in the column value.
- **Wildcard:** These are \* or ?, where \* matches any string of any length and ? matches a single character. For example, ??ext\_io matches any name having 8 letters and ending in *ext\_io*.
- **Regular expression:** A powerful and precise way to filter and manipulate text. You cannot use the **Case Sensitive** option if you are using regular expressions.

Using ! to search for field values that do not contain a particular string can be used with any Filter Pattern Syntax.

The following table lists some special characters used in regular expressions.

Symbol	Description	Example
^	Match at the beginning of a line only.	<i>^word</i> Finds lines with word starting in the first column.
\$	Match at end of a line only.	<i>word\$</i> Finds lines that end with “word” (no white space follows word).
\<	Match at beginning of word only.	<i>\&lt;word</i> Finds wordless and wordly but not fullword or awordinthemiddle.
\>	Match at end of word only.	<i>\&gt;word</i> Finds keyword and sword but not wordless or awordinthemiddle.
.	A period matches any single character.	<i>w.rd</i> Finds lines containing word, ward, w3rd, forward, and so on, anywhere on the line.
*	Asterisk matches zero or more occurrences of the previous character or expression.	<i>word*</i> Finds word, wor, work, and so on.
+	Match one or more occurrences of the previous character or expression.	<i>wor+d</i> Finds word, worrd, worrrd, and so on.
?	Match zero or one occurrences of the previous character or expression.	<i>word?d</i> Finds word and wod.




Symbol	Description	Example
[ ]	Match any one of the characters in brackets but no others.	<i>[AZ ]</i> Finds any line that contains A or Z. <i>[Kk][eE][Nn]</i> Finds any variation of case when spelling "Ken" or "KEen" or "keN".
[ ^ ]	Match any character except those inside the brackets.	<i>[^AZ ]</i> Finds any line that does not contain the letters A or Z.
[ - ]	Match a range of characters.	<i>[A..Z]</i> Finds any line containing letters A through Z on them but not lower case letters.
	A vertical bar acts as an OR to combine two alternatives into a single expression.	<i>word   let+er</i> Finds word, leter, letter, lettter, and so on.
\	Make a regular-expression symbol a literal character.	<i>\*/\$</i> Allows searching for *. This example finds all lines ending in */

A full explanation of regular expressions is beyond the scope of this manual. Unix users may refer to the manual page for *regex* using the command “*man -k regex*”. For a comprehensive explanation of *regex* expressions we refer you to the book “*Mastering Regular Expressions*”, published by O'Reilly and Associates ([www.ora.com/catalog/regex](http://www.ora.com/catalog/regex)).

## Finding Windows


If you have a number of windows open, you can use the options in the **Window** and **View** menus to organize or find particular windows.

You can close the current document window by choosing **Window > Close <current\_window>**. You can close all source files, graphical views, and other document windows by choosing **Window > Close All Document Windows**. If you have many windows open in the document area, you can right-click on the tab for the window you are using and choose **Close All**, **Close All But This**, **Close All Tabs to the Left**, or **Close All Tabs to the Right**.


If you choose **Window > Release Window**, the tabbed area changes to a separate window that can be resized and moved around your screen. You can select **Capture Window** from the drop-down icon  in the upper-right corner of a released window to replace the window within the main *Understand* window.

The Window menu also lets you use **Window > Split Vertically** or **Window > Split Horizontally** to split the document area. When the document area is split, new areas open in the half that has its box checked. You can drag tabs from one half of the document area to the other as needed. Choose **Window > Unsplit** to remove the split. You can use **Window > Tile** or **Window > Cascade** to arrange the open windows.

The **Window > Predefined Window Layouts** command lets you choose from several standard layouts for common tools. The layouts include the “Tight” layout, “Classic” layout, and “Multi-monitor” layout.



The **Window > Windows Navigator** command (Ctrl+Tab) opens a temporary list of currently open windows. When you double-click on an item in this list, the list goes away and focus is given to the item you chose. You can dismiss this area without choosing a window by pressing Esc.



You can reduce the number of windows listed here by choosing a window type from the **Show** list. Or, you can check the **Type-Ahead Filter** box and begin typing some characters in the name of the window you are looking for. Checking the **Alphabetic Sort** box sorts both the docked windows and the document windows. The list of windows is filtered to match the string you type after checking the box.

### Source Visiting History

You can move forward or backward through the history of your source code visiting locations using **Previous** and **Next** icons in the toolbar. This history is stored even between *Understand* sessions.




You can click the down-arrows to see the list of source locations in the history. You can choose **Clear History** from the drop-down Go Back list to clear the browsing history.

### View Menu Commands


If you have analyzed the project during this session, you can use the **View > Analysis Log** command to reopen the log.

The **View > Window Selector** command opens an area that lists currently open windows. By default, this area lists only document windows, but you can use the **Show** drop-down to change the type of window listed. Any released windows are listed in underlined italics.

Click a window name to make it active. By default, the Selector lists all windows, but you can choose to show only Editor windows or various other window types. The icons indicate the type of window, including whether the source file is unsaved.



When the Selector area is active, you can type a filter at the bottom of the area to quickly narrow the list. Press Backspace to erase the filter.

You can use the drop-down icon  to change the order from alphabetic to most recently used or by file extension. You can also use the drop-down icon to change the filename format to show the short, relative, or absolute file paths.

Using the Selector is a convenient way to perform actions—such as Close—on multiple windows by selecting multiple windows from the list, right-clicking, and choosing **Close Selected Window(s)** or **Close Unselected Window(s)**.


If you have created bookmarks in your source code (page 183), you can use the **Bookmarks** command in the View menu to open the list of bookmarks.

---

## Displaying Toolbars

You can hide or display categories of toolbar icons by right-clicking on the toolbar or menu bar and choosing a category. The toolbar is separated into the following categories: Project, File, Edit, Analyze, Editor History, Graphs, User Tools, Browse, Split Workspace, Scopes, and Search.

You can also hide and display toolbar sections by choosing **View > Toolbars** from the menus.




## Searching in a File

The search techniques described in this section are used to search a single source file.

### Find Next and Previous

To search quickly within the current file, press Ctrl+F (or choose **Search > Find**). The status bar of the Source Editor changes to a search bar.



You can type a string in the field. As you type, matches for that string are highlighted in the Source Editor.


Click **Previous** or **Next** to move from match to match. You can check the **Case Sensitive** and **Whole Words** boxes to modify how the search is performed.

If the string does not exist in the file, the search field turns red.

If you check the **Hide** box, then as soon as you click on the code, the incremental search bar is hidden. When you press Ctrl+F again, your last search is shown. Use Ctrl+Shift+F to find the previous occurrence.

### Find & Replace

If you want to use Search-and-Replace or regular expressions for searching within a single source code file, you can use the Find dialog. To open this dialog, choose the **Search > Find & Replace** menu item or press Ctrl+Alt+F.



In the **Find** field, type the string you want to find.


You can check the **Regular expression**, **Match case**, and **Match whole words** boxes to modify how the search is performed. If you check the **Regular expression** box, you can use Unix-style pattern matching. For a list of some of the capabilities of regular expressions, see page 159.


If you want to replace the string you are finding, type that in the **Replace** field.

Click **Previous** or **Next** to search in either direction. Click **Replace All**, **Replace**, or **Replace & Find** if you want to replace the string that was found.

The Find dialog searches only individual files. To search multiple files, see *Find in Files* on page 152.


## Contextual Information Sidebar

The Contextual Information Sidebar (CIS) is similar to the Scope List (see page 169), but more powerful. You can open the CIS by choosing **View > Contextual Information** from the menus. You can click the  icon in the toolbar to open or close the Contextual Information Sidebar.



The CIS shows the structure and information for the currently active Source Editor. The tabs in the CIS provide the following information:

- **Structure Browser:** This is an expanded scope list for the current file. It lists the names of structures in the file. In addition to functions, it lists includes, macros, classes, and more. The icon next to the name indicates the type of entity. If you point your mouse cursor at an item, the hover text shows the entity type and name. Press Ctrl+F to search within this tab.
- **File Information:** This tab provides an Information Browser for the current file.
- **Scope Information:** This tab provides an Information Browser for the current entity—that is, the one highlighted in the Structure Browser tab.
- **Context Browser:** This tab shows the current entity's location in the hierarchy on the left and the entities it contains on the right.

The  switch icon (Ctrl+,) to the right of the File Information tab changes the current file in the Source Editor and the CIS to a file in the same directory with the same name but a different file extension (the “companion file” if such a file exists). For example, the switch icon can toggle from a \*.c or \*.cpp file to a \*.h file with the same name.

As always, right-clicking in any of these tabs provides links to more information about each entity.

## Chapter 6

# Editing Your Source


This chapter covers *Understand*'s source and text file editor.

This chapter contains the following sections:

Section	Page
Source Editor	168
Saving Source Code	172
Refactoring Tools	173
Other Editing Features	179
Annotations	186
Printing Source Views	192

## Source Editor

The **Source Editor** offers a full featured source code editor, with syntax coloring and right-click access to information most entities in your code.



The line numbers and “fold” markings to expand/collapse blocks of code can be turned on and off in the **Editor** category of the Understand Options dialog you can open with the **Tools > Options** command (see page 111). The display font and a number of other items can also be changed in the **Editor** category. You can also enable bookmarks, indent guide marking, and a right margin marker (page guide) in that category of the dialog.

You can zoom in or out to make the text larger or smaller by choosing one of the **View > Zoom** menu options.

The **Editor > Styles** category of the Understand Options dialog (see page 117) lets you change the colors used for different types of source code. The **Key Bindings** category (see page 107) shows a list (and lets you modify the list) of keystrokes you can use in the Editor.





## Scope List

You can jump to a particular function, procedure, or other language-specific construct in the current source file by selecting from the scope drop-down list in the toolbar. The drop-down list shows all such constructs in the file the last time the project was analyzed.

You can click the **+** icon or choose **View > Scope List** to open the list in a Scope tab in the area where the Entity Filter is shown. This tab lists constructs in the current source file. This tab is useful for jumping around in large files.

The numbers next to each name in the Scope tab are the line numbers where each entity is declared in the file. Single-click on an item to view information about it in the Information Browser. Double-click on an item to jump to the location where that item is declared or created and to highlight all occurrences of that name in the current source file.




You can right-click on the Scope tab to choose a sort order from the context menu. The ascending and descending orders sort alphabetically or reverse alphabetically. The default is to sort by line number.



For more power than the scope list, use the *Contextual Information Sidebar* on page 166.


## Status Icons

Each file in a Source Editor has a status icon in its upper-left title bar. The letter in the icon indicates the type of file. The icon color indicates whether the file has been modified but not yet analyzed. An asterisk by the filename means the file has unsaved changes.


-  Yellow icon = analyzed project file (has not been modified)
-  Red icon = modified project file (needs to be analyzed)
-  White icon = file not in the project

## Status Line

When a Source Editor is the active window, the status bar at the bottom of the *Understand* window shows the last time CodeCheck was run on this file, the line number and column number of the cursor position, the tab width setting for this file, whether the file is in read-write or read-only mode, and the source language.



If you click the line number in the status bar (or choose **Search > Go to Line** from the menus), you can use the Go To Line dialog.



If you click the Tab Width, you can change the tab width for this file. See page 182.

If you click the RW (read-write) indicator, it changes the mode to RO (read-only).

If you click the language, you can choose which language this file is treated as using.

## Selecting and Copying Text

Text can be selected (marked) then cut or copied into the Windows (or X11) clipboard. Selecting text works as standard for the operating system in use. On Windows, dragging while holding down the left mouse selects text. Alternately you can hold down the Shift key and move the cursor (via arrows or the mouse). Choose the **Select All** command in the **Edit** menu or the context menu to select the entire file.

If you hold down the Alt key (Ctrl key on X Windows), you can drag the mouse to select a rectangular area of source code—for example, to exclude tabs in the left margin from the copied text. You can also paste rectangular areas of code within the Source Editor.

```

15  #define DO1(buf,i)  {adler += (buf)[i]; sum2 += adler;}
16  #define DO2(buf,i)  DO1(buf,i) ; DO1(buf,i+1) ;
17  #define DO4(buf,i)  DO2(buf,i) ; DO2(buf,i+2) ;
18  #define DO8(buf,i)  DO4(buf,i) ; DO4(buf,i+4) ;
19  #define DO16(buf)   DO8(buf,0) ; DO8(buf,8) ;
20

```

Once you select text, you can use the **Cut** and **Copy** commands in the **Edit** menu or the context menu. You may then paste the text into other applications as needed.

For entities with a class path and files, the **Copy** command copies the short name. The **Copy Full Name** command in the context menu copies the full class path or file path.

## Browse Mode

You can switch a Source Editor to “Browse” mode by clicking the **Browse** button in the main toolbar or choosing **View > Browse Mode** from the menus. When you are in Browse mode, the icon is highlighted.



When you are in Browse Mode, entities in the code act as links. An underline is shown when your mouse cursor moves to a link. Clicking a link moves you to the declaration of that entity and updates the Information Browser to show details about that entity.

If the declaration of an entity you click on is not found, a message is shown in the status bar and your computer beeps.

When you are in Browse Mode, you can still edit the file and the keyboard and right-click function the same as in regular mode. Only left-clicking the mouse is different.

You can temporarily enter Browse Mode by holding down the Ctrl key while using a Source Editor window. You can toggle Browse mode by pressing Ctrl+Alt+B.

See page 118 for settings to control the behavior of Browse Mode.

---

## Context Menu

The context menu in the Source Editor provides access to a number of exploration and editing features. Many of them let you find specific information about the entity you right-click on.

The following exploration features are typically included in the context menu (depending on where you click):

- View Information (see page 133)
- Graphical Views (see Chapter 10)
- Edit Source/Definition (see page 136)
- User Tools (see page 316)
- Explore (see page 141)
- Find in... (see page 152)
- Add Favorite (see page 144)
- Metrics Charts (see page 239)
- Metrics Browser (see page 235)

The following editing features are also typically included in the context menu:


- Undo / Redo
- Cut / Copy / Paste (see page 170)
- Select All (see page 170)
- Jump to Matching Brace (see page 180)
- Select Block (see page 180)
- Hide/Show Inactive Lines (see page 180)
- Fold All (see page 180)
- Soft Wrap (see page 182)
- Comment Selection / Uncomment Selection (see page 181)
- Change Case (see page 181)
- Revert (see page 172)
- Add Bookmark (see page 183)

**Hover Text**

If you point the mouse cursor at an entity in source code, you see a message that shows declaration information about that entity. For example, pointing to a variable shows the variable's type, pointing to a constant shows the constant's value, and pointing to a function call shows the parameters and return value.

```
if (len < 0) error (gzerror(in, &err));
if (len == 0) break;


if ((int)fwrite(buf, 1,
    error("failed fwrite");
```



## Saving Source Code

If you have edited a source file, you can click , press Ctrl+S, or choose **File > Save** to save your changes.

You can choose **File > Save As** to save to a different file. If you save a project file to another filename, you will be asked whether you want to add the new file to the project.

If you have edited multiple source files, you can click  or choose **File > Save All** to save changes to all modified files.

If you want to ignore changes you have made choose since the last save, right-click in a file and choose **Revert**.


You can close the current source file by choosing **Window > Close <current\_file>** from the menus. You can also middle-click on the tab above the source file area to close that tab (if your mouse has a middle button).

You can close all source files by choosing **Window > Close All Document Windows**. You can also right-click on the tab for the source file area and choose **Close**, **Close All**, **Close All But This**, or **Close All Tabs to the Right/Left**.

## Refactoring Tools

Refactoring tools allow you to make structural changes to your code. Ideally, refactoring does not change the behavior of the code.


The refactoring tools allow you to preview the changes using a code comparison window. Refactoring changes can have significant effects on code, and should be reviewed before committing to make certain that the changes are correct.



The following refactoring tools are provided:

- **Rename:** page 174 (various languages)
- **Inline Function:** page 175 (C/C++)
- **Extract Function:** page 176 (C/C++)
- **Extract Temp:** page 178 (C/C++)

If files have not been saved when you select a refactoring command, you are asked if you want to save the files and reanalyze the project. We recommend that you do this, so that the *Understand* database will contain current information about your project.




If you perform a **Refactor** operation and then decide that you did not want that change, right-click and choose **Refactor > Undo** from the context menu. In some cases, the refactoring operation cannot be undone because of subsequent changes.

## Renaming Entities


A command to rename entities is provided in order to support refactoring of your code in order to make your code more readable. It allows you to change the name of an entity throughout your project. The **Refactor > Rename** command is similar to **Replace in Files** (page 155). However, the difference is that the **Refactor > Rename** command determines which uses apply to that specific entity. This makes it a better way to rename such things as variables that are used locally, entities in applications with a variety of namespaces, and entities with names that may be a part of another entity name (for example, renaming a “src” variable without renaming “srcTimer”).

To use the **Refactor > Rename** command, follow these steps:

- 1 Highlight the name of the entity (for example, a function or argument) to change.
- 2 Right-click and choose **Refactor > Rename** from the context menu.
- 3 Type a new name for this entity in the dialog and click **Preview Changes**. If you are absolutely sure you want to perform the renaming operation, click **Apply Changes**.



- 4 A dialog opens that lets you examine all the instances where this entity name is used and how it will be changed. Code Comparison on page 304 describes the icons and drop-down menus in this dialog.




- 5 If you are sure you want to make all the changes, click **OK**.

## Inlining Functions


Inlining functions is a common optimization technique that places the code of a function at the location where it is called instead of in a separate function. In compiled languages, this can often be performed through compiler optimization, but inlining the source code may be useful for various reasons, including code clarity. Note that inlining involves tradeoffs. If a function is called in many places, inlining the code results in a larger code size and less maintainable code.

To use the **Refactor > Inline Function** command, follow these steps:

- 1 Highlight the name of the function you want to inline.
- 2 Right-click and choose **Refactor > Inline Function** from the context menu.
- 3 Click **Preview Changes**. If you are absolutely sure you want to perform the inlining operation, click **Apply Changes**.



- 4 A dialog opens that lets you examine all the changes that will occur. Code Comparison on page 304 describes the icons and drop-down menus in this dialog.




- 5 If you are sure you want to make all the changes, click **OK**.

**Extracting Functions**


The opposite of function inlining is function extraction. You can extract some code to a separate function so that it can be called in several places and maintained in one place.

To use the **Refactor > Extract Function** command, follow these steps:

- 1 Highlight the code that you want to extract as a function.
- 2 Right-click and choose **Refactor > Extract Function** from the context menu.



- 3 Type a name for the function to be extracted and called from this code location.
- 4 Select the value or variable to be returned by the function.
- 5 For the parameters to be passed to the function, you can use the Move Up and Move Down buttons to change the sequence and check the boxes to identify parameters to be passed as const values or by reference.
- 6 Click **Preview Changes**. If you are absolutely sure you want to perform the operation, click **Apply Changes**.
- 7 A dialog opens that lets you examine all the changes that will occur. Code Comparison on page 304 describes the icons and drop-down menus in this dialog.



- 8 If you are sure you want to make all the changes, click **OK**.



## Inline Temp


Inline temp refactoring can be used with a local or temporary variable that is initialized and never set after that. The inlining replaces uses of that variable with the expression to which it is initialized. In the following example, `patlen` could be inlined as `altmin`, so long as the value of `patlen` and `altmin` do not change between the initialization and any usage of `patlen`:

```
int patlen = altmin;


for (k = str + patlen - 1; k < strend;) {
    ...
}
```

To use the **Refactor > Inline Temp** command, follow these steps:

- 1 Highlight the variable to inline.
- 2 Right-click and choose **Refactor > Inline Temp** from the context menu.
- 3 If you want the expression that replaces the variable to be surrounded by parentheses, check the box.
- 4 Click **Preview Changes**. If you are absolutely sure you want to perform the operation, click **Apply Changes**.



- 5 A dialog opens that lets you examine all the changes Code Comparison on page 304 describes the icons and drop-down menus in this dialog.




- 6 If you are sure you want to make all the changes, click **OK**.

## Extract Temp


The opposite of inline temp is extract temp. If you have a complicated expression, you may want to assign a part of that expression to a local or temporary variable that can be reused within that function wherever the expression you select is used.

To use the **Refactor > Extract Temp** command, follow these steps:

- 1 Highlight the expression you would like to extract to a local or temporary variable.
- 2 Right-click and choose **Refactor > Extract Temp** from the context menu.
- 3 Type a name for the extracted variable in the dialog and click **Preview Changes**. If you are absolutely sure you want to perform the operation, click **Apply Changes**.



- 4 A dialog opens that lets you examine all the changes Code Comparison on page 304 describes the icons and drop-down menus in this dialog.



- 5 If you are sure you want to make all the changes, click **OK**.

## Other Editing Features


The Source Editor also provides several other options for displaying and editing files:

- [Previewer on page 179](#)
- [Bracket Matching on page 180](#)
- [Folding and Hiding on page 180](#)
- [Splitting the Editor Window on page 181](#)
- [Commenting and Uncommenting on page 181](#)
- [Changing Case on page 181](#)
- [Indentation on page 182](#)
- [Line Wrapping on page 182](#)
- [Insert and Overtyping Modes on page 182](#)
- [Sorting Lines Alphabetically on page 182](#)
- [Keyboard Commands on page 182](#)
- [Recording, Playing, and Saving Macros on page 182](#)
- [Creating and Opening Files on page 183](#)
- [Bookmarking on page 183](#)
- [Managing Source Editor Tabs on page 185](#)
- [Changing the Source Code Font Size on page 185](#)

### Previewer

The Previewer window is similar to a Source Editor window. To open the Previewer window, choose **View > Previewer**. The differences between the Previewer and the Source Editor are as follows:

- You cannot edit the code in the Previewer window.
- **Sync checkbox**; If this box is checked, a single-click on an entity in another view displays the location where that entity is defined in the Previewer.
- **Prefer checkbox**; If this box is checked, a double-click on an entity in another view displays the location where that entity is defined in the Previewer. (Double-clicking on an entity in the Previewer always opens that entity's definition in the Source Editor.)



---

**Bracket Matching**

A handy feature of the *Understand* editor is syntax bracket matching. Use this feature to find the matching ending character for a brace, parenthesis or bracket. Symbols matched are ( ), { }, and [ ]. Matching isn't done inside comments.

Pressing Ctrl+j (or right-click and **Jump to Matching Brace**) jumps the editor to the matching end or beginning brace. Ctrl+j isn't active unless your editing cursor is by a symbol that it can match. Another Ctrl+j takes you back where you started. You can also choose **Search > Go to Matching Brace** from the menus.

Pressing Ctrl+Shift+J (or right-click and **Select Block**) selects all the text from the bracket to its matching bracket.


Brackets without a match are highlighted in red when you move your cursor to them. Brackets with a match are highlighted in green.

When your cursor is on a preprocessor directive that has a match (for example, #ifdef and #endif), you can use Ctrl+j (or right-click and **Jump to Matching Directive**) to move your editing cursor to the match.

---

**Folding and Hiding**

The - and + markings next to the line numbers allow you to "fold" the code to hide blocks such as functions, if statements, and other statements that have a beginning and end.



```
7  #ifndef std__include
8  #ifndef nested
15 #endif
```

If you right-click on the code, you can choose **Fold All** to close all the open blocks. You can also fold and unfold source code by choosing **View > Fold All** from the menus.


You can add explicit fold markers to code in languages where // is treated as the beginning of a comment. For example:

```
//{{
/* code to hide when folded */
//}}
```

You can also choose **Hide Inactive Lines** to hide preprocessor lines that are not active because a preprocessor macro is not defined. Choose **Show Inactive Lines** to view all lines again. You can also toggle this setting by choosing **View > Hide Inactive Lines** from the menus.

## Splitting the Editor Window

You can click the **Split** icon (circled below) to divide the source editor into two or more separately scrollable panes. Click one of the **Join** icons to merge two panes.



## Commenting and Uncommenting

You can comment code that you have selected by right-clicking and choosing **Comment Selection**. To remove the comment characters, right-click and choose **Uncomment Selection**. You can do the same thing using the **Edit > Comment Selection** and **Edit > Uncomment Selection** commands in the menus.

Note that nested comments within the selection are not analyzed.

## Changing Case

You can change the case of selected text in the Source Editor. Follow these steps:


- 1 Select a word or words in the source code.
- 2 Choose **Edit > Change Case** from the menus, or right-click and choose **Change Case** from the context menu.
- 3 Choose the type of case you want to apply to the selection. The choices are as follows:

Choice	Default Keystroke	Original	Result
Lowercase	Ctrl+U	Test_me please	test_me please
Uppercase	Ctrl+Shift+U	Test_me please	TEST_ME PLEASE
Invert Case	Ctrl+Shift+I	Test_me please	tEST_ME PLEASE
Capitalize	Ctrl+Alt+U	Test_me pleaSe	Test_me PleaSe

---

**Indentation**

You can click **Tab Width** in the status bar at the bottom of the window to open a dialog that lets you set the number of columns for each tab stop in this file. This setting is saved separately for each file, and overrides the setting in the Editor category in the Options dialog (see page 111).



You can make the indentation of selected code match standard usage by selecting the code, right-clicking, and choosing **Reindent Selection**. Indentation preferences are controlled by the **Editor > Advanced** category in the Options dialog (see page 113).

---

**Line Wrapping**

Normally, lines are cut off on the right if your Source Editor window is not wide enough to display the full line length. You can make the Source Editor wrap long lines to display all the code. To do this, right-click in the Source Editor and choose **Soft Wrap**. You can also change the wrapping mode by choosing **View > Soft Wrap** from the menus. The wrapping is for display only; no actual line breaks are added to your source file.

See *Editor > Advanced Category* on page 113 to change the wrap mode for source code printing.

---

**Insert and Overtyping Modes**

Normally, text to the right of your typing cursor is shifted as you type. This is called Insert mode. To switch between Insert mode and Overtyping mode, in which text to the right of the cursor is replaced character-by-character as you type, press the **Insert** key or choose **Edit > Toggle Overtyping** from the menus.

---

**Sorting Lines Alphabetically**

To sort a group of lines into alphabetical order, select the lines, right-click and choose **Sort Selection**.

---

**Keyboard Commands**

To see a list of keystrokes that work in the Source Editor, choose **Tools > Options** and go to the **Key Bindings** category. For example, Ctrl+Alt+K cuts the text from the cursor position to the end of the line. And, Ctrl+T transposes the line at the cursor position with the line above it.

Another way to see a list of key bindings is to choose **Help > Key Bindings**. Search for the line that says “Editor” (around line 110) to get to the beginning of the keystrokes for the Source Editor windows.

---


**Recording, Playing, and Saving Macros**

You can record and replay a set of editing changes that you want to be able to repeat. These are called macros. To record a macro, follow these steps:

- 1 Choose **Tools > Editor Macros > Record Macro** from the menus or press Ctrl+Alt+M.
- 2 Perform the steps you want to be able to repeat in the Source Editor.
- 3 Choose **Tools > Editor Macros > Stop Recording** or press Ctrl+Alt+M. (Note that if your cursor is not in the Source Editor at the end of the macro, you will not be able to stop the recording until you move back to the Source Editor.)

To replay the most recently recorded macro, move your cursor to the desired start location and choose **Tools > Editor Macros > Replay Macro** or press Ctrl+M.

You can save the most recently recorded macro by choosing **Tools > Editor Macros > Save Macro** or pressing Ctrl+Shift+M. You will be asked to type a name for the macro. You can also move to the Shortcut field and press the key combination you want to use to trigger this macro.



You can rename and delete saved macros in the Understand Options dialog by choosing **Tools > Editor Macros > Configure Macros**. See page 116 for details.

## Creating and Opening Files

You can use the Source Editor to create an untitled blank file by choosing **File > New > File** from the menus. You can open files, whether they are in your project or not, by choosing **File > Open > File**.

When you right-click on a filename, the context menu provides options to **Edit File** and to **Edit Companion File**. For example, the companion file of encrypt.c is encrypt.h.


## Bookmarking

You can create “bookmarks” in your code by right-clicking on a line and choosing **Add Bookmark** from the context menu. Or choose **Edit > Bookmarks > Toggle Bookmark** from the menus. Lines with a bookmark have a red arrow next to them.

```
5 ▶ #define __nested__
```

In a file with multiple bookmarks, you can right-click and choose **Previous Bookmark** or **Next Bookmark** to quickly move between places in a file. These commands are also available under **Edit > Bookmarks** in the menus.

You can open a Bookmarks area to view a list of all your bookmarks in all your files by choosing **View > Bookmarks** from the menus.




If you point to bookmarked code in the Bookmarks area, the 5 lines of code surrounding the bookmarked line are shown in the hover text.

Double-click on a bookmark to move to that location in the Source Editor. If you create a bookmark *inside* an entity, the Bookmarks area shows the name and type of entity that contains the bookmark. For example, the function name is shown if you create the bookmark on the first line of code inside a function.

Bookmarks and Favorites (page 144) are stored as part of the project. If you want to mark code locations on a cross-project basis, see *Annotations* on page 186.

The toolbar for this area lets you manage your bookmarks in the following ways:



You can use the **View by** icons to switch between a file-based and a category-based view. The file-base view lets you expand filenames to see the bookmarks in that file. The category-based view lets you assign bookmarks to categories you create.



Select a bookmark and click this icon to change the category the bookmark is in. To create a new category, type the name and click **OK**. To use an existing category, select it from the list.



Select a bookmark and click this icon to delete that bookmark.



Select a bookmark and click this icon to mark it as a temporary bookmark to be deleted 24 hours after marking it as temporary.



Select a file in the file-based view and click this icon to delete all the bookmarks in this file. You can also select a bookmark and click this icon to delete all the bookmarks in the file that contains the selected bookmark.




Select a category in the category-based view and click this icon to delete all the bookmarks in the category. The category itself is not deleted.



Click this icon to delete all your bookmarks.




The drop-down icon  in the upper-right corner of the Bookmarks area provides the following commands:


- **Copy to Clipboard on Double Click:** By default, double-clicking on a line in the Bookmarks list jumps to that location in the code. If you enable this option, double-clicking both jumps to the location in the code and copies that line of code to your clipboard.
- **Show Original Indentation:** Enable this option to display the code line with indentation matching the source code indentation.

## Managing Source Editor Tabs

When you right-click on the tab at the top of a Source Editor, some of the commands allow you to control the behavior of the tab.



If you choose **Show Tab Title as**, you can shorten or lengthen the filename in Source Editor tabs. Likewise, if you choose **Show Window Title as**, you can shorten or lengthen the filename in the *Understand* title bar and any separate Source Editor windows. The **Copy Filename** command lets you copy the long, relative, or short filename to the clipboard.

If you choose **Release Window**, the tabbed area changes to a separate window that can be moved around your screen. Click the  icon in the upper-right corner of a released window and choose **Capture Window** to return the window to a tab within the *Understand* window.


## Changing the Source Code Font Size

You can change the default display font and font size in the **Editor** category of the Options dialog that you open with the **Tools > Options** command (see page 111).

In addition, you can change the display size of the font for an individual source code window by choosing options from the **View > Zoom** submenu. **View > Zoom > Zoom In** makes the font size larger. **View > Zoom > Zoom Out** makes the font size smaller. **View > Zoom > Reset Zoom** changes the font size back to the default.

## Annotations

Annotations let you add comments or notes about entities without changing the source code directly. You can view the annotations inline, following the definition of the entity to which they are attached. They can also be seen in hover text wherever the annotated entity is used, including in graphs and in the Information Browser.




Each annotation can be “tagged” with a key value pair. Such tagging is useful for organizing your notes using keywords, author names, or any other identifier you want to use.

### Adding an Annotation


To add an annotation, follow these steps:

- 1 Highlight an entity, such as a variable or function name, anywhere in *Understand*. For example, you can select an entity in source code, in the Information Browser, or in the Entity Filter.
- 2 Right-click on the entity and choose **Annotate** and the entity or line number you want to annotate from the context menu. (Line numbers cannot be annotated in a file that has not been saved. Annotations to a line number are updated if possible when the line number changes.)




- 3 If this is the first time you are adding an annotation, you will see the Annotations Setup dialog. Type your name in the **Author name** field. The annotations are stored

in a \*.ann file within the project. The **Default Annotations File** is stored in the project directory. The filename includes your name and the name of the project. (See page 188 to learn about managing annotation files.)



- 4 In the Add/Edit Annotations dialog, type your annotation comment in the right box. If you want to tag your comment so that it will be easy to search for, begin the text with a #key or #key:value tag. For example, you can use #reminder:CodeReview to flag items that should be reviewed. Or, you could use #errorchecks to flag items that need to have their status tested. The author name you entered is automatically associated with your annotations, so you don't need to include your name in a #key:value pair. You can type multiple keys in a single annotation, and keys can occur anywhere within the annotation text. If you want to use a # sign in the annotation text without having it treated as a key, type ##.



- 5 If you want to create multiple annotations for the same item, click the "+" icon. The current date and time are added to the left box. You can select annotations using this timestamp when you want to edit annotations.
- 6 Click **Save**. Your annotation appears in the source code where the selected entity is defined. (See page 188 to control how annotations are displayed.)

You can also add an annotation by clicking on an entity and choosing **Annotations > Annotate > Annotate <entity>** from the menus. Options are shown to annotate the current file, the current entity, and any entities that contain the current entity (such as a function that contains the selected variable).

---

### Editing an Annotation

To edit an existing annotation, follow these steps:

- 1 Highlight an entity that has an annotation anywhere in *Understand*.
- 2 Right-click on the entity and choose **Annotate** and the entity you want to annotate from the context menu.
- 3 In the left box, select the timestamp for the annotation you want to edit.
- 4 Modify the annotation text in the right box.
- 5 Click **Save** to store your changes.

If you edit an annotation that was originally created by someone else, that other person remains the author of the annotation. The timestamp for the annotation is updated to the last time it was edited.

---

### Deleting an Annotation

To delete an existing annotation, follow these steps:

- 1 Highlight an entity that has an annotation anywhere in *Understand*.
- 2 Right-click on the entity and choose **Annotate** and the entity whose annotation you want to delete from the context menu.
- 3 In the left box, select the timestamp for the annotation you want to edit.
- 4 Click the “-” (minus) icon above the list of timestamps.
- 5 Click **Save** to finish deleting the annotation.

---

### Managing Annotation Files and Display

You can choose **Annotations > Annotation Options** from the menus, and then set the following options:

- Your name or username to identify the original author of your annotations.
- The annotation files to look in for this project, and which file is the default for annotations you add. For example, you can have *Understand* display annotations from separate files for everyone working on this project.
- The foreground and background colors to use when displaying annotations from each of the files.
- How to display annotations: inline, as hover text, and with an indicator.


See *Annotations* on page 61 for details about setting these options.

If other developers are also annotating code using *Understand*, choose **Annotations > Refresh Annotations** from the menus when you want to get the latest annotations they have added.

## Searching Annotations

You can search for annotations based on the key:value pairs, the author, and the timestamp. To search annotations, follow these steps:

- 1 Choose **Annotations > Search Annotations** from the menus.
- 2 Specify any of the following search parameters you want to use.



- **Date range:** Check one or both date range boxes if you want to find annotations edited after a certain date and time and/or annotations last edited before a certain date and time.
- **Include Orphans:** Check this box if you want the search to also find annotations that are linked to entities that have been deleted. See page 191 for more about orphaned annotations.
- **Search Only Filtered Annotations:** Check this box if you want to limit the search to annotations that match the current filters. See page 190 for more about filtering annotations.
- **Filter values:** You can set up one or more filters for the search based on the author and any #key:value pairs in the annotations. The “has values” and “doesn’t have value” options let you type a value to match or exclude for a #key:value pair. Exact matches for the author name and key values must be used; partial matches and wildcards are not supported. The “any value” option matches any annotation that has that #key, no matter what the value. The “no value” option matches annotations that have that #key, but no #key:value pair. Use **Add Filter** to create another filter, and choose **All** or **Any** to determine how matching is performed.

You can even use **Add Filter Group** to create nested levels of filters that have different settings for **All** and **Any**.

- 3 Click **Search**. The results are shown in the Annotation Search Results area in the main *Understand* window.
- 4 Expand the search results, and double-click on an item to go to the location where that annotation appears in the code. (That is, the location where the entity associated with the annotation is defined.)


Annotations are stored in \*.ann files, which use the SQLite database format. In addition to viewing annotations in *Understand*, you can use other applications that support SQLite to modify and search annotation files.

If other developers are also annotating code using *Understand*, choose **Annotations > Refresh Annotations** from the menus when you want to get the latest annotations they have added.

### Filtering Annotations

You can filter annotations based on the key:value pairs, the author, and the timestamp. To filter annotations, follow these steps:

- 1 Choose **Annotations > Filter Annotations** from the menus.
- 2 Specify any of the following filters you want to use.




- **Date range:** Check one or both date range boxes if you want to find annotations edited after a certain date and time and/or annotations last edited before a certain date and time.

- **Filter values:** You can set up one or more filters for the search based on the author and any #key:value pairs in the annotations. See page 189 for details on using these fields.
- 3 Click **OK** or **Apply**. The filters you specify are applied to the annotations shown throughout *Understand*.

## Managing Orphaned Annotations

If you create an annotation, and later delete the entity with which it was associated, that annotation becomes an “orphan” when you re-analyze the project. Orphan annotations aren’t shown in the code anywhere. You can manage orphan annotations by choosing whether to delete or re-attach them. To manage orphan annotations, follow these steps:

- 1 Choose **Annotations > Manage Orphaned Annotations** from the menus.




- 2 Expand an orphan in the list on the left to see the annotation text.
- 3 If you want to delete the selected annotation, click **Delete Orphan**.
- 4 If you want to attach the selected annotation to a different entity, select an entity from the list on the right. (You can shorten the list by selecting a type of entity from the **Show** drop-down.)
- 5 Click **Attach Orphan To Entity** to connect the selected orphan to the selected entity. The annotation will be shown in the code where the new entity is defined.
- 6 Click **OK**.


## Printing Source Views

The menu option **File > Print** opens the standard print dialog for your operating system so you can print the currently viewed source file. The output shows 66 lines per page.

By default, files are printed in the font and color shown on the screen when you choose the **File > Print** menu option. You can customize code printing in the Options dialog. To open this dialog, choose **Tools > Options**. Expand the **Editor** category, and select the **Advanced** category. Options to control how code is printed are in the Print area. See *Editor > Advanced Category* on page 113 for details about these fields.



To change the print output without changing the online display, choose the **File > Page Setup** from the menus. This dialog offers printing options similar to the following; the options may differ depending on your operating system:



Any annotations in a file are printed along with the source code. See page 186.



This chapter explains the architecture features provided by *Understand* and explains how you can use them to analyze your code.

This chapter contains the following sections:

Section	Page
About Architectures	194
Using the Architecture Browser	195
Viewing Architecture Dependency Graphs	198
Viewing Architecture Metrics	202
Managing Architectures	203
Creating an Architecture	204
Editing an Architecture	206
Using XML to Manage Architectures	208

## About Architectures

An architecture is an abstract hierarchy layered onto a body of source code. For example, a staff architecture could have nodes for each engineer working on a particular project. The nodes would contain a list of source code files belonging to or to be modified by that engineer. Dependencies and interactions could then be derived from that architecture.

Architectures allow you to name regions of a software project or ways of looking at software hierarchically. An architecture creates a hierarchy of source code units (entities). You can use the provided architectures or create your own.


Architectures need not reference every source entity in the database; that is, they can define a subset of the entities. Also, architectures can contain a particular entity more than once. (Technically, that is, the architecture's flattened expansion need not maintain the set property.)

You can combine architectures successively to create novel filters for your entities.

From a more technical perspective, simple set algebra is used to combine and transform architecture hierarchies. The result of the filter is a list of entities. This result list can be viewed as a flat list or in terms of another architecture. The filter definition can be saved as a dynamic architecture. A dynamic filter architecture is updated as the contents of the database change and it can be used to reconstitute the filter at a later date.

## Using the Architecture Browser

To open the Architecture Browser, choose **Project > Architectures > Browse Architectures** from the main menu bar.



You see an expandable list of the architectures currently defined for your project.

This Architectures area is similar to the Filters area. When you click on an item, information about it is automatically shown in the Information Browser (as long as the “Sync” box is checked in the Information Browser).

### Exploring Architectures

To explore the existing architectures, click the “+” signs to expand the hierarchy. Entities, such as files, functions, and variables are shown in the hierarchies.


*Understand* provides some “auto-architectures” that are built in:

- **Directory Structure:** Lists the project files in their normal file hierarchy—showing directories and their subdirectories.
- **Calendar:** Lists files in the project according to their last change date. A hierarchy of dates is shown that progresses from This Year, This Quarter, This Month, and This Week to Yesterday and Today.
- **Language:** Lists files first by their source code language and then by their location in the directory structure. (This architecture exists only if your project contains multiple languages.)
- **Visual Studio Projects:** This architecture is provided only if the project is configured to contain a Visual Studio project. (Existing projects must be reanalyzed for this architecture to be created.)


The auto-architectures are updated only when the project is analyzed. So, if your source code is actively being modified and you have not analyzed it recently, architectures—especially the Calendar architecture—could be out-of-date.

As always, you can right-click on any item in the Architecture Browser to get a list of information you can view about that item.

#### Right-click on file in Architecture



#### Right-click on Architecture node



Notice that the context menu for an architecture node (such as a filesystem directory or “This Quarter”) contains some extra items not available in other context menus:

- **Graphical Views > Graph Architecture:** Creates a graph of the architecture hierarchy from this point down. You are asked whether you want to include entities in the graph or just the architecture nodes. See page 198.
- **Graphical Views > Dependency Graphs:** Shows the dependencies between architecture nodes. See page 198.
- **Metrics Summary:** Provides metrics for the entities within the selected node. The metrics are based on entities in the current node, but not those in sub-nodes lower in the hierarchy. See page 202.

- **Metrics Export:** Creates a CSV output of the metrics from the Metrics Summary. See page 202.
- **XML Export:** Creates an XML export listing the architecture nodes and entities from the selected point down in the hierarchy. See page 208.
- **Edit Architecture:** Opens the Architecture Builder for the selected architecture if it is one you created. You cannot edit the auto-architectures provided with *Understand*. See page 206.
- **Rename Architecture:** Opens a Rename Architecture window that lets you rename the selected architecture or node if it is one you created. You cannot rename the auto-architectures provided with *Understand*. See page 204.
- **Duplicate Architecture:** Opens a Duplicate Architecture window that lets you type a name for a duplicate copy of the selected architecture. See page 204.
- **Manage Architectures:** Opens the Architect Manager window. See page 203.

## Viewing Architecture Dependency Graphs

You can generate graphs that show the hierarchy of an architecture. You can save these graphs as PNG, JPEG, SVG, Visio XML, and DOT files.

**Note:** Dependency graphs are also available for classes and packages.

To create a graph, follow these steps:

- 1 Select the highest-level architecture node you want to graph. You can graph the entire hierarchy or just a sub-hierarchy.
- 2 Right-click on the node and choose **Graphical Views** from the context menu. Depending on the node you select, the submenu allows you to choose **Graph Architecture**, **Depends On**, **Depended On By**, **Butterfly-Dependency Graph**, and **Internal Dependencies**. When you have selected an architecture node, the same list of graphical views is available by choosing **Graphs > Graphs for <current\_entity>** from the menus.

To open the Internal Dependencies graph for an entire architecture, choose from the **Graphs > Dependency Graphs** menu.

Architecture dependency graphs have the same toolbar as other types of graphical views. See page 253 for details about using the icons in the graphical view toolbar.




To save a graph as a JPG, PNG, or SVG file, see page 279. To save a graph to a Visio file, see page 279.

Dependency and relationship graphs provide an additional Graph Customizer toolbar that you can use to modify the graph display. This toolbar lets you control expansion, highlighting, and arrows on a per-node basis. It also lets you undo and redo your changes, and save and load graph customizations. For example, this is the default Depended On By graph for the C/C++ node in the multi-language zlib sample project.

Nodes that are drawn as 3D boxes (like those in this figure) can be expanded to show the nodes they contain by double-clicking on them. You can keep expanding nodes until you get to the file level.

You can hover your mouse cursor over a line that connects two boxes to see which items are connected by the relationship and to highlight the line. (See page 120 if highlighting is disabled.)



Click the **View Dependencies** button or right-click on a dependency graph and choose **View Dependencies** to open the Dependency Browser (page 142) for the selected node or relationship. If you check the **Sync** box in the Dependency Browser, it shows details about any relationship you select in the graph, and the two nodes connected by the relationship are highlighted in the Dependency Browser. In addition, **Show** and **Group By** settings from the dependency graph are synced with the Dependency Browser and the **Dependency Kind** is changed to Depends On.

You can right-click on the gray background of a dependency graph (outside any colored boxes) to control whether long, short, or relative names are displayed for architecture node names and filenames. In addition, you can enable or disable the reference count numbers that show how many times a particular dependency occurs. See Controlling Cluster Graph Layout on page 275 for details about the context menu options within architecture dependency graphs.

The context menu when you right-click on a node in a dependency graph offers commands similar to those you see when right-clicking on an entity or architecture node name elsewhere in *Understand*.

The context menu when you right-click on an edge (arrow) in a dependency graph provides a list of the references that constitute the edge. Choose an item from the list to visit the source code for this relationship. You can limit the length of this list as described for the **Tools > Options** dialog on page 120.

You can customize the display colors, shapes, and arrows used in cluster graphs in the Graphs category of the **Tools > Options** dialog (page 120).

## Graph Customizer Toolbar

The toolbar icons in the Graph Customizer pane perform the following actions:



- **Save icon.** Prompts you for a name for the current settings. Settings apply only to the specific graph type and root node in this view. If you have already saved settings for this graph type/root node combination, you can select a set you want to update from the context menu. Otherwise, type a name for your current settings and click **Save**.
- **Load icon.** Prompts you to select a named group of graph settings that you want to open in the current window. The list shows only settings saved for this graph type/root node combination. To see the full list of saved settings, choose **Graphs > Dependency Graphs > Load Saved Dependency Graph**.
- **Undo icon.** Undo your last change.
- **Redo icon.** Redo the last change you undid.
- **Restore Defaults.** Restores graph to the settings it had when you opened it.
- **Selected Node tools.** Use this drop-down menu to control the display of the currently selected nodes and edges. The icon for this toolbar item changes to reflect the most recently used command. The commands are active depending on whether you have selected nodes, whether any selected nodes have edges coming in or out, and whether any selected nodes have children.

You can select one or more nodes in a dependency graph by using your mouse to drag a rectangle over the nodes you want to select. Or, hold down the Ctrl key while clicking on multiple nodes you want to select.

- **Show Selected Node Children.** Causes any child nodes of the selected node to be displayed. This is the same as double-clicking on a node to expand it.
- **Show Edges Between Children.** Causes arrows to be drawn between the selected child node and any other child nodes as appropriate. If you remove the display of arrows, the graph is reorganized to hide these relationships.

- **Aggregate Child Edges Going Out.** Causes arrows coming from the selected node's children to be drawn coming from the node, and arrows with the same target from multiple children to not be repeated. Toggle this off to cause separate arrows to be drawn from the individual child nodes.
- **Aggregate Child Edges Coming In.** Causes the arrows going to the selected node's children to be drawn as going to the node, and arrows to multiple children are not repeated. Toggle this off to cause separate arrows to be drawn to the individual child nodes.
- **Highlight Edges Going Out.** Causes the selected node to be highlighted in yellow. Arrows pointing from this node to other nodes become darker. Nodes to which they point are highlighted in light blue. Internal Dependency graphs let you highlight such edges; other types of dependency graphs let you show or hide such edges.



- **Highlight Edges Coming In.** Causes the selected node to be highlighted in yellow. Any arrows that point to this node from other nodes become darker, and nodes which point to this node are highlighted in light blue. Internal Dependency graphs only let you highlight such edges; other types of dependency graphs let you show or hide such edges.



- **Hide Selected Node(s).** Removes all the nodes that are currently selected from the graph and reorganizes the graph as needed. (You can later restore the hidden nodes by clicking the Show All Hidden Nodes button.)
- **Global Node tools.** Use this drop-down menu to show and hide various nodes and edges. The icon for this toolbar item changes to reflect the most recently used command.
  - **Hide Nodes With No Highlighted Edges.** This field is available only for Internal Dependency graphs, and you can use it only if you have turned on highlighting of “edges.” If you check this box, all nodes that do not have a highlighted arrow pointing to it or away from it are hidden, and the graph is reorganized as needed to omit those nodes.
  - **Hide Unhighlighted Edges.** This field is available only for Internal Dependency graphs, and you can use it only if you have turned on highlighting of “edges,” which are the connections between nodes. If you check this box, all arrows that are not highlighted are hidden, and the graph is reorganized as needed to omit those non-highlighted relationships.
  - **Clear All Highlighted Edges.** This button is available only for Internal Dependency graphs. If you click this button, all node and “edge” highlighting is removed.




- **Show All Hidden Nodes.** If you click this button, any nodes that have been hidden using the “Hide Selected Nodes” button are restored. This button does not expand any nodes that have been contracted to hide child nodes. If you have hidden any nodes, you can select entities from the **Hidden Nodes** drop-down list to redisplay those nodes.
- **Dependencies Shown.** You can choose the types of dependencies you want shown in the graph from this list. The dependency types available include Inits (initializes), Sets, Uses, Calls, and Modifies. By default, all types of dependencies are shown. If you have the **Sync** box checked in the Dependency Browser, the current Show settings in the dependency graph are copied to the Dependency Browser when you click on a relationship in the graph.
- **Open Dependency Browser.** This button opens the Dependency Browser (page 142) for the most recently selected node or relationship in the graph. Syncing between the dependency graph and the Dependency Browser is turned on by default when you open the Dependency Browser this way.

## Graph Architecture View

The **Graph Architecture** view is different from the Architecture Dependency graphs. It shows the structure of the architecture, rather than dependencies between entities in the architecture. Open the Graph Architecture view the same way you would open other graphical views (see page 251).

This type of graph does not provide a Graph Customizer panel, but you can right-click on the graph to modify the display. For example, in the following Architecture Graph, **Include Entity Lists** was off by default but was turned on by right-clicking.



## Viewing Architecture Metrics

You can generate metrics information about an architecture or a subset of an architecture. The metrics information can be either a text summary or a comma-separated list for use in spreadsheets.

To create a metrics summary, follow these steps:


- 1 Select the highest-level node of the architecture for which you want metrics.
- 2 Right-click on the node and choose **Metrics Summary** from the context menu.
- 3 You see an Architecture Metrics Summary window.

Language/C C++/C - Architecture Metrics Summary		
1		
2		
3	AltAvgLineBlank	: 99.000000
4	AltAvgLineCode	: 1102.000000
5	AltAvgLineComment	: 287.000000
6	AltCountLineBlank	: 1184.000000
7	AltCountLineCode	: 7831.000000
8	AltCountLineComment	: 3056.000000
9	AvgCyclomatic	: 10.190000
10	AvgCyclomaticModified	: 9.820000
11	AvgCyclomaticStrict	: 11.920000
12	AvgEssential	: 5.220000
13	AvgLine	: 543.710000
14	AvgLineBlank	: 50.330000
15	AvgLineCode	: 297.380000
16	AvgLineComment	: 133.620000
17	CountDeclClass	: 0.000000
18	CountDeclFile	: 21.000000
19	CountDeclFileCode	: 21.000000
20	CountDeclFunction	: 173.000000

- 4 When you close the window, you are asked whether you want to save the file. If you click **Save**, you can save the summary as text.

To create a metrics export file, follow these steps:


- 1 Select the highest-level node of the architecture for which you want metrics.
- 2 Right-click on the node and choose **Metrics Export** from the context menu.
- 3 You see a comma-separated values file. The heading label for each column is in the first row. Each node in the architecture hierarchy has a separate row with metrics for that node's contents.



- 4 When you close the window, you are asked whether you want to save the file. If you click **Save**, you can save the data as a .CSV file.




## Managing Architectures





To open the Architect Manager window, choose **Project > Architectures > Manage Architectures** from the main menu bar in *Understand*. The window lists the auto-architectures on the right and custom architectures you have created on the left.



The checkboxes allow you to control whether custom and auto architectures are shown in the Architectures area. Removing the checkmark next to an architecture can improve performance, especially for large projects. So, you might want to disable/hide architectures you never or rarely use.

You can use the icons at the top of this area or right-click on an architecture to perform the following actions:



-  **Create a new architecture:** See page 204.
-  **Edit architecture:** Predefined and custom architectures only. See page 206.
-  **Rename architecture:** Predefined and custom architectures only. See page 204.


-  **Duplicate architecture:** See page 204.
-  **Delete architecture:** Predefined and custom architectures only.
-  **Import architecture from XML:** See page 208.
-  **Export architecture to XML:** See page 208.


---

## Creating an Architecture


There are several ways to create a new architecture:

- To create an architecture from scratch, choose **Project > Architectures > New Architecture** from the menus or click the  icon in the Architect Manager. Use the Architecture Wizard to create the architecture as described in *Using the Architecture Wizard* on page 205.
- To duplicate an existing architecture (which you can then modify), select an architecture and click the  icon in the Architect Manager window. Or, right-click an existing architecture node in the Architecture Browser and choose **Duplicate Architecture** from the context menu to create an architecture from that node and lower in the hierarchy.




You can rename an architecture you have created by selecting an architecture and clicking the  icon in the Architect Manager window. Or, right-click on an existing custom architecture and choose **Rename Architecture** from the context menu.


## Using the Architecture Wizard

When you open the Architecture Wizard by choosing **Project > Architectures > New Architecture** from the menus or clicking the  icon in the Architect Manager window, you see a page that asks for the name of your architecture.


Type a name for the architecture. This name should be fairly short so it can be shown in architecture trees.



Then click **Next** to see the page that lets you add and edit architecture nodes. This is the hierarchy to which entities will be assigned in a later page of the wizard



Click **Add a Node** and type the **Name** of the node you want to add. The default location is within the node you had selected in the Architecture Wizard, but you can select another location in the **Create In** field. Then click **OK**.





You can modify nodes you have created by selecting a node and clicking **Edit Node**. You can delete the selected node by clicking **Remove Node**.


The next window presents an animation that shows how to use the Architecture Builder to add entities to the nodes you have created. When you have finished watching the animation, click **Finish**. This opens the Architecture Builder shown in the animation. Your architecture nodes are shown on the right. See *Editing an Architecture* on page 206 for details on adding entities to each node.

## Editing an Architecture


You can quickly add a file to an existing custom architecture by right-clicking on a file in the Project Browser and choosing **Add to Architecture** and the architecture node within which you want to place the file.








To make changes to an architecture beyond adding files, select that architecture and click the  icon in the Architect Manager window. Or, right-click on an existing architecture and choose **Edit Architecture** from the context menu. Both actions open the Architecture Builder.

You cannot edit the Auto Architectures provided with *Understand*. However, you can use the  icon in the Architect Manager window to create a duplicate architecture of one of the Auto Architectures. Then, you can edit the duplicate architecture.

This dialog allows you to add nodes to architectures. You create an architecture structure on the right-hand side and map entities into the architecture from the left-hand side.



To create and edit nodes in the Architecture Builder, follow these steps:

- Double-click the name of any node on the right side of the Architecture Builder, and rename that node by typing. (Or you can select a node and press Enter.)
- Move one or more nodes by dragging them to the node you want to be the parent node. Within a node, the children are sorted alphabetically.
- Click the  icon to create a new node at the same level as the selected node. Click the  icon to create a new node as the child of the selected node.
- Click the  icon to delete the selected node.
- Click the  icon to undo your last change. Click the  icon to redo you last undo.


To map files to nodes in the Architecture Builder, follow these steps:

- 1 On the left side of the Architecture Builder, select an existing architecture from the drop-down list that will allow you to easily find the files you want. The default is the Directory Structure architecture.

- 2 You can choose whether to show all entries in the architecture or just the unmapped entries. For example, if you want to map all the entries into your new architecture, you might want to select **Show Unmapped Entries** so that you can see which files you haven't mapped yet.
- 3 In the left architecture hierarchy, select one or more files or architecture nodes.
- 4 In the right architecture hierarchy, select the node you want to contain your selection.
- 5 Click the **Add** button or drag your selection to the right side.
- 6 When you finish editing your custom architecture, click **Save**.

You can use the **Remove** button to delete files and nodes from the architecture you are editing.

As always, you can right-click on any node or file to use its context menu to get information.

You can save your edits to the architecture at any point by clicking the  icon. Then, you can continue editing. If you close the Architecture Builder without saving changes, you will be asked if you want to save your changes.

---

## Using XML to Manage Architectures


You can use XML as a way to share architectures between one *Understand* database and another.

In addition to using XML to share architectures, you can use XML export/import to quickly create architectures that are a simple subset of another architecture by selecting a lower node in the hierarchy.

---

### Exporting Architectures to XML


To create an XML file for an architecture, follow these steps:

- 1 Select the highest-level node of the architecture that you want to export. All of the hierarchy below the node you select will be represented in the XML file.
- 2 Click the  icon in the Architect Manager window. Or, right-click on the node you selected and choose **XML Export** from the context menu.
- 3 You see an XML file that contains <arch> and <set> tags for architecture nodes.
- 4 When you close the XML window, you are asked if you want to save the file. If you click **Save**, the default filename is the name of the node you selected.

---

### Importing XML Architectures

To import an XML file for an architecture, follow these steps:

- 1 Click the  icon in the Architect Manager window.
- 2 In the Choose XML File to Import Architecture dialog, select an XML file that matches the tag format used by *Understand* to describe architectures. For example, you can choose XML files created by *Understand*. Click **Open**.
- 3 The architecture described by the XML file is added to your list of architectures.



This chapter describes how to create and view reports and the types of reports available.

This chapter contains the following sections:

<b>Section</b>	<b>Page</b>
Configuring Reports	210
Generating Reports	212
Viewing Reports	213
An Overview of Report Categories	214
Cross-Reference Reports	216
Structure Reports	221
Quality Reports	224
Metrics Reports	228
Importing Report Plugins	231

## Configuring Reports

*Understand* provides a large number of reports you can generate about your code. These can be generated in HTML or text format. You can choose which reports and how to format them.

To configure how reports will be generated, choose **Reports > Configure Reports**. This opens the Project Configuration dialog with the **Reports > Output** category selected. From there, you can also configure the **Reports > Options** and **Reports > Selected** categories.

See page 55 for details on the **Reports > Output** category. In general, you can configure the following:

- **HTML reports:** The “home” file for the reports is index.html, but you can select an alternate title page. You may generate single or multiple HTML files for each report type. It is recommended that you split up the files for large projects. Choose *Alphabetic* to generate multiple HTML files per report that are split up alphabetically by the first letter of the entity name. Choose *Every  $n$  Entities* to generate multiple HTML files per report that are split up every “ $n$ ” number of entities. By default, a single HTML file is generated for each letter of the alphabet.
- **Text reports:** You may generate one text file of the specified name (by choosing File). This one file will contain all the selected reports. Alternately, you may generate multiple text files (by choosing Separate Files) and specify a common filename prefix. The filenames of each text file identify the report.

For details on the **Reports > Options** category, see page 56.

The **Reports > Selected** category lets you select from the available reports for the languages used by your project. This list shows all the reports for all languages:

☒ Data Dictionary  
☒ File Contents  
☒ Program Unit Cross Reference  
☒ Object Cross Reference  
☒ Type Cross Reference  
☒ Macro Cross Reference  
☒ Include File Cross Reference  
☒ Declaration Tree  
☒ Extend Tree  
☒ Invocation Tree  
☒ Simple Invocation Tree  
☒ Import  
☒ With Tree  
☒ Simple With Tree  
☒ Generic Instantiation  
☒ Exception Cross Reference  
☒ Renames  
☒ Program Unit Complexity  
☒ Project Metrics  
☒ Program Unit Metrics  
☒ File Metrics  
☒ File Average Metrics  
☒ Fortran Extension Usage  
☒ Class Metrics  
☒ Class OO Metrics  
☒ Implicitly Declared Objects  
☒ Uninitialized Items  
☒ Unused Variables and Parameters  
☒ Unused Objects  
☒ Unused Types  
☒ Unused Program Units  
☒ Uses Not Needed  
☒ Withs Not Needed

All None

The specific reports available depend upon the source languages used in your project.

See *An Overview of Report Categories* on page 214 for descriptions of the types of reports you can generate.

---

**Customizing Report Colors**

HTML reports use Cascading Style Sheets (CSS) to set colors and font styles used for keywords, comments, strings, numbers, and more. The colors and styles used are defined in the `sourcestyles.css` file, which is created the first time you generate HTML reports in a particular location.

You can customize the `sourcestyles.css` file using a text editor. Any colors and font styles normally supported by CSS can be used in this file. For example:

```
span.comment{color:DarkSeaGreen;font-style:italic}
```

If you modify the stylesheet and want to use it for other reports you generate, you can copy the modified `sourcestyles.css` file to the locations of other HTML reports.

---

## Generating Reports

Once you have specified formatting options and the types of reports to be generated, choose **Reports > Generate Reports** from the menus to open a dialog that lets you begin generating the selected reports. Click **Generate** to show the progress of the report generation.

On Windows, the ASCII text follows the DOS text file format (carriage return and line feed at the end of each line). On Unix, text files are created according to the Unix convention (lines end with a carriage return).

HTML reports are generated as HTML 3.0 format files. The generated HTML is not complex, the only HTML 3.0 (versus HTML 2.0) feature used is frames. Netscape 2.0 and higher, and Internet Explorer 3.0 and higher can display the files.

You can view the reports as described in *Viewing Reports* on page 213.

For large projects, reports can take a long time to generate. You can click **Cancel** to halt report generation. Clicking **Cancel** leaves the reports in a partially generated state.

**Note:** You may want to temporarily toggle off anti-virus protection programs while reports are being generated. This may speed the process of creating reports. If you do this, be sure to turn on virus checking after report generation is finished.

**Note:** HTML, text, and project metrics reports may also be generated with the “und” command line program. Refer to Chapter 14 for details.

## Viewing Reports


To view generated reports, choose **Reports > View Reports**. Then choose the **HTML** or **Text** option.

File names of reports generated vary based on the type and format of the report generated.

- For text files, a single text file containing all selected reports may be generated or separate files for each type of report may be generated. A single text file is named `<project_name>.txt`. For separate text files, the file name is the type of report.
- For HTML reports, you can generate either a single HTML files for each report type, or smaller files divided either alphabetically by entity name or in groups of N number of entities. An index file is also generated that contains links to all the other HTML reports generated. The main window page is named `index.html`.

For HTML reports, a single index file contains an alphabetic list of all entities found in all other generated HTML reports. The entities listed in the index have hyperlinks to the Data Dictionary report for that entity. The entity index file is named `entity_index.html` and can be accessed from the “index” link on the main HTML page.

The following figure shows an example of the entity index.



## An Overview of Report Categories

*Understand* generates a wide variety of reports. The reports fall into these categories:

- **Cross-Reference** reports show information similar to that in the *Information Browser*, except that all entities are shown together in alphabetic order. See *Cross-Reference Reports* on page 216.
- **Structure** reports show the structure of the analyzed program. See *Structure Reports* on page 221.
- **Quality** reports show areas where code might need to be examined. See *Quality Reports* on page 224.
- **Metrics** reports show basic metrics such as the number of lines of code and comments. See *Metrics Reports* on page 228.

The following table shows the type and page number for each report. Note that the specific reports available depend upon the source languages used in your project.

Report Type	Report Name and Page
Cross-Reference	<i>Data Dictionary Report</i> on page 216
Cross-Reference	<i>File Contents Report</i> on page 217
Cross-Reference	<i>Program Unit Cross-Reference Report</i> on page 217
Cross-Reference	<i>Object Cross-Reference Report</i> on page 218
Cross-Reference	<i>Type Cross-Reference Report</i> on page 218
Cross-Reference	<i>Macro Cross-Reference</i> on page 219
Cross-Reference	<i>Include File Cross-Reference</i> on page 219
Cross-Reference	<i>Exception Cross-Reference Report</i> on page 220
Structure	<i>Declaration Tree</i> on page 221
Structure	<i>Extend Tree</i> on page 222
Structure	<i>Invocation Tree Report</i> on page 222
Structure	<i>Simple Invocation Tree Report</i> on page 222
Structure	<i>Import Report</i> on page 223
Structure	<i>With Tree Report</i> on page 223
Structure	<i>Simple With Tree Report</i> on page 223
Structure	<i>Generic Instantiation Report</i> on page 223
Structure	<i>Renames Report</i> on page 223
Quality	<i>Program Unit Complexity Report</i> on page 224
Quality	<i>Uninitialized Items</i> on page 226
Quality	<i>Unused Objects and Functions</i> on page 226
Quality	<i>Unused Objects Report</i> on page 226
Quality	<i>Unused Types Report</i> on page 227
Quality	<i>Unused Program Units Report</i> on page 227
Quality	<i>Uses Not Needed Report</i> on page 227
Quality	<i>Withs Not Needed Report</i> on page 227

Report Type	Report Name and Page
Quality	<i>Implicitly Declared Objects Report</i> on page 225
Quality	<i>Fortran Extension Usage Report</i> on page 225
Metrics	<i>Project Metrics Report</i> on page 228
Metrics	<i>Program Unit Metrics Report</i> on page 230
Metrics	<i>File Metrics Report</i> on page 230
Metrics	<i>File Average Metrics Report</i> on page 231
Metrics	<i>Class Metrics Report</i> on page 229
Metrics	<i>Class OO Metrics Report</i> on page 229

---

### Augment with the PERL or C API

The reports included with *Understand* have evolved over many years to accommodate common customer requests. However, we recognize that not all needs can be covered.

To help you develop custom reports we include both PERL and C interfaces to *Understand* databases.

For details on the PERL interface choose **Help > PERL API Documentation**. Also visit the support page on our website. Java API documentation is provided in the `doc/manuals/java` subdirectory of the *Understand* installation.

The **Reports > Project Interactive Reports** and **Graphs > Project Graphs** commands display a list of user-created plugins, which can be created using the Perl API. For information about creating plugins, please contact [support@scitools.com](mailto:support@scitools.com). The SciTools Support page at [scitools.com/support](http://scitools.com/support) contains information about plugins in the “API/Plugins” category.

## Cross-Reference Reports

Cross-Reference reports show information similar to that in the References section of the Information Browser, except that all entities are shown together in alphabetic order. The following table shows the page that describes each type of cross-reference report.

Report Name
<i>Data Dictionary Report</i> on page 216
<i>Program Unit Cross-Reference Report</i> on page 217
<i>File Contents Report</i> on page 217
<i>Object Cross-Reference Report</i> on page 218
<i>Type Cross-Reference Report</i> on page 218
<i>Class and Interface Cross-Reference</i> on page 218
<i>Macro Cross-Reference</i> on page 219
<i>Include File Cross-Reference</i> on page 219
<i>Exception Cross-Reference Report</i> on page 220

### Data Dictionary Report

The *Data Dictionary Report* lists all entities alphabetically. Each listing shows the entity name, what kind of entity it is (for example, macro, type, variable, function, include, file, or procedure), along with links to the location where each is declared in the source code.

Non-Alpha

A

B

C

D

E

F

G

H

I

J

K

L

M

N

O

P

Q

R

elems (Local Object) [xref]  
[trees.c, 625]

empty\_gz (Static Global Object) [xref]  
[gzlog.c, 117]

encrypt (Public Object) [xref]  
[zip.c, 130]

encrypted (Public Object) [xref]  
[unzip.c, 147]

Name

What kind of entity it is

What file/line it was declared in.

Quick link to cross-reference of this entity


Optionally break up report alphabetically



**Program Unit Cross-Reference Report**

The *Program Unit Cross-Reference Report* lists all program units (such as procedures and functions) analyzed in alphabetic order along with information about what they return (if anything), what parameters are used, and where they are used by other program units.

The HTML version offers hyperlinks to the Data Dictionary report entry and to the source code where each reference occurs.



You can create an additional Program Unit Index report to list all the program units in the project and show the file and line where each is declared. For text reports, this is stored in a \*.pcn file.

**File Contents Report**

Lists functions declared within a source file and the line numbers where they are declared. HTML versions of this report permit hyperlinked jumping to the function in the source as well as viewing of the entire source file.

# File Contents

Non-Alpha

A

B

C

D

E

F

G

H

I

J

K

L

M

N

O

P

Q

R

compress.c

Global Functions

compress

compress2

compressBound

crc32.c

Types

u4

Local Functions

crc32 big

crc32 little

gf2 matrix square

gf2 matrix times

Global Functions

crc32

**Object Cross-Reference Report**

The Object Cross-Reference Report lists all objects (Fortran *variables*, *parameters*, *macros*) in alphabetic order along with declaration and usage references.

```
a      (Parameter)  Declared as: unsigned
Define  [gzappend.c, 100]      gcd
Use     [gzappend.c, 104]      gcd
Modify  [gzappend.c, 109]      gcd
Return  [gzappend.c, 117]      gcd

access::have      (Public Object)  Declared as: :
Define  [zran.c, 71]      access
Set     [zran.c, 102]      addpoint
Use     [zran.c, 106]      addpoint
Modify  [zran.c, 125]      addpoint
```

The HTML version of this report includes hyperlinks to the Data Dictionary Report and the source code where the reference occurs.

This report was previously titled the Class and Interface Cross-Reference Report.

**Type Cross-Reference Report**

The Type Cross-Reference Report lists all declared types in alphabetic order, along with their declaration and usage information. The HTML version of the report offers hyperlinks to the Types data dictionary report entry, as well as the source code where the reference occurs.

```
gz_header      (Typedef)
Declared as: struct gz_header_s
Define  [zlib.h, 124]      zlib.h
Type    [zlib.h, 126]      gz_headerp

gz_header_s     (Struct)
Define  [zlib.h, 109]      zlib.h
Type    [zlib.h, 109]      gz_header
```

**Class and Interface Cross-Reference**

The Class and Interface Cross-Reference Report lists all declared classes and interfaces in alphabetic order, along with their declaration and usage information. The HTML version of the report includes hyperlinks to the data dictionary report entries, as well as the source code where the reference occurs.

```
Error      (Unknown Class)
Declared as:
Create  [REMatch.java, 62]      REMatch.clone
Create  [Grep.java, 273]        Grep.processStream

Event      (Unknown Class)
Declared as:
Typed   [REApplet.java, 198]    e

Exception   (Unknown Class)
Declared as:
Extend   [REException.java, 38]  regexp.REException
Typed    [Grep.java, 236]        ex
```

## Macro Cross-Reference

The Macro Cross-Reference Report lists all macros analyzed in the source code in alphabetic order along with information about where they are declared and where they are used. The HTML version offers hyperlinks to the macro's Data Dictionary report entry and to the source code where each reference occurs.

```

PIECE
Declared as: 16384
Define      [gun.c, 73]          gun.c
Use         [gun.c, 96]          in
Use         [gun.c, 138]         out

```

## Include File Cross-Reference

The Include File Cross-Reference Report lists all include files analyzed in the source code in alphabetic order with information about which files include them. The HTML version offers hyperlinks to the source code where each reference occurs.

# Include File Cross Reference

Non-Alpha	<a href="#">A</a>	<a href="#">B</a>	<a href="#">C</a>	<a href="#">D</a>	<a href="#">E</a>	<a href="#">F</a>	<a href="#">G</a>	<a href="#">H</a>	<a href="#">I</a>	<a href="#">J</a>	<a href="#">K</a>	<a href="#">L</a>	<a href="#">M</a>	<a href="#">N</a>	<a href="#">O</a>	<a href="#">P</a>	<a href="#">Q</a>	<a href="#">R</a>
-----------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------

alloc.h		
Inactive	<a href="#">[zutil.h, 97]</a>	zutil.h
assert.h		
Include	<a href="#">[zpipe.c, 15]</a>	zpipe.c
Include	<a href="#">[fitblk.c, 56]</a>	fitblk.c

## Exception Cross-Reference Report

The *Exception Cross-Reference Report* documents the declaration and usage of all exceptions. Each declaration and any *raises* or *handles* are documented. In the HTML version each raise or handle may be visited in the source, as well as the declaration point of the Exception (if visible).

### Exception Cross Reference

Non-Alpha	<a href="#">A</a>	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	<a href="#">Q</a>	R
-----------	-------------------	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	-------------------	---

```

stack package.stack empty      (Exception)
  Declare  [stack pa.adb, 21]      stack package
  Raise    [stack pa.adb, 114]      stack package.pop
  Raise    [stack pa.adb, 124]      stack package.top

stack package.stack full      (Exception)
  Declare  [stack pa.adb, 22]      stack package
  Raise    [stack pa.adb, 104]      stack package.push
  Raise    [stack pa.adb, 159]      stack package.copy

```

## Structure Reports

Structure reports are designed to help you understand the relationships between various entities. The following table shows the page in this chapter that describes each type of structure report.

Report Name and Page
<i>Declaration Tree</i> on page 221
<i>Extend Tree</i> on page 222
<i>Invocation Tree Report</i> on page 222
<i>Simple Invocation Tree Report</i> on page 222
<i>With Tree Report</i> on page 223
<i>Simple With Tree Report</i> on page 223
<i>Generic Instantiation Report</i> on page 223
<i>Renames Report</i> on page 223
<i>Import Report</i> on page 223

### Declaration Tree

The *Declaration Tree* shows the declaration nesting of each program unit analyzed. Each nesting level is indicated by an indent with a vertical bar used to help align your eyes when viewing. Each nesting level is read as “declares”. In the HTML version of the report each program unit name is a hyperlink to its entry in the *Program Unit Cross-Reference Report*.

```
Package Body Occupants
| Procedure Get
| Function May_I_Get
| Procedure Drop
| Function May_I_Drop
| Procedure Inventory
| Procedure Go
| | Block
```

In the above example, Package Body *Occupants* is the top level program unit. It has declared within it, *Put\_View*, *Look*, *Get*, *May\_I\_Get*, *Drop*, *May\_I\_Drop*, *Inventory*, and *Go*. Nested within *Go* is an unnamed declare block.

The Declaration Tree report shows a representation of the declaration tree in each file.

### Declaration Tree

```
C:\Program Files\SciTools\sample\getopt\GetoptDemo.java File
| GetoptDemo Public Class
| | GetoptDemo.main Public Static Method

C:\Program Files\SciTools\sample\getopt\LongOpt.java File
| getopt.LongOpt Public Class
| | LongOpt.LongOpt Public Constructor
| | LongOpt.getName Public Method
| | LongOpt.getHasArg Public Method
```

**Extend Tree**

The *Extend Tree* report shows the nesting of class declarations in the files analyzed. Each nesting level is indicated by an indent with a vertical bar to help align your eyes when viewing. Each nesting level is read as “extends”. In the HTML version of the report each class name is a hyperlink to its entry in the *Data Dictionary and Interface Cross-Reference Report*.

**Invocation Tree Report**

The Invocation Tree Report shows a textual representation of the invocation tree for each program unit analyzed. The report shows what each program unit calls. Levels are indicated by tabs and are lined up with vertical bars. Each nesting level is read as “calls”. The HTML version has hyperlinks to the corresponding Data Dictionary report entries.

```
main
| strcpy
| strcmp
| setmode
| fileno
| gzdopen
| | sprintf
| | | gz open
| | | malloc
| | | crc32
| | | *** Repeated Subtree ***
| | | strlen
| | | destroy
| | | | free
| | | | deflateEnd
| | | | inflateEnd
| | | | fclose
| | | strcpy
| | | inflateInit2
| | | | zcalloc
| | | | *** Repeated Subtree ***
```

**Simple Invocation Tree Report**

The Simple Invocation Tree Report shows the invocation tree to only one level for each program unit that has been analyzed. The invocation level is indicated by an indent and a vertical bar and is read as “calls”.

```
main
| strcpy
| strcmp
| setmode
| fileno
| gzdopen
| error
| gz uncompress
| gz compress
| file uncompress
| file compress
```

**With Tree Report**

Structured identically to the other hierarchy reports, the *With Tree* report shows a textual version of the With Tree for each program unit that is not Withed by another.

As with the other textual hierarchy reports, indents show level with a vertical bar helping align your eye. For this report, each line is read as “Withs”.

```
Package Body Occupants
|  Package Rename Text_IO
|  |  Package Text_IO
|  |  |  Package IO_Exceptions
|  |  |  Package System
|  |  |  Package Parameters
```

In the above example, the package body *Occupants* Withs package *Text\_IO*, which in turn Withs *IO\_Exceptions*, *System*, and *Parameters*.

**Simple With Tree Report**

The *Simple With Tree* report is similar to the *With Tree* report. It shows a textual representation of the With Tree for each program unit that is not Withed by another. However, it shows only one level of withs. For example:

```
Package Body Occupants
|  Package Rename Text_IO
```

**Generic Instantiation Report**

This report lists each package that was created through instantiation.

In the HTML version, the source where it was instantiated and its Data Dictionary Report entry may be visited from hyperlinks.

```
My_Int_IO    Package Instantiation
             FILE: board.adb  LINE:12
Instantiated From =>    INTEGER_IO    Generic Package
```

**Renames Report**

The *Renames Report* cross-references the use of the Ada command “renames”, as in:

```
function Rouge return Color renames Red;
```

This report lists program units that have been renamed in alphabetic order. Each rename shows the program unit it renames, and in the HTML report a hyperlink to the rename instance in the source is provided.

The Information Browser also identifies packages and program units that rename others or are renamed.

**Import Report**

The *Imports* report lists all source files that import other files and the files they import. The HTML version offers hyperlinks to the data dictionary entry for each imported file.

# Quality Reports

*Understand's* quality reports are designed to provide information about areas of the analyzed source that might not meet standards or that hold the potential for trouble. They also identify areas where extra programming has been done but not needed. This sometimes identifies areas that aren't yet complete, or that haven't been maintained completely.

The following table shows the page in this chapter that describes each type of quality report.

Report Name and Page
<i>Program Unit Complexity Report</i> on page 224
<i>Fortran Extension Usage Report</i> on page 225
<i>Implicitly Declared Objects Report</i> on page 225
<i>Uninitialized Items</i> on page 226
<i>Unused Objects and Functions</i> on page 226
<i>Unused Objects Report</i> on page 226
<i>Unused Types Report</i> on page 227
<i>Unused Program Units Report</i> on page 227
<i>Uses Not Needed Report</i> on page 227
<i>Withs Not Needed Report</i> on page 227

The complete list of quality metrics available in *Understand* changes frequently - more frequently than this manual is reprinted. A complete and accurate list is always available on our website: [scitools.com/support/metrics\\_list/](http://scitools.com/support/metrics_list/).

## Program Unit Complexity Report

The *Program Unit Complexity Report* lists every procedure and function or similar program unit in alphabetic order along with the McCabe (Cyclomatic) complexity value for the code implementing that program unit.

The Cyclomatic complexity is the number of independent paths through a module. The higher this metric the more likely a program unit is to be difficult to test and maintain without error.

The Modified column shows the cyclomatic complexity except that each case statement is not counted; the entire switch counts as 1.

The Strict column shows the cyclomatic complexity except && and || also count as 1.



The Nesting column shows the maximum nesting level of control constructs in this program unit.

### Program Unit Complexity

Click column header for explanation of each metric

	<u>Cyclomatic</u>	<u>Modified</u>	<u>Strict</u>	<u>Essential</u>	<u>Nesting</u>	<u>Path Count</u>
<u>addpoint</u>	8	8	8	6	2	15
<u>adler32</u>	13	13	13	4	2	19
<u>adler32 combine</u>	5	5	5	1	1	16

## Fortran Extension Usage Report

This report lists anywhere your source code has non-standard Fortran extensions. The report factors in what variant (F77, F90, F95) you chose on your project configuration.

The following is a snippet from a sample Fortran Extension Usage report:

## Fortran Extension Usage

Non-Alpha A B C D E F G H I J K L M N O P Q R S

gdTree.f90 EXIT LOOP Statement  
 Line: 484

---

Non-Alpha A B C D E F G H I J K L M N O P Q R S

## Implicitly Declared Objects Report

The *Implicitly Declared Objects Report* lists any variables or parameters that were implicitly declared using Fortran's implicit declaration mode. Using implicitly declared variables is considered a risky practice, and this report helps you weed out where the practice is occurring in your code.

The HTML version offers hyperlinks to the function's Data Dictionary report entry.

**Uninitialized Items** The *Uninitialized Items* report lists items such as variables that are not initialized in the code. The report is organized by file. Each uninitialized item within the file is listed by name along with the line number on which the item is declared. The HTML version offers hyperlinks to the location where the item is declared.

**Unused Objects and Functions** The *Unused Objects and Functions* report lists items that are declared (and perhaps initialized) but never referenced other than that. The report is organized by file. Each unused item is listed by name along with the type of item and the line number on which the item is declared. The function or similar container is shown after the list of unused items within it. Types of items may include functions, parameters, variables, and objects. The HTML version offers hyperlinks to the location where each unused item is declared.

**Unused Objects Report** The *Unused Objects Report* lists objects (for example, variables, parameters, constants) that are declared but never used. The HTML version has links to the function's Data Dictionary report entry and to the source line where the object is declared.

# Unused Objects

Non-Alpha	A	B	C	<u>D</u>	E	<u>F</u>	H	<u>I</u>	J	K	L	M	N	O	P	Q	R
-----------	---	---	---	----------	---	----------	---	----------	---	---	---	---	---	---	---	---	---

<a href="#">inffixed.h</a>	
<a href="#">distfix</a>	87
<a href="#">lenfix</a>	10
<a href="#">inftees.c</a>	
<a href="#">inflate copyright</a>	11

**Unused Types Report** The *Unused Types Report* lists types that are declared but never used. The HTML version has links to the function's Data Dictionary report entry and the source where the type is declared.

Unused Types	
Non-Alpha	A B C D E F <u>G</u> H I J K L M N O P Q R
<a href="#">zconf.in.h</a>	
<a href="#">uIntf</a>	274
<a href="#">zutil.c</a>	
<a href="#">internal state</a>	11

**Unused Program Units Report** The *Unused Program Units Report* identifies program units that are declared but never used.

Note that this listing in this report doesn't mean the system doesn't need this program unit. For instance, interrupt handlers that are called by system interrupts are often never "used" within the other source of the program.

Unused Program Units	
Non-Alpha	<u>A</u> B <u>C</u> <u>D</u> <u>E</u> <u>F</u> <u>G</u> H <u>I</u> J K L <u>M</u> N O P Q R
<a href="#">deflate.c</a>	
<a href="#">deflateBound</a>	489
<a href="#">deflateCopy</a>	894
<a href="#">deflateSetHeader</a>	393
<a href="#">deflateTune</a>	454

**Uses Not Needed Report** The *Uses Not Needed Report* identifies any unneeded "use" statements that provide access to a module's public specifications and definitions. To remove unneeded access, you may add only clauses to use statements.

**Withs Not Needed Report** This report lists, any With statements a program unit has but does not need (by not using items made public by the With statement).

Note that this covers only direct usage in the program unit and doesn't account for side effects that may be needed by the program to operate correctly. For instance, sometimes a package can be Withed just to start a task or to execute code in its begin/end block.

# Metrics Reports

Metrics provide statistical information about your project and entities, such as the number of lines of code and the complexity of various entities.

*Understand* provides a number of ways to gather metrics information. This section describes reports that provide metrics. See page 233 for other ways to gather metrics.

The following table shows the page in this chapter that describes each type of metrics report.

Report Name and Page
<i>Project Metrics Report</i> on page 228
<i>Class Metrics Report</i> on page 229
<i>Class OO Metrics Report</i> on page 229
<i>Program Unit Metrics Report</i> on page 230
<i>File Metrics Report</i> on page 230
<i>File Average Metrics Report</i> on page 231

The complete list of metrics available in *Understand* changes frequently—more frequently than this manual is reprinted.

A complete and accurate list is always available on our website:  
[scitools.com/support/metrics\\_list/](http://scitools.com/support/metrics_list/).

## Project Metrics Report

The *Project Metrics Report* provides metric information about the entire project. The metrics reported include: the total number of files, the total number of program units, and the total number of lines of source code.

Project Metrics	
Classes:	0
Files:	33
Program Units:	173
Lines:	14941
Lines Blank:	1344
Lines Code:	7217
Lines Comment:	4426
Lines Inactive:	1623
Executable Statements:	5152
Declarative Statements:	1074
Ratio Comment/Code:	0.61

These metrics are also reported on the title page of the HTML report.

**Class Metrics Report**

The *Class Metrics Report* provides the following metrics for each class that has been analyzed:

- Total number of lines
- Total number of blank lines
- Total number of lines of code
- Total number of lines that contain comments
- Average number of lines per class
- Average number of comment lines per class
- Average complexity per class
- Maximum complexity within class
- Ratio of comment lines to code lines

**Class Metrics**

Class	<a href="#">Lines</a>	<a href="#">Lines Blank</a>	<a href="#">Lines Code</a>	<a href="#">Lines Comment</a>	Average Lines	Average Lines Comment	Average Complexity	Maximum Complexity	<a href="#">Ratio Comment/Code</a>
<a href="#">GetoptDemo</a>	85	2	70	15	79	14	16	16	0.21%
<a href="#">gnu.getopt.Getopt</a>	960	125	506	337	43	5	6	45	0.67%
<a href="#">gnu.getopt.LongOpt</a>	153	25	48	81	6	0	1	2	1.69%

**Class OO Metrics Report**

The *Class OO Metrics Report* provides the following object-oriented metrics for each class that has been analyzed:

- **LCOM (Percent Lack of Cohesion):** 100% minus the average cohesion for class data members. A method is cohesive when it performs a single task.
- **DIT (Max Inheritance Tree):** Maximum depth of the class in the inheritance tree.
- **IFANIN (Count of Base Classes):** Number of immediate base classes.
- **CBO (Count of Coupled Classes):** Number of other classes coupled to this class.
- **NOC (Count of Derived Classes):** Number of immediate subclasses this class has.
- **RFC (Count of All Methods):** Number of methods this class has, including inherited methods.
- **NIM (Count of Instance Methods):** Number of instance methods this class has.
- **NIV (Count of Instance Variables):** Number of instance variables this class has.
- **WMC (Count of Methods):** Number of local methods this class has.

**Program Unit Metrics Report** The *Program Unit Metrics Report* provides information on various metrics for each program unit that has been analyzed.

## Program Unit Metrics

	<a href="#">Lines</a>	<a href="#">Comments</a>	<a href="#">Blanks</a>	<a href="#">Code</a>	<a href="#">Lines-exe</a>	<a href="#">Lines-dec</a>	<a href="#">Stmt-exe</a>	<a href="#">Stmt-dec</a>	<a href="#">Ratio Comment/Code</a>
<a href="#">uncompress</a>	36	1	6	29	19	7	22	2	0.03
<a href="#">updatewindow</a>	49	3	4	42	29	6	29	2	0.07

The following metrics are provided for each program unit:

- **Lines:** Total number of lines in the function.
- **Comment:** Number of comment lines in the function.
- **Blank:** Number of blank lines in the function.
- **Code:** Number of lines in the function that contain any code.
- **Lines-exe:** Lines of code in the function that contain no declaration.
- **Lines-decl:** Lines of code in the function that contain a declaration or part of a declaration.
- **Stmt-exe:** Number of executable statements in the function.
- **Stmt-decl:** Number of declarative statements in the function. This includes statements that declare classes, structs, unions, typedefs, and enums.
- **Ratio Comment/Code:** Ratio of comment lines to code lines.  
(comment\_lines/code\_lines)

**Note:** code+comment+blank != lines because some lines contain both code and comments.

**File Metrics Report** The *File Metrics Report* provides information similar to that in the *Program Unit Metrics Report*. However, it is organized by file rather than by *program unit*.

Click on each metric column to get a detailed description of it.

**Note:** code+comment+blank != lines because some lines contain both code and comments.

## File Metrics

	<a href="#">Lines</a>	<a href="#">Comments</a>	<a href="#">Blanks</a>	<a href="#">Code</a>	<a href="#">Lines-exe</a>	<a href="#">Lines-dec</a>	<a href="#">Stmt-exe</a>	<a href="#">Stmt-dec</a>	<a href="#">Ratio Comment/Code</a>	<a href="#">Units</a>
<a href="#">deflate.c</a>	1736	456	181	916	617	181	598	109	0.50	22
<a href="#">deflate.h</a>	331	170	61	88	0	88	0	81	1.93	0

---

**File Average Metrics Report**

The *File Average Metrics Report* provides averages for the functions within a file. All lines outside any function are ignored when calculating the averages. The following metrics are provided for each function:

- **Cyclomatic:** The average number of independent paths through the functions in this file. The higher this metric the more likely a program unit is to be difficult to test and maintain without error.
- **Modified:** Same as Cyclomatic complexity except that each case statement is not counted; the entire switch statement counts as 1.
- **Strict:** Same as Cyclomatic complexity except that && and || also count as 1.
- **Essential:** Measures the amount of unstructured code in a function.
- **Lines:** Average number of lines in the functions in this file.
- **Code:** Average number of lines that contain any code in the functions in this file.
- **Comment:** Average number of comment lines in the functions in this file.
- **Blank:** Average number of blank lines in the functions in this file.

---

## Importing Report Plugins

Plugins are special Perl Scripts that can be imported to produce customized reports. Several report plugins are available on the [Support website](#).

To install a report plugin:

- 1 Download a plugin to one of the following locations:
  - <InstallDir>\conf\plugin\User\IReport  
(for example, C:\Program Files\SciTools\conf\plugin\User\IReport)
  - <appdata>\SciTools\plugin\IReport  
(for example, C:\Users\USERID\AppData\Roaming\SciTools\plugin\IReport)
- 2 Restart *Understand*.
- 3 Right-click on a file and choose **Interactive Reports > Plugin Name** to open the report or the options dialog used to run the report.

## Chapter 9

# Using Metrics

This chapter describes how to create and view metrics and the types of metrics available.

This chapter contains the following sections:

<b>Section</b>	<b>Page</b>
About Metrics	233
Metrics Summary	234
Metrics Browser	235
Exporting Metrics to HTML	236
Exporting Metrics to a CSV File	237
Configuring Metric Charts	239
Using the Metrics Treemap	242
Exporting Dependency Metrics	244



---

## About Metrics

*Understand* provides a number of ways to gather metrics information:


- **Information Browser:** The Information Browser tree has a **Metrics** node. You can expand this branch to show a few metrics for the current entity. See page 137.
- **Metrics Summary:** You can choose **Metrics > Metrics Summary** from the menus to see a short list of metrics for the entire project. See page 234.
- **Metrics Browser:** You can choose **Metrics > Browse Metrics** from the menus to see a browser that lets you choose any architecture node, file, or entity to see all the metrics available for that item. See page 235.
- **Export to HTML:** You can click this button in the Project Metrics Browser to export the full list of metrics for all architecture nodes and files. See page 236.
- **Export to CSV:** You can choose **Metrics > Export Metrics** from the menus to create a text file of all the project metrics in comma-delimited format. See page 237. (You can schedule this export to occur regularly; see page 51.)
- **Configure Metric Charts:** You can choose **Metrics > Configure Metric Charts** from the menus to open a dialog that lets you display graphs of volume and complexity metrics on an architecture basis. See page 239.
- **Reports:** When you create reports by choosing **Project > Project Reports**, some of the reports provide metrics. See page 228.
- **PERL/C API:** A more advanced way to get existing metrics and calculate new metrics is with the PERL and C API. These provide full access to the *Understand* database. Choose **Help > PERL API Documentation** for more information. See page 215.

*Understand* provides a large number of metrics you can generate about your code. The complete list of metrics available in *Understand* changes frequently—more frequently than this manual is reprinted.

A complete and accurate list of metrics is always available on our website at [scitools.com/support/metrics\\_list/](http://scitools.com/support/metrics_list/). The “What do the metric names mean?” buttons in metrics dialogs links to this page.

## Metrics Summary

Choose **Metrics > Metrics Summary** from the menus to see a short list of metrics for the entire project.




Metric	Value
Blank Lines	3,271
Classes	30
Code Lines	15,167
Comment Lines	8,162
Comment to Code Ratio	0.54
Declarative Statements	2,807
Executable Statements	9,336
Files	82
Functions	497
Inactive Lines	3,268
Lines	30,083
Preprocessor Lines	2,275
Subprograms	45

If your cursor hovers over a metric, you will see a short description of that metric. A complete and accurate list of metrics is always available on our website at [scitools.com/support/metrics\\_list/](http://scitools.com/support/metrics_list/). The “What do the metric names mean?” buttons in metrics dialogs link to this page.

## Metrics Browser

To open the Project Metrics Browser, choose **Metrics > Browse Metrics** from the menus. You can also open the Metrics Browser with a particular architecture node, file, or entity by right-clicking the name of an item and selecting **Browse Metrics**.


You can browse architectures in your project and select any architecture node, file, or entity. The list on the right shows code size and complexity metrics for the selected item. If your cursor hovers over a metric, you will see a short description of that metric. For a full list of metrics with descriptions, see [scitools.com/support/metrics\\_list/](http://scitools.com/support/metrics_list/). The “What do the metric names mean?” button links to that page.



If you check the **Sync** checkbox, clicking on an entity elsewhere in *Understand* causes the Metrics Browser to display the metrics for that entity.

Double-click a file or entity to open the Source Editor for that item. Right-click to see the standard informational menu choices.

Check the **Show Detailed Architecture Metrics** box to extend the metrics list provided for the selected architecture node. Note that for large projects showing detailed metrics may affect performance when selecting new nodes in the Metrics Browser.



Click **Generate Detailed Metrics** to open the Export Metrics dialog and generate a text file in comma-delimited format as described on page 237.

Click **Export to HTML** to generate reports as described on page 236. You can choose to **Export All Architectures** and all of their nodes or to **Export Selected Architectures** and nodes that you have selected using the Ctrl or Shift key while clicking on the nodes you want in the metrics export.

To copy metrics to the clipboard, select metric rows and click **Copy Selected** or press Ctrl+C. Click **Copy All** to copy the full list for the selected directory or file.

## Exporting Metrics to HTML

You can click the **Export to HTML** button in the Project Metrics Browser (page 235) to export the full list of metrics for all entities and architecture nodes. When you click this button, you see a Browse for Folder dialog appropriate to your operating system.

Choose or create the folder where you want the metrics files to be created. The files are actually stored in a folder called "pixie\_proj\_Metrics" below the folder you select.

If the directory already exists, you are asked if the files should be overwritten. If you answer "No", a number is appended to the old directory name to it to save it as a backup.

If the report is generated successfully, you are asked if you want to view the report. Click **Yes** to open the top-level page, index.html.

**Architecture: Calendar**

**Summary**

**File Types**

C Header File	11
C Code File	22

**Entity Kinds**

None

**Metrics**

CountLineComment	4,426
CountLineInactive	1,623
CountLinePreprocessor	1,599
RatioCommentToCode	0.61
CountDeclFile	33
CountLineBlank	1,344
CountStmtDecl	1,074
CountDeclFunction	173
CountLine	14,94
CountStmtExe	5,152
CountLineCode	7,217
CountDeclClass	0

**File: crc32.c**


**Metrics**

AltCountLineCode	287
MaxCyclomaticStrict	7
AvgCyclomatic	5
CountLine	423
AltAvgLineBlank	3
CountLinePreprocessor	64
RatioCommentToCode	0.41
CountLineBlank	42
MaxCyclomaticModified	7
AvgLineCode	21
AvgCyclomaticModified	5
CountLineInactive	142
AltAvgLineComment	2
AvgEssential	1.86
CountDeclFunction	7
AltAvgLineCode	22
AvgLine	26
CountStmtEmpty	0
CountStmtExe	128
CountStmt	151
AltCountLineBlank	53

The HTML-based report lets you select any architecture node, file, function, or other entity type that has metrics in the left pane. The right pane shows metrics available for that item.

## Exporting Metrics to a CSV File

You can save metric information to a comma-delimited text file by choosing **Metrics > Export Metrics** from the menus or clicking the **Generate Detailed Metrics** button in the Project Metrics Browser. You can use the generated file in Excel and other spreadsheet programs. The Export Metrics dialog looks like this:



The defaults in this dialog come from the Project Configuration dialog in the **Metrics > Options** category (page 53) and the **Metrics > Selected** category (page 54).

You can override the defaults using the following fields:

- **Available Metrics:** Check the boxes next to metrics you want to include in the output. Check the “SELECT ALL” box to select all metrics. Uncheck the “SELECT ALL” box to unselect all metrics. If your cursor hovers over a metric, you will see a short description of that metric.
- **Metrics to Export:** Click the single arrow to move the selected metric up or down one in the list. Click the double arrow to move the selected metric to the top or bottom of the list.
- **Save output to:** Specify the location and name of the file you want to use for metrics output. *Understand* sends its metrics output to a \*.csv (comma-separated values) file.

- **Show File Entity Name as:** Specify whether files should be displayed with **Short** names (just the filename), **Full** names (including the absolute path), or **Relative** names (relative directory path).
- **Show Declared in File:** Check this box if you want the file in which each entity is declared to be included in the output. You can specify whether you want these files displayed with **Short** names, **Full** names, or **Relative** names.
- **Write Column Titles:** Check this box if you want column headings in the CSV file.
- **Show Function Parameter Types:** Check this box if you want the type of each function parameter listed.

After setting options, click **Export** to export the .CSV file. If you check the **View File After Export** box before exporting the file, the CSV file is opened with the default application for working with CSV files. This is likely to be a spreadsheet application.

If the output file already exists, you are asked if the files should be overwritten. If you answer “No”, you can change the output filename and click **Export** again.

You can schedule this metrics to be automatically exported to a CSV file on a regular basis. See page 51 for details.

See *Exporting Dependency Metrics* on page 244 for more types of metrics you can export to a CSV file.

A complete and accurate list of the available metrics is available at:  
[scitools.com/support/metrics\\_list/](https://scitools.com/support/metrics_list/).

## Configuring Metric Charts

Commands in the Metrics menu provide fast access to metrics charts for the current version of the entire project. These commands are:


- **Metrics > Project Metric Charts > Code Volume**
- **Metrics > Project Metric Charts > File Volume**
- **Metrics > Project Metric Charts > Average Complexity**
- **Metrics > Project Metric Charts > Sum Complexity**

You can choose **Metrics > Configure Metric Charts** from the menus to open the Metric Browser, which lets you display graphs of various metrics on an architecture basis.


In this browser, select the following:

- **Architectures:** Checkboxes next to one or more architecture nodes, files, and/or entities. The graph will provide a set of vertical bars for each of the items you select.
- **Metrics:** Select the type of metrics you want to graph from the drop-down list.
  - **Code Volume:** Provides a stacked vertical bar chart showing the count of lines that are blank, contain declarations and executable code, and contain comments.
  - **File Volume:** Provides a vertical bar chart showing the number of files in the selected architecture node that are code files vs. header files (or the number of files for languages that do not have header files).
  - **Average Complexity:** Provides a vertical bar chart of the average and maximum cyclomatic complexity for all nested functions or methods in the architecture node, along with the maximum nesting level of control constructs in the node's files.
  - **Sum Complexity:** Provides a vertical bar chart showing the number of possible paths through the code and the sum of the cyclomatic complexity and the essential complexity of all nested functions or methods.


Click the **View Chart** button to display a chart for your selections or **View Table** to see the values in a table. If you have already selected a graph for this type of metrics, that tab will be reused unless you check the **Open in a new tab** box.



You can open metrics charts for various entities, including files and functions, from the context menus throughout *Understand*.



A typical metrics chart looks similar to the following:






In a graph, you can choose the **Graph View** or the **Table View**. Both views have a toolbar that lets you save the graph or data.

In the **Graph View**, you can use the toolbar to:



- Save the image as a PNG, JPEG, or BMP image.
- Copy the image to the clipboard.
- Print the image using the standard Print dialog.

In the **Table View**, the numeric values for each pie slice or vertical bar is shown in a table. You can use the toolbar to copy the data to the clipboard in comma-separated (CSV), tab-separated, or table format (spaces used so columns align with headings if a font such as Courier is used).




If you are viewing data for several architecture nodes, you can change the number in the lower-right corner to the number of vertical bars you want to view on each page and click the checkmark icon. Then use the arrows in the corners to move from page to page. The text shows which vertical bars are currently shown out of the total number. For example, the figure below indicates that bars 3 and 4 out of a total of 5 are currently shown.



## Using the Metrics Treemap

Treemaps show metrics graphically by varying the size of node blocks and the color gradient. Each node block represents a code file. Different metrics can be tied to size and color to help you visualize aspects of the code.

For example, the following treemap ties the number of lines in each file to the size of the block and the MaxCyclomatic complexity metric to the darkness of the blue. This allows you to learn which files are large and complex vs. files that are large and relatively non-complex.




So we learn that `unzip.c` is large, but not particularly complex, while `inflate.c` is large and highly complex.

By default the maps are nested by directory structure. If you have built other architectures, you can use those as well.

To open the treemap for your project, follow these steps:

- 1 Choose **Metrics > Metrics Treemap** from the menus. You will see the Metrics Treemap Options dialog.







- 2 In the **Map metrics for** field, choose whether you want to select from metrics for Files, Classes/Interfaces/Structs, or Functions/Methods.
- 3 In the **Group by** field, choose how to group blocks in the treemap. The default is to group by the project's directory structure. Alternately, you can choose to group according to any other defined architecture or no architecture (flat).
- 4 In the **Size Options** area, choose a metric to control the size of the blocks. You can also limit the size of the largest blocks to some percentage of the treemap. You might want to use this if one node is taking up so much of the map that you can't see differences between the smaller nodes.
- 5 In the **Color Options** area, choose a metric to control block colors. You can click the left color square to set a color for blocks with the lowest value for this metric; click the right color square to set a color for blocks with the highest value for this metric.
- 6 Check the **Use Logarithmic Scale** box if you want the color scaled by powers of 10 of the selected metric value. This is useful for treemaps with extreme value ranges.

- 7 Uncheck the **Cushion** box if you want to see solid colors in the blocks. By default, the blocks have a gradient fill.
- 8 Check the **Custom Scaling** option and specify **Min** and **Max** values if you want to scale the treemap colors. Nodes for which the metric mapped to the color gradient has a value less than or equal to the Min will have the Min color. Likewise, nodes have the Max color if the metric mapped to the color is greater than or equal to the Max value. This allows easier comparisons between different projects or to allow for before and after pictures that use the same scale.
- 9 Click **Generate Treemap** to display the treemap. You can return to the Options dialog by clicking **Options** in the upper-right corner of the treemap.

Within the treemap, when your mouse cursor hovers over a block, the two metric values chosen for the size and color are shown.

You can double-click on an architecture node (shown as a gray border around a set of colored blocks) to display only the contents of that node. You can also zoom in by right-clicking on a node and choosing **Drill down** from the context menu.

After drilling down in the architecture, you can use the   icons to **Pop up one level** or **Pop up all levels** the treemap. You can also right-click to use the **Pop up one level** and **Pop up all levels** commands in the context menu.

You can click the  **Print** icon to print the currently displayed treemap diagram. Click the  **Export to Image File** icon to save the treemap to a PNG or JPG file.

---

## Exporting Dependency Metrics

The **Reports > Dependency** menu lets you export several types of files that provide metrics about dependencies between architectures, files, and classes/packages.

The output is for most of these commands in CSV (comma-separated values) format, which can be opened with most spreadsheet programs. When you create a CSV file with *Understand*, it is automatically opened in a text file window.


The options available are as follows:

- **Architecture Dependencies >**
  - **Export CSV:** This output lists pairs of architecture nodes for which the node in column A is dependent upon the node in column B. The number of dependencies for each pair is listed in column C. (See page 246.)
  - **Export Matrix CSV:** This output lists all architecture nodes that are dependent upon others in column A. Row 1 lists all architecture nodes that are depended upon. The number of dependencies for each pair is listed at the appropriate row/column intersection. (See page 247.)
  - **Export Cytoscape XML:** This output format can be opened in Cytoscape ([www.cytoscape.org](http://www.cytoscape.org)), a free open-source program for analysis and visualization. It draws large diagrams very quickly, and can be useful if you want an overview picture of dependencies in a very large project. (See page 247.)

- **Export Dot:** This output format uses a plain text graph description language. Various programs are available that can import DOT files to create graphs, perform calculations, and manipulate the data.
- **File Dependencies >**
  - **Export CSV:** This output lists pairs of files for which the file in column A is dependent upon the file in column B. The number of dependencies for each pair is listed in column C. (See page 246.)
  - **Export Matrix CSV:** This output lists all files that are dependent upon others in column A. Row 1 lists all files that are depended upon. The number of dependencies for each pair is listed at the appropriate row/column intersection. (See page 247.)
  - **Export Cytoscape XML:** See the description of the Cytoscape XML export for architecture dependencies. (See page 247.)
- **Class Dependencies >**
  - **Export CSV:** This output lists pairs of classes and packages for which the entity in column A is dependent upon the entity in column B. The number of dependencies for each pair is listed in column C. (See page 246.)
  - **Export Matrix CSV:** This output lists all classes and packages that are dependent upon others in column A. Row 1 lists all classes and packages that are depended upon. The number of dependencies for each pair is listed at the appropriate row/column intersection. (See page 247.)
  - **Export Cytoscape XML:** See the description of the Cytoscape XML export for architecture dependencies. (See page 247.)

## Exporting Dependencies to a CSV File

When you choose to export a CSV file, you can also set the following options. (This figure shows the dialog for exporting File Dependencies; the other two CSV Export dialogs are very similar.)




In this dialog, you can set the following options:

- **Select an architecture to analyze:** This option is available only when you are exporting architecture dependencies.
- **Output File:** Browse for the location to save the CSV file.
- **Columns:** Check the boxes for columns you want to include in the output. The “From” and “To” columns for the type of entity you are exporting are required, and cannot be deselected.
- **Names:** Choose a length for entity names. For example, all types can have a short or long name. Files can also have a relative name.
- **Sort:** Choose how you want dependencies sorted. You can sort based on the “From” column or the “To” column.
- **Dependency Aggregation:** Choose how you want to summarize dependency pairs that occur multiple times. You can show each pair individually or sum pairs for the “From” or “To” column for the type of entity you are exporting.

## Exporting Dependencies to a CSV Matrix File

When you choose to export a CSV matrix file, you can also set the following options. (This figure shows the dialog for exporting File Dependencies; the other two CSV Export dialogs are very similar.)



In this dialog, you can set the following options:

- **Select an architecture to analyze:** This option is available only when you are exporting architecture dependencies.
- **Output File:** Browse for the location to save the CSV matrix file.
- **Names:** Choose a length for entity names. For example, all types can have a short or long name. Files can also have a relative name.

## Exporting Dependencies to Cytoscape

Cytoscape ([www.cytoscape.org](http://www.cytoscape.org)) is an open source software tool for visualizing complex networks.

When you choose to export a Cytoscape file, you can Browse to select the location and filename for the output file. If you are exporting architecture dependencies, you can also select an architecture to analyze.

Once you have exported the \*.xml file, you are asked if you want to open the file in Cytoscape. Note that you can only open Cytoscape if it is installed on your computer. See *Dependency Category* on page 110 for how to configure the location of the Cytoscape installation.

This chapter covers the graphical views in *Understand* and their options.


This chapter contains the following sections:

Section	Page
Project Overview Graphics	249
Graphical View Browsers	251
Types of Views	257
Graphical Notation	266
Controlling Graphical View Layout	266
Controlling Cluster Graph Layout	275
Saving Graphical Views	278
Importing Graphical View Plugins	280
Printing Graphical Views	281



## Project Overview Graphics

You can create graphics that provide an overview of your entire project by choosing **Project > Project Overview Charts** from the menus. This opens a tab in the document area that contains a number of pie charts and vertical bar charts. For example:



The graphs provided are code breakdown (line types), function breakdown, class breakdown, most complex functions, largest non-file entities, largest files, largest functions, best comment-to-code ratio entities, and most complex files.

In each area, you can choose the Graph View or the Table View. Both views have a toolbar that lets you save the graph or data.


In the Graph View, you can use the toolbar to:



- Save the image as a PNG, JPEG, or BMP image.
- Copy the image to the clipboard.

- Print the image using the standard Print dialog.
- Zoom in on the graph in a new tab.


In the Table view, the numeric values for each pie slice or vertical bar is shown in a table. You can use the toolbar to copy the data to the clipboard in comma-separated (CSV), tab-separated, or table format (spaces used so columns align with headings if a font such as Courier is used).



In addition to the Project Overview Charts, you can display metrics graphs that provide additional statistical information about your project or portions of your project. For details, see page 239.

## Graphical View Browsers

The context menu of an entity that has a structure or hierarchy offers a choice called **Graphical Views**:




You can also use the Graphs drop-down menu in the toolbar to select from the types of graphs available for the entity at the current cursor position in a Source Editor tab. The same list of graphical views is available by choosing **Graphs > Graphs for <current\_entity>** from the menus.

The **Graphical Views** menu adapts based on the kind of entity right-clicked. An item is grayed-out if information is normally available for this kind of entity but is not applicable to this particular entity (for instance a package that could be WITHed but isn't).


There are two main types of graphical views in these menus: hierarchy views and structure views.

(Dependency graphs are a separate type of graph described in the chapter on architectures. See page 198 for details. Project overview graphs are described on page 249.)




## Hierarchy Views

A *hierarchy view* shows multiple level relationships between entities. All relationships are multi-level and are shown to the top or bottom of their respective tree unless a level option is set in the preferences. The following is a Call By graph for a function.




See *Hierarchy View Types* on page 257 and *Hierarchy View Examples* on page 258.

Cluster views are a special type of hierarchy view. They provide a more interactive view of call relationships. The Call, Callby, Butterfly and Internal Call variants are available, and can be accessed from the function, class, file, or architecture level. See *Controlling Cluster Graph Layout* on page 275.



## Structure Views



Structure views offer a one glance way to see important structure and relational information about a given entity. The following is an example of a Declaration structure view:




See *Structure View Types* on page 261 and *Structure View Examples* on page 261.

## General Commands for Using Graphical Browsers


There are some general commands that can be used for browsing graphical views. Note that some of these tools are not available in all types of graphs.

- **Entity info:** Anywhere you see an entity, you can right-click on it to see a menu that offers many ways to learn more about that entity. Single-clicking shows information about the entity in the Information Browser. If you are in Screen Drag mode or Zoom mode, click the  icon to be able to select entities.
- **Searching:** Click the  **Search** icon at the top of a graphical view or press Ctrl+F to display the incremental search bar. You can use this bar the same way you use it in the Source Editor to find entities by name or other text in the current graphical view. As you type search text, all instances of the string are highlighted in the graphical view. See page 165 for details.





- **Opening source:** Right-click on an entity in a graphical view and choose **Edit Definition** to open the source location where the entity is declared.
- **Listing open views:** You can choose **Window > Windows Navigator** from the menus or look at the tabs across the top of the document area to see a list of all the separate graphical views you have open.
- **Scrolling:** You can scroll around a graphical view by dragging your cursor within the view when you have selected Screen Drag Mode by clicking the  icon.


- **Expanding hierarchy:** You can expand and contract tree views by clicking the red circle to the right of a node. Right-click on the background of a view and choose **Open All Nodes** or **Close All Nodes** to expand or contract all nodes at once. Choose **Close Unselected Nodes** to contract nodes that are not in the path of any selected nodes. Hold down the Ctrl key if you want to keep multiple nodes open.



- **Path highlighting:** To highlight the path for one or more entities in a tree view (such as a Callby view), select the entity and right-click. In the context menu, choose **Highlight Path**. Hold down the Ctrl key to select multiple entities for path highlighting.



- **Add to favorites:** You can add graphs you may want to reopen to a favorites list by clicking the  Favorites icon in the toolbar.
- **Zooming:** You can zoom in or out using the toolbar.



- **Printing and saving:** Everything you see can be printed or saved. Printing may be done to one page (squeezing the picture) or across multiple pages (poster style).


See *Printing Graphical Views* on page 281 for details on printing. Graphical views can be saved as BMP, JPEG, PNG, Visio XML, and DOT files. See *Saving Graphical Views* on page 278 for details on saving to a graph file.

- **Layout control:** Layout is done automatically; there is no need to move lines or boxes around for a better view. Options are available for changing the layout. For example, you can control whether entities are sorted according to their order in the code or alphabetically. See *Controlling Graphical View Layout* on page 266.


## Filtering Out Entities

You can apply filters to hide certain entities in some graphical views. To create such a filter, follow these steps:

- 1 Right-click on the background of a graphical view and choose **Edit Graphic Filters** from the context menu. (Note that this option is not available for some types of graphs. For example, it is available for Call graphs and Declaration graphs.)



- 2 In the Graphic Filter dialog, put a checkmark in the **Enable Project Filters** box.
- 3 Click **New**. This opens the Graphic Filter Editor dialog.



- 4 Type a filter in the **Filter Text** field. For example, use gr\* to match entity names beginning with gr. Filters are case-sensitive.

- 5 In the **Filter Criteria** field, select whether to compare the filter to long names, definition files, the type text of entities, or parameter text. For example, if you choose long names, a filter of `print*` does not match `SomeProc::printWide`. Instead, you can type `*print*`.
- 6 In the Action field, select one of the following options:
  - **Hide Node:** Items that match the filter are not included in the output.
  - **Hide Sub Nodes:** The item that matches the filter is shown, but any subnodes of these items are removed from the output.
  - **Collapse Sub Nodes:** Any subnodes of items that match the filter are collapsed in the output. An icon is shown after the node to indicate that there are subnodes. Items that match the filter are shown.
- 7 Click **OK** to add the filter to the project.

You can also create filters by right-clicking on an entity in a graphical view and choosing one of the filtering options. The options allow you to quickly filter out entities with that name or in that file.

You can remove filters you have created by clicking **Remove** or **Remove All**.

The filters you create apply to all graphical views that support filtering. You can temporarily disable filtering in the Graphical Settings dialog or by right-clicking on any graphical view and choosing **Disable Graphic Filters** from the context menu.

---

### Reuse Checkbox

The **Reuse** checkbox controls whether a view is reused or a new window is opened when another graphical view is requested. The Reuse box is unchecked by default. At most one graphical view can have the **Reuse** box checked at any time.

You can cause views to be reused if a similar type of graphical view is opened from within a graphical view, no matter whether the **Reuse** box is checked. Change this behavior in the User Interface > Windows category of the **Tools > Options** dialog (page 99).

---

### Sync Checkbox

The **Sync** checkbox controls whether this graphical view changes when a different entity is selected in the Project Browser, Entity Filter, and other windows that let you select an entity. For example, if you check the Sync box in a Declaration graph window and then select a different entity in the Entity Filter, the graph shows declaration information for the newly selected entity.

---

### Graph Options

See page 120 for information about the **Graphs** category in the **Tools > Options** dialog. You can control how the display of relationships between graph nodes changes when you hover the mouse over a graph or double-click on a node.



## Types of Views

There are two main types of graphical views: hierarchy views and structure views.

(Dependency graphs are a separate type of graph described in the chapter on architectures. See page 198 for details. Project overview graphs are described on page 249.)

### Hierarchy View Types

*Hierarchical* views show multi-level relationships between entities. *Understand* offers hierarchy graphs of the following types of relationships. Some types apply to specific source languages.


- **Butterfly:** Shows both calls and called by.
- **Calls:** Shows who this entity calls.
- **Calls Relationship:** Show the call relationships between two entities.
- **Called By:** Shows who calls a given entity.
- **Calledby Relationship:** Show the callby relationships between two entities.
- **Include:** Shows who this file includes.
- **IncludeBy:** Shows who includes this file.
- **Depends On Graph, Depended On By Graph, and Butterfly Graph:** Available for classes, packages, and architectures only. See page 198 for architecture graphs.
- **Derived Classes:** Shows classes derived from a given class.
- **Base Classes:** Show what classes are the base for a class.
- **Extended By:** Shows which classes are extended by this class.
- **Class Inheritance:** Shows who inherits from a given class.
- **Child Lib Units:** Shows Child Library Units of a compilation unit. (Ada 95 only)
- **Declared In:** Shows the declaration tree from where this program unit is declared.
- **Declaration Tree:** Shows declaration nesting of program units in a compilation unit.
- **Instantiated From:** Shows instantiation tree of a generic type or compilation unit.
- **Instantiations:** Shows who instantiates a given generic unit.
- **Invocation:** Shows what compilation units a unit invokes.
- **Parent Lib Unit:** Shows the parent lib units of a given entity.
- **Type Derived From:** Shows tree of types a type is derived from.
- **Type Tree:** Shows types that derive new types from an entity.
- **With:** Shows what compilation unit an entity “Withs” into scope.
- **WithBy:** Shows what compilation units “Withs” a given entity.
- **Uses:** Shows which modules use this item.
- **Used By:** Shows which modules are used by this item.
- **Cluster Call Internal:** Shows call relationships within a file.

- **Cluster Call:** Shows who this entity calls.
- **Cluster Callby:** Shows who calls this entity.
- **Cluster Call Butterfly:** Shows both calls and called by.


## Hierarchy View Examples

Hierarchy views show multi-level relationships between entities. Here are examples of the types of hierarchy views that *Understand* offers.


- **Butterfly:** Shows both calls and called by relationships if they exist. The selected entity is outlined in red.




- **Calls:** Shows the entire chain of calls emanating from this function. Each line between entities is read as “x calls y”.




- **Called By:** Shows what calls an entity. Each line connecting an entity is read as “x is called by y”. In this example, error is called by code (and others), which is called by rules (and others). Note that this view is read from the bottom up or right to left.




- **Calls Relationship / Calledby Relationship:** Shows the call or callby relationships between any two entities. First, right-click on the first entity and select the graph you want to view. Then, click on another entity whose relationship to the first entity you want to find. You can click on the second entity anywhere in the *Understand* interface. The entity name will appear in the “Select a second entity” dialog. This example shows the callby relationship from the deflate() function to main().




- **Include:** Shows the include hierarchy of an entity, such as a file. A connecting line is read as “x includes y.” In this example, align.h includes global.h.




- **Include By:** Shows the include tree in the other direction. In the previous example, align.h is included by several files such as algebra.h.
- **Base Classes:** For classes, shows the base classes from which this class is derived from. In this example, class *CLinearCurve* is derived from class *CCurve*, which is derived from class *CSurface* and so on.



- **Derived Classes:** Shows the classes that are derived from this class. In this example, class *CTexture3d* is a base class for classes *CIrradianceCache* and others.



- **Extended By:** Shows which classes are extended by other classes. A line is read as “class is extended by class.” In this example, the *regex.REToken* class is extended by a number of classes, including the *regex.RE* class, which in turn is extended by the *regex.UncheckedRE* class.



---

## Structure View Types

*Structure* views offer a one glance way to see important structure and relational information about a given entity. *Understand* structure views include the following:

- **Graph Architecture:** Shows the hierarchy of an architecture node. See page 201.
- **Declaration:** Shows what a structure is composed of. For example, shows the parameters, return type, and callbys of a function. For classes, shows what members are provided, who inherits this class, and who it is based on.
- **Parent Declaration:** Shows what a structure is composed of. Shows Calls instead of the Called Bys shown by a Declaration graph.
- **Declaration File:** Shows what entities (such as functions, types, macros, and variables) are defined within a given file.
- **Declaration Type:** Shows what a type is composed of.
- **Class Declaration:** Shows the members defining the class and the parent class
- **Data Members:** Shows what components a class, struct, or type contains.
- **Control Flow:** Shows a flow chart of the function or similar entity type. Clicking on a node in the graphs jumps to the line of code referenced.
- **Cluster Control Flow:** Shows a flow chart of the function or similar entity type. This view type is more interactive than the Control Flow view.
- **UML Class Diagram:** Shows the classes defined in the project or a file and related classes. Adheres to the Unified Modeling Language (UML) structure diagram format.
- **UML Sequence Diagram:** Shows interactions between entities arranged by time sequence. This graph is available for functions and methods that call member methods. See the Scientific Toolworks website for a sample [UML Sequence diagrams](#) and information about how events are displayed.
- **Package:** Shows what entities are declared in a given package (body or spec).
- **Task:** Shows the parameters, invocations, and what entities/entry points are declared in a task. Also shows what the task Withs.
- **Rename Declaration:** Shows what entities are renamed in the entity.


---

## Structure View Examples


Structure views quickly show structure and relations.

*Understand* structure views are designed to present essential information about an entity in a small and concise manner. The structure diagram is derived from the graphs presented by Booch and Buhr in their respective books “Software Engineering with Ada” and “System Design in Ada.” Where needed, symbols and annotations have been extended or altered to represent new kinds of information available from *Understand*.


- **Declaration:** Shows the structure of the entity. For example, shows the parameters, return type, and callbys of a function.




- **Parent Declaration:** Similar to a Declaration graph but shows what the entity calls.




- **UML Class Diagram:** Shows the classes defined in the project or a file and related classes. Right-click to show or hide class details, related classes, and solo classes.




- **Declaration File:** Shows the entities declared in the file. Also shows files included by the file and classes imported by the file.



- **Declaration Type:** Shows information about a type declaration.




- **Class Declaration:** Shows the members defining the class and the parent class from which it is derived.





- **Control Flow:** Shows a flow chart of the function or similar entity type. As the following figure shows, a number of specialized options can be set when you right-click on this type of graph.



## Graphical Notation

The following symbols are used by *Understand* to represent various language constructs. The symbols vary somewhat depending upon the type of view.


- Entities such as functions and other program units are shown in rectangles.
- Files and system-level entities are usually shown in parallelograms.
- Classes and types are shown in flattened hexagons.
- Macros are usually shown in flattened octagons.
- Objects such as variables are usually shown in slightly rounded rectangles.
- Unknown or unresolved entities are drawn with dashed outlines or in gray.
- Other shapes are language-specific.

In Control Flow views, standard flow chart symbols, such as diamonds for decision points, are used.

## Controlling Graphical View Layout

This section applies to non-cluster graphs. For information about using cluster graphs, see Controlling Cluster Graph Layout on page 275.

The two main types of graphical view windows, **Hierarchy** and **Structure**, have a variety of configuration options. You can set them by right-clicking on the background of a graphical view and choosing the option you want to modify from the context menu.




These options control the layout and drawing of the graphic views. The following subsections describe a number of these options. The list of available options varies depending on the type of view.

Note that the options for Cluster graphs are different, and are described in *Controlling Cluster Graph Layout* on page 275.

### Called by Menu

The **Called by** menu controls whether program units that call the current entity are shown in declaration views.



### Comments Menu

The **Comments** menu controls whether to show any comments associated with an entity. The default is Off.

### Constants Menu

The **Constants** menu controls whether to show constants in Declaration views. The default is On.

### Default Members Menu

The **Default Members** menu controls whether declaration views show default members of the class.

### Dependent Of Menu

The **Dependent Of** menu controls whether files a C file is dependent on are drawn in the C File Declaration view. The default is On.

### Dependent Menu

If **Dependents** is on (the default) then files dependent on the current C file are shown in a File Declaration view.

### Depth

Sets the number of levels to which a dependency graph is expanded. The default is 1 level.

### Duplicate Subtrees Menu

The **Duplicate Subtrees** menu controls whether multiple occurrences of the same subtree are shown in hierarchy views. The options are to Hide or Show such subtrees. The default is to show duplicate subtrees. In some applications, hiding duplicate subtrees can dramatically simplify hierarchy views. Duplicate subtrees are not shown if a view has over 1000 nodes.

**Expand Recursive Notes**

Controls whether recursive nodes in a dependency graph are shown as separate items. The default is to show the expansion for recursive nodes. If you turn this setting off, a particular item is expanded only at the highest level where it occurs in the architecture, class, or package hierarchy. Unexpanded nodes that are recursive at lower levels display “(recursive)” as part of their text.

**Expand Repeated Notes**

Controls whether repeated nodes in a dependency graph are shown as separate items. The default is to show the expansion for repeated nodes. If you turn this setting off, a particular item is expanded only at the highest level where it occurs in the architecture, class, or package hierarchy. Unexpanded nodes that are repeated at lower levels display “(repeated)” as part of their text.

**Extended By Menu**

The **Extended By** menu controls whether declaration views show classes by which the selected class is extended.

**Extends Menu**

The **Extends** menu controls whether declaration views show classes that the selected class extends.

**External Functions Menu**

If **External Functions** is on then functions defined in a header file or in a file included by a header file are shown in the Declaration View for a header file. The default is On.

**Filename Menu**

The **Filename** menu controls how filenames are displayed in views. It is available for both declaration and hierarchy views.

- **None:** Filenames are not shown in the view.
- **Shortname:** Where filenames are relevant, only the name of the file is shown in square brackets.
- **Fullname:** Where filenames are relevant, the full file path and filename are shown in square brackets.

**Function Pointer Menu**

The **Function Pointer** menu controls whether function pointers are displayed as invocations in the Call and CallBy trees.

**Globals Menu**

The **Globals** menu controls whether to show globals in Declaration views. The default is On.

**Implements Menu**

The **Implements** menu controls whether declaration views show entities that the selected entity implements.


**Implemented By Menu**

The **Implemented By** menu controls whether declaration views show entities by which the selected entity is implemented.


**Imports Menu**

The **Imports** menu controls whether declaration views show entities imported by the current entity.

View with Imports set to On



View with Imports set to Off

**Included By Menu**

If **IncludeBy** is on (default) then files that include the Header File being drawn in a Header File Declaration view are shown.

**Includes Menu**

The **Includes** menu controls if include files are drawn on file declaration diagrams (C file, Header file). The default is On.

**Inherits Menu**

The **Inherits** menu controls whether declaration views show entities that the selected entity inherits.

**Inherited By Menu**

The **Inherited By** menu controls whether declaration views show entities inherited by the selected entity.


**Intrinsic Functions Menu**

The **Intrinsic** menu controls whether intrinsic functions (for example, cos and sin) are displayed or hidden.


**Invocations Menu**

The **Invocations** menu controls whether procedures and functions called by the current procedure or function are shown in Declaration views.

View shows Invocations




View without Invocations shown




## Layout Menu

The **Layout** menu controls the layout algorithm for a hierarchical chart. It is available only in hierarchy views (calls, callby, etc.). The options are:


- **Crossing:** A left-to-right view, minimizing space used but sacrificing some readability by permitting lines between entities to cross.



- **Horizontal Non-Crossing:** A left-to-right layout, using more space in some situations but enhancing readability by having no crossing lines.





- **Vertical Non-Crossing:** A top-to-bottom layout similar to Horizontal Non-Crossing.



**Level Menu**

The **Level** menu controls the number of levels to be traversed when laying out a hierarchical view. The default value is “All Levels”. Values of 1 to 5 may be set. It is available only in hierarchy views.

**All Levels****One Level****Locals Menu**

The **Locals** menu controls whether local items are shown in Declaration views. The default is On.

**Members Menu**

The **Members** menu controls whether members and operators are shown in the Type Tree and Type Derived From views. The choices are to show None, Components, Operators, or Operators and Components.

**Name Menu**

The **Name** menu controls whether or not fullnames are used in views. It is available for both declaration and hierarchy views.

A fullname includes its parent compilation units. For example:

- Text\_lo.Put is the fully specified name.
- Put is the Short Name

Longer versus shorter names can alter the layout of pictures substantially.

**Objects Menu**


The **Objects** menu controls whether to show objects in Declaration views. The default is On.

**Operators Menu**


The **Operators** menu controls whether entities that are operators are shown in the Callby, Declaration, Declaration Tree, and Invocation views.

**Parameters Menu**

The **Parameters** menu controls whether parameters are shown in hierarchical views. This menu is available for any hierarchical graphical view (invocation and callby). The default is Off; turning this On can make hierarchical pictures much bigger.



Parameters Off (the default)



Parameters On

**Private Members Menu**

The **Private Members** menu controls whether declaration views show private members of the entity.

**Protected Members Menu**

The **Protected Members** menu controls whether declaration views show protected members of the entity.

**Public Members Menu**

The **Public Members** menu controls whether declaration views show public members of the entity.

**Renames Menu**

The **Renames** menu controls whether declarations that are renames are shown in Declaration views. The default is to show rename declarations.

**Routines Menu**

The **Routines** menu controls whether to show routines (procedures, functions, etc.) in Declaration views. The default is On.

**Scale Menu**

The **Scale** menu allows you to choose the size of the text used. It is available for both declaration and hierarchy views. All picture sizes and layouts vary with text point size. The currently selected size is indicated by a check mark.

Other point sizes can be added by customizing configuration files found in the *Understand* installation directory. Contact [support@scitools.com](mailto:support@scitools.com) for information on how to do this.



**Sort Menu**

The **Sort** menu lets you specify whether entity names in tree views should be sorted alphabetically. If this option is off (the default), entities are sorted in the order they are encountered in the project.

**Spacing Menu**

The **Spacing** menu lets you choose to change the space between boxes. You can choose compact, small, normal, wide, or extra wide.

**Sql Menu**

The **Sql** menu lets you specify whether SQL entities should be shown in graphical views. This option is on by default.


**Static Menu**

The **Static** menu controls if static functions are drawn in function, C File and Header File declaration views. Static functions are those declared using the “static” keyword. They are visible only within the file they are declared in. If enabled static functions are drawn with the edge of their box inside the edge of the outer declaration box for their enclosing unit (C file). The default is On.

**Text Menu**

The **Text** menu sets the way entity names are trimmed or altered to accommodate the layout of graphics. It is available for both declaration and hierarchy views. Names may be truncated to a certain length or wrapped at a certain length.

- **No Truncation:** Uses the name as defined in the source code. This is the default.
- **Truncate Short:** Cuts off names at 10 characters.
- **Truncate Medium:** Cuts off names at 20 characters.
- **Truncate Long:** Cuts off names at 30 characters.
- **No Wrap:** Never wraps text to the next line.
- **Wrap Short:** Wraps the name between 8 and 10 characters. Location in that range depends on if a natural wrapping character is found. Natural wrapping characters are . \_ - and :
- **Wrap Medium:** Similar to *Wrap Short* except wrapping range is 15-20 characters.
- **Wrap Long:** Similar to *Wrap Short* except wrapping range is 20-30 characters.

**Types Menu**

The **Types** menu controls whether to show types in Program Declaration views. The default is On.

### Typetext Menu

The **Typetext** menu tells declaration views (Function Declaration, C File Declaration, Header File Declaration) to include types on the view. The default is On.

### Unknown Menu


The **Unknown** menu controls whether entities should be shown if they are used in the source, but are never declared or defined.

### Unresolved Menu

The **Unresolved** menu controls whether entities should be shown if they have been declared but not defined. For example, an entity may be declared in a header file, but never defined in the source. This option is available on hierarchy and structure views.

Unresolved include files are those that are included but not found along a declared include path (either a compiler or project include path).

Unresolved entities are drawn as normal but with a dashed border:



### Usedby Menu

The **Usedby** menu tells Declaration views whether to show items that use this item.

### Uses Menu

The **Uses** menu tells Uses views whether to show only items that are used directly, or to also show items that are used by nested subprograms. The default is to show both.

### Variables Menu

The **Variables** menu controls whether to show globals in Declaration views. The default is On.

### Withs Menu

The **Withs** menu controls on Declaration views of compilation units (packages, tasks, separate procedures, etc...) if Withs are drawn. The default is On.


### With Bys Menu

Controls if **With Bys** (who Withs a given compilation unit) are shown on Declaration views. The default is On.


## Controlling Cluster Graph Layout

Cluster graphs are a special type of hierarchy view. They provide a more interactive view of call relationships than other hierarchy views. The **Cluster Call**, **Cluster Callby**, **Cluster Call Butterfly**, **Cluster Call Internal**, and **Cluster Control Flow** variants are available, and can be accessed from the function, class, file, or architecture level. The Architecture Dependency graphs (page 198) behave similarly to the cluster graphs. There are some special menus for Cluster Control Flow graphs that are described on page 277.

For example, if you open a Cluster Call Butterfly graph for a file, you see a graph similar to the following:



If you then double-click on some of the file boxes, you can see call relationships for functions within the files that you expand.




Hold down Ctrl+Shift and use the mouse wheel to zoom in and out in cluster graphs.

Hold down Alt and click on an entity to go to the code that defines that entity.

The toolbar for cluster graphs is the same as for other graphs, and the context menu for entities in the graph is similar to elsewhere.

The context menu when you right-click on the background of a cluster graph offers the following options:

- **Aggregate Nodes by:** Choose an architecture you want to organize entity nodes.
- **Edges Shown:** Choose which relationships to the originally selected entity you want shown. “Forward” is call relationships. “Reverse” is callby relationships. “Butterfly” is both call and callby relationships.
- **Entity Name Format as:** Choose whether you want to display short or long names for entities.
- **Highlight Paths to Selected Node(s):** You can highlight all paths between the node for which you opened a Cluster Call or Cluster Callby graph and some other node. To do this, select a node (not the original node), right-click on the background of the graph (not on an entity or within a box), and choose this option. You can hold down the Ctrl key to select multiple entities for path highlighting



- **Include Virtual Edges:** Set this item to On if you want to show override and overriddenby edges. Such edges are light blue by default. If you want to change this color, choose **Tools > Options**. In the **Graphs** category, make sure **Use custom style on cluster call graphs** is checked. Then create a new Edges style called "overrides,overriddenby".
- **Show Edge Labels:** Set this item to On if you want the number of occurrences of this relation to be shown in the graph. For bi-directional call relationships, the two numbers in the label show calls in each direction.
- **Show Edges Between Children By Default:** Set this item to On if you want to show inter-child edges initially for nodes that are expanded. Note that changing this setting only affects nodes that are using the defaults; You may need to click the **Restore Defaults** icon to affect the entire graph.
- **Show Legend:** Set this item to On if you want to show a graph legend in the upper left. The legend identifies the shapes and arrow styles used in the graph.
- **Show Node Children By Default:** Set this item to On if you want nodes to be opened by default when you open a cluster graph. For example, all functions within files will be shown by default if this option is enabled when you open the Cluster Callby graph for a file.

The context menu when you right-click on a node in a cluster graph offers commands similar to those you see when right-clicking on an entity name elsewhere in *Understand*.

The context menu when you right-click on an edge (arrow) in a cluster graph provides a list of the references that constitute the edge. Choose an item from the list to visit the source code for this relationship. You can limit the length of this list as described for the **Tools > Options** dialog on page 120.


The Graph Customizer to the right of a cluster graph offers the same settings as those described for Architecture Dependency Graphs in *Graph Customizer Toolbar* on page 199.

You can customize the display colors, shapes, and arrows used in cluster graphs in the Graphs category of the **Tools > Options** dialog (page 120).

## Cluster Control Flow Graphs

Cluster Control Flow graphs show the execution flow of an entity such as a function. These graphs have the same toolbar as other graphs and a Graph Customizer toolbar (page 199) similar to those in other Cluster Graphs and Architecture Dependency Graphs. However, the context menu when you right-click includes the following options:

- **Allow Call Expansion:** Allows called functions to be expanded by clicking. If this option is on, expandable calls are shown as a 3D box. Off by default.
- **Cluster:** Uses a box to enclose statements in a group such as the “if” or “else” branch of a conditional statement. On by default.
- **Collapse:** Combines statements into a single box if there are no decision points between them. On by default.
- **Debug:** Shows details about the information about each item in the flow. In order, the detail information is: nodeID, nodeKind, startLine, startCol, endLine, endCol, endNode, commaSeparatedListOfChildren. Off by default.




- **Expand Macros:** Enabling this option shows macros expanded if you have enabled the **Save macro expansion text** option in the C++ project configuration (page 71). Off by default.
- **Filter:** Hides implicit actions, such as “endif”. On by default.
- **Layout:** Choose whether to arrange the graph vertically or horizontally. The default is Vertical.
- **Show Comments:** Shows comments associated with statements in the graph. On by default.
- **Show Finally-Block Flows:** Shows edges representing exceptional exits from a try-catch block in languages like Java and C#. On by default.
- **Show Entity Name:** Shows the name of the entity in the Start box at the beginning. Off by default. You can also choose to show entity names with parameters included.
- **Show Labels:** Shows text for edges (for example, yes/no) and start block. On by default.
- **Show Legend:** Set this item to On if you want to show a graph legend in the upper left. The legend identifies the shapes and arrow styles used in the graph.
- **Show Source Code:** Shows source code in boxes. On by default.
- **Styled Labels:** Highlights keywords, comments, and strings in source code shown in the graph. The formats defined in the Editor > Styles category of the Understand Options dialog (page 117) are used. On by default.

---

## Saving Graphical Views

*Understand* offers a number of ways to export your graphical views and use them in other ways. The toolbar for each graphical view provides the following icons for copying and printing graphs.




In addition to printing, you can save graphical views as JPEG, PNG, SVG files (page 279), Visio XML files (page 279), and DOT files (page 280). The first three formats are common graphics formats.


For cluster graphs, you can save and load customized graph settings as described for Dependency graphs (page 199).

## Saving Views to Files

To save a graphical view in one of the following formats, use the **Export** drop-down the graphical view toolbar to choose the **Export to Image File** option. Or choose **File > Export to Image File** from the menus. In the Export dialog, choose a location, filename, and file type for the view.



- **JPEG** files are compressed bitmaps. They can be viewed with most web browsers, document editors, and graphics programs. This format is “lossy”; some data is lost in the compression.
- **PNG** files store compressed bitmaps similar to GIF files. They can be viewed with most web browsers, document editors, and graphics programs. They use a non-patented compression method.
- **SVG** files are Scalable Vector Graphics files. This file type uses XML to describe a 2-dimensional vector-based image.

You can also copy a graphical view to the clipboard and paste it as a bitmap into the image program or word processor of your choice. To do this, click the  **Copy** icon on the graphical view toolbar or choose **Edit > Copy Image to Clipboard** from the menus. Then, paste the image into another program.


Note that if the graph would result in an image larger than 200 MB, the graph will be resized to a smaller size.

## Saving Views as Visio Files

Microsoft Visio is a vector-based graphics program used for drawing flowcharts and similar graphics. That is, it deals with shapes and objects rather than pixels. Visio XML is an Extended Markup Language that is supported by Visio and a number of other graphics applications.

You do not need to have Visio installed in order to save a graphical view as a Visio XML file.


To save a Visio XML file, use the **Export** drop-down the graphical view toolbar to choose the **Export to Image File** option. In the Export dialog, choose a location and filename for the view. The file extension for Visio XML files is \*.vdx.



### **Saving Views as DOT Files**

DOT is a language used to describe graphs in plain text. This format can be imported and edited by a number of external tools. You can export many (but not all) types of graphs produced by *Understand* to a DOT file.

To save a DOT file, use the **Export** drop-down the graphical view toolbar to choose the **Export to .Dot** option. In the Export dialog, choose a location and filename for the view. The file extension is \*.dot.



If this option is not shown in the **Export** drop-down, the current graph cannot be exported to the DOT format.

---

## **Importing Graphical View Plugins**

Plugins are special Perl Scripts that can be imported to provide customized graphical views. Several graphical view plugins are available on the [Support website](#).

To install a graphical view plugin:

- 1 Download a plugin to one of the following locations:
  - <InstallDir>\conf\plugin\User  
(for example, C:\Program Files\SciTools\conf\plugin\User)
  - <appdata>\SciTools\plugin  
(for example, C:\Users\USERID\AppData\Roaming\SciTools\plugin)
- 2 Restart *Understand*.
- 3 Select an entity you want to graph, and choose **Graphs > Project Graphs > Plugin Name** to open the graph.

Be aware that generating graphs for large projects can often be very resource intensive, and in some cases the system can be non-responsive for a long period of time while the graphs are generated.

Plugins are also available to generate reports (page 231). One of the available reports is the [Batch Graph Generator](#), which automates the generation of various graphical views.




## Printing Graphical Views


*Understand* has these printing modes:

- **Source File** printing sends a text file to the printer using 66 lines of source per page. See *Printing Source Views* on page 192.
- **Graphical view printing** provides options for how to fit the image to a page. See *Graphical View Printing* on page 281.

### Graphical View Printing

To print the current graphical view, you can click  **Print** icon on the graphical view toolbar. Or, choose **File > Print Entity Graph** from the menus.

When you choose to print a graphical view, you see the Graphic Print Options dialog.



You can choose to print the image at one of the following sizes:

- **Full size** uses the default scaling of 100%. The dialog shows the number of pages in width x height format. The page size selected with Page Setup is used.
- **Fit to a single page** scales the image to fit on the selected page size.
- **Scale by** lets you choose the sizing percentage and shows the number of pages that will be printed.

Check the **Save to PDF** file box if you want the image saved to an Adobe Acrobat file rather than being sent to a printer. This PDF printing feature does not require that you have third-party PDF generating software installed on your computer.

Check the **Print page number identifiers** box if you want page numbers on each page in the upper-left and lower-right corners. The page numbers are in “(column, row)” format. For example, (1,3) indicates that the page goes in the leftmost (first) column of the third row when you piece the pages together. The page number is not printed if the view fits on a single page.

(1,3)

Check the **Print page numbers in margin area** to place the page numbers outside the borders of the graph. If this box is unchecked, page number indicators are printed just inside the border markers.

Check the **Print page border markers** box to place corner markers in each corner of each page.

Click the **Printer** button to open the standard Print dialog for your operating system. When you click **Print** or **OK** in that dialog, you return to the Graphic Print Options dialog.

Click the **Page Setup** button to open a Page Setup dialog, which allows you to choose the paper size, paper source (if applicable), page orientation, and margin width. Click **OK** to return to the Graphic Print Options dialog.

Click the **OK** button in the Graphic Print Options dialog to send the graphical view to the printer (or a PDF file).

**Note:** The **File > Page Setup** menu option applies only to printing source code and other text files. The **Page Setup** button on the Graphic Print Options dialog saves its settings separately.

# Using CodeCheck for Standards Verification


This chapter explains how to use CodeCheck to find places where your code does not conform standards you select.

This chapter contains the following sections:

Section	Page
About CodeCheck	284
Running a CodeCheck	285
Viewing CodeCheck Results	288
Using CodeCheck Configurations	295
Writing CodeCheck Scripts	296

## About CodeCheck

*Understand* provides a tool called CodeCheck to make sure your code conforms to published coding standards or your own custom standards. These checks can be used to verify naming guidelines, metric requirements, published best practices, or any other rules or conventions that are important for your team.



Checks are available to make sure your code conforms to several published coding standards. You can select a subset of individual checks to test for from these standards. For example, you can check to make sure that all if...elseif constructs contain a final else clause.

For all languages, checks are provided to let you verify that various entity types conform to your naming conventions and to confirm that your code meets metric requirements you set for complexity, function length, and nesting depth.

If you want to perform custom checks, you can create your own checks using Perl. For example, you can create a check to find lines longer than 80 characters or filenames that begin with a number.


CodeCheck validation suites are available from the [SciTools website](#).

## Running a CodeCheck


To open the CodeCheck tool, choose **CodeCheck > Open CodeCheck** from the menus.

### Files Tab



In the **Files** tab, choose whether to check all files in the project, only files that have changed since you last ran CodeCheck, only files that have changed since a specific date, or the files you select.



If no files have been changed since a date you select or since the last time you ran CodeCheck, you will see a message that says no files meet the criteria.

You can click the **Search**  icon to open a search bar below the list of files that lets you search by filename.

If your project contains many files, you can more easily select specific files by following these steps:


- 1 Export the entire list of currently selected files (with full file paths) to a text file by clicking the  **Export Selected Files** icon.
- 2 Edit the file with a text editor. Delete the lines for files you do not want to inspect, and save the file as plain text.
- 3 Click the  **Import File List** icon and import the file you edited. This will select only the files listed in the file.

Once you have finished selecting the files to inspect, click **Next** to move to the Checks tab.

## Checks Tab

In the **Checks** tab, the default configuration is **New** and all the **SciTools' Recommended Checks** that apply to your programming languages are selected.

If you want to use a different CodeCheck configuration or save the configuration you are creating for later use, see *Using CodeCheck Configurations* on page 295.



Choose the checks you want to perform. The following types of options are provided:

- **SciTools' Recommended Checks:** This category lists recommended checks for your source code languages. These are standards violations that we feel are most serious.
- **Published Standards:** Collections of checks are provided to see if your code conforms to the following standards or recommendations:
  - Effective C++ (3rd Edition) Scott Meyers
  - Hersteller Initiative Software (HIS) Metrics
  - MISRA-C 2012
  - MISRA-C 2004
  - MISRA-C++ 2008
- **Custom Checks:** Any custom checks you have installed are listed in the Checks tab. See *Writing CodeCheck Scripts* on page 296.
- **Clang Static Analyzer:** Checks provided by the Clang Static Analyzer tool. These checks are most accurate when used with the strict C parser.
- **Language Specific Checks:** All checks that *Understand* can perform are listed here. They are organized first by programming language, then by category, and finally by check. Currently, most checks apply to C/C++ code, but some checks are available for other languages. You can confirm that your naming conventions are met for various entity types in most supported languages. You should check specific languages under the All Checks node; if you check the **All Checks** box, some of the checks may conflict with others, and errors are likely to occur.

- **Metrics Checks:** You can perform checks based on the values of complexity, function length, and nesting depth metrics, which are described in the list at [scitools.com/support/metrics\\_list/](http://scitools.com/support/metrics_list/).
- **General Checks:** General checks for preferences such as lines longer than a maximum number of characters or the presence of various control characters.

Press Ctrl+F or click the **Search**  icon to be able to search for a check.

When you select a check, information about that check is shown in the **Detailed Description** area. You can copy the text in the description if you want to paste it into a report or email message. You can hide the description by clicking the arrowhead above the description.

For a number of checks, options are shown below the description. For example, if you select a metrics check, you can set a value that needs to be met. If you select a Naming Conventions check, you can specify a minimum and maximum length for acceptable names, any required prefix or suffix, and the types of characters and capitalization rules that names need to follow. The description provides details about the options.

Options:

☒ Test All Const names

Minimum Length:

Maximum Length:

Required Prefix:

Required Suffix:

Character Set:

Capitalization:

Consecutive Capitals:

Check the **Use Verbose Logging** box if you want the Result Log to include a separate line for each violation found. Otherwise, the Result Log will present a summary and you can use the other tabs to sort through and view specific violations.

Once you have finished selecting the checks to perform, click **Inspect**.



You can choose **CodeCheck > Analyze Changes and Re-Run Previous Checks** from the menu bar to run the **Analyze Changed Files** command and then the **Re-Run Previous Checks** command.

If you have made changes to the checks being performed, you are asked if you want to save the configuration before performing the analysis. Click **Yes** if you might want to perform this same set of checks in the future. If you were using the “New” configuration, you are then prompted to type a name for this configuration. Type a name and click **OK**. See *Using CodeCheck Configurations* on page 295 for more information.


If more than 300,000 violations are detected, you are asked if you want to continue the check.

## Exporting and Importing Configurations

If you want to edit the list of checks being performed using a text file, do the following:

- 1 Export the entire list of currently selected checks (with full file paths) to a \*.ini file by clicking the  **Export Configuration to File** icon in the Checks tab.
- 2 Edit the file with a text editor. Delete the lines for checks you do not want to apply, and save the file as plain text.
- 3 Click the  **Import Configuration from File** icon in the Checks tab and import the \*.ini file you edited. This will select only the checks listed in the file.

Exporting the configuration to a file is also required if you want to be able to perform a CodeCheck analysis from the command line.

You can export the list of checks performed to a text file by clicking the **Export Selected Checks to Text File**  icon. This file includes a description of each test.

## Viewing CodeCheck Results


After you perform a CodeCheck analysis, you can view the results in the Results Log (page 288), Results by File tab (page 289), Results by Check tab (page 290), Result Locator tab (page 291), and Result Treemap (page 292). You can also print or export the results (page 293).

You can hide results by ignoring particular checks and violations (page 293).

## Using the Result Log



When you run a CodeCheck analysis, you automatically see the **Result Log** tab, which provides a summary of the results.

The Result Log includes the number of files checked, how many checks were performed, and the number of violations found.





If you checked the **Use Verbose Logging** box in the **Checks** tab, the Result Log also includes a separate line for each violation found.




You can copy the log to your clipboard for pasting by clicking the  **Copy** icon. To save the log to a file, click the  **Export** icon.








## Using the Results by File Tab

Choose the **Results by File** tab to list the problems in each file of your project.

The table lists the number of violations in each file and full file paths. Uncheck the **Show Violation Counts** box above the table to hide the number of violations. Uncheck the **Flatten Files List** box to organize files in a folder hierarchy that you can expand as needed.

Click the arrow next to a filename to expand the list of violations found in that file. The line for a violation shows the problem, the name of the entity, the line number on which the problem occurs, the number of the column (0 indexed) where the problem began, and a short description of the check performed.



Results by File:   ☒ Show Violation ☒ Show Ignored ☒ Flatten Files List   

Results	Entity	Line	Column	Check
4 Number of Results: 4				
1  C:\Program Files\SciTools\sample\fastgrep\egrep.c				
1  C:\Program Files\SciTools\sample\fastgrep\regerror.c				
2  C:\Program Files\SciTools\sample\fastgrep\timer.c				
  Violation: regerror defined but not called.	regerror	89	0	Unused Functions
  Unused Local Variable	dummy	54	13	Unused Local Var
52	<code>int ncomp, nexec, nsub;</code>			
53	<code>struct try one;</code>			
54	<code>char dummy[512];</code>			
55				
56	<code>if (argc &lt; 4) {</code>			

Click the arrow next to a violation to see the 5 lines of code surrounding the problem. You can double-click on the code to open the source file.

When you select a violation, the description of that check and any exceptions to the check are shown below the table. You can select text in this area and press Ctrl+C to copy it to your clipboard for pasting into other applications.


Click **Expand All** or **Collapse All** to show or hide all violation details.

Click the  **Print** icon to print the list or the  **Export** icon to send the full list of violations to HTML files in a directory you select, your clipboard, or a text file.


Check the **Show Ignored Violations** box if you want to see the full list of violations by overriding any ignored checks and violations. See page 293 for details.

## Using the Results by Check Tab

The **Results by Check** tab is similar to the Results by File tab (page 289). However, all violations of a particular type are listed together. The organization under each violation is either a list of files if the **Flatten Files List** box is checked or a folder hierarchy if the **Flatten Files List** box is unchecked.



If many violations of a particular type are detected, you might want to look at the individual checks in the **Checks** tab to see if you can set options to control the sensitivity of the checks. For example, for the “Magic Numbers” check, you can specify that bitfields can be set to fixed values and you can allow exceptions for values like 0 and 1. Another example is that for the “Functions Too Long” check, you can set the length that is considered too long and choose to ignore comment lines and blank lines.

In the Results by Check tab, the  **Export** icon allows you to either a detailed or summary report to HTML files in a directory you select, your clipboard, or a text file. The summary report is similar to the following:

```
CodeCheck Summary
Number of Results: 704
  SciTools' Recommended Checks704
    ""Commented Out"" Code7
    Definitions in Header Files28
    Functions Too Long5
    Goto Statements28
    Magic Numbers300
    Overly Complex Functions10
    Unused Functions36
    Unused Local Variables50
    Variables should be commented15
```

## Using the Result Locator

The **Result Locator** tab lets you search for violations using pattern matching and sorting on the file, violation name, line number, and column number.

Result Locator: ☐ Show Ignored Violations

File	Violation	Line	Column
reg	value	≥	≥
regex.h	Fixed Value(1) used inco...	15	21
regsub.c	Fixed Value(0) used inco...	73	35
regsub.c	Fixed Value(0) used inco...	60	29
regsub.c	Fixed Value(1) used inco...	64	30
regsub.c	Fixed Value(0) used inco...	65	25

**Rationale**  
Using fixed values(Magic Number) in code makes it difficult to know why the engineer chose that number in choosing that number and makes it hard to adapt and extend the program. Magic numbers should be replaced with name constants to make them more usable.

**Exceptions**

```

13      char *regmust;          /* Internal use only. */
14      int regmlen;            /* Internal use only. */
15      char program[1];        /* Unwarranted chumminess w
16 } regexp;
```

You can type values to match filenames and violations. Right-click a column header or click the small drop-down icon to see the context menu for that column. You can choose for the filter to be case sensitive or not. You can also choose for the filter pattern matching syntax to use fixed strings (the default), wildcards, or regular expressions. To search for field values that do not contain a particular string, type ! (exclamation mark) and then the filter.


For details about using the locator fields, see *Filtering the List* on page 159.

Five lines of code surrounding the violation are shown at the bottom of the window. You can double-click this code to open the file.

## Using the Result Treemap



Treemaps show metrics graphically by varying the size of node blocks and the color gradient. Each node block represents a code file. Different metrics can be tied to size and color to help you visualize aspects of the code.

CodeCheck lets you create treemaps that show the total number or density of check violations and the number of types of violations. For example, in this treemap larger block sizes indicate more violations in that file and darker blue indicates more types of violations in that file. So, while `egrep.c` has the most violations, `timer.c` has more types of violations. Notice that the text above the treemap indicates the settings used.




If you double-click on a file block, you see the Results by File listing with the list of violations for that file expanded.

By default, the treemap is organized using the file structure of the project as architecture nodes. Within the treemap, you can double-click on an architecture node (shown as a gray border around a set of colored blocks) to display only the contents of that node. You can also zoom in by right-clicking on a node and choosing **Drill down** from the context menu.

After drilling down in the architecture, you can use the   icons to **Pop up one level** or **Pop up all levels** the treemap. You can also right-click to use the **Pop up one level** and **Pop up all levels** commands in the context menu.

Click the **Options** button to modify which metrics are assigned to size and color:



For information about using these fields, see *Using the Metrics Treemap* on page 242.

## Printing and Exporting Results

In the Result Log tab, you can copy the log to your clipboard for pasting by clicking the **Copy** icon. To save the log to a text file, click the **Export** icon.

In the Results by File, Results by Check, and Result Locator tabs, you can click the **Print** icon to print the currently displayed results. You can click the **Export** icon to export the detailed results to an HTML directory, your clipboard, or a text file.

In the Result Treemap tab, you can click the **Print** icon to print the currently displayed treemap diagram. Click the **Export to Image File** icon to save the treemap to a PNG or JPG file.


See page 281 for details about the Print Options dialog.


## Ignoring Checks and Violations

A number of options let you ignore some CodeCheck violations in all or part of your project. For example, you might want to ignore violations in third-party code used by your project.

If many violations are detected, you might want to look at the individual checks in the **Checks** tab to see if you can set options to control the sensitivity of the checks. For example, for the “Magic Numbers” check, you can specify that bitfields can be set to fixed values and you can allow exceptions for values like 0 and 1.

Wherever you see a violation listed in the results, you can right-click and choose to ignore this violation instance, ignore violations of this check for the specified entity, or ignore violations of this check for the current file or a selected directory level within the

project. You can also choose to ignore all violations in a specific file or directory. If you select a directory, violations in all of its subdirectories will be ignored. You can also click the  Ignore icon above the results to access the Ignores menu.




When you choose to ignore a violation, you are first asked to confirm that it is OK to ignore multiple violations of the same type in the same file. Next, you are asked if you want to add a note about this ignored violation. If you click **Yes**, you can type text regarding this violation and why it is ignored.


If you are not sure whether you want to ignore the violation, choose **Go to Check** for more information about the check that was violated.


Violations that you choose to ignore are not listed in the Results by File or Result Locator tabs unless you check the **Show Ignored Violations** box. They are highlighted with a pink background if they are shown. The violation totals in the Results by File tab *do not* include the ignored violations. Totals in the Results by Check tab *do* include ignored violations.


If you choose to ignore any violations, you can use the **Ignores List** tab to find and sort ignored violations. Only one item is listed if you have ignored multiple violations of the same type in a file or directory. You can search this list as you would the Result Locator list. See *Filtering the List* on page 159 for details.


The toolbar above the Ignore List lets you perform the following actions:

 Add or edit the text note for the selected violation to be ignored. You can also open the Ignored Violation Note dialog from the right-click menu or by pressing the + key.

 Remove the text note for the selected ignored violation. You can also remove the note from the right-click menu or by pressing the - key.

 Stop ignoring this violation. You can also open the Ignored Violation Note dialog from the right-click menu or by pressing the Delete key.

 Export a list of the violations to ignore to a text file. You are prompted to specify the location and filename. The exported file is a comma-separated values file that lists the full file path, the internal ID string used to identify the entity, the type of violation that occurred, and the check being performed that identified this violation.

 Import a list of violations to ignore from a text file. The file must be in the same format exported from the CodeCheck tool.

In addition, you can add comments to your code to cause *Understand* to ignore specific violations. For details, see the [CodeCheck Comment Keywords](#) support page.


## Using CodeCheck Configurations

If you have a set of checks you want to use, you can save that list of checks as a “configuration”. Such configurations are stored outside of the project, so that you can use the same CodeCheck configuration with multiple projects.


Note that the set of files to be inspected is not saved as part of a CodeCheck configuration. The most recent set of files used is the default.

To save a configuration, follow these steps:

- 1 In the Checks tab, select the boxes for all the checks you want performed when this configuration is used.
- 2 Click the **Save** icon next to the Configuration drop-down list.



- 3 Type a name for your configuration in the dialog, and click **OK**.



You can use a configuration you have saved by selecting it in the **Configuration** drop-down list at the top of the Checks tab.

Another way to run a configuration is from the **CodeCheck > Saved Configurations** menu item, which you can use even if the CodeCheck window is not open.

The **CodeCheck > Re-Run Previous Checks** command runs the most recently selected CodeChecks. If you have made changes to any files, you will be asked if you want to re-analyze the changed files before running CodeCheck.

The **CodeCheck > Analyze Changes and Re-Run Previous Checks** command runs the **Analyze Changed Files** command automatically and then runs the **Re-Run Previous Checks** command.

## Writing CodeCheck Scripts

CodeCheck scripts are special Perl scripts that let you provide custom checks for verifying your team's coding standards. They can be used to verify naming guidelines, metric requirements, published best practices, or any other rules or conventions that are important for your team.

You can develop these scripts using the Understand Perl API along with a set of special functions designed to interact with the Understand CodeCheck interface.

CodeCheck script files have a \*.upl extension.

To begin writing your own check, follow these steps:

- 1 Choose **CodeCheck > Implement Your Corporate Standard** from the menus.
- 2 In the web page this command takes you to, save the codecheck\_template.upl to a file with the same name on your computer.
- 3 Edit this template file (with a text editor).
- 4 Modify the name, description, and detailed\_description to match what you plan for this check to do. For example, you could use the following descriptions for a check to make sure lines do not exceed a specified length:

```
# Required - Return the short name of the check
```

```
sub name { return "Characters per line";}
```

```
# Required - Return the short description of the check
```

```
sub description { return "Lines should not exceed a set number of characters";}
```

```
# Required - Return the long description of the check
```

```
sub detailed_description { return "For readability, lines should be limited to a certain number of characters. The default is 80 characters per line.";}
```

- 5 Modify the test\_language subroutine to test for the desired languages. For example, the following test makes the check apply to C++, Java, and Python. You can look at other scripts in the \conf\plugin\SciTools\Codecheck subdirectory of your installation for more examples.

```
sub test_language {  
    my $language = shift;  
    return $language =~ /C++|Java|Python/;  
    return 1;  
}
```

- 6 If your check should be run on a per-entity basis, return 1 for the test\_entity subroutine. If the check should be run only once per file, return 0 for the test\_entity subroutine. For example:

```
sub test_entity { return 1;}
```

- 7 If your check should be run only once per project, return 1 for the test\_global subroutine. Otherwise, return 0 for the test\_global subroutine. For example:

```
sub test_global { return 0;}
```



- 8 If your check requires the user to set options, modify the `define_options` subroutine. For example:

```
sub define_options{
    my $check = shift;
    $check->option->integer("charPerLine", "Max Characters per line", 80);
}
```

Modify the check subroutine to include the check and to signal a CodeCheck violation reporting the problem. The following example reports filenames that do not begin with a letter character:

```
if ($file->name =~ /^[^a-zA-Z]/){
    $check->violation(0,$file,-1,-1,"File name does not begin with a letter");
}
```

The following example reports lines longer than the specified maximum number:

```
sub check {
    my $check = shift;
    my $file = shift;
    return unless $file->kind->check("file");

    my $maxChar = $check->option->lookup("charPerLine");
    my $lineNum = 1;
    foreach my $line (split('\n',$file->contents)){
        my $length = length($line);
        if( $length > $maxChar){
            $check->violation($file,$file,$lineNum,-1,
                "$length characters on line(Max: $maxChar)");
        }
        $lineNum++;
    }
}
```

- 9 Verify that your Perl syntax is correct. The easiest way to do this is to open a command line and run the Perl application that ships with Understand: `upperl -c mysample.upl`.

To learn more, you may want to read about [Understand's Perl API](#). Browsing the CodeCheck scripts that are shipped with Understand can also be very beneficial. If you have questions about CodeCheck scripts, the [SciTools website](#) can be a great place to ask them.

## Installing Custom Scripts

You can install a script in *Understand* by dragging and dropping the script file into the *Understand* window. You will be asked if you want to install the plugin. Click **Install**.

When you install a custom check, you will see a message that identifies the directory where the check was installed. For example,  
 C:\Users\YourName\AppData\Roaming\SciTools\plugin\Codecheck. You can install future checks by copying files directly to this directory.

## Chapter 12

# Comparing Source Code


This chapter explains the source-code comparison features provided by *Understand*.

This chapter contains the following sections:

Section	Page
Comparing Files and Folders	299
Comparing Entities	302
Comparing Text	303
Exploring Differences	304

## Comparing Files and Folders


*Understand* provides a tool for comparing files and folders. To open this tool, choose **Tools > Compare > Compare Files/Folders** from the menus.



In this dialog, select a file or folder for the left and right comparison. Both sides should be similar files or similar folders. Click the file button to browse for a file; click the folder button to browse for a directory.

Subdirectories of the directories you choose are also compared.


A quick way to compare two files in a project is to right-click on the name of one file (for example, in the Project Browser) and choose **Compare > Set as Left File/Directory Comparison** from the context menu, right-click another file and choose **Compare > Set as Right File/Directory Comparison**, and then choose **Compare > Compare Files/Directories**.




When begin the comparison, the status bar at the bottom of the *Understand* window shows what is being compared.

The code comparison section of the results window is described on page 304. If you are comparing folders, there is an additional top section that lets you see the folder-level and file-level differences and select individual files whose contents you want to compare.

The comparison uses the following file and folder icons.




By default, all files and folders are listed. You can use the **Show** drop-down to choose whether to restrict the list to showing only:





- **Different:** Show files and folders that either exist in only one version or are different in the two versions.
- **Left Only:** Show files that are contained in the left version only. All different folders are shown because some may contain files that are only in the left version.
- **Right Only:** Show files that are contained in the right version only. All different folders are shown because some may contain files that are only in the right version.
- **Same:** Show files that are the same in both versions. All folders are shown because some that are different may contain files that are the same.



The **Filter** field lets you type characters you want to match in the directory path or filename. For example, “sim” matches any folders or files with “sim” in their names. All files within folder that match the **Filter** (and the **Show** drop-down setting) are shown. Filtering occurs as you type. If you want to use regular expressions, enable that option by clicking the **Options** button to see that menu. Wildcards are not recognized.

You can change the colors use for folder and file names that differ in the two versions by choosing a color from the **Options** menu and selecting a new color in the color picker.




You can highlight all items that exist in only the left or right version. To do this, first right-click on the file list and choose **Expand All**. Then click the **Select** button and choose either **Orphans left** or **Orphans right**. You will see a warning that some items may have been skipped; this applies only if you did not use **Expand All**.





You can copy folders and files from one side to the other. The copied items overwrite any items with the same names. To copy, first select the items you want to copy. (To copy a folder and its contents, select the folder *and* all the folders and files it contains.) Then click the **Copy/Merge** button and choose either **to the right** or **to the left**. This opens the Copy Files dialog, which lists the files or folders to be copied. If the list is correct, click **OK**. Click the  icon to undo your last copy/merge change. Click the  icon to redo you last undo.

The code comparison section of the results window is described on page 304. By default, the file on the left is in read-only mode, and the file on the right is in read-write mode. You can change the mode for either file by clicking in the file and then clicking “RO” or “RW” in the status bar to toggle the mode.




If you modify one or more files that are listed in the comparison area and then switch to the comparison of another file, you are asked whether you want to save and recompare the files.

You can save changes you make to files in the file and folder comparison. If you have modified a file on the right, you can click the  **Save** icon to save that file to its existing location. You can use the  **Save As** icon on either the left or right to save a file to a different location. After you save changes, you can click **Rescan** to compare the modified files and folders.

## Comparing Entities


You can compare two entities by choosing **Tools > Compare > Compare Entities** from the menus. You see the Comparison window.



A quick way to compare the code that defines two entities in a project is to right-click on the name of one entity and choose **Compare > Set as Left Entity Comparison** from the context menu, right-click another files and choose **Compare > Set as Right Entity Comparison**, and then choose **Compare > Compare Entities**.



The middle and lower portions are similar to file comparisons (page 304).


At the top of the comparison is an entity filter (page 131). Select a type of entity in the **Show** drop-down. Then use the lists to select two entities you want to compare. The **Filter** fields let you type a string you want to match anywhere in the entity name. Filtering occurs as you type. Wildcards and regular expressions are not recognized.

If you are comparing an entity other than a file (such as a function), merging changes and saving files in the comparison is not permitted. You can still use the  button to create a patch file in “unified format”.


If you are comparing a file, you can merge changes and use the  **Save** and  **Save As** buttons for the version of the file on the right.

## Comparing Text


You can compare text that you paste into a window by choosing **Tools > Compare > Compare Arbitrary Text** from the menus. You see a window like this:



Paste the before and after text you want to compare into the left and right sides. Then, click **OK** to see the comparison.



The text comparison is similar to the comparison between two entities. You can merge and unmerge differences, but cannot save files.


Click the  fold icon to hide or view the patch file syntax and/or the list of differences.

A quick way to compare text is to highlight some text, right-click, and choose **Compare > Set as Left Text Comparison** from the context menu. Then highlight other text, right-click, and choose **Compare > Set as Right Text Comparison**. Finally, choose **Compare > Compare Text Selections**.

## Exploring Differences

When you compare items, you see a comparison window. Depending on what you are comparing, you see several of the following areas to help you navigate the differences:


- **Changed Entities:** This area lets you select files or entities to compare. It differs depending on what you are comparing.
- **Code Comparison:** This area allows you to examine the differences in the code. See page 304.
- **Patch File:** The patch area shows the patch file syntax to convert from the left version to the right version. See page 307.
- **Difference List:** This list allows you to select individual differences between two versions. See page 307.

The small  fold icon between the areas allows you to close and reopen areas to make more space for the other areas. If you point your mouse to the right or left of either fold icon, you see the pane resize mouse cursor, which allows you to resize the areas as needed.



### Code Comparison

The Code Comparison area shows individual differences between versions of an entity. The display is similar to that of common differencing tools.




The left side shows the code from the first item you are comparing; the right side shows the code from the second item. The entity path is shown just above the code.



Scrolling of the two versions is synchronized horizontally and vertically. The scrollbar shows the location and size of changed sections of code using the comparison colors.

For certain languages that *Understand* understands—such as C code—you can click the + and - signs in the code to expand and compress code constructs such as if and else statements, functions, extended comments, and so on.

The currently selected difference is highlighted in blue (or bluish purple on some screens) by default. Other differences are highlighted in pink by default.



```

1431 {
1432     return busy == NOTBUSY;
1433 }
1434
1435 void QTrackBackApp::showTotal()
1436 {
1437     if(!mPopup->isVisible()) && mB
1438     #ifdef WIN32

```

You can use the small fold icon (like the one shown here) between the two code versions to hide the left version of the code temporarily. Or, click the right arrow next to a code change to do the same thing.


You can edit the source code if you like in the right version of the files. You cannot save code directly to a file. Instead, you can use the [Save Patch](#) button to save a patch file or you can copy and paste code with merged differences and edits into another application.

You can select text and copy it to the clipboard. To select text, use the mouse or your keyboard. To select all, press Ctrl+A or right-click and choose **Select All**. To copy text to the clipboard, press Ctrl+C or right-click and choose **Copy**.


As always, right-click on any entity name or other text in the code to see lots of item-specific options in the context menu.

The status bar at the bottom of the window shows your line location in the source code where you last clicked.


The toolbar at the top of the Code Comparison area contains the following controls:


 **Options button:** Use the Options drop-down to set the following options:


- **Options->Case Insensitive:** By default, changing the case of a letter is not treated as a difference. For example, if you change “a” to “A”, the Difference List shows “No Differences” if that was the only change.
- **Options->Skip Whitespace:** By default, changing the number of spaces or tabs is not treated as a difference. The Difference List shows “No Differences” if only whitespace was changed. You can change this behavior by toggling this option off.
- **Options->Skip Blank Lines:** By default, a different number of blank lines is treated as a difference. You can change this behavior by toggling this option on.
- **Options->Files are Unicode:** By default, differences are reported only for ASCII files. If *Understand* says “File is Binary”, use this command to turn on Unicode file handling.
- **Options->Hide Common Lines:** By default, all lines in both files are shown. If you check this option, most lines that are the same in both versions are hidden in the left (older) version.
- **Options->Patch lines of context:** The patch area shows the patch file syntax to convert from the left version to the right version. By default, 3 matching lines are shown around a change to provide context. You can choose this option and change the number of lines in the Patch Lines of Context dialog.
- **Color choices:** These options let you change the highlighting in the code comparisons. The Different Word color is an overlay that is combined with the other highlight colors as appropriate.
- **Options->Double Click Merging:** A shortcut for merging is to double-click on a difference in the code. This works only if you enable it here.



The Case Insensitive, Skip Whitespace, and Files are Unicode options are not available if you have made a change to a file.

 **Refresh button:** You can use the Refresh button to update the Difference List at the bottom of the Change Results. This list may become out-of-date if you merge differences or edit the file directly.

 **Save Patch button:** You can use the Save Patch button to create a patch file in “unified format” (or unidiff). This patch file can be used with the Unix patch tool and other similar programs.



Click the **Prev** and **Next** buttons above the Code Comparison area to jump to another difference between the entities.



You can merge differences into the version of an entity shown on the right. You cannot save code directly to a file. Instead, you can save a patch file or copy and paste code with merged differences and edits into another application. To merge differences, follow these steps:

- 1 Select a difference in the code or by selecting a line in the Difference List area.
- 2 Click the **Merge Selected** button. This copies the older (left) version of this difference to the current (right) version of the code. (If you change your mind, click **Unmerge Selected**.)
- 3 Click the **Prev** or **Next** button to move to another difference and repeat the previous step.


In the Difference List, merged differences are shown in blue italics. In the code, differences you have merged are highlighted in green. (The currently selected difference is still highlighted in blue/purple, even if it has been merged.)

A shortcut for merging is to double-click on a difference in the code if you have enabled **Double Click Merging** in the Options drop-down.



If you know you want to merge all of the differences, click **Merge All**. If you want to undo all merges you have made, click **Unmerge All**.

## Patch File

This area shows the differences in patch file format. Such patch files can be used with the Unix patch tool and other similar programs. You can hide this area by clicking the small  fold icon above the area.


The **Patch lines of context** command in the **Options** button menu lets you adjust the number of unchanged lines shown around a difference.

## Difference List

The Difference List area shows a list of the differences in the code shown in the Code Comparison area.

1: Changed 1 line on the left to 2 lines on the right	line 114: s->stream.transparent = (voidpf)0;
2: Deleted 1 line on the right	line 117: s->file = NULL;
3: Changed 1 line on the left to 1 line on the right	line 123: s->crc = crc64(0L, Z_NULL, 0);

In the Difference List, merged differences are shown in blue italics.

You can hide the Difference List portion of the results by clicking the small  fold icon below the area. This makes more space for the Code Comparison area.

# Running Tools and External Commands

This chapter will show you how to configure and use source code editors and other external tools from within *Understand*.

This chapter contains the following sections:

Section	Page
Configuring Tools	309
Adding Tools to the Context Menus	316
Adding Tools to the Tools Menu	317
Adding Tools to the Toolbar	318
Importing and Exporting Tool Commands	319
Running External Commands	320
Using the Eclipse Plugin	321

## Configuring Tools

Select **Tools > User Tools > Configure** from the menus to open the Tool Configurations dialog, where you can configure external tools such as source code editors for use within *Understand*. External tools configured for use will be available for context-sensitive launching. The Tool Configurations dialog provides a number of categories that determine how they are launched.

First, use the **User Tools** category of the Tool Configurations dialog to define a command and parameters as follows:

- 1 Click **New**.
- 2 In the **Menu Text** field, type the name you want to appear in *Understand* menus for this tool. You can use variables in the Menu Text. For example, you can use `$CurEntity` to put the name of the currently selected entity in the tool name. See *Variables* on page 311 for a full list of variables.

- 3 If the tool you use is on your executable search path, simply type its name in the **Command** field. If not, use the **Browse** button to specify the full path to its executable.
- 4 In the **Parameters** field, specify parameters that need to be passed on the tool's command line. See *Variables* on page 311 for a full list of variables. Variables beginning with \$Cur are current position variables that apply only from a Source Editor window. Variables beginning with \$Decl are declaration variables that apply only when an entity with a declaration is selected. Variables beginning with \$Prompt display a dialog to ask the user for some information. You can use the < sign to separate parameters that need to come from stdin. For example, if the password for a tool needs to come from stdin, use: < \$PromptForPassword

Quote marks in the parameter list are handled the same as quotes in the Microsoft Windows command prompt window and a Linux terminal. This is a change from previous behavior. For example:

Parameter Text	Old Result	New Result
"some text\"	2 args = { \ , some text\ }	2 args = { "some, text" }
-arg="a b"	2 args = { -arg= , a b }	1 arg = { -arg=a b }
-arg=\$Prompt...	2 args = { -arg=, result }	1 arg = { -arg=result }

- 5 In the **Initial Directory** field, specify the directory in which the tool should start running. You can use variables such as \$CurProjectDir in this field.
- 6 In the **Icon file** field, type or browse for a small graphic file to act as the icon for this command. You can choose a BMP, GIF, PBM, PGM, PNG, PPM, XBM, or XPM file.
- 7 Choose the **Input** you want to use for the command. The options are **None** (default), **Selected Text**, and **Entire Document**. The Selected Text and Entire Document options are intended to be used when running a tool from the Source Editor.
- 8 Choose what you want done with the **Output** from the command. Options are:
  - **Discard** the output. This is the default.
  - **Capture** it in a Command Window, which is an area that appears by default near the Information Browser. The command window is reused by default if you run another tool or re-run the same tool. You can force results to go to a new window by unchecking the Reuse box on the command results window(s).
  - **Replace Selected Text** in the current Source Editor window.
  - **Replace Entire Document** in the current Source Editor window.
  - **Create a New Document** in a Source Editor window.
  - **Copy to Clipboard** so you can paste the results elsewhere.
- 9 Check the **Understand perl script** box if this is a Perl script that uses the Understand Perl API.
- 10 Check the **Disable for this project** box if you do not want this user tool to be available when the current project is open.
- 11 In the "Analysis Options" area, choose actions you would like to be performed before and/or after this user tool has completed its action and returned. These

actions can include saving all files, re-scanning for new files in project directories, analyzing modified files, and analyzing all files.

- 12** In the “Add to...” area, choose ways you want to access this command in *Understand*. The **Pop Up Menu** checkbox adds the tool to the right-click context menu. The **Main Menu** checkbox adds the tool to the **Tools > User Tools** submenu. The **Toolbar** checkbox adds the tool’s icon to the toolbar.

To edit settings for an existing tool, select it in the list and make changes as needed. Click **OK** to save your changes. If you want to remove a tool, select it and click **Delete**.

For information about using the **Import** button, see *Importing and Exporting Tool Commands* on page 319.


## Variables

Variables beginning with \$Cur are current position variables that apply only from a Source Editor window. Variables beginning with \$Decl are declaration variables that apply only when an entity with a declaration is selected. Variables beginning with \$Prompt display a dialog to ask the user for some information.


You can use the following variables in the Command or the Parameter field.

Variable	Description
\$CppIncludes	Lists all of the include directories specified in the Project Configuration. This may be useful, for example, if the tool you want to run is a compiler or linker.
\$CppMacros	Lists all of the macro definitions specified in the Project Configuration.
\$CurArchitecture	Name of current architecture.
\$CurCol	Column position of cursor position in current file.
\$CurEntity	Full name of selected entity.
\$CurEntityShortName	Short name of selected entity.
\$CurEntityType	Type of selected entity.
\$CurFile	Current file’s full path.
\$CurFileDir	Current file’s directory.
\$CurFileExt	Current file’s extension.
\$CurFileFlatStr	Current file’s full path with all directory separation characters (such as / and \) replaced with an underscore (_).
\$CurFileName	Current file’s name not including extension or full path.
\$CurFileShortName	Current file’s name without full path.
\$CurLine	Line number of cursor position in current file.
\$CurProject	Current fullname location of opened project.
\$CurProjectDir	Directory in which the opened project is located.
\$CurProjectName	Current short filename of opened project (not including extension).
\$CurReportHtml	Current fullname location of opened project’s HTML report.
\$CurReportText	Current fullname location of opened project’s CSV report.


Variable	Description
\$CurScopeEntity	Scope of current entity.
\$CurSelection	Currently selected text in the current window (file windows only).
\$CurWord	The word/text at the current cursor position in the current file window.
\$DeclCol	Column in which the selected entity was declared, defaults to 1.
\$DeclFile	Full path name of the file in which the selected entity was declared.
\$DeclFileShortName	Filename only of the file in which the selected entity was declared.
\$DeclLine	Line in which the selected entity was declared, defaults to 1.
\$DeclScopeEntity	Name of the entity within which the selected entity is declared.
\$NamedRoot	Specify \$NamedRoot "namedrootname", where the namedrootname is the actual name of the named root. Note that the named root must be active. This variable can be used in either the Parameters field or the Initial Directory field.
\$PromptForCheckBox	Prompts user for a true/false value required by the command. A 0 (unchecked) or 1 (checked) is passed to the command in place of this variable. This variable should be followed by a string to be displayed as text next to the checkbox. For example, <code>\$PromptForCheckBox "Show Debug Text"</code> displays the following prompt








\$PromptForCheckBoxGH	Prompts user with a series of checkboxes displayed in a horizontal group. For example, <code>\$PromptForCheckBoxGH "Show=Debug Text;Tool Tips;Line Numbers"</code> displays the following prompt. The label ("Show" in this example) is optional. A semicolon must be used to separate items. The text strings for all checked items (separated by spaces) are passed to the command.
-----------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------





\$PromptForCheckBoxGV	Prompts user with a series of checkboxes displayed in a vertical group. For example, <code>\$PromptForCheckBoxGV "Show=Debug Text;Tool Tips;Line Numbers"</code> displays the following prompt. The text strings for all checked items (separated by spaces) are passed to the command.
-----------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------





Variable	Description
\$PromptForDir	<p>Prompts user to select a directory and passes the full path as a string. For example, <code>\$PromptForDir "Directory Path=\$CurProjectDir"</code> displays the following prompt with the current project directory as the default. The “...” button opens the standard directory selection dialog for your operating system:</p> 
\$PromptForFile	<p>Prompts user to select a file and passes the full path as a string. For example, <code>\$PromptForFile "Filename=\$CurFile"</code> displays the following prompt with the current source file as the default. The “...” button opens the standard file selection dialog for your operating system:</p> 
\$PromptForPassword	<p>Prompts user for a password. Characters typed in this field are obscured.</p> 
\$PromptForRadioBoxGH	<p>Prompts user for a selection from a set of options displayed horizontally. For example, <code>\$PromptForRadioBoxGH "Format=PNG;BMP;GIF;JPEG"</code> displays the following prompt. The text string for the selected item is passed to the command.</p> 
\$PromptForRadioBoxGV	<p>Prompts user for a selection from a set of options displayed vertically. For example, <code>\$PromptForRadioBoxGV "Format=PNG;BMP;GIF;JPEG"</code> displays the following prompt. The text string for the selected item is passed to the command.</p> 

Variable	Description
\$PromptForSelect	<p>Prompts user to select from a drop-down box. For example, <code>\$PromptForSelect "Build Version=Debug;Release;Optimized"</code> displays the following prompt. The text string for the selected item is passed to the command.</p> 
\$PromptForSelectEdit	<p>Prompts user to select from a drop-down box or edit the text in the box. For example, <code>\$PromptForSelectEdit "Build Version=Debug;Release;Optimized"</code> displays the same prompt as the example for <code>\$PromptForSelect</code>, except that you can edit the string in the box.</p>
\$PromptForText	<p>Prompts user for a string required by the command. For example, <code>\$PromptForText "Replace=foo"</code> displays the following prompt and provides a default value. The text provided is passed as a string.</p> 

In general, the multiple-selection `$Prompt` variables accept strings of the format `"label=item1;item2"`. Any number of items may be separated by semicolons. The item strings for all selected items (separated by spaces) are passed to the command.

The label is optional except in the cases of `$PromptForCheckBox`, `$PromptForDir`, `$PromptForFile`, and `$PromptForText`. The default value is optional in the cases of `$PromptForDir`, `$PromptForFile`, and `$PromptForText`.


Prompts are processed after the other types of variables, so you can use other variables in the labels and values. For examples, see `$PromptForDir` and `$PromptForFile` in the previous table.

In addition, operating system environment variables can be used in prompt syntax. For example, `$PromptForSelect "Dir=$PATH"` presents a drop-down list of all the directory paths in your `$PATH` definition.

You can optionally provide the item list in a separate file. In that case, the syntax for most `$Prompt` variables is `label=@fullpath_of_listfile.txt`.

You can combine variables to pass all the parameters needed by a command. All prompts are combined into one dialog. For example if the command is “ls”, you can use the following parameters to create a dialog that lets you select command-line options for the ls command:


```
$PromptForRadioButtonGH "Show option=-A;-a" $PromptForSelect "Sort=-e;-t" $PromptForCheckBoxGV "Additional flags=-d;-D;-l;-L;-s;-l;-u;-x;-c" $PromptForDir "Dir:=$CurProjectDir"
```



## Adding Tools to the Context Menus

Once a command is defined in the Tools tab, the **Context Menu** category in the Tool Configurations dialog lists user tools that are currently in the context menu on the left and commands you can add to that menu on the right. (Context menus are sometimes called contextual, shortcut, right-click, or pop-up menus.)


Choose **Tools > User Tools > Context Menu Order** to open this dialog.



To add a tool to the context menus, select it on the right and click **Add**. To remove a tool from the context menus, select it on the left and click **Remove**.

User tools appear in the context menu in the order they are listed in the left column. Use the **Move Up** and **Move Down** buttons to sort the tools as desired.

This figure shows a context menu for an entity showing the available external tools.




Tools are active or inactive on the context menu based on the context of the parameters provided to the tool. For example, a source editor that specifies \$DeclFile as a parameter is selectable from the context menu for any entity where the declaration is known, but will not be active for an undeclared entity or when no entity is selected.

## Adding Tools to the Tools Menu


Once a command is defined in the Tools tab, the **Top Level Menu** category in the Tool Configurations dialog lists user tools that are currently in the **Tools > User Tools** menu on the left and commands you can add to that menu on the right.

Choose **Tools > User Tools > Top Level Menu Order** to open this dialog.



To add a tool to the menus, select it on the right and click **Add**. To remove it from the menus, select it on the left and click **Remove**.


User tools appear on the **Tools** menu in the order they are listed in the left column. Use the **Move Up** and **Move Down** buttons to sort the tools as desired.



## Adding Tools to the Toolbar

Once a command is defined in the Tools tab, the **Toolbar** category in the Tool Configurations dialog shows user tools currently in the toolbar in the left box and commands you can add to the toolbar in the right box.

Choose **Tools > User Tools > Toolbar Order** to open this dialog.



To add a tool to the toolbar, select it on the right and click **Add**. To remove it from the toolbar, select it on the left and click **Remove**.

To add a vertical separator to the toolbar, select the item in the Toolbar order box that should have a vertical line to the right of it. Click **Insert Separator** to add "-----" to the list.

Icons for the selected tools appear on the toolbar in the order they are listed in the left column. Use the **Move Up** and **Move Down** buttons to sort the icons as desired.

To change the icon for a particular tool, use the **Icon file** field in the User Tools category.

For example, in the following figure, the first icon is provided by *Understand* to open the Tool Configurations dialog. The second icon is the default icon for a user tool if none is specified.



In this toolbar, two icons have been added for user tools. A separator has been added between them.




**Note:** You can control which icons are visible in the main toolbar by right-clicking on the background of the toolbar and checking or unchecking items for the various toolbar sections.

## Importing and Exporting Tool Commands

You can import and export tool commands from files. This makes it easy to share tool commands with co-workers.

- 1 To export commands, choose **Tools > User Tools > Export User Tools** from the menus. You will see the following dialog.




- 2 Check the boxes next to commands you want to share.
- 3 Click **Export to file**.
- 4 Choose a location and filename for an initialization file (\*.ini) that contains the selected user tool information.
- 5 Click **Save**.

To import commands, choose the User Tools category in the Tool Configurations dialog and click the **Import** button. Browse for an initialization file created by another *Understand* user and click **Open**. In the Import User Tools dialog, check the boxes next to the tool commands you want to be available in your copy of *Understand*.

## Running External Commands

The **Tools > Run Command** menu item permits any external command to be run directly from *Understand*. Common commands to invoke are compilers, configuration management tools, and Perl programs written using Understand's API.

The **Run a Command** dialog looks like this:




To run a command, follow these steps:

- 1 Type a **Command** or click ... and browse for a file to run. A number of Perl programs are provided in the *Understand* installation.
- 2 Type any command-line **Parameters** required by the command. Click the right arrow if you want to select one of the special variables. These are listed on page 311.
- 3 Click ... and browse for the directory that should act as the **Working Directory**.
- 4 If you want the output sent to a window in *Understand*, leave the **Capture Output** box checked.
- 5 If you are running a Perl script, check the **STI Perl script** box if this is a script provided by Scientific Toolworks.
- 6 Click **Run**. The output is shown in a Command Window in *Understand* if you checked the **Capture Output** box. Otherwise, the command runs in the background



and output is shown in the **Running Commands** box. You can select a command from this list and click **Stop** to halt the command.




The font used in the Command Window is determined by settings in the User Interface category of the Understand Options dialog, which you can open by choosing **Tools > Options** from the menus. See page 101.

On Unix systems, output to both stdout and stderr are captured.

## Using the Eclipse Plugin

If you use the Eclipse IDE for code development, you can access a number of *Understand* features within the Eclipse IDE by installing the Understand plugin for Eclipse. These features include the Entity Filter, Information Browser, Metrics, Treemaps, Butterfly graphs and Control Flow graphs. See <http://scitools.com/eclipse/> for details on installing this plugin.



This chapter shows how to use *Understand* from the command line. Command line processing can be used in a batch file for automatic re-building and report generation of projects.

This chapter describes the “und” command line, which allows you to analyze sources and create *Understand* databases from the command line. In addition, it allows you to generate metrics and reports.

**Note:** The “und” commands were standardized in build 571, and the tool should now be much easier to use. Because of the extensive changes, this new version is not backwards compatible with older versions of und. The old und executable has been renamed “undlegacy”. If you have legacy scripts, you should rename the binary run by these scripts in order for them to continue to work.

Most examples in this chapter refer to C/C++ files. However, you can use “und” with any supported language.

This chapter contains the following sections:

Section	Page
Using the und Command Line	323
Using the understand Command Line	331
Using Buildspy to Build Understand Projects	332

## Using the und Command Line

The command-line tool for creating and building *Understand* databases is *und*.

The *Understand* installer can optionally place the appropriate bin directory in your operating system's PATH definition to simplify running the "und" command line. For example the Windows PATH definition might include the C:\Program Files\SciTools\bin\pc-win64 path.

Und can be run in the following modes:

- **Interactive mode:** You enter this mode if you simply type `und` on the command line with no command or text file. While in the interactive shell, settings such as open database are remembered from command to command. This is a good mode to use to test a sequence of commands you want to use in a batch file. You can optionally specify the database to open on the command line to run the interactive shell.

```
c:\Program Files\SciTools\bin\pc-win64>und
Welcome to und. Type "help" for a list of commands. "quit" to quit
und> _
```

- **Batch mode:** Once you identify a sequence of commands you want to run more than once, you can store them in a text file that you can run in batch mode with the `und process` command. The text file should contain one command per line. Omit the "und" from each command within a batch file. You can use `#` to begin comments. For example use either of the following commands to run the sequence in the `This.txt` file:

```
und process This.txt
und process This.txt MyDatabase.udb
```

The `This.txt` file might contain commands similar to these:

```
# My command file
c:\projects\MyDatabase.udb
settings -C++MacrosAdd VERSION="Option_2"
analyze      # update database
report       # generate reports
metrics      # generate metrics
```

- **Line mode:** You can specify a single command or set of commands on a single command line. You must specify the database to be used on each command line, because it is not remembered from line to line. Commands are run in the order they appear on the command line. The help and list commands cannot be combined with other commands. For example, you could run either of the following commands to create a database, add files, analyze all, and then exit:

```
und create -db c:\myDb.udb -languages c++ add @myFiles.txt analyze -all
und create -languages c++ add @myFiles.txt analyze -all c:\myDb.udb
```

This is the equivalent of running the following set of commands in interactive mode:

```
create -languages c++ c:\myDb.udb
add @myFiles.txt
analyze -all
```

Alternately, you could run a sequence of line mode commands like the following:

```
und create -languages c++ c:\myDb.udb
und add @myFiles.txt c:\myDb.udb
und analyze -all c:\myDb.udb
```

In general, und commands are case-insensitive.

Und returns a value of 1 if an error occurred.

Und supports the following options that can be added to any command:

Option	Discussion
-db	Specify the database to use
-ini <i>filename</i>	Specify a configuration file to use
-quiet	Print only errors. Do not print warnings or informational messages
-verbose	Print extra informational details.

Und accepts a number of separate commands. A different set of options is supported for each of these commands, and separate help is available for each. For example, for help on the add command, type:

```
und help add
```

The commands supported by und are as follows:

Option	Discussion	See
add	Adds files, directories, and roots	page 325
analyze	Analyzes the project files	page 328
codecheck	Runs CodeCheck	page 329
create	Creates an empty database	page 325
export	Exports settings, dependencies, or architectures	page 327
help	Gives help information for a command	page 325
import	Imports project settings and architectures	page 327
list	Lists information about the project	page 326
metrics	Generates project metrics	page 329
process	Runs all the commands in a text file in batch mode	page 323
purge	Purges the database	page 328
remove	Removes files, directories, roots, and architectures	page 326
report	Generates project reports	page 328
settings	Sets project settings and overrides	page 327
upperl	Runs Perl scripts	page 329
version	Shows the current software version	page 325

Refer to the sections that follow for details on the commands supported by und.

**Getting Help on Und**

Since we do frequent builds of *Understand*, it is likely that this manual may not describe all the options of the “und” command line. We recommend that you check the command-line help. For example, to get details on the report command, type:

```
und help report
```

You can see the version of *Understand* for the und command tool by using the following command:

```
und version
```

**Creating a New Project**

Use the `und create` command to create a new database (project). Specify the name of the database either with the `-db` option or as the last parameter. Any settings allowed with the `settings` command (see page 327) can also be used with `create`. For example:

```
und create -db newDB.udb -languages c++ c#
und create -open_files_as_read_only on newDB.udb
```

For more information, use the following command:

```
und help create
```

**Adding Files to a Project**

If you have a small number of source files then it may be easiest to just supply their names to the analyzer using the wildcard abilities of your operating system shell. For example:

```
und -db myproject.udb add \usr\myproject
und -db myproject.udb add file1.cpp file2.cpp
und -db myproject.udb add *.cpp
```

In some cases, there may be too many file locations to use the `-add` technique. A common command line limitation is 255 characters. A directory with hundreds or thousands of files may easily exceed this limit. If wildcards (for example, `proj*.c`) do not match the correct list of files or you want more fine-grained/repeatable control over what files are processed, you should create a “listfile”. This file must have a format of one filename per line:

```
c:\myfiles\myproject\myproject.c
c:\myfiles\myproject\myproject.h
c:\myfiles\myproject\support.c
c:\myfiles\myproject\io.c
c:\myfiles\myproject\io.h
h:\shared\allprojects\file2.c
h:\options\file3.c
h:\options\file4.c
h:\options\file5.c
. . .
```

You can then add all of these files as follows:

```
und -db myproject.udb add @myfiles.lis
```

Note that there is no limit on the number of files listed in the list file.

Another way to add files to a project is to add the files and file override settings already configured in one database to another database. The command format for this is:

```
und add source_project.udb destination_project.udb
```

You can also use the `add` command to add named roots and Visual Studio projects. Options are available to set the watch behavior, subdirectory adding, the exclude list, file filtering, and languages.

**Exclude strings** are processed relative to the top-level directory passed to the `add` command, and are applied to all files in all subdirectories. The exclude strings are internally processed as follows:

- 1 Separate the exclude string into the list of wild cards based on spaces, commas, and semicolons.
- 2 For each separate exclude string, replace forward and back slashes with the pattern `[\\]`, which matches either slash.
- 3 Prepend the absolute path of the top-level directory to the wild card, ensuring that `[\\]` separates the path from the initial wild card.
- 4 Compare the wild card to both the file short name and file long name for every file below that top-level directory. The comparison is done with QRegExp wild card matching.

Named roots definitions on the “und” command line have the highest precedence. The next precedence is named roots defined as environment variables at the operating system level, and finally by named roots defined in the *Understand* project configuration. See page 109.

For more information, use the following command:

```
und help add
```

---

### Removing Items from a Project

Use the `und remove` command to remove files, directories, Visual Studio files, named roots, and architectures from a project.

Unless there is a name conflict, the type of item to be removed is automatically detected by `und`. If there is a conflict, the command defaults to deleting the directory with the specified name. You can use the `-file`, `-vs`, `-root`, and `-arch` options to override this default.

For example:

```
und remove someFile.cpp myProject.udb
und remove C:\SomeDirectory myProject.udb
und -db myProject.udb remove vs1.vcproj vs2.vcproj
und remove -file main.c myProject.udb
```

For more information, use the following command:

```
und help remove
```

---

### Getting Information about a Project

Use the `und list` command to list file, setting, architecture, or named root settings in a project. For example:

```
und list -tree files myProject.udb
und list settings myProject.udb
und list arches myProject.udb
und list roots myProject.udb
```

There are a number of options for listing settings for the project. You can list all settings, language-specific settings, report settings, metric settings, include directories, macro definitions, and more. For example:

```
und list -override f1.cpp f2.java settings myDB.udb
und list -override @listfile.txt myDB.udb
und list -metrics -reports settings myDB.udb
und list -all settings myDB.udb
und list -lang C++ -macros -includes settings myDB.udb
und list -lang fortran settings myDB.udb
```

For more information, use the following command:

```
und help list
```

---

## Modifying Project Settings

Use the `und settings` command to modify the settings in a project. You can find the names for each setting by using the following command:

```
und list -all settings myProject.udb
```

For example, the following command adds the specified directory to the list of C/C++ include directories in the project:

```
und settings -c++includesadd c:\myincludes myProject.udb
```

In general, setting names are the same as the field name in *Understand*, but with spaces omitted. For example:

```
und settings -ReportDisplayCreationDate on myProject.udb
und settings -ReportFileNameDisplayMode full myProject.udb
und settings -ReportReports "Data Dictionary" "File Contents" myProject.udb
und settings -C++MacrosAdd MYLONG="Long Text" myProject.udb
und settings -ReportNumberOfPages 250 myProject.udb
```

For more information, use the following command:

```
und help settings
```

---

## Importing into a Project

Use the `und import` command to import project settings or architectures from an XML file. In general, you might use this command when creating a new database to import setting that you have exported from another database.

For example:

```
und import settings.xml myNewProject.udb
und import -arch myArch.xml myProject.udb
```

For more information, use the following command:

```
und help import
```

---

## Exporting from a Project

Use the `und export` command to export project settings, architectures, or a list of dependencies to an XML file.

For example, this command exports project settings to an XML file that you can use with the `und import` command:

```
und export toHere.xml myProject.udb
```

This command exports architectures to an XML file that you can use with the `und import` command:

```
und export -arch "Calendar" toHere.xml myProject.udb
```

These commands export file, architecture, and class dependencies to a CSV, matrix, or Cytoscape file. Several options are available to control the output of dependencies.

```
und export -dependencies file csv output.csv myProject.udb
und export -dependencies class matrix output.csv myProject.udb
und export -dependencies arch myArch csv output.csv myProject.udb
und export -dependencies -col refs -format short file csv out.csv myDB.udb
```

For more information, use the following command:

```
und help export
```

---

### Analyzing a Project

Use the `und analyze` command to run (or rerun) the project analysis.

When you analyze a project, you have several options. You may re-analyze all files with the `-all` option (the default), only files that have changed with the `-changed` option, or a list of files with the `-files` option. For example:

```
und analyze myProject.udb
und analyze -files @someFile.txt
und -db myProject.udb analyze -rescan -changed
und analyze -files file1.cpp file2.cpp myProject.udb
und -db myProject.udb -rescanwithoutanalyze
```

You can scan project directories for new files with the `-rescan` option. (This is done automatically when you analyze all.)

If you are doing your first analysis after creating a new project, it doesn't matter which option you choose as it will analyze all files regardless. However, if you are performing this function on a regular basis, you may prefer to do an incremental analysis where only the modified files and any other files dependent on those files are re-analyzed.

Use the `und purge` command to remove all analyzed data from the Understand database, leaving only the project definition. This significantly shrinks the `udb` file size, which you may want to do before sharing the file or backing it up. Running the `analyze` command will repopulate the project. For example:

```
und purge myProject.udb
```

For more information, use the following command:

```
und help analyze
```

---

### Generating Reports

Use the `und report` command to generate reports for the project. This command uses the current report settings, which can be viewed by using the `und list` command (see page 326), and changed using the `settings` command (see page 327). For example:

```
und list -reports settings myProject.udb
und report myProject.udb
```



---

**Generating Metrics**

Use the `und metrics` command to generate metrics reports for the project. You can generate project metrics (the default), architecture metrics, and the HTML metrics report. For example:

```
und metrics myProject.udb
und metrics -arch myArch myProject.udb
und metrics -html arch1 arch2 c:\temp myProject.udb
```

This command uses the current metrics settings, which can be viewed by using the `und list` command (see page 326), and changed using the settings command (see page 327). For example:

```
und list -metrics settings myProject.udb
```

For more information, use the following command:

```
und help metrics
```

---

**Using CodeCheck**

Use the `und codecheck` command to run the CodeCheck tool on the project and print the log to the screen. You need to provide the name of a CodeCheck configuration file and an output directory for the reports. For example:

```
und codecheck config.ini C:\temp myProject.udb
```

You can create a CodeCheck configuration file as described in *Using CodeCheck Configurations* on page 295.

Options are provided to specify which files to run the CodeCheck configuration on, whether to show ignored violations, whether to flatten the directory tree, and whether to generate HTML output in addition to the default CSV output. You can also export the list of checks performed and the ignored violations to a file without running the CodeCheck configuration.

For example, the following command runs the specified configuration file on the files listed in `filelist.txt` and generates both the HTML and CSV versions of the results:

```
und codecheck -html -files filelist.txt config.ini C:\temp myProject.udb
```

For more information, use the following command:

```
und help codecheck
```

---

**Running Perl Scripts**

Use the `und uperl` command to run Perl scripts from the command line. For example, the following command would run the `myScript.pl` file with the `arg1` space and `arg2` arguments passed to Perl:

```
und uperl myScript.pl -quiet "arg1 space" arg2 myProject.udb
```

For more information, use the following command:

```
und help uperl
```

Note that the `und uperl` command does not support any graphical `uperl` commands, such as `$ent->draw`.

.....

## Creating a List of Files

Where a command accepts a `@lisfile.txt` for an option, the file must contain one item per line. Full or relative paths may be used. Relative paths are relative to the current directory. A `#` sign in the first column of a line in the file indicates a comment. If an item has a definition, for example a macro definition, the macro name and its value must be separated by an `=` sign. For example, `DEBUG=true`.

On Unix here are a couple ways to create such a file:

- Use the `'ls'` command, as in:

```
ls *.c *.h > my_project.txt
```

- Use the `'find'` command to recurse subdirectories, as in:

```
find . -name "*.c *.h" -print > my_project.txt
```

In a Windows command shell:

- Use the `dir` command with the `/b` option:

```
dir /b *.c *.h > my_project.txt
```

- Use the `/s` option to recurse subdirectories, as in:

```
dir /b /s *.c *.h > my_project.txt
```

## Using the understand Command Line

The *Understand* GUI is launched by the “understand” executable. Normally, you launch this using the shortcuts provided by the installation. If you like, you can modify this using the following command-line syntax.

```
understand [file_1 ... file_n] [-options]
```

Any filenames listed on the command line are opened along with The *Understand* GUI. For example:

```
understand source.c source.h -db myproject.ldb
```

The available command-line options (also called command-line switches) are as follows:

Option	Discussion
-contextmenu <i>filename</i> [-line # -col # -text #]	Shows the context (right-click) menu for the specified filename at the mouse location. Optionally shows the context menu for the entity located at -line -col (The -text option provides a name hint for the entity).
-cwd <i>path</i>	Set the current working directory to "path". This takes precedence over the last working directory for a project loaded with -db or -lastproject.
-db <i>filename</i>	Open the project specified by the filename.
-diff <i>left_path right_path</i>	Compare the two specified files or folders as with the Tools > Compare command within <i>Understand</i> .
-existing	Detects any running instance of <i>Understand</i> and sends the command line to that instance.
-importusertools <i>importfile.ini</i>	Import user tool definitions from an initialization file.
-lastproject	Open the last project opened by the application.
-lastproject_cwd	Use the directory of the last opened project as the current working directory.
-new	Force the creation of a new instance of <i>Understand</i> . If you use the operating system to open a file with an extension that opens <i>Understand</i> , by default that file opens in any existing instance. You can use this command-line option to force a new instance to open.
-noproject	Ignore all project load requests on startup. (This also clears the "Open Last Project" application setting.)
-no_splashscreen	Use this option to skip the splash screen when <i>Understand</i> starts up. This setting is stored until you change it in the Tools > Options dialog.
-quiet_startup	Use this option to disable all dialogs and splash screens shown during startup.

Option	Discussion
-visit <i>filename</i> [ <i>line# column#</i> ]	Open the file "filename" in an editor window. Optionally position the cursor at the specified line number and column number in the specified file.
-wait	When used with the -existing option, causes this instance of <i>Understand</i> to block while waiting for the other instance to finish the given command.

---

## Using Buildspy to Build Understand Projects

Buildspy is a tool that allows gcc/g++ users to create an *Understand* project during a build. Buildspy gets lists of files, includes, and macros from the compiler. This can save time and improve project accuracy.

To use Buildspy, follow these steps:

- 1 Change the compiler command from `gcc/g++` to `gccwrapper/g++wrapper` in your makefile or build system.
- 2 Either add the `<SciTools>/bin/<platform>/buildspy` directory to your PATH definition or use the full path to the `gccwrapper/g++wrapper` executables in your makefile or build system. On Linux, this might be the `/SciTools/bin/linux32/buildspy` directory. On Windows, this might be the `C:\Program Files\SciTools\bin\pc-win64\buildspy` directory.
- 3 Perform a `make clean` or equivalent command. (This step is optional; Buildspy can be run incrementally to update only the files it is run on.)
- 4 From the directory where your make file is located, run a command similar to the following:

```
buildspy -db path/name.udb -cmd <compile_command>
```

For example:

```
buildspy -db ~/Documents/MyProject.udb -cmd make
```

- 5 When the build has finished running, open the *Understand* project that was created and choose **Project > Analyze All Files**.

The `buildspy` command sends information from `gccwrapper/g++wrapper` to Buildspy, which allows it to build a complete *Understand* project. The wrappers then call the corresponding compiler.

The wrappers work with any compiler that has gcc-like syntax. You can use any of the following methods to specify which compilers `gccwrapper` and `g++wrapper` should call:

- Use Buildspy's `-cc` and/or `-cxx` command line arguments.
- Define the `UND_PBCCCOMPILER` and `UND_PBCXXCOMPILER` environment variables. These environment variables are checked whenever `gccwrapper` and `g++wrapper` are run.
- Edit the configuration file located in `$HOME/.config/SciTools` on Linux systems and `$HOME/Library/Preferences` on Mac.

This chapter lists of commands provided by *Understand*. These lists provide cross references to information about these commands in this manual.

Since new versions of *Understand* are provided frequently, these lists are subject to change.

This chapter contains the following sections:.

Section	Page
File Menu	334
Edit Menu	335
Search Menu	335
View Menu	336
Project Menu	336
Reports Menu	337
Metrics Menu	337
Graphs Menu	338
CodeCheck Menu	338
Annotations Menu	338
Tools Menu	339
Window Menu	339
Help Menu	340

---

## File Menu

The **File** menu in *Understand* contains the following commands:

Command	See
New > Project	page 34
New > File	page 183
Open > Project	page 20
Open > File	page 183
Close <i>project_name</i>	page 20
Save <i>project_name</i> As	page 39
Export to Image File	page 279
Save Configuration	page 295
Save <i>filename</i>	page 172
Save <i>filename</i> As	page 172
Save All	page 172
Page Setup	page 192
Print <i>filename</i>	page 192
Print Entity Graph	page 281
Recent Files	page 102
Recent Files > Clear Menu	page 102
Recent Projects	page 102
Recent Projects > Clear Menu	page 102
Exit	page 52

## Edit Menu

The **Edit** menu in *Understand* contains the following commands:

Command	See
Undo	page 171
Redo	page 171
Cut	page 170
Copy	page 170
Copy Image to Clipboard	page 279
Paste	page 170
Select All	page 170
Comment Selection	page 181
Uncomment Selection	page 181
Change Case	page 181
Toggle Overtyping	page 182
Bookmarks	page 183

## Search Menu

The **Search** menu in *Understand* contains the following commands:

Command	See
Find	page 165
Find Previous	page 165
Find & Replace	page 165
Go to Line	page 169
Go to Matching Brace	page 180
Instant Search	page 150
Find in Files	page 152
Replace in Files	page 155
Show Find in Files Results	page 154
Find Entity	page 157

---

## View Menu

The **View** menu in *Understand* contains the following commands:

Command	See
Toolbars	page 164
Browse Mode	page 170
Zoom	page 168
Fold All	page 180
Soft Wrap	page 182
Hide Inactive Lines	page 180
Analysis Log	page 123
Bookmarks	page 183
Contextual Information	page 166
Dependency Browser	page 142
Entity Filter	page 131
Entity Locator	page 157
Favorites	page 145
Information Browser	page 133
Previewer	page 179
Project Browser	page 139
Scope List	page 169
Window Selector	page 162

---

## Project Menu

The **Project** menu in *Understand* contains the following commands:

Command	See
Configure Project	page 39
Rescan Project Directories	page 47
Analyze Changed Files	page 123
Analyze All Files	page 123
Improve Project Accuracy > Undefined Macros	page 125
Improve Project Accuracy > Missing Includes	page 127
Improve Project Accuracy > More Information	page 124
Project Overview Charts	page 249
Architectures > New Architecture	page 204
Architectures > Browse Architectures	page 195
Architectures > Manage Architectures	page 203



---

## Reports Menu

The **Reports** menu in *Understand* contains the following commands:

Command	See
Configure Reports	page 210
Generate Reports	page 212
View Reports > HTML	page 213
View Reports > Text	page 213
Dependency > Architecture Dependencies	page 244
Dependency > File Dependencies	page 244
Dependency > Class Dependencies	page 244
Project Interactive Reports	page 31

---

## Metrics Menu

The **Metrics** menu in *Understand* contains the following commands:

Command	See
Metrics Summary	page 234
Browse Metrics	page 235
Export Metrics	page 237
Project Metric Charts > Code Volume	page 239
Project Metric Charts > File Volume	page 239
Project Metric Charts > Average Complexity	page 239
Project Metric Charts > Sum Complexity	page 239
Configure Metric Charts	page 239
Metrics Treemap	page 242

---

## Graphs Menu

The **Graphs** menu in *Understand* contains the following commands:

Command	See
Dependency Graphs > By <i>architecture</i>	page 198
Dependency Graphs > Load Saved Dependency Graph	page 199
Project Graphs	page 31
Graphs for <i>selected entity</i>	page 251

---

## CodeCheck Menu

The **CodeCheck** menu in *Understand* contains the following commands:

Command	See
Open CodeCheck	page 285
Re-Run Previous Checks	page 295
Analyze Changes and Re-Run Previous Checks	page 295
Standards	page 295
Saved Configurations	page 295
Implement Your Corporate Standard	page 296

---

## Annotations Menu

The **Annotations** menu in *Understand* contains the following commands:

Command	See
Annotate	page 186
Filter Annotations	page 190
Manage Orphaned Annotations	page 191
Search Annotations	page 189
Annotation Options	page 61
Refresh Annotations	page 61
Display Inline	page 61
Display Hover	page 61
Display Indicator	page 61
Automatic Reload	page 61

## Tools Menu

The **Tools** menu in *Understand* contains the following commands:

Command	See
Run Command	page 320
User Tools > <i>tool_name</i>	page 317
User Tools > Configure	page 309
User Tools > Context Menu Order	page 309
User Tools > Top Level Menu Order	page 317
User Tools > Toolbar Order	page 318
User Tools > Export User Tools	page 319
Editor Macros > Record Macro	page 182
Editor Macros > Replay Macro	page 182
Editor Macros > Save Macro	page 182
Editor Macros > Configure Macros	page 116
Scheduler > Scheduled Activities	page 51
Compare > Compare Files/Folders	page 299
Compare > Compare Entities	page 302
Compare > Compare Arbitrary Text	page 303
Options	page 98

## Window Menu

The **Window** menu in *Understand* contains the following commands:

Command	See
Close <i>current_file</i>	page 172
Close All Document Windows	page 162
Release Window	page 162
Split Vertically	page 162
Split Horizontally	page 162
Unsplit	page 162
Tile	page 162
Cascade	page 162
Predefined Windows Layouts	page 162
< <i>open source file list</i> >	page 162
Windows Navigator	page 162

## Help Menu

The **Help** menu in *Understand* contains the following commands:

Command	See
Help Content	page 15
Key Bindings	page 107
Example Projects	page 15
PERL API Documentation	page 31
Python API Documentation	page 31
Frequently Asked Questions	page 15
Getting Started	page 20
Licensing	
Check for Updates	page 20
About Understand	page 15

# Index

## Symbols

^ in regular expressions 160  
 : in F77 identifiers, Fortran 85  
 ? in regular expressions 160  
 ? wild card 160  
 . in regular expressions 160  
 " prefixing octal constants or string literals, Fortran 85  
 "" surrounding normal includes 74  
 [ - ] in regular expressions 161  
 [ ] in regular expressions 161  
 [ ^ ] in regular expressions 161  
 \* comments field 85  
 \* in regular expressions 160  
 \* wild card 160  
 /\* ... \*/ C-style comments 71, 85  
 \ in regular expressions 161  
 \< in regular expressions 160  
 \> in regular expressions 160  
 # comment in command line file 330  
 + expanding tree in Information Browser 134  
 + in regular expressions 160  
 <> surrounding system includes 74  
 = macro definition in command line 330  
 | in regular expressions 161  
 \$ in regular expressions 160  
 \$ prefixing external tool parameters 310, 311

## A

About Understand option, Help menu 15  
 absolute portability mode 48  
 Activate when Control key is pressed field, Browse  
     Mode Editor options 118  
 actual parameters, relationship to formal parameters,  
     Ada 64  
 Ada  
     configuration for 63  
     macro definitions 65  
     versions supported 14  
 Ada category, Project Configuration dialog 63  
 Add found include files to source list field, C++ Includes  
     73, 81  
 Add found system include files to source list field, C++  
     Includes 73, 81

-addDir option, und command 325  
 -addFiles option, und command 325  
 Adobe Acrobat, saving graphical views to 282  
 Advanced category, Editor options 113  
 Aggregate Nodes by options 276  
 Alerts category, User Interface options 103  
 Allow 85  
 Allow Colons in Names field, Fortran 85  
 Allow C-style comments field, Fortran 85  
 Allow embedded SQL field, Pascal 91  
 Allow function declaration without parentheses field,  
     Fortran 85  
 Allow interactivity during intensive processing field,  
     General options 100  
 Allow Nested Comments field, C++ 71  
 Allow parameter declaration without parentheses field,  
     Fortran 85  
 Allow PreExpansion field 110  
 Allow quote in octal constants field, Fortran 85  
 Alternating row colors field 105  
 Analysis Log option, View menu 124  
 Analysis Log window 124  
     reopening previous analysis Log 163  
     saving to text file 124  
 Analysis Options area 310  
 Analyze All Files option, Project menu 52, 123  
 Analyze category, Understand Options dialog 108  
 Analyze Changed Files option, Project menu 52, 123  
 -analyze option, und command 328  
 -analyzeFiles option, und command 328  
 analyzing projects 123  
     after changing configuration of 40  
     beep on completion of 108  
     on command line 328  
     scheduling 52  
 and operators, including in strict complexity, Ada 64  
 angle brackets (<>) surrounding system includes 74  
 Animate windows/drawers field, User Interface options  
     101  
 Annotations category, Project Configuration dialog 61  
 Annotations menu 338  
 anti-virus software, turning off while generating reports  
     212  
 Apache Lucene syntax 150  
 APIs 31  
 Append the names of externally linkable entities with  
     field

---

- C++ 72
- Fortran 85
- Application font field, General options 99
- Architect Manager 197, 203
- Architecture Browser 29, 195
  - duplicating architectures 197, 204
  - graphical views in 196, 198
  - metrics in 196, 202
  - opening Architect Manager from 197, 203
  - opening Architecture Builder from 197
  - renaming architectures 197
  - right-clicking in 196
  - XML listing in 197
- Architecture Builder 197, 207
- Architecture Graph View 261
- Architecture Wizard 205
- architectures 18, 194
  - auto-architectures 195
  - creating 204
  - duplicating 197, 204
  - editing. *See* Architecture Builder
  - exporting dependency list 244
  - graphical views of 196, 198
  - hierarchies of, exploring 195
  - hierarchies of, graphical view of 261
  - list of 195
  - listing 29
  - managing. *See* Architect Manager
  - metrics about 196, 202
  - metrics graphs about 239
  - navigating 29
  - renaming 197, 204
  - XML listing of 197, 208
- arrows, for Information Browser history 138
- ASCII text. *See* text
- ASP style tags 97
- assembly
  - configuration for 67
  - embedded in C code 72, 76
  - include files, directories for 67
- Assembly category, Project Configuration dialog 67
- asterisk (\*)
  - in regular expressions 160
  - wild card 160
- Auto Category, C++ Includes 74
- auto-architectures 29, 195, 196
- Auto-complete fields, Advanced Editor options 114

- Auto-indent fields, Advanced Editor options 115, 116
- Automatic compool file field, JOVIAL 89
- Average Complexity metrics graph 239

## B

- background processing, interactivity during 100
- backslash (\) in regular expressions 161
- base classes
  - count of 229
  - displaying 257, 259, 264
- Base Classes View 257, 259
- Basic
  - configuration for 68
- beep on analysis completion 108
- bitmaps, saving graphical views as 279
- black text 117
- blank lines
  - in Entity Comparison area 306
- Blank metric 231
- blocks
  - expanding and collapsing 168, 180
  - in Filter Area 24
- blue italic text 117
- blue text 117
- bookmarks
  - creating 183
  - list of 164, 184
  - navigating 183
- Bookmarks option, Edit menu 183
- Bookmarks option, View menu 164, 184
- Boolean searches 151
- braces, matching. *See* brackets
- brackets
  - in regular expressions 161
  - matching 180
- Browse Architectures option, Project menu 195
- Browse Metric Charts option, Metrics menu 243
- Browse Metrics option, Metrics menu 233, 235
- Browse Mode option, View menu 170
- Browse Mode, Source Editor 170
- Browser Area 19
- Build Log 33
- Buildspy 332
- Butterfly View 257, 258
- Butterfly-Dependency graph 198

## C

### C/C++

- API for custom reports 31, 215, 233
- configuration for 71, 78, 83
- include files, auto including 74
- include files, directories for 73, 80
- include files, ignoring 74
- macro definitions 75, 82
- preprocessor directives 75
- strict analysis 78, 83
- versions supported 14

### C#

- configuration for 83
- reference files, importing 83
- versions supported 14

C# category, Project Configuration dialog 83

C++ (Strict) category, Project Configuration dialog 78, 83

C++ category, Project Configuration dialog 71

caching include files, C++ 72

Calendar auto-architecture 29, 195

Called by menu, graphical views 267

Called By View 257, 258

Calls View 257, 258

capitalization, of selected text 181

caret (^) in regular expressions 160

Caret Line field, Editor options 112

Cascading Style Sheet 212

### case

- changing for selected text 181
- of displayed entity names, Ada 64
- of displayed entity names, Fortran 86
- of displayed entity names, JOVIAL 90
- of displayed entity names, Pascal 92
- of displayed entity names, PL/M 93
- of externally linkable entities, Ada 64, 90
- of externally linkable entities, Fortran 85
- of externally linkable entities, Pascal 91
- of identifier names, Fortran 85

Case of externally linkable entities field

Ada 64, 90

Fortran 85

Pascal 91

Case sensitive identifiers field, Fortran 85

case sensitivity

- of Entity Comparison area 306

of Fortran identifiers 85

CBO (Count of Coupled Classes) metric 229

Change Case menu option 181

Change Case option, Edit menu 181

Change Log 33

Changed Entities area, Change Results window 304

character strings, red text for 117

Check for Updates option, Help menu 21

Child Lib Units View 257

children of entity 257

CIS. *See* Contextual Information Sidebar

Class and Interface Cross-Reference report 218

Class Declaration View 261, 264

class diagram 263

.class files 88

Class Inheritance View 257

Class Metrics report 229

Class OO Metrics report 229

Class Paths category, Java 88

### classes

- base classes for 229, 257, 259, 264
- cohesion of 229
- coupled 229
- declaration for 264
- derived 229, 257, 260
- exporting dependency list 245
- extended by other classes 257, 260, 268
- extending other classes 268
- as hexagons, in graphical views 266
- implemented 268
- implemented by 268
- information about 261
- inherited from other classes 257
- listing in Filter Area 24
- metrics about 229
- providing without source code, Java 88
- reports about 218, 222, 229

clipboard 305

copying graphical view to 279

copying text from Source Editor to 170

Close All Document Windows option, Window menu 162, 172

Close option

File menu 21

Window menu 162, 172

Close Selected Window(s) command 164

cluster graphs 275

---

CMake category, Project Configuration dialog 60  
 COBOL  
     configuration for 69  
     copybook files, directories for 70  
 COBOL category, Project Configuration dialog 69  
 Code metric 231  
 Code Volume metrics graph 239  
 CodeCheck 283  
     checks 286  
     configuration 288, 295  
     ignoring violations 293  
     result log 288  
     running 285  
     scripts 296  
 CodeCheck menu 338  
 cohesion for class data members 229  
 colon (:) in F77 identifiers, Fortran 85  
 Color Mode field, Advanced Editor options 113  
 colors  
     in Entity Comparison area 306  
     in file/folder comparisons 300  
     of highlighted differences in Entity Comparison area 305  
     in HTML reports 212  
     of merged differences in Difference List area 307  
     of merged differences in Entity Comparison area 307  
     for printing source code 113  
     of rows in User Interface, alternating 106  
     in Source Editor, customizing 168, 117  
     in Source Editor, default 117  
 column truncation  
     Fortran 85  
     JOVIAL 89  
 command line. *See* und command; understand  
     command  
 command renames, reports about 223  
 Command window 320  
 Command Window Font 102  
 commands, external. *See* external tools  
 Comment metric 231  
 Comment Selection menu option 181  
 comments  
     adding or removing 181  
     associating with entities, Ada 64  
     associating with entities, C 79  
     associating with entities, C++ 72  
     associating with entities, Java 87  
     blue italic text for 117  
     C-style 71  
     nested, C++ 71  
 companion file 183  
 Compaq Pascal 91  
 Compare Arbitrary Text option, Tools menu 303  
 Compare Entities option, Tools menu 302  
 Compare files by content field 81  
 Compare Files/Folders option, Tools menu 299  
 compilation environment, Ada 64  
 compilation unit  
     Child Library Units of 257  
     declaration nesting of program units in 257  
     entities called by 257  
     instantiation tree for 257  
     With By relationships of 257, 274  
     With relationships of 257  
 compiler  
     COBOL 69  
     compared to Understand 33  
 Compiler field  
     C++ 71  
     PL/M 93  
 Compiler Include Paths field, C++ 71  
 complexity  
     exception handlers included in, Ada 64  
     FOR-loops included in, Ada 64  
     metrics graphs about 239  
     strict, and/or operators in, Ada 64  
 Component field, Key Bindings options 107  
 compool file, JOVIAL 89  
 Configure Metric Charts option, Metrics menu 233, 239  
 Configure option, Project menu 39  
 Configure Reports option, Reports menu 210  
 constants  
     displayed in graphical views 267  
     reports about 226  
 Constants menu, graphical views 267  
 contact information 14  
 Context Browser, Contextual Information Sidebar 166  
 -contextmenu option, understand command 331  
 Contextual Information option, View menu 166  
 Contextual Information Sidebar (CIS) 166  
 Contiguous Selection field 105  
 Control Flow View 261, 265  
 !COPY directives, directories to search, JOVIAL 90  
 Copy category, JOVIAL 90

---



Copy option, Edit menu 170  
 Copybook category 70  
 copybook files  
   adding to project, COBOL 70  
 copying text 305  
   rectangular area 170  
 Count and/or operators in strict complexity field, Ada 64  
 Count exception handlers in complexity field, Ada 64  
 Count for-loops in complexity field, Ada 64  
 Count of All Methods metric 229  
 Count of Base Classes metric 229  
 Count of Coupled Classes metric 229  
 Count of Derived Classes metric 229  
 Count of Instance Methods metric 229  
 Count of Instance Variables metric 229  
 Count of Methods metric 229  
 coupled classes 229  
 Create and cross-reference record object components  
   field, Ada 64  
 Create implicit special member functions field 72  
 Create references in inactive code field, C++ 72  
 Create references in inline assembly, C++ 72  
 Create references to local objects field, C++ 72  
 Create references to macros during macro expansion  
   field, C++ 72  
 Create references to parameters field, C++ 72  
 Create relations between formal and actual parameters  
   field, Ada 64  
 Crossing layout option 270  
 cross-reference reports 216  
 cross-referencing record object components, Ada 64  
 CSS files 14  
 C-style comments  
   in Fortran 85  
   nesting of, allowing 71  
 CSV file  
   exporting dependencies to 244  
   exporting metrics to 52, 233, 237  
   exporting project overview charts to 250  
 Ctrl+Alt+F keystroke, find and replace text 165  
 Ctrl+F keystroke, find text 165  
 Ctrl+j keystroke, jump to matching bracket 180  
 Ctrl+right-click keystroke  
   creating new windows 22, 129  
 Ctrl+Shift+j keystroke, select text in brackets 180  
 \$Cur variables 310, 311  
 Cut option, Edit menu 170

-cwd option  
   understand command 331  
 Cyclomatic complexity 224, 231  
 Cytoscape  
   installation location 110  
   XML output 245  
 Cytoscape XML 244, 245

## D

dashed outline shapes, in graphical views 266  
 Data Dictionary report 216  
 Data Members View 261  
 database 18, 33  
   changes to format of 33  
   creating on command line 323  
   file extension for 18, 33  
   multi-user read/write access for 33  
   See *also* project  
 Date Format field 114  
 -db option  
   understand command 331  
 DEC Pascal 91  
 \$Decl variables 310, 311, 312  
 Declaration File View 261, 263  
 Declaration Tree report 221  
 Declaration Tree View 257  
 Declaration Type View 261, 264  
 Declaration View 261, 262  
 declaration views  
   calling methods displayed in 267  
   constants displayed in 267  
   default members displayed in 267  
   extended by classes displayed in 268  
   extended classes displayed in 268  
   external functions displayed in 268  
   file dependencies displayed in 267  
   globals displayed in 268  
   header files include by's displayed 269  
   implemented by classes displayed in 268  
   implemented classes displayed in 268  
   imported entities displayed in 269  
   include files displayed in 269  
   inherited entities displayed in 269  
   invocations displayed in 269  
   local items displayed in 271  
   members displayed in 271  
   objects displayed in 271

---

- operators displayed in 271
- private members displayed in 272
- protected members displayed in 272
- public members displayed in 272
- rename declarations in 272
- static functions displayed in 273
- types displayed in 273, 274
- used-by items shown in 274
- variables displayed in 274
- With By relationships displayed in 274
- With relationships displayed in 274
- See *also* graphical views
- declarations
  - implicit, report about 225
  - local, including in database, C++ 72
- Declared In View 257
- Default Members menu, graphical views 267
- Default style field, Editor options 111
- default working directory 100
- defines. See macros
- Delphi Pascal 91
- Depended On By graph 198, 257
- dependencies
  - browsing 142
  - exporting 143, 244
  - file 267
- Dependency Browser 142
- Dependency category, Understand Options dialog 110
- Dependency Graph 196
- Dependency Graphs option, Graphs menu 198
- Dependency menu 244
- Dependent menu
  - graphical views 267
- Dependent Of menu, graphical views 267
- Depends On graph 198, 257
- Depth menu, graphical views 267
- derived classes 229, 257, 260
- Derived Classes View 257, 260
- DFM converter exe field 91
- diff option, understand command 331
- Difference List area, Change Results window 304, 307
- Dim highlight color field 106
- directives, C++ 75
- directories
  - adding to project 44
  - comparing 299
  - copying 300
  - deleting from project 45
  - overriding settings for 46
  - watched, scanning 47, 52
  - watched, setting 45, 46
- Directory Structure auto-architecture 29, 195
- Display entity names as field
  - Ada 64
  - Fortran 86
  - JOVIAL 90
  - Pascal 92
  - PL/M 93
- DIT (Max Inheritance Tree) metric 229
- Dock Window Layouts field, User Interface options 101
- docking windows 17
- Document Area 19
- documentation 15, 21
- dollar sign (\$)
  - in regular expressions 160
  - prefixing external tool parameters 310, 311
- DOS line termination style
  - for reports 212
  - for saving source files 112
- DOT files, saving graphical views as 280
- double quotes. See quotes
- double-click merging, in Entity Comparison area 306, 307
- double-clicking
  - in Bookmarks area 184
  - column header dividers 157
  - entities in Entity Filter 136
  - entities in graphical view 253
  - entities in Information Browser 136
  - in Exploring View 141
  - in Find Results window 154
  - messages in Analysis Log window 124
  - in Project Browser 235
  - in Source Editor 28
- drawers 17, 101
- Drill down command 244
- drop-down menu See right-clicking
- .dsp file extension 58
- .dsw file extension 58
- Duplicate Architecture menu option 197
- duplicate references, C++ 72
- Duplicate Subtrees menu, graphical views 267

---

## E

- Eclipse IDE 321
- Edges Shown options 276
- edges, in dependency graphs 200
- Edit Architecture menu option 197, 207
- Edit Graphic Filters menu option 255
- Edit menu 335
  - Bookmarks option 183
  - Change Case option 181
  - Copy option 170
  - Cut option 170
  - Select All option 170
  - Toggle Overtyping option 182
- Editor category, Understand Options dialog 111
- Editor Macros option, Tools menu 182
- editor windows, saving automatically 99
- editor, external 119
- editor, source. *See* Source Editor
- Emacs editor 119
- embedded SQL, in Pascal 91
- Enable Editor Tooltips field 118
- Enable permissions checking for NTFS filesystems field 100
- encoding formats 50, 111
- entities 18
  - comments associated with, Ada 64
  - comments associated with, C 79
  - comments associated with, Java 87
  - comparing two entities 302
  - comparisons between versions of 304
  - components of 261
  - current, information about 166
  - declaration structure for 261, 262
  - displaying source for. *See* Source Editor
  - favorites of, displaying 145
  - favorites of, marking 144
  - full name of, displaying 132
  - graphical views of. *See* graphical views
  - hierarchy of, exploring 141, 166
  - hierarchy of, graphical view 252, 257
  - information about. *See* Information Browser
  - list of, alphabetic 216
  - listed in Entity Filter 131
  - listed in Entity Locator 25, 157
  - listed in Filter Area 24
  - metrics for. *See* metrics
  - names of, formatting for reports 56
  - as rectangles, in graphical views 266
  - references for 137
  - relationships between 18
  - renamed 261
  - reports about. *See* reports
  - sorting of 131
  - structural information about, graphical view of 253, 261
  - unknown 274
  - unresolved 274
  - XML listing of 197
  - See also specific entities*
- Entity Comparison area, Change Results window 304
- Entity Filter 131
  - displaying information about entities in 133
  - displaying source of selected entity 136
  - entities not listed in 25, 157
  - jumping to entities in 24
  - location of 19
  - right-clicking in 23
- Entity Graph option, Window menu 253
- entity index, for HTML reports 213
- Entity Locator 25, 157
  - column headers in, customizing 158
  - columns in, hiding and reordering 158
  - columns in, resizing 157
  - filtering by selection 159
  - filtering manually 160
  - filtering with regular expressions 160
  - filtering with wildcards 160
  - length of names in 157
  - opening 157
  - right-clicking in 25, 157
  - right-clicking on column header 158, 160
  - right-clicking on entities 159
  - sorting entities in 158
- Entity Locator option, View menu 25, 157
- entity\_index.html file 213
- environment variables
  - using in include paths, assembly 68, 70
  - using in include paths, C++ 73, 80
- equal sign (=) in macro definition in command line 330
- errors
  - displaying from Analysis Log window 124
  - parse errors, prompting for, Ada 65
  - parse errors, prompting for, Fortran 86

---

Essential metric 231  
Example Projects option, Help menu 15  
Exception Cross-Reference report 220  
exceptions  
    handlers for, including in Ada complexity 64  
    reports about 220  
-existing option, understand command 331  
Expand Recursive Nodes menu, graphical views 268  
Expand Repeated Nodes menu, graphical views 268  
Expand/Collapse code snippet field 105  
Exploring view 141  
Export Dependency CSV 244  
Export Metrics option, Metrics menu 52, 233, 237  
exporting tool commands 319  
Extend Tree report 222  
Extended By menu, graphical views 268  
Extended By View 257, 260  
Extends menu, graphical views 268  
extensions. *See* file extensions  
external editor 119  
External Editor category, Editor options 119  
External Functions menu, graphical views 268  
external tools  
    adding to Right-click Menu 311, 316  
    adding to toolbar 318  
    adding to User Tools menu 317  
    commands for, importing and exporting 319  
    commands for, running 320  
    configuring 309  
    editor 119  
externally linkable entities  
    case of, Ada 64, 90  
    case of, Fortran 85  
    case of, Pascal 91  
    prefix for 72, 85, 92  
    suffix for, C++ 72  
    suffix for, Fortran 85  
Externally Modified Files field, Editor options 112  
Extract Function refactoring 176  
Extract Temp refactoring 178

**F**

F5 key, Find in Files option 152  
FAQ option, Help menu 15  
favorites 26  
    displaying 145  
    marking entities as 144  
Favorites option, View menu 26, 145  
File Average Metrics report 231  
File Contents report 217  
file extensions  
    configuring for project 49  
    for database 18, 33  
    for MSVC project files 58  
File Information, Contextual Information Sidebar 166  
File menu 334  
    Close option 21  
    New > File option 183  
    New > Project option 34  
    Open > File option 183  
    Open > Project option 21  
    Page Setup option 192  
    Print Entity Graph option 281  
    Print option 192  
    Recent Projects option 21  
    Save All option 172  
    Save option 172  
File Metrics report 230  
File Mode field, Editor options 111  
File Options category, Project Configuration dialog 50  
file permission checking 100  
File Sync box 136  
File Types category, Project Configuration dialog 49  
File Volume metrics graph 239  
Filename menu, graphical views 268  
filenames  
    in graphical views 268  
    for reports 213  
    in title areas 102  
files  
    comparing 299  
    copying 300  
    exporting dependency list 245  
    Information Browser for 166  
    location included in listing of 132  
    searching 26, 152  
    searching and replacing in 155  
    toolbar for 164  
    *See also* database; header files; include files; MSVC  
        project; project; source files  
Files category, Project Configuration dialog 43  
Filter Area 24  
    *See also* Entity Filter; Project Browser

---

Filter By Selection menu option 159  
Filter field, Entity Filter 132  
filters  
    for graphical views 255  
    *See also* Entity Filter; Entity Locator  
Find dialog 165  
Find Entity option, Search menu 157  
Find in Files dialog 19, 26  
Find in Files menu option 26, 152  
Find option, Search menu 165  
Find Results window 26, 154  
fixed file format, Fortran 84  
flow chart symbols 266  
flow charts 261, 265  
Fold All option, View menu 180  
fold icon 304  
folders. *See* directories  
folding code 180  
font  
    Command Window 102  
    for printing source code 113  
    for Source Editor windows 111  
    in Source Editor windows 185  
    in Understand, changing 99  
Font Size field, Advanced Editor options 113  
FOR-loops, including in complexity metrics, Ada 64  
formal parameters, relationship to actual parameters,  
    Ada 64  
Format field, Fortran 84  
Fortran  
    configuration for 84  
    extensions supported 14  
    include files 86  
    macro definitions 86  
    reports showing non-standard extension usage 225  
    versions supported 14  
Fortran category, Project Configuration dialog 84  
Fortran Extension Usage report 225  
frames in windows, sliding 17  
Frameworks Category, C++ Includes 81  
free file format, Fortran 84  
function declarations without parentheses, Fortran 85  
Function Pointer menu, graphical views 268  
functions  
    external 268  
    in graphical views 272  
    listing in Filter Area 24

    metrics about 231  
    reports about 217, 231  
    static 273  
    *See also* invocations; procedures; program units  
fuzzy search 151

## G

gcc build 332  
General category, Understand Options dialog 99  
Generate Reports option, Reports menu 212  
Generic Instantiation report 223  
generic unit  
    instantiation hierarchy for 257  
    instantiation tree for 257  
Getting Started dialog  
    displaying at startup 99  
    opening 21  
Getting Started option, Help menu 15, 21  
Getting Started tab 20  
Globals menu, graphical views 268  
Go To Line dialog 170  
Go to Matching Brace option, Search menu 180  
Graph Architecture 196, 198  
Graph Architecture graph 198  
Graph Architecture View 261  
Graph Customizer pane 198  
Graph View of graphs 249  
Graph View, for metrics graphs 241  
Graphic Filter dialog 255  
graphical user interface (GUI), parts of 19  
graphical views 30, 249  
    of architecture 196, 198  
    browsing 253  
    calling methods displayed in 267  
    constants displayed in 267  
    copying to clipboard 279  
    default members displayed in 267  
    diagram of 19  
    displaying 251  
    entity name truncation for 273  
    expanding or contracting nodes in 254  
    extended by classes displayed in 268  
    extended classes displayed in 268  
    external functions displayed in 268  
    file dependencies displayed in 267  
    filename display options 268  
    filtering 255

---

- fullnames displayed in 271
- function pointers displayed in 268
- functions displayed in 272
- globals displayed in 268
- Graph View of 249
- header files include by's displayed 269
- hierarchy levels displayed in 271
- hierarchy views 252, 257
- implemented by classes displayed in 268
- implemented classes displayed in 268
- imported entities displayed in 269
- include files displayed in 269
- inherited entities displayed in 269
- intrinsic functions displayed in 269
- invocations displayed in 269
- layout configuration for 255, 266, 270
- local items displayed in 271
- members displayed in 271
- multiple subtrees displayed in 267
- objects displayed in 271
- open, list of 253
- operators displayed in 271
- parameters, displaying in 272
- path highlighting in 254
- printing 254, 281
- private members displayed in 272
- procedures displayed in 272
- protected members displayed in 272
- public members displayed in 272
- rename declarations in 272
- reusing 256
- saving 254, 278
- saving as PDF 282
- scrolling in 253
- sorting entities in 273
- spacing entities in 273
- SQL entities shown in 273
- static functions displayed in 273
- structure views 253, 261
- synchronizing with other windows 256
- Table View of 250
- text size of 272
- types displayed in 273, 274
- unknown entities, displaying 274
- unresolved entities, displaying 274
- used-by items shown in 274
- uses items shown by 274

- variables displayed in 274
- With By relationships displayed in 274
- With relationships displayed in 274
- zooming 254
- See also* structure views; hierarchy views
- Graphical Views menu option 196, 198, 251
- Graphs category, Understand Options dialog 120
- Graphs for option, Graphs menu 198, 251
- Graphs menu 338
  - Dependency Graphs option 198
  - Graphs for option 198, 251
  - Project Graphs option 31, 215
- graphs, of metrics 239
- gray background for text 117
- gray shapes, in graphical views 266
- green text 117
- GUI (graphical user interface), parts of 19
- GVIM editor 119

## H

- header files 269
- help 15, 21
- Help menu 340
  - About Understand 15
  - Check for Updates option 21
  - Example Projects option 15
  - FAQ option 15
  - Getting Started option 15, 21
  - Help Content option 15
  - Key Bindings option 15, 182
  - Perl API Documentation option 15, 31, 233
  - Python API Documentation option 15, 31
- help option, und command 325
- hexagons, in graphical views 266
- Hide Inactive Lines option, View menu 180
- hiding common lines, in Entity Comparison area 306
- hierarchy views 30, 252
  - layout of 270
  - list of 257
  - multiple subtrees displayed in 267
  - number of levels in 271
  - parameters, displaying in 272
  - See also* graphical views
- highlighting full line at cursor 112
- history
  - Information Browser 134, 138
  - Source Editor 163

toolbar for 164  
 Horizontal Non-Crossing layout option 270  
 HTML  
   colors in reports 212  
   entity index in reports 213  
   exporting metrics to 52, 233, 236  
   files 14  
   generating reports as 31, 55, 210, 212  
   viewing reports as 213  
 Hyper Grep. *See* Find in Files dialog  
 hyphen (-) collapsing tree in Information Browser 134

## I

IB. *See* Information Browser  
 IFANIN (Count of Base Classes) metric 229  
 Ignore category, C++ Includes 74  
 Ignore directories in include names field 74, 81  
 Ignore Parent Overrides field 47  
 Implementation fields field, JOVIAL 89  
 Implemented By menu, graphical views 268  
 Implements menu, graphical views 268  
 implicit special member functions, C++ 72  
 Implicitly Declared Objects report 225  
 import files  
   adding to project, Python 95  
 Import report 223  
 imported entities, displaying in graphical views 269  
 importing tool commands 319  
 Imports category  
   Python 95  
 Imports menu, graphical views 269  
 -importusertools option, understand command 331  
 inactive code, cross-reference information for, C++ 72  
 inactive lines, hiding 180  
 Include By View 259  
 Include File Cross-Reference report 219  
 include files  
   adding as source files, assembly 67  
   adding as source files, C++ 73, 80  
   adding as source files, Fortran 86  
   adding as source files, PL/M 93  
   adding before each project file, C++ 74  
   adding in bulk, assembly 68, 70  
   adding in bulk, C++ 73, 80  
   adding in bulk, Fortran 86  
   adding in bulk, PL/M 93  
   adding to project, assembly 67  
   adding to project, C++ 73, 80  
   adding to project, COBOL 70  
   adding to project, Fortran 86  
   adding to project, PL/M 93  
   compiler path for, C++ 71  
   displayed in graphical views 269  
   environment variables in paths for, assembly 68, 70  
   environment variables in paths for, C++ 73, 80  
   hierarchy of, for source files 257, 259  
   ignoring during analysis, C++ 74  
   overriding MSVC project settings for 59  
   Pascal search path 92  
   replacement text for, C++ 75  
   replacement text for, Fortran 86  
   replacement text for, PL/M 93  
   reports about 219  
   system include files, C++ 74  
 Include line numbers in rich text field 114  
 Include View 257, 259  
 IncludeBy View 257  
 Included By menu, graphical views 269  
 Includes category  
   C++ 73, 80  
   Fortran 86  
   PL/M 93  
 Includes menu, graphical views 269  
 Indent field, Editor options 112  
 indentation 115, 116  
   fixing 182  
 Information Browser (IB) 24, 27, 133  
   architecture information in 195  
   copying information in 134, 138  
   displaying from entity in Entity Filter 133  
   displaying source of selected entity 136  
   entity information displayed by, choosing 135  
   expanding and collapsing the tree 134  
   for current entity 166  
   for current file 166  
   history for 134, 138  
   location of 19  
   metrics in 137, 233  
   multiple occurrences open 136  
   References in 137  
   right-clicking in 23  
   saving information in 134, 138  
   searching 135

---

- synchronizing 136
- Information Browser option, View menu 133
- Inherited By menu, graphical views 269
- Inherits menu, graphical views 269
- initialization files 21
- Inline Function refactoring 175
- Inline Temp refactoring 177
- Insert Spaces Instead of Tabs field, Editor options 112
- instance methods 229
- instance variables 229
- Instant Search 150
- Instant Search menu option 150
- Instantiated From View 257
- instantiation
  - of compilation units 257
  - of generic types 257
  - of generic units 257
  - reports about 223
- Instantiations View 257
- interactivity during background processing 100
- interfaces
  - listing in Filter Area 24
  - reports about 218
- Internal Dependencies graph 198
- interrupt handlers, listed as unused program units 227
- intrinsic functions, parsing, Fortran 85
- Intrinsic menu, graphical views 269
- Intrinsics file field, Fortran 85
- Invocation Tree report 222
- Invocation View 257
- invocations
  - reports about 222
  - views of 257, 258, 261, 262
- Invocations menu, graphical views 269

## J

- .jar files 88
- Java
  - configuration for 87
  - versions supported 14
- Java category, Project Configuration dialog 87
- JavaScript files 14
- JDK, versions supported 14
- JNI external entities, Java 87
- JOVIAL
  - configuration for 89

- directories for !COPY directives 90
- versions supported 14
- JOVIAL category, Project Configuration dialog 89
- JPEG format, saving graphical views as 279
- jQuery analysis 96
- Jump to Matching Brace menu option 180
- Jump to Matching Directive menu option 180

## K

- Key Bindings category, Understand Options dialog 107, 182
- Key Bindings option, Help menu 15, 182
- keyboard mappings 107
- Keyboard Scheme field, Key Bindings options 107
- keywords, blue text for 117
- KNI external entities, Java 87

## L

- Language auto-architecture 29, 195
- Languages category, Project Configuration dialog 41
- lastproject option, understand command 331
- lastproject\_cwd option, understand command 331
- Layout menu, graphical views 270
- layout, for graphical views 270
- LCOM (Percent Lack of Cohesion) metric 229
- Less memory usages versus speed field, Ada 64
- Level menu, graphical views 271
- libraries, standard
  - Ada, directory for 64
  - including in Analysis Log 108
  - Pascal, paths for 92
- Library directories field, Ada 65
- line endings for source files 111
- line numbers, displaying in Source Editor 168
- line termination style
  - for reports 212
  - for saving source files 112
- Lines metric 231
- @lisfile.txt file 330
- Local menu, graphical views 271
- local object declarations, including in database, C++ 72
- local parameters, listed in Entity Locator 25
- Lucene, Apache syntax 150

## M

- Macintosh line termination style 112



- 
- Macro Cross-Reference report 219
  - macros
    - adding in bulk, C++ 76
    - changing, Ada 66
    - compiler-specific, C++ 71
    - defining in command line 330
    - defining on command line, Ada 66
    - defining, Ada 65
    - defining, C++ 75, 82
    - of editing changes, recording and replaying 182
    - expansion text for, C++ 72
    - importing, Ada 66
    - listing in Filter Area 24
    - as octagons, in graphical views 266
    - overriding MSVC project settings for 59
    - recording references when expanding, C++ 72
    - reports about 218, 219
    - undefined, C++ 77
    - See also* objects
  - Macros category
    - Ada 65
    - C++ 75, 82
    - Fortran 86
    - Pascal 92
  - Main subprograms field, Ada 65
  - makefile 332
  - Manage Architectures option, Project menu 197, 203
  - Margins field, Editor options 113
  - "Mastering Regular Expressions" (O'Reilly) 161
  - Max Inheritance Tree metric 229
  - McCabe (Cyclomatic) complexity 224, 231
  - members
    - cohesion of 229
    - default 267
    - displayed in graphical views 271
    - graphical views of 261
    - private 272
    - protected 272
    - public 272
  - Members menu, graphical views 271
  - memory
    - caching include files, C++ 72
    - optimizing analysis to use less, Ada 64
  - menu bar 19
  - menus. *See specific menus*
  - merging, in Entity Comparison area 306
  - methods
    - cohesion of 229
    - instance 229
    - listing in Filter Area 24
    - metrics about 229
  - metrics 196, 202
    - calculating automatically 52
    - configuring 53
    - displayed in Information Browser 137
    - exporting to CSV file 52, 233, 237
    - exporting to HTML 52, 233, 236
    - for project 234, 235
    - graphs for 239
    - in Information Browser 233
    - list of, online 224, 228, 233, 234, 235
    - reports about 228, 229, 230, 231, 233
    - selecting 54
  - Metrics Browser 233
  - Metrics category, Project Configuration dialog 53
  - Metrics Export 197
  - Metrics Export menu option 203
  - Metrics menu 337
    - Browse Metric Charts option 243
    - Browse Metrics option 233, 235
    - Configure Metric Charts option 233, 239
    - Export Metrics option 52, 233, 237
    - Metrics Summary option 233, 234
  - Metrics Summary 196, 202
  - Metrics Summary option, Metrics menu 233, 234
  - Microsoft Visio files, saving graphical views as 279
  - Microsoft Visual C++ project. *See* MSVC project
  - Microsoft Visual C++, as editor 119
  - minus sign (-) collapsing tree in Information Browser 134
  - Modified metric 231
  - modules, listing in Filter Area 24
  - MSVC project, importing into Understand project 36, 58
  - multiple users, initialization files for 21
- ## N
- Name menu, graphical views 271
  - named root portability mode 48
  - named roots 109
  - Navigation category, Editor options 118
  - Navigation Mode, Source Editor 118
  - nested comments, C++ 71
  - New Architecture option, Project menu 204, 205
  - New File option, File menu 183

---

- new option, understand command 331
- New Project option, File menu 34
- New Project Wizard 34, 102
- next button 17
- Next icon 28
- NIM (Count of Instance Methods) metric 229
- NIV (Count of Instance Variables) metric 229
- No Truncation text option 273
- No Wrap text option 273
- no\_splashscreen option, understand command 331
- NOC (Count of Derived Classes) metric 229
- Node.js analysis 96
- noproject option, understand command 331
- NTFS filesystem 100

## O

- Object Cross-Reference report 218
- Objective C/C++ 14
  - configuration 78
  - enabling 42
- object-oriented metrics 229
- objects
  - displayed in graphical views 271
  - listing in Project Window 24
  - reports about 218, 226
- Objects menu, graphical views 271
- octagons in graphical views 266
- online help 15, 21
- Open File option, File menu 183
- Open last project at startup field, General options 100
- Open Project option, File menu 21
- Operators menu, graphical views 271
- operators, displayed in graphical views 271
- Options option, Tools menu 98
- Options subcategory, Reports 56
- or operators, including in strict complexity, Ada 64
- Output subcategory, Reports 55, 210

## P

- Package View 261
- packages
  - declaration structure for 261
  - listing in Filter Area 24
  - reports about 223
  - With By relationships for 261
  - With relationships for 261

- page guide, showing 112
- Page Setup option, File menu 192
- parallelograms, in graphical views 266
- parameter declarations without parentheses, Fortran 85
- parameters
  - cross-reference information for, C++ 72
  - included in listing of 132
  - relationships between formal and actual, Ada 64
  - reports about 218, 225, 226
  - See also* objects
- Parameters menu, graphical views 272
- parent
  - of class. *See* base classes
  - of entity 257
- Parent Declaration View 261, 262
- Parent Lib Unit View 257
- parentheses, matching. *See* brackets
- parsing. *See* analyzing projects
- Pascal
  - configuration for 91
  - macro definitions 92
  - search paths 92
  - standard libraries, paths for 92
  - versions supported 14
- Pascal category, Project Configuration dialog 91
- Patch File area, Change Results window 304, 307
- patching lines of context, in Entity Comparison area 306, 307
- PATH definition 323
- path highlighting, in graphical views 254
- pattern matching. *See* regular expressions
- PC line termination style
  - for reports 212
  - for saving source files 112
- .pcn file 217
- PDF, saving graphical views to 282
- Percent Lack of Cohesion metric 229
- period (.) in regular expressions 160
- Perl
  - API for custom reports 31
  - CodeCheck scripts 296
  - interface for custom reports 215, 233
  - scripts 18
- Perl API Documentation option, Help menu 15, 31, 233
- permission checking 100
- PHP files 14, 97

- PHP version field 97
- pin icons. *See* pushpin icons
- pink background for text 117
- PL/M
  - configuration for 93
  - versions supported 14
- PL/M category, Project Configuration dialog 93
- plus sign (+)
  - expanding tree in Information Browser 134
  - in regular expressions 160
- PNG format, saving graphical views as 279
- Popup Menu category, Tool Configurations dialog 316
- Portability category, Understand Options dialog 109
- portability of project 48
- pound sign (#) comment in command line file 330
- pragma statements, defining macros referenced in, Ada 65
- Predeclared entities file field, Pascal 91
- Prefix Headers Category, C++ Includes 82
- Prepend the names of externally linkable entities with field
  - C++ 72
  - Fortran 85
  - Pascal 92
- Prepend the names of JNI/KNI external entities with field, Java 87
- preprocessor directives, C++ 75
- Preprocessor field, Ada 63
- preprocessor macros. *See* macros
- preprocessor statements, green text for 117
- preprocessor support, enabling, Fortran 85
- previous button 17
- Previous icon 28
- Print Entity Graph option, File menu 281
- Print option, File menu 192
- printing
  - CodeCheck results 293
  - graphical views 281
  - source files 192, 281
- Private Members menu, graphical views 272
- procedures
  - in graphical views 272
  - reports about 217
  - See also* invocation; functions; program units
- Program Unit Complexity report 224
- Program Unit Cross-Reference report 217
- Program Unit Metrics report 230
- program units
  - metrics about 230
  - reports about 221, 222, 223, 224, 227, 230
  - With relationships for 223, 227
- programming languages
  - selecting for project 41
  - setting in Source Editor 170
- project 18
  - adding source files on command line 325
  - analyzing (parsing). *See* analyzing projects
  - closing 21
  - closing automatically when opening new project 103
  - configuring 39
  - creating 34
  - creating, with New Project Wizard 102
  - directory hierarchy for, displaying 139
  - existing, opening 20
  - metrics for 228, 234, 235
  - opening most-recent project at startup 100
  - portability of 48
  - saving configuration of 40
  - toolbar for 164
- Project Browser 139
- Project Browser option, View menu 139
- Project Configuration dialog 39, 210
  - Ada category 63
  - Assembly category 67
  - C# category 83
  - C++ (Strict) category 78, 83
  - C++ category 71
  - CMake category 60
  - COBOL category 69
  - File Options category 50
  - File Types category 49
  - Files category 43
  - Fortran category 84
  - Java category 87
  - JOVIAL category 89
  - Languages category 41
  - Metrics category 53
  - Pascal category 91
  - PL/M category 93
  - Python category 94
  - Reports category 55
  - saving configuration 40
  - Scheduled Activities category 51
  - Visual Basic category 68

---

- Visual Studio category 58
- Web category 96
- Project Graphs option, Graphs menu 31, 215
- Project Interactive Reports option, Reports menu 31, 215
- Project menu 336
  - Analyze All Files option 52, 123
  - Analyze Changed Files option 52, 123
  - Browse Architectures option 195
  - Configure option 39
  - Manage Architectures option 203
  - New Architecture option 204, 205
  - Project Overview Charts option 249
  - Rescan Project Directories option 47, 52
  - Rescan Watched Project Directories option 47
- Project Metrics report 228
- Project Overview Charts option, Project menu 249
- Prompt before closing the current project field, User Interface Alerts options 103
- Prompt for missing include files field 73, 81
- Prompt for missing includes field, C++ Includes 74, 81
- Prompt on parse errors field
  - Ada 65
  - Fortran 86
- \$Prompt variables 310, 311, 312
- prompt when files modified externally 112
- Protected Members menu, graphical views 272
- Public Members menu, graphical views 272
- pushpin icons 17
- Python
  - API for custom reports 31
  - configuration for 94
  - versions supported 14
- Python API Documentation option, Help menu 15, 31
- Python category, Project Configuration dialog 94

## Q

- quality reports 224
- question mark (?)
  - in regular expressions 160
  - wild card 160
- quiet\_startup option, understand command 331
- quote (") prefixing octal constants or string literals 85
- quotes (""") surrounding normal includes 74

## R

- read-only access 50
- Recent files most recently use list field, User Interface Lists options 102
- Recent projects most recently use list field, User Interface Lists options 102
- Recent Projects option, File menu 21
- Record Macro option, Tools menu 182
- rectangles, in graphical views 266
- rectangles, rounded, in graphical views 266
- rectangular area, copy and paste 170
- rectangular text selection 170
- red project file icon 169
- red text 117
- refactoring 173
  - Extract Function 176
  - Extract Temp 178
  - Inline Function 175
  - Inline Temp 177
  - Rename 174
- Reference Count option 199
- reference files, C# 83
- References category, C# 83
- References, in Information Browser 137
- regular expressions
  - book about 161
  - in filters for Entity Locator 160
  - in Find dialog 165
- Reindent Selection command 182
- relationship 18
- relative portability mode 48
- Rename Architecture menu option 197
- Rename Declaration View 261
- rename declarations
  - displayed in graphical views 272
  - reports about 223
- Rename entity 174
- Renames menu, graphical views 272
- Renames report 223
- Replace in Files area 155
- Replace in Files option, Search menu 155
- Replacement Text category
  - C++ Includes 75
  - Fortran Includes 86
  - PL/M Includes 93
- Replay Macro option, Tools menu 183

reports 31, 210

- anti-virus software, turning off while generating reports 212
- canceling generation of 212
- categories of 214
- colors in 212
- configuring 210
- cross-reference reports 216
- customizing 31
- customizing with Perl or C 215, 233
- entity name format in 56
- filenames for 213
- generating 210, 212
- generation time of 56, 212
- HTML output 55, 212
- HTML output, entity index for 213
- list of, choosing from 57, 211
- metrics reports 228, 233
- quality reports 224
- structure reports 221
- text output 56, 212
- viewing 213
- See also specific reports*

Reports category, Project Configuration dialog 55

- Options subcategory 56
- Output subcategory 55, 210
- Selected subcategory 57, 211

Reports menu 337

- Configure Reports option 210
- Generate Reports option 212
- Project Interactive Reports option 31, 215
- View Reports option 213

Rescan project before analyzing changed files field 108

Rescan Project Directories option, Project menu 47, 52

Rescan Watched Project Directories option 47

Restore Default Position field 105

RFC (Count of All Methods) metric 229

Right-click Menu

- external tools available in 311, 316
- Find in Files option 152

right-clicking 17, 129

- + or - sign in Information Browser tree 134
- on Analyze icon 123
- anywhere in Understand 22
- in Architecture Browser 196
- in background of graphical views 266
- bold heading in Information Browser 135

- creating windows by 22
- on entities in graphical views 253
- on entities to display source 136
- on entities in Entity Locator 25
- on entities in Entity Locator entities 159
- on entities in Information Browser 23
- on entities in Source Editor 22, 28
- in Entity Filter 23
- in Entity Locator 157
- on Entity Locator column headers 158, 160
- in Information Browser 138
- on Selector window 164
- reusing windows by 22, 129
- on selected text 170, 181
- in Source Editor 171
- on Source Editor tabs 185
- See also Ctrl+right-click*

RO (read-only) indicator, in Source Editor 170

Root filters, Entity Filter 133

Routines menu, graphical views 272

routines. *See* functions; procedures

row colors, alternating 106

Run Command option, Tools menu 320

RW (read-write) indicator, in Source Editor 170

## S

Save all modified editor windows when application loses focus field, General options 99

Save All option, File menu 172

Save comments associated with entities field

- Ada 64
- C 79
- C++ 72
- Java 87

Save duplicate references field, C++ 72

Save macro expansion text field

- C++ 72

Save on command field, User Interface Alerts options 103

Save on parse field, User Interface Alerts options 103

Save option, File menu 172

saving edits automatically 99

Scale menu, graphical views 272

Scheduled Activities category, Project Configuration dialog 51

Scheduler option, Tools menu 51, 52

Scientific Toolworks website 14

---

Scope Information, Contextual Information Sidebar 166  
 Scope List option, View menu 169  
 Scope List, Source Editor 169  
     See also Structure Browser, Source Editor 166  
     toolbar for 164  
 scripts  
     CodeCheck 296  
     Perl 18  
 Search for include files among project files field, C++  
     Includes 74, 81  
 Search menu 149, 335  
     Find Entity option 157  
     Find in Files option 26, 152  
     Find option 165  
     Go to Matching Brace option 180  
     Instant Search option 150  
     Replace in Files option 155  
 Search Paths Category, Pascal 92  
 searching  
     files 149, 152  
     graphical views 253  
 Select All option, Edit menu 170  
 Select Block menu option 180  
 Selected subcategory, Reports 57, 211  
 selecting text 305  
 Selector area 163  
 sharp sign (#) comment in command line file 330  
 shortcut commands 107  
 Show Edge Labels options 276  
 Show Page Guide field, Editor options 112  
 Show standard library files field, Analyze options 108  
 Show tabs field, User Interface options 101  
 Show the Getting Started dialog on startup field,  
     General options 99  
 Show the Splash-Screen on startup field, General  
     options 99  
 Simple Invocation Tree report 222  
 Simple With Tree report 223  
 SlickEdit editor 119  
 sliding frames 17  
 Soft Wrap option, View menu 182  
 "Software Engineering with Ada" (Booch) 261  
 Sort menu, graphical views 273  
 Sort Selection command 182  
 sorting entities 131  
 Sound beep field 103  
 Sound beep on analysis completion field, Analyze  
     options 108  
 Source Editor 28, 168  
     auto-complete options 114  
     auto-indent options 115, 116  
     bookmarks, creating 183  
     bookmarks, navigating 183  
     bracket matching in 180  
     Browse Mode in 170  
     case, changing in 181  
     closing files 172  
     colors in, customizing 117, 168  
     colors in, default 117  
     commenting and uncommenting code 181  
     configuring 111  
     Contextual Information Sidebar (CIS) in 166  
     copying to clipboard from 170  
     creating files 183  
     displaying by right-clicking on entities 136  
     displaying from Find Results window 26, 154  
     external editor replacing 119  
     folding (hiding blocks in) code 180  
     hiding inactive lines in 180  
     history of locations visited in, moving through 163  
     jumping to specific line number 170  
     keystrokes in, list of 182  
     language, setting 170  
     line numbers displayed in 168  
     list of specific structures in 166, 169  
     location of 19  
     macros of editing changes, recording and replaying  
         182  
     moving between windows of 28  
     opening files 183  
     printing from 113, 192  
     read-write (RW) and read-only (RO) indicators 170  
     right-clicking in 22, 28, 171  
     right-clicking tabs in 185  
     saving files 172  
     Scope List in 169  
     searching and replacing text in source files 165  
     searching in source files 149  
     status bar in 169  
     status icon in 169  
     tabs in, controlling behavior of 185  
     toolbar for 164  
 source files  
     adding to project 37, 43, 140

---

- adding to project on command line 325
  - analyzing using projects. *See* project
  - closing 162, 172
  - creating 183
  - declaration structure for 261, 263
  - deleting from project 45
  - directories for, adding to project 44
  - directories for, deleting from project 45
  - displaying by double-clicking entity 136
  - displaying by right-clicking on entities 136
  - displaying from Find Results window 26, 154
  - editing. *See* Source Editor
  - encoding for 50, 111
  - excluding from source list 45
  - external editor for 119
  - imported classes in 263
  - imported, report about 223
  - include files specified as, assembly 67
  - include files specified as, C++ 73, 80
  - include files specified as, Fortran 86
  - include files specified as, PL/M 93
  - include hierarchy for 257, 259
  - line endings for 111
  - list of, generating from command line 330
  - listing in Filter Area 24
  - metrics about 230
  - moving between windows of 28
  - opening 183
  - opening from graphical view 253
  - overriding settings for 47
    - as parallelograms, in graphical views 266
  - portability of 48
  - printing 192, 281
  - printing, configuration for 113
  - read-only access for 50
  - removing from project 140
  - saving 172
  - searching 26, 140, 149, 152
  - Sources tab, Project Configuration dialog 43
  - sourcestyles.css file 212
  - spaces, converting tabs to 112
  - Spacing menu, graphical views 273
  - special member functions, C++ 72
  - splash screen, displaying at startup 99
  - split
    - Source Editor 181
    - workspace 162
    - workspace, toolbar for 164
  - Sql menu, graphical views 273
  - SQL, embedded, in Pascal 91
  - square brackets. *See* brackets
  - src.jar file 88
  - src.zip file 88
  - Standard field, Ada 64
  - standard libraries
    - Ada, directory for 64
    - displaying in Analysis Log 108
    - Pascal, paths for 92
  - Standard Library Paths category, Pascal 92
  - standards, CodeCheck 286
  - Start menu, Understand commands in 20
  - startup
    - Getting Started dialog displayed on 99
    - Splash-Screen displayed on 99
  - static functions, displayed in graphical views 273
  - Static menu, graphical views 273
  - status bar, Source Editor 169
  - status icon, in Source Editor 169
  - status line 19
  - strict C/C++ analyzer 42, 78, 83
  - strict complexity, count and/or operators in, Ada 64
  - Strict metric 231
  - Structure Browser, Contextual Information Sidebar 166
  - structure reports 221
  - structure views 30, 253, 261
    - See also* declaration views; graphical views
  - Styles category, Editor options 117
  - subprograms, listing in Filter Area 24
  - subtraction sign (-) collapsing tree in Information Browser 134
  - Sum Complexity metrics graph 239
  - support contact information 14
  - SVG format, saving graphical views as 279
  - switches, command line
    - understand command 331
  - synchronizing Information Browser 136
  - Sysroot field, C++ Includes 81
  - "System Design in Ada" (Buhr) 261
  - system include files, C++ 74
- ## T
- tab, automatic 115, 116
  - Table View of graphs 250
  - Table View, for metrics graphs 241

---

- tabs for windows, displaying 101
- tabs, converting to spaces 112
- Task View 261
- tasks
  - declaration structure for 261
  - With relationships for 261
- technical support contact information 14
- temporary bookmark 184
- text
  - comparing 303
  - copying to clipboard 170
  - generating reports as 31, 56, 210, 212
  - selecting 170
  - size of, in graphical views 272
  - viewing reports as 213
- Text Comparison window 303
- text favorite 147
- Text menu, graphical views 273
- TextPad editor 119
- title areas, filenames in 102
- title bar 17
- Title Formats field, User Interface options 102
- title page 56
- Toggle Overtyping option, Edit menu 182
- tool commands, importing and exporting 319
- Tool Configurations dialog
  - Popup Menu category 316
  - Toolbar category 318
- toolbar
  - external tools available from 318
  - hiding and displaying icons 164
  - location of 19
  - visibility of icons in, controlling 318
- Toolbar category, Tool Configurations dialog 318
- Tools menu 339
  - Compare Arbitrary Text option 303
  - Compare Entities option 302
  - Compare Files/Folders option 299
  - Editor Macros option 182
  - Options option 98
  - Run Command option 320
  - Scheduler option 51, 52
  - User Tools option 309, 311, 317, 319
- tools, external. *See* external tools
- tooltips 118
- Treat system includes as user includes field
  - C++ Includes 74

- Tree row indentation field, User Interface options 106
- treemap
  - CodeCheck 292
  - metrics 242
- Truncate column field
  - Fortran 85
  - JOVIAL 89
- Truncate Long text option 273
- Truncate Medium text option 273
- Truncate Short text option 273
- truncation at column
  - Fortran 85
  - JOVIAL 89
- Turbo Pascal 91
- Type Cross-Reference report 218
- Type Derived From View 257
- Type Tree View 257
- types
  - displayed in graphical views 273, 274
  - as hexagons, in graphical views 266
  - information about 261, 264
  - listing in Filter Area 24
  - reports about 218, 227
  - types derived from 257
- Types menu, graphical views 273
- Typetext menu, graphical views 274

## U

- .udb file extension 18, 33
- UML Class Diagram 261, 263
- UML Sequence Diagram 261
- Uncomment Selection menu option 181
- und command 322, 323
  - adding files to project 325
  - analyzing a project 328
  - options in latest version, listing 325
- undefined macros, C++ 77
- Undefines category, C++ Macros 77
- Understand
  - compared to compiler 33
  - contact information 14
  - features of 13
  - multiple users for 21
  - online help for 15, 21
  - starting 20
  - starting from command line 331
  - windows in 17, 19



- understand command 331
- Understand Options dialog 98
  - Analyze category 108
  - Dependency category 110
  - Editor category 111
  - General category 99
  - Graphs category 120
  - Key Bindings category 107, 182
  - Portability category 109
  - User Interface category 101
- undocking windows 17
- Unicode file handling, in Entity Comparison area 306
- Uninitialized Items report 226
- Unix
  - line termination style, for reports 212
  - line termination style, for saving source files 112
- unknown entities, displaying in graphical views 274
- Unknown menu, graphical views 274
- unresolved entities
  - displaying in graphical views 274
- Unresolved menu, graphical views 274
- unresolved variables, listed in Entity Locator 25
- Unused Object report 226
- Unused Objects and Functions report 226
- Unused Program Unit report 227
- Unused Type report 227
- Update Information Browser field, Browse Mode Editor
  - options 118
- uperc command 18
- Use alternating row colors field, User Interface options 106
- Use case-insensitive lookup for includes field
  - C++ Includes 74
- Use default working directory field, General options 100
- Use include cache field, C++ 72
- Use preprocessor field, Fortran 85
- use statements, reports about 227
- Use the New Project Wizard when creating new
  - projects field, Configure options 102
- Used By View 257
- Usedby Menu, graphical views 274
- User Interface category, Understand Options dialog 101
- user interface, parts of 19
- User Tools option, Tools menu 309, 311, 317, 319
- users, multiple, initialization files for 21
- Uses Menu, graphical views 274

- Uses Not Needed report 227

- Uses View 257

## V

- variables
  - displayed in graphical views 274
  - instance 229
  - listed in Entity Locator 25
  - metrics about 229
  - reports about 218, 225, 226
  - as rounded rectangles, in graphical views 266
  - uninitialized, report about 226
  - unresolved 25
  - See also* objects
- Variables menu, graphical views 274
- .vcp file extension 58
- .vcw file extension 58
- Version field
  - Ada 63
  - Fortran 84
  - Java 87
  - JOVIAL 89
  - Pascal 91
- vertical bar (|) in regular expressions 161
- Vertical Non-Crossing layout option 270
- VHDL
  - terminology 95
  - versions supported 14
- vi editor 119
- View menu 336
  - Analysis Log option 124
  - Bookmarks option 164, 184
  - Browse Mode option 170
  - Contextual Information option 166
  - Entity Locator option 25, 157
  - Favorites option 26, 145
  - Fold All option 180
  - Hide Inactive Lines option 180
  - Information Browser 133
  - Project Browser option 139
  - Scope List option 169
  - Soft Wrap option 182
  - Window Selector option 163
  - Zoom option 168, 185
- View Reports option, Reports menu 213
- views. *See* declaration views; graphical views; hierarchical views

---

- violations
  - checking for 286
  - ignoring 293
- Visio files, saving graphical views as 279
- visit option, understand command 332
- Visit Source field, Browse Mode Editor options 118
- Visual Basic
  - configuration for 68
- Visual Basic category, Project Configuration dialog 68
- Visual C++, as editor 119
- Visual Studio
  - as external editor 119
  - auto-architecture 195
  - files, synchronizing with Understand project 36, 58
- Visual Studio category, Project Configuration dialog 58

## W

- wait option, understand command 332
- warnings, displaying from Analysis Log window 124
- watched directories
  - scanning 47, 52
  - setting 45, 46
- Web category, Project Configuration dialog 96
- Web support 14
- websites
  - external editor information 119
  - metrics, list of 224, 228, 233, 234, 235
  - O'Reilly and Associates 161
  - Scientific Toolworks 14
- white file icon 169
- whitespace
  - in Entity Comparison area 306
  - indicators for 112
- Whitespace field, Editor options 112
- wild cards, in filters for Entity Locator 160
- %WINDIR% environment variable 21
- Window menu 162, 339
  - Close All Document Windows option 162, 172
  - Close option 162, 172
  - Entity Graph option 253
  - Windows Navigator option 163
- Window Selector option, View menu 163
- windows 17, 19
  - animated opening and closing of 101
  - closing 17
  - creating with Ctrl+right-click 22, 129

- docking and undocking 17
- docking layout for 101
- filenames in title area of 102
- frames in, sliding 17
- list of 130
- list of open windows 163
- organizing 162
- reusing for graphical views 256
- reusing with right-click 22, 129
- tabs for, displaying 101
- Windows category, Application Styles options 106
- Windows category, User Interface options 104
- Windows CE project 58
- Windows CE workspace 58
- Windows folder 21
- Windows line termination style
  - for reports 212
  - for saving source files 112
- Windows Navigator option, Window menu 163
- With Bys menu, graphical views 274
- With Tree report 223
- With, WithBy Views 257
- Withs menu, graphical views 274
- Withs Not Needed report 227
- WMC (Count of Methods) metric 229
- workbench file 58
- working directory, default 100
- workspace file 58
- Wrap Long text option 273
- Wrap Medium text option 273
- Wrap Mode field, Advanced Editor options 113
- Wrap Short text option 273
- wrapping lines
  - display 182
  - printing 113

## X

- XML Export 197, 208
- XML output 244, 245
- XML, sharing architectures using 208

## Y

- yellow background for text 117
- yellow project file icon 169

**Z**

Zoom option, View menu 168, 185

zooming

graphical views 254

source views 168