

Firmware Release Note



Model : SL-M4070FX, M4071FX, M4075FX, M4076FX

Date :

September 21, 2015

Version	Category	Change Description
V4.00.01.09 (26-Mar, 2014)	Fix Defect	Fixed the copy setting is changed to default value after ACR(auto color registration)
		Scan to PC notify message is not translated to other languages.
		Scan to PC setting page is not working on Mac OS.
V4.00.01.35 (9-Jan, 2015)	Add Func.	Support New Solutions(BCPS 1.2, SecuThru Lite)
		Samsung Cloud Print feature
	Fix Defect	Can not connect to DropBox/Evernote for ScanToCloud
		Russia summer time issue
		"Control Panel Lock" feature is not working
V4.00.01.38 (21-Sep, 2015)	Fix Defect	[SWAS Job Accounting] Device didn't send a reponse to SWAS
		Scan to SMB issue with Mac 10.10
		Chinese string displayed at some places are wrong.
		When user install an invalid Application via SWS, user cannot access to SWS and network status of device is not available.
		Port 7000/udp was found to be open
		Google Cloud Print does not work properly.
		To prevent POODLE attack by disabling SSL v3 support in OpenSSL
		Machine reboots when cancel N-up copy job.
	Add Func.	Apply to Toner Status and Easy setup of Samsung Cloud Print
		Touch Pannel response time enhancement
		Apply new font data in PCL6, PCL6, PS


※ Note

- Please do not turn off the printer and your computer until firmware update finishes.
- If you are using USB connection, disconnect all other USB printers from the PC.
- The firmware update you are about to install has been tested for compatibility with Samsung toner cartridge products ONLY.
Installing The upgrade may cause a non-Samsung toner cartridge to malfunction.
- Do not run your printer during the firmware update.(Do not have any print job)

How to update the firmware using a USB cable.

1. Make sure that the machine is connected to the PC with a USB cable.
2. Menu > Setup > Admin Setup > Firmware Upgrade > ON
3. Drag the firmware file(*.hd) and Drop down it on usblist2.exe.

And then, firmware update will be started automatically.



4. The firmware update will start.

Once the firmware update is complete, the machine will be rebooted automatically.

Updating from the Network

1. Go to the SyncThruWeb Service (SWS) main home page.
Login as Admin in SyncThruWeb Service.
NOTE: Login using the Administrator ID and Password established during initial machine setup.
2. Click [Maintenance] on the top menu.
And then click [Firmware Upgrade] or Application Management > Application
3. Click Add button
4. Click [Browse]. Choose installation file by browsing file system. And click OK button
5. The uploading step will start. After this step, next step will be started automatically.
6. The firmware update will start.
7. Once the f/w update is complete, the machine power-off and power-on automatically.